ROCSCIENCE

hjhjh
Slide2 - An Interactive Slope Stability Program
Date Created: 13/03/2026, 8:34:42 am
Software Version: 9.041

Table of Contents

Project Summary 3
General Settings 4
Analysis Options 5
Groundwater Analysis 6
Random Numbers 7
Surface Options 8
Seismic Loading 9
Materials 10
Global Minimums 11
Method: bishop simplified 11
Valid and Invalid Surfaces 12
Method: bishop simplified 12
Error Code Descriptions 12
Slice Data 13
Global Minimum Query (bishop simplified) - Safety Factor: 0.986763 13
Interslice Data 14
Global Minimum Query (bishop simplified) - Safety Factor: 0.986763 14
Entity Information 15
Group 1 15
Shared Entities 15

Slide2 Analysis Information

hjhjh

Project Summary

File Name:	hjhjh.slmd
Slide2 Modeler Version:	9.041
Compute Time:	00h:00m:00.380s
Project Title:	Slide2 - An Interactive Slope Stability Program
Date Created:	13/03/2026, 8:34:42 am

General Settings

Units of Measurement:	Metric Units
Time Units:	days
Permeability Units:	meters/second
Data Output:	Standard
Failure Direction:	Right to Left

Analysis Options

Slices Type:	Vertical
Analysis Methods Used	
	Bishop simplified
Number of slices:	25
Tolerance:	0.0001
Maximum number of iterations:	100
Check malpha < 0.2:	Yes
Create Interslice boundaries at intersections with water tables and piezos:	Yes
Initial trial value of FS:	1
Steffensen Iteration:	Yes

Groundwater Analysis

Groundwater Method:	Water Surfaces
Pore Fluid Unit Weight [kN/m3]:	9.81
Advanced Groundwater Method:	None

Random Numbers

Pseudo-random Seed:	10116
Random Number Generation Method:	Park and Miller v.3

Surface Options

Surface Type:	Circular
Search Method:	Grid Search
Radius Increment:	10
Composite Surfaces:	Disabled
Reverse Curvature:	Invalid Surfaces
Minimum Elevation:	Not Defined
Minimum Depth:	Not Defined
Minimum Area:	Not Defined
Minimum Weight:	Not Defined

Seismic Loading

Advanced seismic analysis:	No
Staged pseudostatic analysis:	No

Materials

Material 1	
Color	
Strength Type	Mohr-Coulomb
Unit Weight	20 kN/m3
Cohesion	3 kPa
Phi	19.6 °
Water Surface	None
Ru Value	0

Global Minimums

Method: bishop simplified

FS	0.986763
Center:	29.070, 55.495
Radius:	30.496
Left Slip Surface Endpoint:	30.029, 25.014
Right Slip Surface Endpoint:	51.652, 35.000
Resisting Moment:	11710.2 kN-m
Driving Moment:	11867.3 kN-m
Total Slice Area:	46.9424 m2
Surface Horizontal Width:	21.6229 m
Surface Average Height:	2.17096 m

Global Minimum Support Data

No Supports Present

Valid and Invalid Surfaces

Method: bishop simplified

Number of Valid Surfaces:	8501
Number of Invalid Surfaces:	760

Error Codes

Error Code -103 reported for 284 surfaces
Error Code -108 reported for 476 surfaces

Error Code Descriptions

The following errors were encountered during the computation:

-103 = Two surface / slope intersections, but one or more surface / nonslope external polygon intersections lie between them. This usually occurs when the slip surface extends past the bottom of the soil region, but may also occur on a benched slope model with two sets of Slope Limits.

-108 = Total driving moment or total driving force < 0.1. This is to limit the calculation of extremely high safety factors if the driving force is very small (0.1 is an arbitrary number).

Slice Data

Global Minimum Query (bishop simplified) - Safety Factor: 0.986763

Slice Number	Width [m]	Weight [kN]	Angle of Slice Base [deg]	Base Material	Base Cohesion [kPa]	Base Friction Angle [deg]	Shear Stress [kPa]	Shear Strength [kPa]	Base Normal Stress [kPa]	Pore Pressure [kPa]	Effective Normal Stress [kPa]	Base Vertical Stress [kPa]	Effective Vertical Stress [kPa]
1	0.864918	3.39871	2.61525	Material 1	3	19.6	4.38596	4.3279	3.72918	0	3.72918	3.92952	3.92952
2	0.864918	9.98279	4.24341	Material 1	3	19.6	7.01737	6.92448	11.0212	0	11.0212	11.5419	11.5419
3	0.864918	16.1388	5.87501	Material 1	3	19.6	9.42374	9.299	17.6897	0	17.6897	18.6594	18.6594
4	0.864918	21.8635	7.51142	Material 1	3	19.6	11.6097	11.456	23.7473	0	23.7473	25.2781	25.2781
5	0.864918	27.1524	9.15401	Material 1	3	19.6	13.5791	13.3994	29.2049	0	29.2049	31.3931	31.3931
6	0.864918	32.0002	10.8042	Material 1	3	19.6	15.3353	15.1323	34.0714	0	34.0714	36.998	36.998
7	0.864918	36.3999	12.4636	Material 1	3	19.6	16.8806	16.6572	38.3538	0	38.3538	42.0849	42.0849
8	0.864918	40.3435	14.1336	Material 1	3	19.6	18.217	17.9759	42.0572	0	42.0572	46.6443	46.6443
9	0.864918	43.8215	15.8161	Material 1	3	19.6	19.3459	19.0898	45.1854	0	45.1854	50.6656	50.6656
10	0.864918	46.8227	17.5126	Material 1	3	19.6	20.2678	19.9995	47.7401	0	47.7401	54.1354	54.1354
11	0.864918	49.3342	19.2252	Material 1	3	19.6	20.983	20.7052	49.7219	0	49.7219	57.0392	57.0392
12	0.864918	51.3413	20.9558	Material 1	3	19.6	21.4908	21.2063	51.1293	0	51.1293	59.3598	59.3598
13	0.864918	52.8268	22.7067	Material 1	3	19.6	21.7902	21.5018	51.9592	0	51.9592	61.0773	61.0773
14	0.864918	53.7712	24.4803	Material 1	3	19.6	21.8797	21.5901	52.207	0	52.207	62.1691	62.1691
15	0.864918	54.152	26.2793	Material 1	3	19.6	21.7568	21.4688	51.8663	0	51.8663	62.6094	62.6094
16	0.864918	53.9434	28.1067	Material 1	3	19.6	21.4184	21.1349	50.9287	0	50.9287	62.3683	62.3683
17	0.864918	53.1156	29.9658	Material 1	3	19.6	20.8609	20.5848	49.3837	0	49.3837	61.4112	61.4112
18	0.864918	51.6341	31.8604	Material 1	3	19.6	20.0797	19.8139	47.219	0	47.219	59.6982	59.6982
19	0.864918	49.4586	33.7949	Material 1	3	19.6	19.0695	18.8171	44.4196	0	44.4196	57.1831	57.1831
20	0.864918	46.5422	35.7742	Material 1	3	19.6	17.8241	17.5882	40.9682	0	40.9682	53.8112	53.8112
21	0.864918	42.8293	37.8041	Material 1	3	19.6	16.3361	16.1199	36.8449	0	36.8449	49.5184	49.5184
22	0.864918	38.2535	39.8915	Material 1	3	19.6	14.5973	14.4041	32.0264	0	32.0264	44.2279	44.2279
23	0.864918	32.7349	42.0447	Material 1	3	19.6	12.5981	12.4313	26.4862	0	26.4862	37.8474	37.8474
24	0.864918	23.0797	44.2738	Material 1	3	19.6	9.37217	9.24811	17.5467	0	17.5467	26.6843	26.6843
25	0.864918	7.90828	46.5911	Material 1	3	19.6	4.5891	4.52835	4.29209	0	4.29209	9.14341	9.14341

Interslice Data

Global Minimum Query (bishop simplified) - Safety Factor: 0.986763

Slice Number	X coordinate [m]	Y coordinate - Bottom [m]	Interslice Normal Force [kN]	Interslice Shear Force [kN]	Interslice Force Angle [deg]
1	30.0289	25.0144	0	0	0
2	30.8938	25.0539	3.64616	0	0
3	31.7587	25.1181	9.0083	0	0
4	32.6236	25.2071	15.5847	0	0
5	33.4886	25.3212	22.9178	0	0
6	34.3535	25.4605	30.5922	0	0
7	35.2184	25.6256	38.2322	0	0
8	36.0833	25.8168	45.5003	0	0
9	36.9482	26.0346	52.0968	0	0
10	37.8131	26.2796	57.7585	0	0
11	38.6781	26.5525	62.2593	0	0
12	39.543	26.8541	65.4105	0	0
13	40.4079	27.1854	67.0619	0	0
14	41.2728	27.5473	67.1034	0	0
15	42.1377	27.9411	65.468	0	0
16	43.0026	28.3682	62.1346	0	0
17	43.8676	28.8301	57.1331	0	0
18	44.7325	29.3288	50.5496	0	0
19	45.5974	29.8663	42.535	0	0
20	46.4623	30.4452	33.314	0	0
21	47.3272	31.0684	23.1986	0	0
22	48.1922	31.7394	12.6051	0	0
23	49.0571	32.4624	2.07659	0	0
24	49.922	33.2424	-7.68638	0	0
25	50.7869	34.0857	-14.3768	0	0
26	51.6518	35	0	0	0

Discharge Sections

Entity Information

Group 1

Shared Entities

Type	Coordinates (x,y)
External Boundary	70, 20 70, 35 50, 35 30, 25 20, 25 20, 20