ROCSCIENCE

Case7
Slide2 - An Interactive Slope Stability Program
Date Created: 27/03/2026, 9:23:52 pm
Software Version: 9.041

Table of Contents

Project Summary 3
General Settings 4
Analysis Options 5
Groundwater Analysis 6
Random Numbers 7
Surface Options 8
Seismic Loading 9
Materials 10
Global Minimums 11
Method: bishop simplified 11
Method: spencer 11
Valid and Invalid Surfaces 12
Method: bishop simplified 12
Method: spencer 12
Error Code Descriptions 12
Slice Data 13
Global Minimum Query (bishop simplified) - Safety Factor: 0.940158 13
Global Minimum Query (spencer) - Safety Factor: 1.0494 14
Interslice Data 15
Global Minimum Query (bishop simplified) - Safety Factor: 0.940158 15
Global Minimum Query (spencer) - Safety Factor: 1.0494 16
Entity Information 17
Group 1 17
Shared Entities 17
Scenario-based Entities 17

Slide2 Analysis Information

Case7

Project Summary

File Name:	Case7.slmd
Slide2 Modeler Version:	9.041
Compute Time:	00h:00m:01.975s
Project Title:	Slide2 - An Interactive Slope Stability Program
Date Created:	27/03/2026, 9:23:52 pm

General Settings

Units of Measurement:	Metric Units
Time Units:	days
Permeability Units:	meters/second
Data Output:	Standard
Failure Direction:	Right to Left

Analysis Options

Slices Type:	Vertical
Analysis Methods Used	
	Bishop simplified
	Spencer
Number of slices:	50
Tolerance:	0.001
Maximum number of iterations:	75
Check malpha < 0.2:	Yes
Create Interslice boundaries at intersections with water tables and piezos:	Yes
Initial trial value of FS:	1
Steffensen Iteration:	Yes

Groundwater Analysis

Groundwater Method:	Water Surfaces
Pore Fluid Unit Weight [kN/m3]:	9.81
Advanced Groundwater Method:	None

Random Numbers

Pseudo-random Seed:	10116
Random Number Generation Method:	Park and Miller v.3

Surface Options

Surface Type:	Circular
Search Method:	Auto Refine Search
Divisions along slope:	20
Circles per division:	10
Number of iterations:	10
Divisions to use in next iteration:	50%
Composite Surfaces:	Disabled
Minimum Elevation:	Not Defined
Minimum Depth:	Not Defined
Minimum Area:	Not Defined
Minimum Weight:	Not Defined

Seismic Loading

Advanced seismic analysis:	No
Staged pseudostatic analysis:	No

Materials

TBA	
Color	
Strength Type	Mohr-Coulomb
Unit Weight	16 kN/m3
Cohesion	12 kPa
Phi	38 °
Water Surface	Water Table
Hu Type	Automatically Calculated
Specify alternate strength type above water surface	No

Global Minimums

Method: bishop simplified

FS	0.940158
Center:	1.659, 9.000
Radius:	6.866
Left Slip Surface Endpoint:	5.001, 3.002
Right Slip Surface Endpoint:	8.525, 9.000
Left Slope Intercept:	5.001 4.609
Right Slope Intercept:	8.525 9.000
Resisting Moment:	667.678 kN-m
Driving Moment:	710.176 kN-m
Total Slice Area:	9.43891 m2
Surface Horizontal Width:	3.52395 m
Surface Average Height:	2.6785 m

Method: spencer

FS	1.049400
Center:	2.474, 10.379
Radius:	7.759
Left Slip Surface Endpoint:	5.016, 3.048
Right Slip Surface Endpoint:	10.110, 9.000
Left Slope Intercept:	5.016 4.609
Right Slope Intercept:	10.110 9.000
Resisting Moment:	1197.93 kN-m
Driving Moment:	1141.54 kN-m
Resisting Horizontal Force:	108.973 kN
Driving Horizontal Force:	103.843 kN
Total Slice Area:	15.2765 m2
Surface Horizontal Width:	5.09348 m
Surface Average Height:	2.99923 m

Global Minimum Support Data

No Supports Present

Valid and Invalid Surfaces

Method: bishop simplified

Number of Valid Surfaces:	8998
Number of Invalid Surfaces:	0

Method: spencer

Number of Valid Surfaces:	2040
Number of Invalid Surfaces:	6958

Error Codes

Error Code -108 reported for 89 surfaces
Error Code -111 reported for 6869 surfaces

Error Code Descriptions

The following errors were encountered during the computation:
-108 = Total driving moment or total driving force < 0.1. This is to limit the calculation of extremely high safety factors if the driving force is very small (0.1 is an arbitrary number).
-111 = Safety factor equation did not converge

Slice Data

Global Minimum Query (bishop simplified) - Safety Factor: 0.940158

Slice Number	Width [m]	Weight [kN]	Angle of Slice Base [deg]	Base Material	Base Cohesion [kPa]	Base Friction Angle [deg]	Shear Stress [kPa]	Shear Strength [kPa]	Base Normal Stress [kPa]	Pore Pressure [kPa]	Effective Normal Stress [kPa]	Base Vertical Stress [kPa]	Effective Vertical Stress [kPa]
1	0.0702196	1.13001	29.4633	TBA	12	38	8.98661	8.44883	11.018	15.5633	-4.54532	16.0948	0.53147
2	0.0702196	1.17638	30.1386	TBA	12	38	9.49928	8.93082	11.2403	15.1687	-3.9284	16.7554	1.5867
3	0.0702196	1.22151	30.8186	TBA	12	38	9.99739	9.39913	11.4342	14.7632	-3.32897	17.3983	2.63507
4	0.0702196	1.26537	31.5034	TBA	12	38	10.4809	9.8537	11.5994	14.3466	-2.74717	18.023	3.67639
5	0.0702196	1.30792	32.1933	TBA	12	38	10.9497	10.2944	11.7356	13.9186	-2.18302	18.6292	4.71058
6	0.0702196	1.34914	32.8884	TBA	12	38	11.4037	10.7213	11.8423	13.479	-1.63671	19.2164	5.7374
7	0.0702196	1.38899	33.5891	TBA	12	38	11.8428	11.1341	11.9192	13.0275	-1.10835	19.7842	6.75672
8	0.0702196	1.43766	34.2954	TBA	12	38	12.3439	11.6052	12.0586	12.5638	-0.505249	20.4776	7.91376
9	0.0702196	1.59146	35.0078	TBA	12	38	19.246	18.0943	9.18997	1.38959	7.80038	22.6701	21.2805
10	0.0702196	1.77214	35.7264	TBA	12	38	20.3137	19.0981	10.6325	1.54735	9.08517	25.2436	23.6963
11	0.0702196	1.95131	36.4516	TBA	12	38	21.3446	20.0673	12.0295	1.70379	10.3257	27.7957	26.092
12	0.0702196	2.12893	37.1836	TBA	12	38	22.3382	21.0014	13.3802	1.85888	11.5213	30.3257	28.4668
13	0.0702196	2.30495	37.9228	TBA	12	38	23.2941	21.9001	14.6842	2.01257	12.6716	32.833	30.8204
14	0.0702196	2.47932	38.6695	TBA	12	38	24.2118	22.7629	15.9407	2.16483	13.7759	35.3168	33.152
15	0.0702196	2.652	39.424	TBA	12	38	25.0907	23.5892	17.1491	2.3156	14.8335	37.7765	35.4609
16	0.0702196	2.82293	40.1869	TBA	12	38	25.9303	24.3786	18.3087	2.46485	15.8439	40.2114	37.7465
17	0.0702196	2.99205	40.9584	TBA	12	38	26.7299	25.1303	19.4184	2.61252	16.8059	42.6203	40.0078
18	0.0702196	3.1593	41.739	TBA	12	38	27.4886	25.8436	20.4776	2.75855	17.719	45.0026	42.244
19	0.0702196	3.3246	42.5292	TBA	12	38	28.2058	26.5179	21.4849	2.90288	18.582	47.3572	44.4544
20	0.0702196	3.48788	43.3296	TBA	12	38	28.8805	27.1522	22.4394	3.04545	19.394	49.6832	46.6378
21	0.0702196	3.64907	44.1407	TBA	12	38	16.5332	15.5438	35.9292	31.3934	4.5358	51.9737	20.5803
22	0.0702196	3.80807	44.963	TBA	12	38	17.6154	16.5612	36.6461	30.808	5.83813	54.2388	23.4308
23	0.0702196	3.9648	45.7974	TBA	12	38	18.6539	17.5376	37.2908	30.2031	7.08774	56.4713	26.2682
24	0.0702196	4.11914	46.6444	TBA	12	38	19.6475	18.4718	37.8611	29.5776	8.28349	58.67	29.0924
25	0.0702196	4.27098	47.5049	TBA	12	38	20.5948	19.3624	38.3541	28.9307	9.4234	60.8333	31.9026
26	0.0702196	4.42021	48.3798	TBA	12	38	21.4942	20.2079	38.7669	28.2612	10.5057	62.9591	34.6979
27	0.0702196	4.56667	49.2699	TBA	12	38	22.3439	21.0068	39.0962	27.568	11.5282	65.0458	37.4778
28	0.0702196	4.71024	50.1765	TBA	12	38	23.142	21.7571	39.3384	26.8498	12.4886	67.091	40.2412
29	0.0702196	4.81759	51.1006	TBA	12	38	23.693	22.2752	39.2569	26.1052	13.1517	68.6206	42.5154
30	0.0702196	4.74438	52.0435	TBA	12	38	23.1783	21.7913	37.8647	25.3325	12.5322	67.5781	42.2456
31	0.0702196	4.64145	53.0068	TBA	12	38	22.5002	21.1538	36.2461	24.5299	11.7162	66.1124	41.5825
32	0.0702196	4.53481	53.9921	TBA	12	38	21.811	20.5058	34.5823	23.6954	10.8869	64.5938	40.8984
33	0.0702196	4.4242	55.0013	TBA	12	38	21.1096	19.8463	32.8695	22.8266	10.0429	63.0186	40.192
34	0.0702196	4.30929	56.0366	TBA	12	38	20.3949	19.1744	31.1039	21.921	9.18287	61.3823	39.4613
35	0.0702196	4.18976	57.1005	TBA	12	38	19.6657	18.4889	29.2809	20.9755	8.30538	59.68	38.7045
36	0.0702196	4.06517	58.1959	TBA	12	38	18.9204	17.7882	27.3952	19.9866	7.40858	57.9058	37.9192
37	0.0702196	3.93505	59.3262	TBA	12	38	18.1574	17.0708	25.4405	18.9501	6.4904	56.0529	37.1028
38	0.0702196	3.79884	60.4954	TBA	12	38	17.3745	16.3348	23.4095	17.8612	5.54825	54.1131	36.2519
39	0.0702196	3.65585	61.7086	TBA	12	38	16.5693	15.5778	21.2933	16.7139	4.57936	52.0768	35.3629
40	0.0702196	3.50524	62.9715	TBA	12	38	15.7387	14.7969	19.0809	15.5011	3.57983	49.932	34.4309
41	0.0702196	3.34598	64.2917	TBA	12	38	14.879	13.9886	16.7592	14.2139	2.54534	47.6641	33.4502
42	0.0702196	3.17677	65.6785	TBA	12	38	13.9854	13.1485	14.311	12.8411	1.46993	45.2543	32.4132
43	0.0702196	2.99591	67.1443	TBA	12	38	13.0516	12.2706	11.7143	11.368	0.34635	42.6787	31.3107
44	0.0702196	2.80112	68.7055	TBA	12	38	12.0694	11.3472	8.93951	9.77511	-0.835597	39.9047	30.1296
45	0.0702196	2.58923	70.3851	TBA	12	38	11.027	10.3672	5.94514	8.03509	-2.08995	36.8872	28.8521
46	0.0702196	2.35556	72.2173	TBA	12	38	9.90716	9.3143	2.67011	6.10765	-3.43754	33.5594	27.4517
47	0.0702196	2.09264	74.2566	TBA	12	38	8.68214	8.16258	-0.983016	3.92865	-4.91167	29.8151	25.8865
48	0.0702196	1.78712	76.601	TBA	12	38	7.30211	6.86514	-5.1892	1.38313	-6.57233	25.4642	24.081
49	0.0767035	1.51363	79.6465	TBA	12	38	5.25774	4.94311	-9.0324	0	-9.0324	19.7464	19.7464
50	0.0767035	0.628	85.7138	TBA	12	38	1.61941	1.5225	-13.4105	0	-13.4105	8.19653	8.19653

Global Minimum Query (spencer) - Safety Factor: 1.0494

Slice Number	Width [m]	Weight [kN]	Angle of Slice Base [deg]	Base Material	Base Cohesion [kPa]	Base Friction Angle [deg]	Shear Stress [kPa]	Shear Strength [kPa]	Base Normal Stress [kPa]	Pore Pressure [kPa]	Effective Normal Stress [kPa]	Base Vertical Stress [kPa]	Effective Vertical Stress [kPa]
1	0.101057	1.6126	19.5199	TBA	12	38	9.53461	10.0056	12.5771	15.1298	-2.55265	15.9573	0.827454
2	0.101057	1.74304	20.3136	TBA	12	38	10.4104	10.9247	13.3942	14.7705	-1.37631	17.2479	2.47743
3	0.101057	1.87089	21.1115	TBA	12	38	11.263	11.8194	14.1644	14.3956	-0.231158	18.5131	4.11747
4	0.101057	1.99612	21.9136	TBA	12	38	12.0925	12.6899	14.8878	14.0048	0.882955	19.7523	5.74746
5	0.101057	2.11869	22.7203	TBA	12	38	12.899	13.5362	15.5639	13.5977	1.96622	20.9651	7.36736
6	0.101057	2.3481	23.5318	TBA	12	38	20.899	21.9314	14.1342	1.42267	12.7116	23.2352	21.8125
7	0.101057	2.76255	24.3484	TBA	12	38	22.8431	23.9716	16.999	1.67606	15.323	27.3363	25.6603
8	0.101057	3.17739	25.1702	TBA	12	38	24.7492	25.9718	19.8109	1.92775	17.8832	31.4413	29.5135
9	0.101057	3.58935	25.9976	TBA	12	38	26.5993	27.9133	22.5459	2.17769	20.3682	35.5178	33.3401
10	0.101057	3.99839	26.8309	TBA	12	38	28.3933	29.7959	25.2036	2.42586	22.7778	39.5653	37.1394
11	0.101057	4.40443	27.6703	TBA	12	38	30.131	31.6195	27.784	2.67221	25.1118	43.5832	40.911
12	0.101057	4.80741	28.5163	TBA	12	38	31.8121	33.3836	30.2865	2.9167	27.3698	47.5708	44.6541
13	0.101057	5.20724	29.3691	TBA	12	38	33.4363	35.0881	32.7107	3.15928	29.5514	51.5273	48.368
14	0.101057	5.60386	30.2291	TBA	12	38	35.0031	36.7323	35.0558	3.39991	31.6559	55.4519	52.052
15	0.101057	5.99718	31.0967	TBA	12	38	20.551	21.5662	46.9485	34.7044	12.2441	59.3441	24.6397
16	0.101057	6.38711	31.9723	TBA	12	38	22.5365	23.6498	49.1354	34.2243	14.9111	63.2026	28.9783
17	0.101057	6.77355	32.8563	TBA	12	38	24.4656	25.6742	51.2255	33.7233	17.5022	67.0265	33.3032
18	0.101057	7.1564	33.7493	TBA	12	38	26.3375	27.6386	53.2173	33.2009	20.0164	70.815	37.6141
19	0.101057	7.53555	34.6516	TBA	12	38	28.1513	29.542	55.109	32.6563	22.4527	74.5668	41.9105
20	0.101057	7.87748	35.5639	TBA	12	38	29.7456	31.215	56.6829	32.0888	24.5941	77.9503	45.8615
21	0.101057	7.8562	36.4867	TBA	12	38	29.5765	31.0376	55.8648	31.4977	24.3671	77.7396	46.2419
22	0.101057	7.73326	37.4206	TBA	12	38	28.9334	30.3627	54.3854	30.8821	23.5033	76.5231	45.641
23	0.101057	7.60607	38.3663	TBA	12	38	28.2849	29.6822	52.8733	30.2412	22.6321	75.2646	45.0234
24	0.101057	7.47446	39.3245	TBA	12	38	27.6306	28.9956	51.327	29.5737	21.7533	73.9622	44.3885
25	0.101057	7.33826	40.2961	TBA	12	38	26.9703	28.3026	49.7452	28.8788	20.8664	72.6145	43.7357
26	0.101057	7.19725	41.2818	TBA	12	38	26.3033	27.6027	48.1258	28.1552	19.9706	71.219	43.0638
27	0.101057	7.05122	42.2827	TBA	12	38	25.6295	26.8956	46.4672	27.4016	19.0656	69.7741	42.3725
28	0.101057	6.89993	43.2998	TBA	12	38	24.9484	26.1808	44.7671	26.6166	18.1505	68.277	41.6604
29	0.101057	6.74312	44.3341	TBA	12	38	24.2593	25.4577	43.0235	25.7985	17.225	66.7254	40.9269
30	0.101057	6.58049	45.3871	TBA	12	38	23.5617	24.7257	41.2337	24.9456	16.2881	65.116	40.1704
31	0.101057	6.4117	46.46	TBA	12	38	22.8553	23.9843	39.395	24.0559	15.3391	63.4458	39.3899
32	0.101057	6.23639	47.5545	TBA	12	38	22.1389	23.2326	37.5044	23.1273	14.3771	61.711	38.5837
33	0.101057	6.05415	48.6725	TBA	12	38	21.4123	22.4701	35.5582	22.1572	13.401	59.9077	37.7505
34	0.101057	5.86451	49.8158	TBA	12	38	20.6743	21.6956	33.5527	21.1428	12.4099	58.0311	36.8883
35	0.101057	5.66693	50.9868	TBA	12	38	19.9242	20.9084	31.4833	20.0811	11.4022	56.076	35.9949
36	0.101057	5.4608	52.1882	TBA	12	38	19.1607	20.1073	29.345	18.9682	10.3768	54.0363	35.0681
37	0.101057	5.24542	53.423	TBA	12	38	18.3828	19.2909	27.1318	17.7999	9.33195	51.905	34.1051
38	0.101057	5.01995	54.6948	TBA	12	38	17.5889	18.4578	24.837	16.5714	8.26562	49.6739	33.1025
39	0.101057	4.78342	56.0078	TBA	12	38	16.7774	17.6062	22.4524	15.2768	7.17565	47.3333	32.0565
40	0.101057	4.53467	57.3671	TBA	12	38	15.9464	16.7342	19.9686	13.9091	6.05948	44.8718	30.9627
41	0.101057	4.27228	58.779	TBA	12	38	15.0935	15.8391	17.3737	12.4599	4.91384	42.2754	29.8155
42	0.101057	3.99454	60.2508	TBA	12	38	14.2158	14.918	14.6538	10.9189	3.73492	39.5271	28.6082
43	0.101057	3.69927	61.7922	TBA	12	38	13.3096	13.9671	11.791	9.27313	2.51784	36.6052	27.3321
44	0.101057	3.38368	63.4154	TBA	12	38	12.3706	12.9817	8.76239	7.50593	1.25646	33.4824	25.9765
45	0.101057	3.04411	65.1367	TBA	12	38	11.3925	11.9553	5.53807	5.59535	-0.0572757	30.1223	24.5269
46	0.101057	2.67554	66.9783	TBA	12	38	10.3673	10.8794	2.07707	3.51136	-1.43429	26.4751	22.9637
47	0.101057	2.27073	68.9723	TBA	12	38	9.28327	9.74186	-1.67947	1.21081	-2.89028	22.4694	21.2586
48	0.114594	2.02292	71.3344	TBA	12	38	7.67112	8.05007	-5.05569	0	-5.05569	17.6525	17.6525
49	0.114594	1.34038	74.2118	TBA	12	38	5.54436	5.81825	-7.91227	0	-7.91227	11.6965	11.6965
50	0.114594	0.484417	77.7638	TBA	12	38	3.28947	3.45197	-10.941	0	-10.941	4.227	4.227

Interslice Data

Global Minimum Query (bishop simplified) - Safety Factor: 0.940158

Slice Number	X coordinate [m]	Y coordinate - Bottom [m]	Interslice Normal Force [kN]	Interslice Shear Force [kN]	Interslice Force Angle [deg]
1	5.00078	3.00235	12.656	0	0
2	5.071	3.04202	3.29562	0	0
3	5.14122	3.08279	6.17068	0	0
4	5.21144	3.12468	8.62461	0	0
5	5.28166	3.16771	10.6569	0	0
6	5.35188	3.21192	12.2671	0	0
7	5.4221	3.25733	13.4549	0	0
8	5.49232	3.30396	14.2201	0	0
9	5.56254	3.35186	14.594	0	0
10	5.63276	3.40104	15.4929	0	0
11	5.70298	3.45155	16.3816	0	0
12	5.7732	3.50341	17.2558	0	0
13	5.84342	3.55668	18.111	0	0
14	5.91364	3.61139	18.9426	0	0
15	5.98386	3.66759	19.7462	0	0
16	6.05408	3.72532	20.5173	0	0
17	6.1243	3.78463	21.2513	0	0
18	6.19452	3.84558	21.9439	0	0
19	6.26474	3.90823	22.5903	0	0
20	6.33496	3.97264	23.1862	0	0
21	6.40518	4.03888	23.7269	0	0
22	6.4754	4.10702	22.4389	0	0
23	6.54562	4.17715	21.1054	0	0
24	6.61584	4.24935	19.7222	0	0
25	6.68606	4.32373	18.2854	0	0
26	6.75627	4.40037	16.7913	0	0
27	6.82649	4.4794	15.2361	0	0
28	6.89671	4.56096	13.616	0	0
29	6.96693	4.64517	11.9276	0	0
30	7.03715	4.73219	10.1742	0	0
31	7.10737	4.82221	8.39255	0	0
32	7.17759	4.91542	6.59339	0	0
33	7.24781	5.01204	4.78288	0	0
34	7.31803	5.11233	2.96808	0	0
35	7.38825	5.21658	1.15702	0	0
36	7.45847	5.32512	-0.640978	0	0
37	7.52869	5.43836	-2.41507	0	0
38	7.59891	5.55674	-4.15244	0	0
39	7.66913	5.68083	-5.83783	0	0
40	7.73935	5.81129	-7.45275	0	0
41	7.80957	5.94893	-8.97446	0	0
42	7.87979	6.09479	-10.3745	0	0
43	7.95001	6.25015	-11.6163	0	0
44	8.02023	6.41674	-12.6518	0	0
45	8.09045	6.5969	-13.4151	0	0
46	8.16067	6.79394	-13.8126	0	0
47	8.23089	7.01287	-13.7018	0	0
48	8.30111	7.26196	-12.8475	0	0
49	8.37133	7.55673	-10.8054	0	0
50	8.44803	7.97658	-6.61008	0	0
51	8.52473	9	0	0	0

Global Minimum Query (spencer) - Safety Factor: 1.0494

Slice Number	X coordinate [m]	Y coordinate - Bottom [m]	Interslice Normal Force [kN]	Interslice Shear Force [kN]	Interslice Force Angle [deg]
1	5.01615	3.04845	11.9399	0	0
2	5.11721	3.08428	4.70246	0	0
3	5.21827	3.12169	8.54123	0	0
4	5.31932	3.16071	11.5128	0	0
5	5.42038	3.20136	13.614	0	0
6	5.52144	3.24367	14.8416	0	0
7	5.6225	3.28768	16.3413	0	0
8	5.72355	3.33341	17.8724	0	0
9	5.82461	3.3809	19.4327	0	0
10	5.92567	3.43019	21.0096	0	0
11	6.02673	3.4813	22.5907	0	0
12	6.12778	3.53429	24.1634	0	0
13	6.22884	3.5892	25.7154	0	0
14	6.3299	3.64607	27.2341	0	0
15	6.43096	3.70496	28.7072	0	0
16	6.53201	3.76591	27.9224	0	0
17	6.63307	3.82899	27.1005	0	0
18	6.73413	3.89426	26.2296	0	0
19	6.83519	3.96178	25.2978	0	0
20	6.93624	4.03163	24.2934	0	0
21	7.0373	4.10388	23.2039	0	0
22	7.13836	4.17863	22.0175	0	0
23	7.23942	4.25595	20.7363	0	0
24	7.34047	4.33595	19.3648	0	0
25	7.44153	4.41874	17.9079	0	0
26	7.54259	4.50443	16.3708	0	0
27	7.64364	4.59315	14.759	0	0
28	7.7447	4.68505	13.0788	0	0
29	7.84576	4.78028	11.3369	0	0
30	7.94682	4.87902	9.54052	0	0
31	8.04787	4.98145	7.69799	0	0
32	8.14893	5.08779	5.8183	0	0
33	8.24999	5.19829	3.91156	0	0
34	8.35105	5.31321	1.98911	0	0
35	8.4521	5.43286	0.0637837	0	0
36	8.55316	5.5576	-1.84983	0	0
37	8.65422	5.68782	-3.73498	0	0
38	8.75528	5.82401	-5.57227	0	0
39	8.85633	5.96671	-7.33902	0	0
40	8.95739	6.11658	-9.00841	0	0
41	9.05845	6.2744	-10.5483	0	0
42	9.15951	6.44113	-11.9197	0	0
43	9.26056	6.61795	-13.0741	0	0
44	9.36162	6.80636	-13.9506	0	0
45	9.46268	7.0083	-14.4699	0	0
46	9.56374	7.22637	-14.5264	0	0
47	9.66479	7.4642	-13.9726	0	0
48	9.76585	7.72708	-12.593	0	0
49	9.88045	8.06631	-9.99888	0	0
50	9.99504	8.4716	-6.15677	0	0
51	10.1096	9	0	0	0

Discharge Sections

Entity Information

Group 1

Shared Entities

Type	Coordinates (x,y)
External Boundary	0, 0 12, 0 12, 9 7, 9 5, 3 0, 3

Scenario-based Entities

Type	Coordinates (x,y)	Master Scenario
Water Table	0, 4.609 5.53621, 4.60862 6.44028, 7.32085 12, 8	Assigned to: TBA