

Below are the Examples of how you can perform various operations on Triggers.

Disable a Trigger

```
ALTER TRIGGER <trigger_name> DISABLE;
```

Example: ALTER TRIGGER CUSTOMER_AFTER_UPDATE DISABLE;

Enable a Trigger

```
ALTER TRIGGER <trigger_name> ENABLE;
```

Example: ALTER TRIGGER CUSTOMER_AFTER_UPDATE ENABLE;

Disable all the Triggers present on the table

```
ALTER TABLE <table_name> DISABLE ALL TRIGGERS;
```

Example: ALTER TABLE CUSTOMER DISABLE ALL TRIGGERS;

Enable all the Triggers present on the table

```
ALTER TABLE <table_name> ENABLE ALL TRIGGERS;
```

Example: ALTER TABLE CUSTOMER ENABLE ALL TRIGGERS;

Dropping a Trigger

```
DROP TRIGGER <trigger_name>;
```

Example: DROP TRIGGER CUSTOMER_AFTER_UPDATE;

Renaming a Trigger name

```
ALTER TRIGGER <old_trigger_name> RENAME TO <new_trigger_name>;
```

Example: ALTER TRIGGER CUSTOMER_AFTER_UPDATE RENAME TO CUSTOMER_AFTER_UPDATE_ACTION;