

FastPay

Mục lục

1. Overview	4
1.1 Purpose of the document	4
1.2 Scope	4
2. Method	5
2.1 Request	5
2.2 Service Code: cardtelco	5
2.2.1.1 Command Code: usecard	5
2.2.1.1.1 Table of CardType	6
2.2.1.1.2 Table ResponseCode	7
2.2.1.2 Callback (when case Status = -2, -326 for function usecard)	8

1. Overview

1.1 Purpose of the document

Instructions on how to connect the Payment Gateway system with other service systems

1.2 Scope

Documentation provided to partners to connect to the Payment system

2. Method

- URL: <https://apicard.fasttransfer.pro/usecard.ashx> (JSON Post)

2.1 Request

2.2 Service Code: cardtelco

2.2.1.1 Command Code: usecard

- **Description:** function to use card
- **In Put:**

Object RequestData: (Serialize Object)

```
public class RequestData
{
    public string PartnerCode { get; set; }
    public string CardSerial { get; set; }
    public string CardCode { get; set; }
    public string CardType { get; set; }
    public string RefCode { get; set; }
    public string Signature { get; set; }
}
```

Paramters	Data Type	Description
partnerCode	string	Partnercode (will provide when connected)
CardSerial	string	Seri
CardCode	string	Cardcode
CardType	string	Card Type ▪ vms: Mobiphone ▪ vnp: Vinaphone ▪ viettel: Viettel
RefCode	string	Reference Code (Usually will be the Transaction Id of the counterparty, this should be unique)
Amount	int	Declared card denomination (Must be accurate)
CallbackUrl	string	Callback url (Use in case of questionable card processing or slow processing after a 90-second

		waiting period)
signature	string	signature: MD5(partnerCode + cardCode+ cardSeri+ refCode+ partnerKey) partnerKey : will provide when connected

- **Out Put:**

JSON of **Object APIResponse**

```
public class APIResponse
{
    public int ResponseCode { get; set; }
    public string Description { get; set; }
    public string ResponseContent { get; set; }
    public string Signature { get; set; }
}
```

Paramters	Data Type	Option	Description
ResponseCode	int	yes	The error code in case 1 is successful. In other cases, see the error code table for details
ResponseContent	string	yes	Real Amount of Card
Description	string	no	Description
Signature	string	no	Signature

2.2.1.1.1 Table of CardType

code	Telco
viettel	Viettel
vms	Mobifone
vnp	Vinaphone

2.2.1.2 Callback

- **Descriptoin** : If these cases are successful, the system will process and return the results via the Url Callback transmitted by the partner in section 3.1. first . Partners need to build this Service according to the standards below
- **Mothead**: POST
- **Content-Type**: application/json
- **In Put**:

Paramters	Data Type	Option	Description
RefCode	string	yes	Reference Code of parner
Status	int	yes	Status (1 is success)
Amount	int	yes	Amount of Card
Signature	string	No	Signature MD5(RefCode + Status + Amount + PartnerKey)

- **OutPut**: return string
 - success: 1|success
 - failed: -1|failed