

FastPay

Mục lục

1. Overview	3
1.1 Purpose	3
1.2 Scope	3
2. Platform	3
2.1 Cash	3
Step 1 Enter order information cash out	3
Step 3: Transaction settlement	3
3. Cash API	4
3.1 Get Usdt Rate	4
3.2 Get List Bank Support	4
3.3 Get QR code info	4
3.4 Cash	6
3.5 Callback	8
3.6 GetTransction	9
3.7 Table ResponseCode	11

1. Overview

1.1 Purpose

Documentation provided to partners to connect to the Payment system. This document is only for technical staff, programmers responsible for system design, solution integration into Website, Mobile App, or e-commerce application

1.2 Scope

Documentation provided to partners to connect to the Payment system. This document is only for technical staff, programmers responsible for system design, solution integration into Website, Mobile App, or e-commerce application

2. Platform

2.1 Cash

Step 1 Enter order information cash out

- User accesses the Partner's website and App to place a withdrawal order
- The user enters the account information, the bank to withdraw money, the amount to withdraw

Step 2: The SHOP system places cash out orders and announces the results

- FastPay system places cash out orders and announces the results

Step 3: Transaction settlement

- Total payment data will be confirmed by both parties after each reconciliation cycle

3. Cash API

3.1 Get Usdt Rate

- **Description:** get balance of bank
- **URL:** <https://bankgate.coroach.xyz/ServiceHandler/GetUsdtRate.ashx>
- **Method:** GET
- **Out Put:**

```
{  
  "rate": 26298,  
}
```

3.2 Get List Bank Support

- **Description:** get list banks support
- **URL:** <https://bankgate.coroach.xyz/ServiceHandler/GetBanks.ashx>
- **Method:** GET
- **Out Put:**

```
{{{"id":1,"code":"ABB","shortName":"ABBANK","isTransfer":1},{  
"id":2,"code":"ACB","shortName":"ACB"},{  
"id":3,"code":"BAB","shortName":"BacABank"},{  
"id":4,"code":"BIDV","shortName":"BIDV}}}
```

```
public class BankCodeInfo  
{  
    public int code { get; set; }  
    public string shortName { get; set; }  
  
}
```

Paramters	Data Type	Description
code	string	Bankcode using for api cash
shortName	string	Name of bank

3.3 Get QR code info

- **Description:** get bank info by qr code
- **URL:** <https://bankgate.coroach.xyz/ServiceHandler/GetQRInfo.ashx>
- **Method:** POST
- **In Put:** Json Object

```
{
    "qrtext":
    "00020101021238570010A000000727012700069704220113VQRQABUMX40580208QRIBFTT
    A53037045405470005802VN62270823DH1002913537 09778655436304D987",
    "type":2
}
```

Object RequestData:

```
public class RequestData
{
    public string qrtext { get; set; }
    public string type { get; set; }
}
```

Paramters	Data Type	Description
qrtext	string	QR text
type	string	1: static qr code 2: dynamic qr code

- **Out Put:**

```
{
    "bankAccountNumber": "VQRQABUMX4058",
    "bankCode": "MB",
    "bankName": "MBBank",
    "amount": 47000,
    "content": "DH1002913537 0977865543",
    "countryCode": "VN",
    "responsecode": 1
}
```

```
public class APIResponse
{
    public int responsecode { get; set; }
    public string bankAccountNumber { get; set; }
```

```

        public string bankCode { get; set; }
        public string bankName { get; set; }

        public int amount { get; set; }
        public string content { get; set; }

    }

```

Paramters	Data Type	Description
responsecode	int	Status of transaction results. 1 means successfully
bankAccountNumber	string	Bank account number
bankcode	string	Code of bank
bankAccountNumber	string	Account number receiving money
content	String	Content of transfer
amount	Int	Amount of money transfer

3.4 Cash

- **Description:** create order to cash out
- **URL:** <https://bankgate.coroach.xyz/bankout/cash.ashx>
- **Method:** POST
- **In Put:** Json Object

Object RequestData:

```

public class RequestData
{
    public string PartnerCode { get; set; }
    public string AccountNumber { get; set; }
    public string BankCode { get; set; }
    public string RefCode { get; set; }
    public string Content { get; set; }
    public int Amount { get; set; }
    public string CallbackUrl { get; set; }
    public string Signature { get; set; }

}

```

Paramters	Data Type	Description
-----------	-----------	-------------

PartnerCode	string	PartnerCode (will provide when connected)
BankCode	string	Bank code: in api list bank support
AccountNumber	string	Account number receiving money
CallbackUrl	String	Callback Url
RefCode	string	Reference Code (Usually will be the Transaction Id of the counterparty, this should be unique)
Content	string	transfer content
Amount	int	Amount received by the user
Signature	string	MD5(partnerCode + AccountNumber + BankCode + Amount + RefCode + CallbackUrl + partnerKey) partnerKey : will provide when connected

- **Out Put:**

```
{
  "ResponseCode": 1,
  "Description": "Transaction is successful",
  "ResponseContent": ""
}
```

```
public class APIResponse
{
    public int ResponseCode { get; set; }
    public string Description { get; set; }
    public string ResponseContent { get; set; }
}
```

Paramters	Data Type	Description
ResponseCode	string	Status of transaction results. 1 means successfully receiving the order
Description	string	Description

3.5 Callback

- **Description:** This is a partner API built according to the below standards to receive
- **URL:** it is CallbackUrl param at [4.1](#)
- **Method:** POST
- **Content-Type:** application/json
- **In Put:**

JSON InPut:

```
{  
  "ResponseCode": 1,  
  "Description": "Transaction is successful",  
  "RefCode": "RE01123",  
  "TransactionID": "VC9762UA",  
  "Amount": 1000000,  
  "Signature": "778a2c01dbdac3c4310deb1987c9e6e2"  
}
```

Body of json:

```
public class APIResponse  
{  
    public int ResponseCode { get; set; }  
    public string Description { get; set; }  
    public string RefCode { get; set; }  
    public string TransactionID { get; set; }  
    public int Amount { get; set; }  
    public string Signature { get; set; }  
}
```

Paramters	Data Type	Description
ResponseCode	string	Status of Result 1 is success
Description	string	Description
TransactionID	string	Transaction of system
RefCode	string	Reference Code (Usually will be the Transaction Id of the counterparty, this should be unique)
Amount	int	Amount actually received
Signature	string	MD5(ResponseCode+ Description+ RefCode + partnerKey)

--	--	--

- **OutPut:** After receiving the Callback, the partner processes the transaction and returns the string delimiter code|description content as follows
 - **success:** 1|success
 - **failed:** -1|failed

3.6 GetTransction

- **Description:** get tranfer status
- **URL:** <https://bankgate.coroach.xyz/bankout/getdetail.ashx>
- **Method:** Post
- **In Put:** Json Object

Object RequestData:

```
public class RequestData
{
    public string PartnerCode { get; set; }
    public string RefCode { get; set; }
    public string Signature { get; set; }
}
```

Paramters	Data Type	Description
PartnerCode	string	PartnerCode (will provide when connected)
RefCode	string	Reference Code
Signature	string	MD5(partnerCode + RefCode + partnerKey) partnerKey : will provide when connected

- **Out Put:**

```

{
  "ResponseCode": 1,
  "Description": "Transaction is successful",
  "ResponseContent":
    "{\\"Amount\\":20000,\\"RefCode\\":\\"2\\",\\"TransactionID\\":\\"1000011\\",\\"LasTime\\":\\"\\/Date(1752160017623)\\/\\"}"
}

```

```

public class APIResponse
{
    public int ResponseCode { get; set; }
    public string Description { get; set; }
    public string ResponseContent { get; set; }
}

```

Paramters	Data Type	Description
ResponseCode	string	Status of transaction. 1 is success 0: is process - 320 transaction not exist -357 bank info invalite -1 transaction is fail
Description	string	Description
ResponseContent	string	Contents of transaction results when ResponseCode =1

ResponseContent: JSON of Object when ResponseCode =1

```

public class TransactionInfo
{
    public string RefCode { get; set; }

    public int Amount { get; set; }
    public dateime LastTime { get; set}
}

```

Paramter	Data Type	Description
RefCode	string	Reference Code (Usually will be the Transaction Id of the counterparty, this should be unique)
Amount	int	Amount actually received

LastTime	datetime	Time is transaction success
----------	----------	-----------------------------

3.7 Table ResponseCode

Only ResponseCode = 1 is the case of success, the rest of the codes will be specific failures described in the following error code table.

Code	Description
1	Transaction Successful
-1	Transaction Failed
-323	Parameter Invalid
-313	Signature Invalid
-317	Service Not Exists
-312	Partner Not Exists Not Active
-301	System Error
-310	Access Denied
-5	Transaction Cancel
-356	Bank Amount Invalid
-357	Bank Info Invalid
-352	Bank Code Invalid
-358	Bank Code Maintain
-300	System Maintain
-51	Balance Not Enough