

QXPay

Menu

1. Overview	3
1.1 Purpose	3
1.2 Scope	3
2. Platform	3
2.1 Recharge platform	3
Step 4: Transaction settlement	3
2.2 Cash	4
Step 1 Enter order information cash out	4
Step 3: Transaction settlement	4
3. Recharge API (WebHook - JSon-Post)	5
3.1 Create Order	5
3.2 Callback (Webhook built from partner)	7
3.3 GetTransaction	9
3.4 Table ResponseCode	11
4. Cash API (WebHook - JSon-Post)	11
4.1 GetBalance	11
4.2 Cash	12
4.3 Callback	14
4.4 GetTransaction	15
4.5 Table ResponseCode	17
4.6 Table Bank Code	18

1. Overview

1.1 Purpose

Documentation provided to partners to connect to the Payment system. This document is only for technical staff, programmers responsible for system design, solution integration into Website, Mobile App, or e-commerce application

1.2 Scope

Documentation provided to partners to connect to the Payment system. This document is only for technical staff, programmers responsible for system design, solution integration into Website, Mobile App, or e-commerce application

2. Platform

2.1 Recharge platform

Step 1: Get transfer information

- User enters to get transfer information (Important: It is the content that User needs to enter when making a transfer, in the content contains username to distinguish which user performs the transfer)
- The Partner takes this information and displays it on the screen for the customer to transfer

Step 2: User makes the transfer according to the transfer

- Partner receives customer's electronic order and sends Request to QXPay, QXPay Response for transfer information

Step 3: Announcement of transaction results

- After receiving the order, QXPay will put it in the queue to process the User's transfer

Step 4: Transaction settlement

- QXPay will notify the Partner of the transaction results via the Callback link

2.2 Cash

Step 1 Enter order information cash out

- User accesses the Partner's website and App to place a withdrawal order
- The user enters the account information, the bank to withdraw money, the amount to withdraw

Step 2: The system places cash out orders and announces the results

- QXPay system places cash out orders and announces the results

Step 3: Transaction settlement

- Total payment data will be confirmed by both parties after each reconciliation cycle

3. Recharge API (WebHook - JSon-Post)

3.1 Create Order

- **Description:** Create order & show recive bank
- **URL:** <https://bankgate.qxpay.info/bankin/order.ashx>
- **Method:** POST
- **Content-Type:** application/json
- **In Put:** Json Object

Object RequestData:

```
public class RequestData
{
    public string PartnerCode { get; set; }
    public int Amount { get; set; }
    public string BankCode { get; set; }
    public string CallbackUrl { get; set; }
    public string RefCode { get; set; }
    public string Signature { get; set; }
}
```

Paramters	Data Type	Description
PartnerCode	string	PartnerCode (will provide when connected)
BankCode	string	BankCode=random. The system will randomly return information to a receiving account
RefCode	string	Reference Code (Usually will be the Transaction Id of the counterparty, this should be unique)
Amount	int	Amount of tranfer
CallbackUrl	String	Callback url

Signature	string	Signature: MD5(PartnerCode + BankCode + Amount + RefCode + CallbackUrl + partnerKey) partnerKey : will provide when connected
-----------	--------	---

- **Out Put:**

```
{
  "ResponseCode": 1,
  "Description": "Transaction is successful",
  "ResponseContent":
  "{\"Status\":\"1\",\"BankCode\":\"ACB\",\"Url\":\"xxx\",\"QRCode\":\"xxxx\",\"AccountNumber\":\"123123123\",\"AccountName\":\"Nguyen Van A\",\"Amount\":\"10000\",\"RefCode\":\"1223\",\"OrderNo\":\"AA123123\"}"
}
```

Described as follows:

```
public class APIResponse
{
    public int ResponseCode { get; set; }
    public string Description { get; set; }
    public string ResponseContent { get; set; }
}
```

Paramters	Data Type	Description
ResponseCode	string	Status of transaction (1 sucess)
Description	string	Description
ResponseContent	string	Content of the transaction result (In case the result fails,the content of this string will not be available)

ResponseContent: JSON of List Object

```

public class Order
{
    public string BankCode { get; set; }
    public string BankAccountNumber { get; set; }
    public string BankAccountName { get; set; }
    public int Amount { get; set; }
    public int RefCode { get; set; }
    public string OrderNo { get; set; }
    public string LinkWebView{ get; set; }
    public string QRCode{ get; set; }
}

```

Thuộc tính	Data Type	Description
BankCode	string	Code of bank.
BankAccountNumber	string	Account number to receive
BankAccountName	string	Account Name to receive
Amount	Int	Amount of Tranfer
LinkWebView	string	payment page address
QRCode	String	QR Code (data base64 image)
RefCode	string	The partner's reference code is transmitted in the Request order section
OrderNo	string	The transaction code generated by QXPay is also the transfer content that the User needs to enter when transferring money

3.2 Callback (Webhook built from partner)

- **Description:** This is a partner API built according to the below standards to receive
- **URL:** CallbackUrl parameter at api [3.2](#)
- **Method:** POST
- **Content-Type:** application/json
- **In Put:**

JSON InPut:

```

{
    "ResponseCode": 1,
    "Description": "Transaction is successful",

```

```

    "ResponseContent":
    {"RefCode\":"xxx\","OrderNo\":"EZ12669754\","Amount\:50000,
    \\"Mobile\":"xxxx\","OrderInfo\":"60718786288\"}  "
    "Signature": "778a2c01dbdac3c4310deb1987c9e6e2"
}

```

Body JSON:

```

public class APIResponse
{
    public int ResponseCode { get; set; }
    public string Description { get; set; }
    public string ResponseContent { get; set; }
}

```

Paramters	Data Type	Description
ResponseCode	string	Status of Result
Description	string	Description
ResponseContent	string	Data of Callback
Signature	string	MD5(ResponseCode+ Description+ ResponseContent + partnerKey)

ResponseContent: JSON of List Object

```

public class DataCallback
{
    public string RefCode { get; set; }
    public string OrderNo { get; set; }
    public int Amount { get; set; }
    public int Fee { get; set; }
    public string OrderInfo { get; set; }
}

```

Parameter	Data Type	Description
RefCode	string	Reference Code (Usually will be the Transaction Id of the counterparty, this should be unique)
OrderNo	string	The name of the user performing the money transfer on the system
Amount	int	Amount actually received
Fee	int	Fee Amount

OrderInfo	String	Transaction code of bank or momo
-----------	--------	----------------------------------

- **OutPut:** After receiving the Callback, the partner processes the transaction and returns the string delimiter code|description content as follows
 - **success:** 1|success
 - **failed:** -1|failed

3.3 GetTransaction

- **Description:** get tranfer status
- **URL:** <https://bankgate.qxpay.info/bankin/getdetail.ashx>
- **Method:** Post
- **In Put:** Json Object

Object RequestData:

```
public class RequestData
{
    public string PartnerCode { get; set; }
    public string RefCode { get; set; }
    public string Signature { get; set; }
}
```

Paramters	Data Type	Description
PartnerCode	string	PartnerCode (will provide when connected)
RefCode	string	Reference Code
Signature	string	MD5(partnerCode + RefCode+ partnerKey) partnerKey : will provide when connected

- **Out Put:**

```
{
  "ResponseCode": 1,
  "Description": "Transaction is successful",
```

```

"ResponseContent":
  "{\\"Amount\\":20000,\\"RefCode\\":\\"2\\",\\"TransactionID\\":\\"1000011\\",\\"LasTime\\":\\"\\/Date(1752160017623)\\/\\"}"
}

```

```

public class APIResponse
{
    public int ResponseCode { get; set; }
    public string Description { get; set; }
    public string ResponseContent { get; set; }
}

```

Paramters	Data Type	Description
ResponseCode	string	Status of transaction. 1 is success 0: is process - 320 transaction not exist -357 bank info invalite -1 transaction is fail
Description	string	Description
ResponseContent	string	Contents of transaction results when ResponseCode =1

ResponseContent: JSON of Object when ResponseCode =1

```

public class TransactionInfo
{
    public string RefCode { get; set; }
    public int Fee { get; set; }

    public int Amount { get; set; }
    public datetime LastTime { get; set; }
}

```

Paramter	Data Type	Description
RefCode	string	Reference Code (Usually will be the Transaction Id of the counterparty, this should be unique)
Amount	int	Amount actually received
Fee	int	Fee Amount

LastTime	datetime	Time is transaction success
----------	----------	-----------------------------

■

3.4 Table ResponseCode

Only ResponseCode = 1 is the case of success, the rest of the codes will be specific failures described in the following error code table

Code	Description
1	Transaction Successful
-1	Transaction Failed
-323	Parameter Invalid
-313	Signature Invalid
-317	Service Not Exists
-312	Partner Not Exists Not Active
-301	System Error
-310	Access Denied
-326	Transaction Timeout
-327	Provider Not Found
-356	Bank Amount Invalid
-300	System Maintain

4. Cash API (WebHook - JSon-Post)

4.1 GetBalance

Description get balance

- **URL:** <https://bankgate.qxpay.info/ServiceHandler/GetBalanceV2.ashx>
- **Method:** Get
- **In Put 2 param**

Paramters	Data Type	Mô tả
partnerCode	string	PartnerCode (will provide when connected)

signature	string	MD5(partnerCode +panerKey)
-----------	--------	----------------------------

Out Put: system balance

4.2 Cash

- **Description:** create order to cash out
- **URL:** <https://bankgate.qxpay.info/bankout/cash.ashx>
- **Method:** POST
- **In Put:** Json Object

Object RequestData:

```
public class RequestData
{
    public string PartnerCode { get; set; }
    public string AccountName { get; set; }
    public string AccountNumber { get; set; }
    public string BankCode { get; set; }
    public string RefCode { get; set; }
    public int Amount { get; set; }
    public string CallbackUrl { get; set; }
    public string Signature { get; set; }
}
```

Paramters	Data Type	Description
PartnerCode	string	PartnerCode (will provide when connected)
BankCode	string	Bankcode With Momo BankCode=MOMO Bank code: in the table below
AccountName	string	Account anme receiving money
AccountNumber	string	Account number receiving money
CallbackUrl	Strign	Callback Url
RefCode	string	Reference Code (Usually will be the Transaction Id of the counterparty, this should be unique)

Amount	int	Amount received by the user
Signature	string	MD5(partnerCode + AccountNumber + AccountName + BankCode + Amount + RefCode + CallbackUrl + partnerKey) partnerKey : will provide when connected

- **Out Put:**

```
{
  "ResponseCode": 1,
  "Description": "Transaction is successful",
  "ResponseContent":
    "{\\"Status\\":\\"Success\\",\\"BankcODE\\":\\"MOMO\\",\\"BankAccountNumbe
r\\":\\"0904123456\\",\\"BankAccountName\\":\\"LUU CONG
TUYEN\\",\\"Amount\\":1000000,\\"RefCode\\":\\"RFT0913\\"\\\"OrderNo\\":\\"A
D4571MB
}
```

```
public class APIResponse
{
    public int ResponseCode { get; set; }
    public string Description { get; set; }
    public string ResponseContent { get; set; }
}
```

Paramters	Data Type	Description
ResponseCode	string	Status of transaction results. 1 means successfully receiving the order
Description	string	Description

4.3 Callback

- **Description:** This is a partner API built according to the below standards to receive
- **URL:** it is CallbackUrl param at [4.1](#)
- **Method:** POST
- **Content-Type:** application/json
- **In Put:**

JSON InPut:

```
{  
  "ResponseCode": 1,  
  "Description": "Transaction is successful",  
  "ResponseContent":  
    "{\"RefCode\":\"RE01123\",\"TransactionID\":\"VC9762UA\",\"Amount\":1000000 }",  
  "Signature": "778a2c01dbdac3c4310deb1987c9e6e2"  
}
```

Body of json:

```
public class APIResponse  
{  
    public int ResponseCode { get; set; }  
    public string Description { get; set; }  
    public string ResponseContent { get; set; }  
    public string Signature { get; set; }  
}
```

Paramters	Data Type	Description
ResponseCode	string	Status of Result 1 is success
Description	string	Description
ResponseContent	string	Data of Callback
Signature	string	MD5(ResponseCode+ Description+ ResponseContent + partnerKey)

ResponseContent: JSON of List Object

```
public class DataCallback  
{  
    public string RefCode { get; set; }  
    public string TransactionID{ get; set; }  
    public int Amount { get; set; }  
}
```

Thuộc tính	Data Type	Description
TransactionID	string	Transaction of system
RefCode	string	Reference Code (Usually will be the Transaction Id of the counterparty, this should be unique)
Amount	int	Amount actually received

- **OutPut:** After receiving the Callback, the partner processes the transaction and returns the string delimiter code|description content as follows
 - **success:** 1|success
 - **failed:** -1|failed

4.4 GetTransction

- **Description:** get tranfer status
- **URL:** <https://bankgate.qxpay.info/bankout/getdetail.ashx>
- **Method:** Post
- **In Put:** Json Object

Object RequestData:

```
public class RequestData
{
    public string PartnerCode { get; set; }
    public string RefCode { get; set; }
    public string Signature { get; set; }
}
```

Paramters	Data Type	Description
PartnerCode	string	PartnerCode (will provide when connected)
RefCode	string	Reference Code
Signature	string	MD5(partnerCode + RefCode + partnerKey) partnerKey : will provide when connected

- **Out Put:**

```
{
  "ResponseCode": 1,
  "Description": "Transaction is successful",
  "ResponseContent":
    "{\\"Amount\\":20000,\\"RefCode\\":\\"2\\",\\"TransactionID\\":\\"1000011\\",\\"LasTime\\":\\"\\/Date(1752160017623)\\/\\"}"
```

```
public class APIResponse
{
    public int ResponseCode { get; set; }
    public string Description { get; set; }
    public string ResponseContent { get; set; }
}
```

Paramters	Data Type	Description
ResponseCode	string	Status of transaction. 1 is success 0: is process - 320 transaction not exist -357 bank info invalite -1 transaction is fail
Description	string	Description
ResponseContent	string	Contents of transaction results when ResponseCode =1

ResponseContent: JSON of Object when ResponseCode =1

```
public class TransactionInfo
{
    public string RefCode { get; set; }

    public int Amount { get; set; }
    public dateime LastTime { get; set}
}
```


Paramter	Data Type	Description
RefCode	string	Reference Code (Usually will be the Transaction Id of the counterparty, this should be unique)
Amount	int	Amount actually received
LastTime	datetime	Time is transaction success

4.5 Table ResponseCode

Only ResponseCode = 1 is the case of success, the rest of the codes will be specific failures described in the following error code table.

Code	Description
1	Transaction Successful
-1	Transaction Failed
-323	Parameter Invalid
-313	Signature Invalid
-317	Service Not Exists
-312	Partner Not Exists Not Active
-301	System Error
-310	Access Denied
-326	Transaction Timeout
-327	Provider Not Found
-5	Transaction Cancel
-356	Bank Amount Invalid
-350	Bank Info Invalid
-352	Bank Code Invalid
-358	Bank Code Maintain
-300	System Maintain
-51	Balance Not Enough

4.6 Table Bank Code

ICB - VietinBank

VCB - Vietcombank

BIDV - BIDV

VBA - Agribank

OCB - OCB

MB - MBBank

TCB - Techcombank

ACB - ACB

VPB - VPBank

TPB - TPBank

STB - Sacombank

HDB - HDBank

VCCB - VietCapitalBank

SCB - SCB

VIB - VIB

SHB - SHB

EIB - Eximbank

MSB - MSB

SGICB - SaigonBank

BAB - BacABank

PVCB - PVcomBank

Oceanbank - Oceanbank

NCB - NCB

SHBVN - ShinhanBank

ABB - ABBANK

VAB - VietABank

NAB - NamABank

PGB - PGBank
VIETBANK - VietBank
BVB - BaoVietBank
SEAB - SeABank
COOPBANK - COOPBANK
LPB - LienVietPostBank
KLB - KienLongBank
KBank - KBank
UOB - UnitedOverseas
SCVN - StandardChartered
PBVN - PublicBank
NHB HN - Nonghyup
IVB - IndovinaBank
IBK - HCM - IBKHCM
IBK - HN - IBKHN
VRB - VRB
WVN - Woori
KBHN - KookminHN
KBHCM - KookminHCM
HSBC - HSBC
HLBVN - HongLeong
GPB - GPBank
DOB - DongABank
DBS - DBSBank
CIMB - CIMB
CBB - CBBank
CITIBANK - Citibank
KEBHANAHCN - KEBHanaHCN
KEBHANAHN - KEBHANAHN

MAFC - MAFC

VBSP - VBSP