

28Pay

Mục lục

1. Overview	4
1.1 Purpose of the document	4
1.2 Scope	4
2. UseCard	5
2.1 Request	5
2.2 Table ResponseCode	7
2.3 Callback	7

1. Overview

1.1 Purpose of the document

Instructions on how to connect the Payment Gateway system with other service systems

1.2 Scope

Documentation provided to partners to connect to the Payment system

2. UseCard

- URL: <https://apicard.28pay.info/usecard.ashx>
- (JSON Post)

2.1 Request

- **Description:** function to use card
- **In Put:**

Object RequestData: (Serialize Object)

Object UseCardRequest:

```
public class RequestData
{
    public string PartnerCode { get; set; }

    public string CardSerial { get; set; }
    public string CardCode { get; set; }
    public string CardType { get; set; }
    public string RefCode { get; set; }
    public string CallbackUrl { get; set; }
    public int Amount { get; set; }
    public string Signature { get; set; }
}
```

Paramters	Data Type	Description
Partnercode	string	Partnercode (will provide when connected)
CardSerial	string	Serial
CardCode	string	Pin
CardType	string	Card Type ▪ vms: Mobiphone ▪ vnp: Vinaphone ▪ viettel: Viettel ▪ zing: zing ▪ vcoin: vcoin

RefCode	string	Reference Code (Usually will be the Transaction Id of the counterparty, this should be unique)
Amount	int	Denomination of card (Requires standard)
CallbackUrl	string	Callback url (Use in case of questionable card processing or slow processing after a 90-second waiting period)
Signature	string	signature: MD5(PartnerCode + cardcode + cardserial + refcode + partnerKey) partnerKey : will provide when connected

Sample JSON Request:

```
{
  "partnerCode": "xxx",
  "CardSerial": "xxx",
  "CardCode": "xxxx",
  "CardType": "xxxx",
  "Amount": 50000,
  "RefCode": "1708185637",
  "CallbackUrl": "xxx",
  "signature": "2d684522e32c28dacd6f1a5a8fffb4b2"
}
```

- **Out Put:**

JSON of **Object APIResponse**

```
public class APIResponse
{
    public int ResponseCode { get; set; }
    public string Description { get; set; }
    public string ResponseContent { get; set; }
    public string Signature { get; set; }
}
```

Paramters	Data Type	Option	Description
ResponseCode	int	yes	The error code in case 0 is card process waiting callback. In other cases, see the error code table for details
Description	string	no	Description

2.2 Table ResponseCode

ResponseCode

Code	Desription
6	Received card successfully
-330	Used card
-331	The card has been locked
-332	Card is expired
-333	The card does not exist or has not been activated.
-334	Invalid serial number or card code
-335	Invalid card code or serial number
-323	The parameter passed is incorrect
-1	Fail
-7	Transaction Rejected
-326	Timeout

2.3 Callback

- **Mothead:** POST
- **Content-Type:** application/json
- **In Put:**

Paramters	Data Type	Description
RefCode	string	Reference Code of parner
Status	int	Status (1 is success)
Amount	int	Amount of Card
Signature	string	Signature MD5(RefCode + Status + Amount + PartnerKey)

- **OutPut: return string**
 - success: 1|success
 - failed: -1|failed

