

SHOP THENHANH

Mục lục

1. Overview	4
1.1 Purpose of the document	4
1.2 Scope	4
2. Method	5
2.1 Request	5
2.2 Service Code: cardtelco	5
2.2.1.1 Command Code: usecard	5
2.2.1.1.1 Table of CardType	7
2.2.1.1.2 Table ResponseCode	7
2.2.1.2 Callback (when case Status = -2, -326 for function usecard)	8

1. Overview

1.1 Purpose of the document

Instructions on how to connect the Payment Gateway system with other service systems

1.2 Scope

Documentation provided to partners to connect to the Payment system

2. Method

- URL: <https://apicard.coroach.xyz/VPJsonService.ashx> (JSON Post)

2.1 Request

2.2 Service Code: cardtelco

2.2.1.1 Command Code: usecard

- **Description:** function to use card
- **In Put:**

Object RequestData: (Serialize Object)

```
public class RequestData
{
    public string PartnerCode { get; set; }
    public string ServiceCode { get; set; }
    public string CommandCode { get; set; }
    public string RequestContent { get; set; }
    public string Signature { get; set; }
}
```

Paramters	Data Type	Option	Description
partnerCode	string	yes	Partnercode (will provide when connected)
serviceCode	string	yes	serviceCode: cardtelco
commandCode	string	yes	commandCode: usecard
requestContent	string	yes	JSON of Object UseCardRequest
signature	string	yes	signature: MD5(partnerCode + serviceCode + commandCode + requestContent + partnerKey) partnerKey : will provide when connected

Object UseCardRequest:

```
public class UseCardRequest
{
    public string CardSerial { get; set; }
    public string CardCode { get; set; }
}
```

```

        public string CardType { get; set; }
        public string AccountName { get; set; }
        public string AppCode { get; set; }
        public string RefCode { get; set; }
    }

```

Paramters	Data Type	Option	Description
CardSerial	string	yes	Serial
CardCode	string	yes	Pin
CardType	string	yes	Card Type ▪ vms: Mobiphone ▪ vnp: Vinaphone ▪ viettel: Viettel
AccountName	string	yes	AccountName of your system
RefCode	string	yes	Reference Code (Usually will be the Transaction Id of the counterparty, this should be unique)
AppCode	string	not	Default “ ”
AmountUser	int		Mệnh giá thẻ khai báo (Cần chuẩn)
CallbackUrl	string		Callback url (Use in case of questionable card processing or slow processing after a 90-second waiting period)

Sample JSON Request:

```

{"PartnerCode":"pp1","ServiceCode":"cardtelco","CommandCode":"usecard","RequestContent":{"CardSerial":"072231000005868","CardCode":"807674683479","CardType":"vnp","AccountName":"big.002","AppCode":"UnitTest","RefCode":"00008","Amount":0,"AmountUser":10000,"CallbackUrl":"http://dichvu001.com"},"Signature":"ccc946073dcd9414abcceb0253b78472"}

```

• Out Put:

JSON of Object APIResponse

```

public class APIResponse
{
    public int ResponseCode { get; set; }
    public string Description { get; set; }
    public string ResponseContent { get; set; }
}

```

```

        public string Signature { get; set; }
    }

```

Paramters	Data Type	Option	Description
ResponseCode	int	yes	The error code in case 1 is successful. In other cases, see the error code table for details
ResponseContent	string	yes	Real Amount of Card
Description	string	no	Description
Signature	string	no	Signature

2.2.1.1.1 Table of CardType

code	Telco
viettel	Viettel
vms	Mobifone
vnp	Vinaphone

2.2.1.1.2 Table ResponseCode

Duy nhất **mã = 1** là trường hợp thành công còn lại các mã khác sẽ là thất bại cụ thể được miêu tả trong bảng mã lỗi sau

Code	Desription
1	Susscess
-330	Used card
-331	The card has been locked
-332	Card is expired

-333	The card does not exist or has not been activated.
-334	Invalid serial number or card code
-335	Invalid card code or serial number
-323	The parameter passed is incorrect
-1	Fail
-7	Transaction Rejected
-326	Timeout
-372	Incorrect card value compared to the declaration (Note that in this case, an error code will be returned but the Amount will still be in the ResponseContent)
-2	Questionable card (Success or failure card ? SHOP will apply Notify automatically)

2.2.1.2 Callback (when case Status = -2, -326 for function usecard)

- **Descriptoin** : Error codes -2, -326 SHOP will use the re-scan and process method. If these cases are successful, the system will process and return the results via the Url Callback transmitted by the partner in section 3.1. first . Partners need to build this Service according to the standards below
- **Mothead**: POST
- **Content-Type**: application/json
- **In Put**:

Paramters	Data Type	Option	Description
RefCode	string	yes	Reference Code of parner
Status	int	yes	Status

Amount	int	yes	Amount of Card
Signature	string	No	Signature MD5(RefCode + Status + Amount + PartnerKey)

- **OutPut: return string**
 - success: 1|success
 - failed: -1|failed