

SHOP

DOCUMENTS READING CONNECTION OF BANK, CASH OUT Wallet PAYMENT GATEWAY

1. Overview	3
1.1 Purpose	3
1.2 Scope	3
2. Plaform	3
3. Method (WebHook - JSon-Post).....	4
3.1 Cash	4
3.2 Table ResponseCode	8
3.3 Table of BankCode.....	9

1. Overview

1.1 Purpose

Instructions on how to connect the Payment Gateway system with other service systems

1.2 Scope

Documentation provided to partners to connect to the Payment system. This document is only for technical staff, programmers responsible for system design, solution integration into Website, Mobile App, or e-commerce application.

2. Plaform

Setp 1 Enter order information cash out

User accesses the Partner's website and App to place a withdrawal order

The user enters the account information, the bank to withdraw money, the amount to withdraw

Step 2: The SHOP system places cash out orders and announces the results

The SHOP system places cash out orders and announces the results

Step 4: Transaction settlement

- Total payment data will be confirmed by both parties after each reconciliation cycle

3. Method (WebHook - JSon-Post)

3.1 Cash

- **URL:** <https://bankgate.coroach.xyz/VPJsonService.ashx>
- **Method:** POST
- **In Put:** JSON

Object RequestData:

```
public class RequestData
{
    public string PartnerCode { get; set; }
    public string ServiceCode { get; set; }
    public string CommandCode { get; set; }
    public string RequestContent { get; set; }
    public string Signature { get; set; }
}
```

Parameters	Data Type	Description
PartnerCode	string	partnerCode (will provide when connected)
ServiceCode	string	serviceCode: bankcash
CommandCode	string	commandCode: cash
RequestContent	string	LJSON of Object: OrderRequest
Signature	string	signature: MD5(partnerCode + serviceCode + commandCode + requestContent + partnerKey) partnerKey : will provide when connected

requestContent JSON of Object OrderRequest:

```
public class OrderRequest
{
```

```

    public string Type { get; set; }
    public string BankName { get; set; }
    public string BankAccountName { get; set; }
    public string BankAccountNumber { get; set; }
    public string AppCode { get; set; }
    public string Note { get; set; }

    public string RefCode { get; set; }
    public int Amount { get; set; }
    public string CallbackUrl { get; set; }
}

```

Parameter	Data Type	Optional	Description
Type	string	Yes	Type: momocash Momo bankcash Bank
BankName	string	Yes	Bankcode momo : Momo wallet Bank code: in the table below
BankAccountName	string	Yes	Account name receiving money
BankAccountNumber	string	Yes	Account number receiving money
AppCode	string	No	
Note	String	Yes	Note
CallbackUrl	Strign	Yes	Callback Url
RefCode	string	Yes	Reference Code (Usually will be the TransactionId of the counterparty, this should be unique)
Amount	int	Yes	Amount received by the user (from 50,000 to 20,000,000)

- **Out Put:**

```

{
    "ResponseCode": 1,
    "Description": "Transaction is successful",
}

```

```

    "ResponseContent": "",
    "Signature": "778a2c01dbdac3c4310deb1987c9e6e2"
}

```

Description:

```

public class APIResponse
{
    public int ResponseCode { get; set; }
    public string Description { get; set; }
    public string ResponseContent { get; set; }
}

```

Parameters	Data Type	Description
ResponseCode	string	Status of transaction results
Description	string	Description
ResponseContent	string	Contents of transaction results (In case of failure results, the content of this string will not be Yes)

ResponseContent: JSON of Object

```

public class Order
{
    public string Status { get; set; }
    public string BankName { get; set; }
    public string BankAccountNumber { get; set; }
    public string BankAccountName { get; set; }
    public int Amount { get; set; }
    public int RefCode { get; set; }
    public string OrderNo { get; set; }
}

```

Paramters	Data Type	Description
Status	string	Transaction reference status
BankName	string	Bank code, receiving e-wallet
BankAccountNumber	string	Receiving account number
BankAccountName	string	Recipient Account Name
Amount	Int	Amount the customer will receive
RefCode	string	The reference code of the partner passed in the Request order field

--	--	--

3.2 Callback

Description : This is a partner API built according to the below standards to receive transaction

URL: supply partner

Method: POST

Content-Type: application/json

In Put:

JSON InPut:

```
{
  "ResponseCode": 1,
  "Description": "Transaction is successful",
  "ResponseContent":
    "{\"RefCode\":\"RE01123\",\"TransactionID\":\"VC9762UA\",\"Amount\":\"1000000\"}",
  "Signature": "778a2c01dbdac3c4310deb1987c9e6e2"
}
```

Body is JSON:

```
public class APIResponse
{
    public int ResponseCode { get; set; }
    public string Description { get; set; }
    public string ResponseContent { get; set; }
    public string Signature { get; set; }
}
```

Paramters	Data Type	Description
ResponseCode	string	Status of Result
Description	string	Description
ResponseContent	string	Data of Callback
Signature	string	Sign: MD5(ResponseCode+ Description+
		ResponseContent + partnerKey) partnerKey :

ResponseContent: JSON of Object

```

public class DataCallback
{
    public string RefCode { get; set; }
    public string TransactionID { get; set; }
    public int Amount { get; set; }
}

```

Propertie	Data Type	Option	Description
RefCode	string	yes	Reference Code (Usually will be the Transaction Id of the counterparty, this should be unique)
TransactionID	string	yes	Transaciton of system
Amount	int	yes	Amount actually received (Exactly the amount that User made the transfer)

OutPut: After receiving the Callback, the partner processes the transaction and returns the string delimiter code|description content as follows

Success T: 1|success

Failed: -1|failed

3.3 Check Cash

- **Description:** Check cash → get status of cash
- **URL:** <https://bankgate.coroach.xyz/VPGJsonService.ashx>
- **Method:** POST
- **In Put:** JSON of List Object
- **Object RequestData:**

```

public class RequestData
{
    public string PartnerCode { get; set; }
    public string ServiceCode { get; set; }
    public string CommandCode { get; set; }
    public string RequestContent { get; set; }
    public string Signature { get; set; }
}

```

Paramters	Data Type	Optional	Description
PartnerCode	string	Yes	partnerCode (swill provide when connected)
ServiceCode	string	Yes	serviceCode : bankcash
CommandCode	string	Yes	commandcode : checktrans
RequestContent	string	Yes	Reference Code . it is RefCode in api 3.2

Signature	string	Có	Sign: MD5(partnerCode + serviceCode + commandCode + requestContent + partnerKey) partnerKey : will provide when connected

Out Put:

```
{
  "ResponseCode": 1,
  "Description": "Transaction is successful",
  "ResponseContent":
    "{\\"RefCode\\":\\"xxxxx\\",\\"Amount\\":10000,\\"LasTime\\":\\"\\Date(1552038984297)\\\\"}"
  "Signature": "778a2c01dbdac3c4310deb1987c9e6e2"
}
```

Described as follows

```
public class APIResponse
{
    public int ResponseCode { get; set; }
    public string Description { get; set; }
    public string ResponseContent { get; set; }
    public string Signature { get; set; }
}
```

Parameter	Data Type	Optional	Description
ResponseCode	string	Yes	Status of transaction. 1 is success , 0: is process, - 320 transaction not exist, -1 transaction is fail
Description	string	Yes	Description
ResponseContent	string	Yes	Contents of transaction results when ResponseCode =1
signature	string	Yes	Sign: MD5(partnerCode + serviceCode + commandCode + requestContent + partnerKey) partnerKey : will provide when connected

ResponseContent: JSON of Object when ResponseCode =1

```
public class TransactionInfo
{
    public string RefCode { get; set; }

    public int Amount { get; set; }
    public dateime LastTime { get; set;}
}
```

Paramter	Data Type	Description
RefCode	string	Reference Code (Usually will be the Transaction Id of the counterparty, this should be unique)
Amount	int	Amount actually received
LastTime	datetime	Time is transaction success

3.4 Table ResponseCode

Only ResponeCode = 1 is the case of success, the rest of the codes will be specific failures described in the following error code table.

Code	Description
1	Transaction Successful
-1	Transaction Failed
-323	Parameter Invalid
-313	Signature Invalid
-317	Service Not Exists
-312	Partner Not Exists Not Active
-301	System Error
-310	Access Denied
-326	Transaction Timeout
-327	Provider Not Found
-8	Transaction Pending
-9	Transaction Processing
-5	Transaction Cancel
-356	Bank Amount Invalid
-350	Bank Info Innvalid
-352	Bank Code Invalid

3.5 Table of BankCode

ICB - VietinBank
VCB - Vietcombank

BIDV - BIDV
VBA - Agribank
OCB - OCB
MB - MBBank
TCB - Techcombank
ACB - ACB
VPB - VPBank
TPB - TPBank
STB - Sacombank
HDB - HDBank
VCCB - VietCapitalBank
SCB - SCB
VIB - VIB
SHB - SHB
EIB - Eximbank
MSB - MSB
SGICB - SaigonBank
BAB - BacABank
PVCB - PVcomBank
Oceanbank - Oceanbank
NCB - NCB
SHBVN - ShinhanBank
ABB - ABBANK
VAB - VietABank
NAB - NamABank
PGB - PGBank
VIETBANK - VietBank
BVB - BaoVietBank
SEAB - SeABank
COOPBANK - COOPBANK
LPB - LienVietPostBank
KLB - KienLongBank
KBank - KBank
UOB - UnitedOverseas
SCVN - StandardChartered
PBVN - PublicBank
NHB HN - Nonghyup
IVB - IndovinaBank
IBK - HCM - IBKHCM
IBK - HN - IBKHN
VRB - VRB
WVN - Woori
KBHN - KookminHN
KBHCM - KookminHCM
HSBC - HSBC
HLBVN - HongLeong
GPB - GPBank
DOB - DongABank
DBS - DBSBank
CIMB - CIMB
CBB - CBBank
CITIBANK - Citibank

KEBHANAHCM - KEBHanaHCM

KEBHANAHN - KEBHANAHN

MAFC - MAFC

VBSP - VBSP