

SHOP

1. Overview	3
1.1 Purpose of the document	3
1.2 Scope	3
2. Platform	3
3. Method (WebHook - JSon-Post)	4
3.1 Get List Bank	4
3.2 Create Order	6
3.3 Callback	9
3.4 Table of ResponseCode	10

1. Overview

1.1 Purpose of the document

Instructions on how to connect the Payment Gateway system with other service systems

1.2 Scope

Documentation provided to partners to connect to the Payment system. This document is only for technical staff, programmers responsible for system design, solution integration into Website, Mobile App, or e-commerce application

2. Platform

Step 1: Get transfer information

- User enters to get transfer information (**Important → It is the content that User needs to enter when making a transfer, in the content contains username to distinguish which user performs the transfer**)
- The Partner takes this information and displays it on the screen for the customer to transfer
- **Note :**
 - *Should leave the COPY feature of each transaction information for the convenience of the User*

Step 2: User makes the transfer according to the transfer

Step 3: Announcement of transaction results

The SHOP will notify the Partner of the transaction results through the Callback link

Bước 4: Transaction settlement

Total payment data will be confirmed by both parties after each reconciliation cycle

3. Method (WebHook - JSon-Post)

3.1 Get List Bank (For bank)

- **Desription** get list of banks. Momo skip this function
- **URL:** <https://bankgate.coroach.xyz/VPJsonService.ashx>
- **Method:** POST
- **InPut:** JSON **Object RequestData:**

```
public class RequestData
{
    public string PartnerCode { get; set; }
    public string ServiceCode { get; set; }
    public string CommandCode { get; set; }
    public string RequestContent { get; set; }
    public string Signature { get; set; }
}
```

Paramters	Data Type	Optional	Descripton
PartnerCode	string	yes	partnerCode (swill provide when connected)
ServiceCode	string	yes	serviceCode : bankdirect
CommandCode	string	yes	commandCode : getbanks
RequestContent	string	yes	JSON of Object: GetBankRequest
Signature	string	yes	signature: MD5(partnerCode + serviceCode + commandCode + requestContent + partnerKey) partnerKey : will provide when connected

requestContent JSON of Object GetBankRequest:

```
public class GetBankRequest
{
    public string AccountName { get; set; }

    public string Type { get; set; }
}
```

Paramters	Data Type	Optional	Description
AccountName	String	yes	username of partner's system

Type	string	yes	Type : bank
------	--------	-----	--------------------

- **OutPut**

JSON OutPut: like that

```
{
  "ResponseCode": 1,
  "Description": "Transaction is successful",
  "ResponseContent":
    "[{"BankName\\":\\"TCB\\",\\"Name\\"\\":\\"Techcombank\\"},{\\"BankName\\":\\"VCB\\",\\"Name\\"\\":\\"Vietcombank\\"}]",
  "Signature": "0503f99407575c2c0597c907fca82cff"
}
```

Described as follows

```
public class APIResponse
{
    public int ResponseCode { get; set; }
    public string Description { get; set; }
    public string ResponseContent { get; set; }
    public string Signature { get; set; }
}
```

Paramters	Data Type	Optional	Description
ResponseCode	string	yes	Status of transaction
Description	string	yes	Description
ResponseContent	string	yes	Contents of transaction results
signature	string	yes	signature: MD5(partnerCode + serviceCode + commandCode + requestContent + partnerKey)

ResponseContent: JSON of List Object

```
public class BankAccount
{
    public string BankName { get; set; }
    public string Name { get; set; }
}
```

Paramters	Data Type	Description
-----------	-----------	-------------

BankName	string	Code of Bank
Name	string	Nam of Bank

3.2 Create Order

- **Description:** Create order → show recive bank
- **URL:** <https://bankgate.coroach.xyz/VPGJsonService.ashx>
- **Method:** POST
- **In Put:** JSON of List Object
- **Object RequestData:**

```
public class RequestData
{
    public string PartnerCode { get; set; }
    public string ServiceCode { get; set; }
    public string CommandCode { get; set; }
    public string RequestContent { get; set; }
    public string Signature { get; set; }
}
```

Paramters	Data Type	Optional	Description
PartnerCode	string	Yes	partnerCode (swill provide when connected)
ServiceCode	string	Yes	serviceCode : bankdirect
CommandCode	string	Yes	commandcode : order
RequestContent	string	Yes	JSON of Object: OrderRequest
Sgnature	string	Có	Sign: MD5(partnerCode + serviceCode + commandCode + requestContent + partnerKey) partnerKey : will provide when connected

requestContent is JSON of **Object OrderRequest**:

```
public class OrderRequest
{
    public string Type { get; set; }
    public string AccountName { get; set; }
```

```

        public string BankName { get; set; }
        public string AppCode { get; set; }
        public string RefCode { get; set; }
        public int Amount { get; set; }
        public string CallbackUrl { get; set; }
    }

```

Parameter	Data Type	Optional	Mô tả
Type	string	yes	Type: banktransfer (bank) momo (momo)
AccountName	string	yes	AccountName of your system
BankName	string	yes	momo : Momo wallet Bank code: in the first api
AppCode	string	yes	Default “ ”
RefCode	string	yes	Reference Code (Usually will be the Transaction Id of the counterparty, this should be unique)
Amount	int	int	Amount of tranfer
CallbackUrl	String	yes	Callback url

- **Out Put:**

```

{
    "ResponseCode": 1,
    "Description": "Transaction is successful",
    "ResponseContent":
    "{\\"Status\\":\\"pending\\",\\"BankName\\":\\"Vietcombank\\",\\"BankAccountNumber\\":\\"0491000173648\\",\\"BankAccountName\\":\\"LUU CONG TUYEN\\",\\"Amount\\":1000000,\\"RefCode\\":\\"RFT0913\\",\\"OrderNo\\":\\"AD4571MB\\",\\"Timeout\\":30},\\"Url\\":\\"xxx.com\\",
    "Signature": "778a2c01dbdac3c4310deb1987c9e6e2"
}

```

Described as follows

```

public class APIResponse
{
    public int ResponseCode { get; set; }
    public string Description { get; set; }
    public string ResponseContent { get; set; }
    public string Signature { get; set; }
}

```

}

Parameter	Data Type	Optional	Mô tả
ResponseCode	string	Yes	Status of transaction
Description	string	Yes	Description
ResponseContent	string	Yes	Contents of transaction results
signature	string	Yes	Sign: MD5(partnerCode + serviceCode + commandCode + requestContent + partnerKey) partnerKey : will provide when connected

ResponseContent: JSON of Object

```
public class Order
{
    public string Status { get; set; }
    public string BankName { get; set; }
    public string BankAccountNumber { get; set; }
    public string BankAccountName { get; set; }
    public int Amount { get; set; }
    public int RefCode { get; set; }
    public string OrderNo { get; set; }
    public int Timeout { get; set; }
}
```

Paramter	Data Type	Description
Status	string	Status of transaction
BankName	string	Code of Bank
BankAccountNumber	string	Account number to receive
BankAccountName	string	Account Name to receive
LinkOpenApp	string	Link to open momo app to transfer money
QRCode	string	QRCode momo money transfer (base64 data format)
Amount	Int	Amount of Tranfer
RefCode	string	Reference Code (Usually will be the Transaction Id of the counterparty, this should be unique)
OrderNo	string	The name of the user performing the money transfer on the system

3.3 Callback

- **Description** : This is a partner API built according to the below standards to receive transaction
- **URL: supply partner**
- **Method: POST**
- **Content-Type: application/json**
- **In Put:**

Chuỗi JSON InPut:

```
{  
  "ResponseCode": 1,  
  "Description": "Transaction is successful",  
  "ResponseContent": "{ \"RefCode\": \"RE01123\", \"OrderNo\": \"test\", \"Amount\": 1000000 }",  
  "Signature": "778a2c01dbdac3c4310deb1987c9e6e2"  
}
```

Body is JSON:

```
public class APIResponse  
{  
    public int ResponseCode { get; set; }  
    public string Description { get; set; }  
    public string ResponseContent { get; set; }  
    public string Signature { get; set; }  
}
```

Paramters	Data Type	Option	Description
ResponseCode	string	Yes	Status of Result
Description	string	Yes	Description
ResponseContent	string	Yes	Data of Callback
signature	string	Yes	Sign: MD5(ResponseCode+ Description+ ResponseContent + partnerKey) partnerKey :

ResponseContent: JSON of Object

```
public class DataCallback  
{
```

```

        public string RefCode { get; set; }
        public string OrderNo { get; set; }

        public string Amount { get; set; }
    }

```

Thuộc tính	Data Type	Option	Description
RefCode	string	yes	Reference Code (Usually will be the Transaction Id of the counterparty, this should be unique)
OrderNo	string	yes	The name of the user performing the money transfer on the system
Amount	int	yes	Amount actually received (Exactly the amount that User made the transfer)

- **OutPut:** After receiving the Callback, the partner processes the transaction and returns the string delimiter code|description content as follows
 - **Success T:** 1|success
 - **Failed:** -1|failed

3.4 Table of ResponseCode

Only ResponseCode = 1 is the case of success, the rest of the codes will be specific failures described in the following error code table

Code	Description
1	Transaction Successful
-1	Transaction Failed
-323	Parameter Invalid
-313	Signature Invalid
-317	Service Not Exists
-312	Partner Not Exists Not Active
-301	System Error
-310	Access Denied
-326	Transaction Timeout

-327	Provider Not Found
-8	Transaction Pending
-9	Transaction Processing
-5	Transaction Cancel
-356	Bank Amount Invalid
...	...