

**TN99Pay**

## Menu

|                                                |   |
|------------------------------------------------|---|
| <b>1. Overview</b>                             | 1 |
| 1.1 Purpose                                    | 1 |
| 1.2 Scope                                      | 1 |
| <b>2. Platform</b>                             | 1 |
| 2.1 Recharge platform                          | 1 |
| <b>Step 4: Transaction settlemen</b>           | 1 |
| 2.2 Cash                                       | 1 |
| <b>Step 1 Enter order information cash out</b> | 1 |
| <b>Step 3: Transaction settlement</b>          | 1 |
| <b>3. Recharge API (WebHook - JSon-Post)</b>   | 1 |
| 3.1 Get List Bank Code                         | 1 |
| 3.2 Create Order                               | 1 |
| 3.3 Callback (Webhook buil from partner)       | 1 |
| 3.4 GetTransction                              | 1 |
| 3.5 Table ResponseCode                         | 1 |
| <b>4. Cash API (WebHook - JSon-Post)</b>       | 1 |
| 4.1 GetBalance                                 | 1 |
| 4.2 Cash                                       | 1 |
| 4.3 Callback                                   | 1 |
| 4.4 GetTransction                              | 1 |
| 4.5 Table ResponseCode                         | 1 |
| 4.6 Table Bank Code                            | 1 |

# 1. Overview

## 1.1 Purpose

Documentation provided to partners to connect to the Payment system. This document is only for technical staff, programmers responsible for system design, solution integration into Website, Mobile App, or e-commerce application

## 1.2 Scope

Documentation provided to partners to connect to the Payment system. This document is only for technical staff, programmers responsible for system design, solution integration into Website, Mobile App, or e-commerce application

# 2. Platform

## 2.1 Recharge platform

### Step 1: Get transfer information

- User enters to get transfer information (Important → It is the content that User needs to enter when making a transfer, in the content contains username to distinguish which user performs the transfer)
- The Partner takes this information and displays it on the screen for the customer to transfer

### Step 2: User makes the transfer according to the transfer

- Partner receives customer's electronic order and sends Request to FastPay, FastPay Response for transfer information

### Step 3: Announcement of transaction results

- After receiving the order, FastPay will put it in the queue to process the User's transfer

**Step 4: Transaction settlement**

- FastPay will notify the Partner of the transaction results via the Callback link

**2.2 Cash****Step 1 Enter order information cash out**

- User accesses the Partner's website and App to place a withdrawal order
- The user enters the account information, the bank to withdraw money, the amount to withdraw

**Step 2: The system places cash out orders and announces the results**

- FastPay system places cash out orders and announces the results

**Step 3: Transaction settlement**

- Total payment data will be confirmed by both parties after each reconciliation cycle

### 3. Recharge API (WebHook - JSon-Post)

#### 3.1 Get List Bank Code

- **Description:** get list of banks. Momo skip this function
- **URL:** <https://bankgate.tn99.info/bankin/info.ashx>
- **Method:** POST
- **Content-Type:** application/json
- **InPut:** Json Object

**Object RequestData:**

```
public class RequestData
{
    public string PartnerCode { get; set; }
}
```

| Paramters   | Data Type | Description                               |
|-------------|-----------|-------------------------------------------|
| PartnerCode | string    | PartnerCode (will provide when connected) |

**JSON OutPut:**

```
{
  "ResponseCode": 1,
  "Description": "Transaction is successful",
  "ResponseContent": "[{"BankName": "ACB", "Name": "Ngân hàng Á Châu ACB"}, {"BankName": "VCB", "Name": "Vietcombank"}]",
}
```

**Described as follows:**

```
public class APIResponse
{
    public int ResponseCode { get; set; }
    public string Description { get; set; }
    public string ResponseContent { get; set; }
}
```

}

| Paramters       | Data Type | Description                                                                                                   |
|-----------------|-----------|---------------------------------------------------------------------------------------------------------------|
| ResponseCode    | string    | Status of transaction (1 sucess)                                                                              |
| Description     | string    | Description                                                                                                   |
| ResponseContent | string    | Content of the transaction result (In case the result fails,the content of this string will not be available) |

**ResponseContent:** JSON of List Object

```
public class BankAccount
{
    public string BankCode { get; set; }
    public string Name { get; set; }
}
```

| Paramters | Data Type | Description  |
|-----------|-----------|--------------|
| BankName  | string    | Code of bank |
| Name      | string    | Name of bank |

### 3.2 Create Order

- **Description:** Create order → show recive bank

**URL:** <https://bankgate.tn99.info/bankin/order.ashx>

- **Method:** POST
- **Content-Type:** application/json
- **In Put:** Json Object

**Object RequestData:**

```
public class RequestData
{
```

```

    public string PartnerCode { get; set; }
    public int Amount { get; set; }
    public string BankCode { get; set; }
    public string CallbackUrl { get; set; }
    public string RefCode { get; set; }
    public string Signature { get; set; }
}

```

| Paramters   | Data Type | Description                                                                                                                                                                                                                                                                           |
|-------------|-----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| PartnerCode | string    | PartnerCode (will provide when connected)                                                                                                                                                                                                                                             |
| BankCode    | string    | <p>Bank code that the User chooses (get the list in api section 3.1)</p> <p>In case the partner does not want to choose a bank, he or she can transmit BankCode=random. The system will randomly return information to a receiving account</p> <p><b>With momo BankCode =MOMO</b></p> |
| RefCode     | string    | Reference Code (Usually will be the Transaction Id of the counterparty, this should be unique)                                                                                                                                                                                        |
| Amount      | int       | Amount of tranfer                                                                                                                                                                                                                                                                     |
| CallbackUrl | String    | Callback url                                                                                                                                                                                                                                                                          |
| Signature   | string    | <p>Signature:</p> <p>MD5(<b>PartnerCode + BankCode + Amount + RefCode + CallbackUrl + partnerKey</b>)</p> <p>partnerKey : will provide when connected</p>                                                                                                                             |

- **Out Put:**

```

{
  "ResponseCode": 1,
  "Description": "Transaction is successful",
  "ResponseContent":
    "{\"Status\":\"1\", \"BankCode\":\"ACB\", \"Url\":\"xxx\", \"QRCode\":"
    "\"xxxx\", \"AccountNumber\":\"123123123\", \"AccountName\":\"Nguy"
    "en Van"
    "A\", \"Amount\":\"10000\", \"RefCode\":\"1223\", \"OrderNo\":\"AA123123\"}"
}

```

**Described as follows:**

```

public class APIResponse
{
    public int ResponseCode { get; set; }
    public string Description { get; set; }
    public string ResponseContent { get; set; }
}

```

| Paramters       | Data Type | Description                                                                                                   |
|-----------------|-----------|---------------------------------------------------------------------------------------------------------------|
| ResponseCode    | string    | Status of transaction (1 sucess)                                                                              |
| Description     | string    | Description                                                                                                   |
| ResponseContent | string    | Content of the transaction result (In case the result fails,the content of this string will not be available) |

**ResponseContent: JSON of List Object**

```

public class Order
{
    public string BankCode { get; set; }
    public string BankAccountNumber { get; set; }
    public string BankAccountName { get; set; }
    public int Amount { get; set; }
    public int RefCode { get; set; }
    public string OrderNo { get; set; }
    public string LinkWebView{ get; set; }
    public string QRCode{ get; set; }
}

```

| Thuộc tính        | Data Type | Description                                                                                                                        |
|-------------------|-----------|------------------------------------------------------------------------------------------------------------------------------------|
| BankCode          | string    | Code of bank.                                                                                                                      |
| BankAccountNumber | string    | Account number to receive                                                                                                          |
| BankAccountName   | string    | Account Name to receive                                                                                                            |
| Amount            | Int       | Amount of Tranfer                                                                                                                  |
| LinkWebView       | string    | payment page address                                                                                                               |
| QRCode            | String    | QR Code (data base64 image)                                                                                                        |
| RefCode           | string    | The partner's reference code is transmitted in the Request order section                                                           |
| OrderNo           | string    | <b>The transaction code generated by FastPay is also the transfer content that the User needs to enter when transferring money</b> |

### 3.3 Callback (Webhook built from partner)

- **Description:** This is a partner API built according to the below standards to receive
- **URL:** CallbackUrl parameter at api [3.2](#)
- **Method:** POST
- **Content-Type:** application/json
- **In Put:**

**JSON InPut:**

```
{
  "ResponseCode": 1,
  "Description": "Transaction is successful",
  "ResponseContent":
  {
    "RefCode": "xxx",
    "OrderNo": "EZ12669754",
    "Amount": 50000,
    "Fee": 500,
    "OrderInfo": "60718786288"
  }
  "Signature": "778a2c01dbdac3c4310deb1987c9e6e2"
}
```

**Body JSON:**

```
public class APIResponse
{
    public int ResponseCode { get; set; }
```

```

public string Description { get; set; }
public string ResponseContent { get; set; }

```

| Parameters      | Data Type | Description                                                  |
|-----------------|-----------|--------------------------------------------------------------|
| ResponseCode    | string    | Status of Result                                             |
| Description     | string    | Description                                                  |
| ResponseContent | string    | Data of Callback                                             |
| Signature       | string    | MD5(ResponseCode+ Description+ ResponseContent + partnerKey) |

#### ResponseContent: JSON of List Object

```

public class DataCallback
{
    public string RefCode { get; set; }
    public string OrderNo { get; set; }
    public int Amount { get; set; }
    public int Fee { get; set; }
    public string OrderInfo { get; set; }
}

```

| Parameter | Data Type | Description                                                                                    |
|-----------|-----------|------------------------------------------------------------------------------------------------|
| RefCode   | string    | Reference Code (Usually will be the Transaction Id of the counterparty, this should be unique) |
| OrderNo   | string    | The name of the user performing the money transfer on the system                               |
| Amount    | int       | Amount actually received                                                                       |
| Fee       | int       | Fee Amount                                                                                     |
| OrderInfo | String    | Transaction code of bank or momo                                                               |

- **OutPut:** After receiving the Callback, the partner processes the transaction and returns the string delimiter code|description content as follows
  - **success:** 1|success
  - **failed:** -1|failed

### 3.4 GetTransction

- **Description:** get tranfer status

**URL:** <https://bankgate.tn99.info/bankin/getdetail.ashx>

- **Method:** Post
- **In Put:** Json Object

**Object RequestData:**

```
public class RequestData
{
    public string PartnerCode { get; set; }
    public string RefCode { get; set; }
    public string Signature { get; set; }
}
```

| Paramters   | Data Type | Description                                                                        |
|-------------|-----------|------------------------------------------------------------------------------------|
| PartnerCode | string    | PartnerCode (will provide when connected)                                          |
| RefCode     | string    | Reference Code                                                                     |
| Signature   | string    | MD5(partnerCode + RefCode+ partnerKey)<br>partnerKey : will provide when connected |

- **Out Put:**

```
{
  "ResponseCode": 1,
  "Description": "Transaction is successful",
  "ResponseContent":
  "{\"Amount\":20000,\"RefCode\":\"2\",\"TransactionID\":\"1000011\", \"LasTime\":\"\\/Date(1752160017623)\\/\"}"
}
```

```
}
```

```
public class APIResponse
{
    public int ResponseCode { get; set; }
    public string Description { get; set; }
    public string ResponseContent { get; set; }
}
```

| Paramters       | Data Type | Description                                                                                                                                 |
|-----------------|-----------|---------------------------------------------------------------------------------------------------------------------------------------------|
| ResponseCode    | string    | Status of transaction.<br>1 is success<br>0: is process -<br>320 transaction not exist<br>-357 bank info invalite<br>-1 transaction is fail |
| Description     | string    | Description                                                                                                                                 |
| ResponseContent | string    | Contents of transaction results when ResponseCode =1                                                                                        |

**ResponseContent:** JSON of Object when ResponseCode =1

```
public class TransactionInfo
{
    public string RefCode { get; set; }
    public int Amount { get; set; }
    public int Fee { get; set; }
    public datetime LastTime { get; set; }
}
```

| Paramter | Data Type | Description                                                                                    |
|----------|-----------|------------------------------------------------------------------------------------------------|
| RefCode  | string    | Reference Code (Usually will be the Transaction Id of the counterparty, this should be unique) |
| Amount   | int       | Amount actually received                                                                       |
| Fee      | int       | Fee Amount                                                                                     |
| LastTime | datetime  | Time is transaction success                                                                    |

■

### 3.5 Table ResponseCode

Only ResponseCode = 1 is the case of success, the rest of the codes will be specific failures described in the following error code table

| Code | Description                   |
|------|-------------------------------|
| 1    | Transaction Successful        |
| -1   | Transaction Failed            |
| -323 | Parameter Invalid             |
| -313 | Signature Invalid             |
| -317 | Service Not Exists            |
| -312 | Partner Not Exists Not Active |
| -301 | System Error                  |
| -310 | Access Denied                 |
| -326 | Transaction Timeout           |
| -327 | Provider Not Found            |
| -356 | Bank Amount Invalid           |
| -300 | System Maintain               |

## 4. Cash API (WebHook - JSon-Post)

### 4.1 GetBalance

**Description** get balance

**URL:** <https://bankgate.tn99.info/ServiceHandler/GetBalanceV2.ashx>

- **Method:** Get
- **In Put 2 param**

| Paramters   | Data Type | Mô tả                                     |
|-------------|-----------|-------------------------------------------|
| partnerCode | string    | PartnerCode (will provide when connected) |

|           |        |                            |
|-----------|--------|----------------------------|
| signature | string | MD5(partnerCode +panerKey) |
|-----------|--------|----------------------------|

**Out Put: system balance**

## 4.2 Cash

- **Description:** create order to cash out

**URL:** <https://bankgate.tn99.info/bankout/cash.ashx>

- **Method:** POST
- **In Put:** Json Object

**Object RequestData:**

```
public class RequestData
{
    public string PartnerCode { get; set; }
    public string AccountName { get; set; }
    public string AccountNumber { get; set; }
    public string BankCode { get; set; }
    public string RefCode { get; set; }
    public int Amount { get; set; }
    public string CallbackUrl { get; set; }
    public string Signature { get; set; }
}
```

| Paramters     | Data Type | Description                                                          |
|---------------|-----------|----------------------------------------------------------------------|
| PartnerCode   | string    | PartnerCode (will provide when connected)                            |
| BankCode      | string    | Bankcode<br>With Momo BankCode=MOMO<br>Bank code: in the table below |
| AccountName   | string    | Account anme receiving money                                         |
| AccountNumber | string    | Account number receiving money                                       |
| CallbackUrl   | Strign    | Callback Url                                                         |

|           |        |                                                                                                                                                                                                                   |
|-----------|--------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| RefCode   | string | Reference Code (Usually will be the Transaction Id of the counterparty, this should be unique)                                                                                                                    |
| Amount    | int    | Amount received by the user                                                                                                                                                                                       |
| Signature | string | MD5( <b>partnerCode</b> + <b>AccountNumber</b> + <b>AccountName</b> + <b>BankCode</b> + <b>Amount</b> + <b>RefCode</b> + <b>CallbackUrl</b> + <b>partnerKey</b> )<br><br>partnerKey : will provide when connected |

- **Out Put:**

```
{
  "ResponseCode": 1,
  "Description": "Transaction is successful",
  "ResponseContent":
  "{\\"Status\\":\\"Success\\",\\"BankcODE\\":\\"MOMO\\",\\"BankAccountNumbe
r\\":\\"0904123456\\",\\"BankAccountName\\":\\"LUU CONG
TUYEN\\",\\"Amount\\":1000000,\\"RefCode\\":\\"RFT0913\\"\\\"OrderNo\\":\\"A
D4571MB
}
```

```
public class APIResponse
{
    public int ResponseCode { get; set; }
    public string Description { get; set; }
    public string ResponseContent { get; set; }
}
```

| Paramters    | Data Type | Description                                                             |
|--------------|-----------|-------------------------------------------------------------------------|
| ResponseCode | string    | Status of transaction results. 1 means successfully receiving the order |
| Description  | string    | Description                                                             |

### 4.3 Callback

- **Description:** This is a partner API built according to the below standards to receive
- **URL:** it is CallbackUrl param at [4.1](#)
- **Method:** POST
- **Content-Type:** application/json
- **In Put:**

**JSON InPut:**

```
{
  "ResponseCode": 1,
  "Description": "Transaction is successful",
  "ResponseContent":
    "{\"RefCode\":\"RE01123\",\"TransactionID\":\"VC9762UA\",\"Amount\":\"1000000 }",
  "Signature": "778a2c01dbdac3c4310deb1987c9e6e2"
}
```

**Body of json:**

```
public class APIResponse
{
    public int ResponseCode { get; set; }
    public string Description { get; set; }
    public string ResponseContent { get; set; }
    public string Signature { get; set; }
}
```

| Paramters       | Data Type | Description                                                  |
|-----------------|-----------|--------------------------------------------------------------|
| ResponseCode    | string    | Status of Result 1 is success                                |
| Description     | string    | Description                                                  |
| ResponseContent | string    | Data of Callback                                             |
| Signature       | string    | MD5(ResponseCode+ Description+ ResponseContent + partnerKey) |

**ResponseContent: JSON of List Object**

```
public class DataCallback
{
    public string RefCode { get; set; }
    public string TransactionID{ get; set; }
```

```

        public int Amount { get; set; }
    }

```

| Thuộc tính    | Data Type | Description                                                                                    |
|---------------|-----------|------------------------------------------------------------------------------------------------|
| TransactionID | string    | Transaction of system                                                                          |
| RefCode       | string    | Reference Code (Usually will be the Transaction Id of the counterparty, this should be unique) |
| Amount        | int       | Amount actually received                                                                       |

- **OutPut:** After receiving the Callback, the partner processes the transaction and returns the string delimiter code|description content as follows
  - **success:** 1|success
  - **failed:** -1|failed

#### 4.4 GetTransction

- **Description:** get tranfer status  
**UL:** <https://bankgate.tn99.info/bankout/getdetail.ashx>
- **Method:** Post
- **In Put:** Json Object

##### Object RequestData:

```

public class RequestData
{
    public string PartnerCode { get; set; }
    public string RefCode { get; set; }
    public string Signature { get; set; }
}

```

| Paramters   | Data Type | Description                               |
|-------------|-----------|-------------------------------------------|
| PartnerCode | string    | PartnerCode (will provide when connected) |
| RefCode     | string    | Reference Code                            |

|           |        |                                                                                    |
|-----------|--------|------------------------------------------------------------------------------------|
| Signature | string | MD5(partnerCode + RefCode+ partnerKey)<br>partnerKey : will provide when connected |
|-----------|--------|------------------------------------------------------------------------------------|

- **Out Put:**

```
{
  "ResponseCode": 1,
  "Description": "Transaction is successful",
  "ResponseContent":
    "{\\"Amount\\":20000,\\"RefCode\\":\\"2\\",\\"TransactionID\\":\\"1000011\\",\\"LasTime\\":\\"\\/Date(1752160017623)\\/\\"}"
}
```

```
public class APIResponse
{
    public int ResponseCode { get; set; }
    public string Description { get; set; }
    public string ResponseContent { get; set; }
}
```

| Paramters       | Data Type | Description                                                                                                                                 |
|-----------------|-----------|---------------------------------------------------------------------------------------------------------------------------------------------|
| ResponseCode    | string    | Status of transaction.<br>1 is success<br>0: is process -<br>320 transaction not exist<br>-357 bank info invalite<br>-1 transaction is fail |
| Description     | string    | Description                                                                                                                                 |
| ResponseContent | string    | Contents of transaction results when ResponseCode =1                                                                                        |

**ResponseContent:** JSON of Object when ResponseCode =1

```
public class TransactionInfo
```

```

{
    public string RefCode { get; set; }

    public int Amount { get; set; }
    public datetime LastTime { get; set; }
}

```

| Paramter | Data Type | Description                                                                                    |
|----------|-----------|------------------------------------------------------------------------------------------------|
| RefCode  | string    | Reference Code (Usually will be the Transaction Id of the counterparty, this should be unique) |
| Amount   | int       | Amount actually received                                                                       |
| LastTime | datetime  | Time is transaction success                                                                    |

#### 4.5 Table ResponseCode

Only ResponseCode = 1 is the case of success, the rest of the codes will be specific failures described in the following error code table.

| Code | Description                   |
|------|-------------------------------|
| 1    | Transaction Successful        |
| -1   | Transaction Failed            |
| -323 | Parameter Invalid             |
| -313 | Signature Invalid             |
| -317 | Service Not Exists            |
| -312 | Partner Not Exists Not Active |
| -301 | System Error                  |
| -310 | Access Denied                 |
| -326 | Transaction Timeout           |
| -327 | Provider Not Found            |
| -5   | Transaction Cancel            |
| -356 | Bank Amount Invalid           |

|      |                    |
|------|--------------------|
| -350 | Bank Info Invalid  |
| -352 | Bank Code Invalid  |
| -358 | Bank Code Maintain |
| -300 | System Maintain    |
| -51  | Balance Not Enough |

#### 4.6 Table Bank Code

ICB - VietinBank

VCB - Vietcombank

BIDV - BIDV

VBA - Agribank

OCB - OCB

MB - MBBank

TCB - Techcombank

ACB - ACB

VPB - VPBank

TPB - TPBank

STB - Sacombank

HDB - HDBank

VCCB - VietCapitalBank

SCB - SCB

VIB - VIB

SHB - SHB

EIB - Eximbank

MSB - MSB

SGICB - SaigonBank

BAB - BacABank

PVCB - PVcomBank

Oceanbank - Oceanbank

NCB - NCB  
SHBVN - ShinhanBank  
ABB - ABBANK  
VAB - VietABank  
NAB - NamABank  
PGB - PGBank  
VIETBANK - VietBank  
BVB - BaoVietBank  
SEAB - SeABank  
COOPBANK - COOPBANK  
LPB - LienVietPostBank  
KLB - KienLongBank  
KBank - KBank  
UOB - UnitedOverseas  
SCVN - StandardChartered  
PBVN - PublicBank  
NHB HN - Nonghyup  
IVB - IndovinaBank  
IBK - HCM - IBKHCM  
IBK - HN - IBKHN  
VRB - VRB  
WVN - Woori  
KBHN - KookminHN  
KBHCM - KookminHCM  
HSBC - HSBC  
HLBVN - HongLeong  
GPB - GPBank  
DOB - DongABank  
DBS - DBSBank

CIMB - CIMB

CBB - CBBank

CITIBANK - Citibank

KEBHANAHCN - KEBHanaHCN

KEBHANAHN - KEBHANAHN

MAFC - MAFC

VBSP - VBSP