

Data Augmentation Table : map of the current augmentations

list_daug_ph0 =	['reface', 'empty']	
list_daug_ph1 =	['gibbs', 'affine']	
list_daug_ph2 =	['gain_inhom', 'zipper', 'add_noise', 'contrast_core']	
Phase 0		
-----	Refacing	refacing is done randomly to 20% of data
Phase 1		
-----	Gibbs	15% weightage is given to gibbs
		radius = random.randint(70, 100)
-----	Affine	75% weightage is given to affine
		param_map = [#1 #2 #3 #4 #5 #6 #7 #8 #9 #10 #11 #12]
		[x-shift y-shift z-shift z-angle x-angle y-angle x-scale y-scale z-scale y/x-shear z/x-shear z/y-shear]
		shift range is plus/minus 32% of grid size list_shift = [-5,-10,-15,-20,-25,-30,5,10,15,20,25,30]
		scaling range is plus/minus 20% of grid size rand_scale = round(random.uniform(0.8, 1.2), 1)
		shearing range is plus/minus 0.1111 rand_shear = round(random.uniform(-0.1, 0.1), 2)
		rotation range is plus/minus 30 degrees rand_rot = random.randint(-30, 30)
Phase 2		
-----	gain_inhom	list_axis=['i','j','k'] rand_axis=random.choices(list_axis,weights=(10, 80, 10)) win_min = 2 win_max = 2.8
-----	zipper	list_axis=['i','j','k'] zip_width = 5

-----	add_noise	noise_lvl=[0.1, 0.2, 0.3] rand_noise_lvl=random.choice(noise_lvl) list_axis=['i','j','k'] rand_axis=random.choice(list_axis)
-----	Contrast variation inside core	dim_factor = 6