

FORTYGUARD

Heat Intelligence Report

Heatmap Metadata

Location:	33.4519999999481785, -112.074
Date and Time:	2026-08-23 12:00
Temperature:	44.44°C (112.0°F)



Table of Contents

Table of Contents	2
Map	6
Geographic Analysis	7
1. General Location	7
2. Terrain & Elevation	7
3. Proximity to Water Bodies	7
4. Green Spaces & Vegetation	8
5. Land Cover Type	8
6. Building Density & Height	8
7. Shadow Coverage	9
8. Urban Geometry & Street Canyon Effects	9
Environmental Factors Analysis	10
1. Air Quality & Atmospheric Opacity	10
Typical AQI Range and EPA Classification	10
Primary Pollutants and Sources	10
Air Quality Influence on Local Temperature	10
Seasonal and Industrial Factors	10
Heat-Pollution Feedback Loop	10
2. Climate Classification & Historical Weather	11
Köppen Climate Classification	11
Historical Climate Normals for August 23	11
Comparison to Normals	11
Extreme Temperature Records	11
Long-Term Climate Profile and UHI Behavior	11
3. Climate Trends & Projections	11
Observed Temperature and Humidity Trends	11
Urban Expansion and Land-Use Change	12
Climate Change Projections (2030s and 2050s)	12
Regional Climate Drivers	12
4. Soil Moisture & Permeability	12
Typical Soil Types and Permeability	12
Expected Soil Moisture Conditions (August)	12
Soil Characteristics and Heat Dynamics	12
Urbanization and Soil Sealing	13
Groundwater Table and Moisture Availability	13
5. Heat Retention Capacity of Surfaces	13
Dominant Surface Materials	13
Comparative Heat Retention and Surface Temperatures	13
Thermal Admittance and Albedo	13
Contribution to Urban Heat Island Intensity	13
Known Cooling Infrastructure	14
6. Humidity Levels	14
Typical Relative Humidity Range	14



Dew Point Temperature and Moisture Indicator	14
Humidity and Perceived Temperature (Heat Index)	14
Seasonal Humidity Patterns	14
Humidity-Driven Heat Stress Phenomena	15
7. Solar Radiation Intensity	15
Expected Global Horizontal Irradiance (GHI)	15
Solar Elevation Angle and Radiation Intensity	15
Peak Sunlight Hours and Thermal Lag	15
Terrain, Urban Structures, and Cloud Cover Modulation	15
Differential Heat Absorption by Surface Materials	15
8. Nighttime Cooling Rates	16
Typical Diurnal Temperature Range (DTR)	16
Surface Thermal Mass and Urban Geometry Effects on Nocturnal Cooling	16
Nighttime Cooling Strength and Heat Stress Implications	16
Factors Suppressing Nocturnal Cooling	16
Urban vs. Rural Nighttime Temperature Differential	16
9. Thermal Comfort Index	17
Most Applicable Thermal Comfort Metric	17
Heat Index Calculation and Component Interactions	17
Estimated Thermal Comfort Classification	17
Heat Stress Risks for Vulnerable Populations	17
Local Mitigation Measures	17
10. Seasonal Variability of Urban Heat Islands	18
UHI Intensity Variation by Season	18
Driving Factors for Seasonal UHI Variation	18
Known Urban-Rural Temperature Differentials Across Seasons	18
Seasonal Adaptation Measures in Place or Planned	18
Season of Greatest Compound Heat Risk	19
Urban Factors Analysis	19
1. Urban Land Use Characteristics	19
Dominant Land Use Types	19
Impervious Surface Fraction	19
Heat Differentials and Land Use Patterns	19
Zoning and Urban Planning	19
2. Anthropogenic Heat Sources	20
Major Economic Activities	20
Energy-Intensive Sectors	20
Vehicle Density and Transportation Heat	20
HVAC Rejection Heat	20
Impervious Commercial Surfaces	20
Sustainability Initiatives	21
Notable Heat-Contributing Zones	21
3. Green Infrastructure & Urban Cooling Systems	21
Urban Vegetation Strategy	21
Cooling Mechanisms and Effectiveness	21



Corporate and Public Greening Initiatives	21
Engineered Cooling Infrastructure	22
Cooling Equity and Distribution	22
Notable Cooling Infrastructure	22
4. Building Material Thermal Properties	22
Dominant Building Materials	22
Albedo Values for Major Surfaces	22
Thermal Mass and Heat Retention	22
Glass Curtain Wall Effects	23
Heat Mitigation Techniques	23
Building Stock Age and Thermal Performance	23
5. Urban Expansion & Development Trends	23
Population Growth and Density Trends	23
Construction Trends	23
Net Change in Impervious Surface	24
Climate-Adaptive Urban Design	24
Development Impact on Local Heat Profile	24
6. Pedestrian Infrastructure & Outdoor Thermal Comfort	24
Walkability and Pedestrian Accessibility	24
Shading Infrastructure	24
Mean Radiant Temperature (MRT) and Pedestrian Thermal Load	25
Heat Exposure Risk and Thermal Comfort	25
Cooling Interventions and Comfort Infrastructure	25
Cycling Infrastructure	25
Notable Pedestrian Comfort Zones and Deficits	25
Events Analysis	26
Extreme Weather Events & Heat Event History	26
Heat-Related Events	26
Droughts	26
Wildfires	27
Heatwave Frequency & Intensity	27
Heatwave Definition and Thresholds	27
Frequency and Trend	27
Intensity Metrics	27
Comparison of Provided Temperature (112°F Average on August 23, 2026)	28
Heat Dome and Blocking Pattern Susceptibility	28
Public Health Impacts & Heat Vulnerability	28
Heat-Related Health Burden	28
Vulnerable Populations	28
Heat-Mortality Relationship	29
Consecutive Hot Night Risk	29
Heat Advisory and Warning Systems	29
Cooling Infrastructure and Public Health Interventions	29
Heat Vulnerability Mapping	30
Health-System Preparedness	30



Equity Dimension	30
Anthropogenic Factors Analysis	30
1. Heat Emissions from Vehicles & Industry	30
Transportation Heat Footprint	31
Industrial and Commercial Waste Heat	31
Spatial Heat Concentration Zones	31
Temporal Patterns at Given Datetime	31
Emission-Reduction Measures & EV Adoption	31
2. Cooling Infrastructure & Waste Heat Feedback Loop	32
Cooling Infrastructure Prevalence	32
The AC Feedback Loop & Waste Heat Contribution	32
Balance-Point Temperature & Cooling Activation	32
Cooling Inequality & Access Disparities	33
District Cooling Systems	33
Innovative & Passive Cooling Strategies	33
Cooling Demand Classification at 112°F	33
3. Energy System Load & Grid Stress	34
Energy Demand Profile	34
Temperature-Demand Sensitivity	34
Grid Stability & Heat-Related Risk	34
Grid Heat Vulnerability: Infrastructure Derating	34
Load Shedding & Emergency Protocols	34
Energy Resilience Measures	35
Assessment at 112°F: Demand Curve Position	35
4. Traffic Behavior & Vehicular Heat Contribution	35
Traffic Pattern Characterization	35
Waste Heat Concentration Zones	36
Pavement Heat Interaction	36
Public Transit Role & Mode Share	36
Heat-Induced Behavioral Shifts	37
Mitigation Measures in Place or Planned	37
Assessment at Given Datetime: Traffic-Driven Heat Load	37
5. Seasonal Population Dynamics & Heat Demand	38
Population Variability & Seasonal Patterns	38
Demand Translation: Population Fluctuations to Heat & Energy Load	38
Current Season Assessment: August 23, 2026	38
Weekend/Weekday & Time-of-Day Demand Variation	38
Infrastructure & Policy Adjustments for Seasonal Demand	39
Anthropogenic Heat Load at Given Datetime: Summary	39
Summary & Integrated Assessment	39



Map



Figure 1: Overview Area



Figure 2: Tile Area



Geographic Analysis

1. General Location

- **City:** Phoenix, Arizona, United States
- **Geographic Classification:** Urban core within an arid inland basin; rapidly expanding metropolitan area in the Sonoran Desert
- **Köppen Climate Zone:** BWh (hot desert climate). Characterized by extremely hot, dry summers with minimal precipitation (annual average ~8 inches), intense solar radiation year-round, and low relative humidity. Winter temperatures are mild.
- **Historical Temperature Extremes:** Phoenix's all-time record high is 122°F (July 1990). August average high is approximately 100°F; the provided reading of 112°F at midday on August 23 is elevated but consistent with extreme heat events common in late summer.
- **Comparison to Climate Normals:** The 112°F reading is approximately 12°F above the typical August 23 average high (~100°F), indicating a heat event above normal seasonal conditions but within the range of observed variability for this date in Phoenix's climate record.

Sources:

- Köppen-Geiger climate classification system
- NOAA National Centers for Environmental Information (Phoenix climate normals and extremes)
- U.S. National Weather Service Phoenix office historical records

2. Terrain & Elevation

- **Elevation:** Approximately 1,100 feet above sea level in central Phoenix; ranges from ~1,000 feet in the urban core to ~2,700 feet in surrounding foothills and mountains.
- **Terrain Type:** Phoenix sits in the Salt River Valley, a broad, flat to gently rolling basin surrounded by the Sierra Estrella Mountains to the south and west, the South Mountains to the south, and the McDowell Mountains to the north.
- **Basin Effect on Heat Retention:** The valley basin configuration traps air masses and inhibits nighttime radiative cooling. Warm air aloft can create weak inversions, particularly during high-pressure systems in summer, reducing vertical mixing and concentrating heat near the surface. The basin's low elevation relative to surrounding peaks limits katabatic (downslope) wind drainage that would otherwise provide nighttime cooling.
- **Slope Orientation:** The surrounding mountains have varied exposures; south and west-facing slopes receive maximum solar radiation and re-radiate heat into the valley. This contributes to the urban heat island effect by warming the air mass above the city.

Sources:

- USGS elevation and topographic data for Arizona
- U.S. Geological Survey Basin and Range Province geology
- Atmospheric boundary layer research on desert basin inversions

3. Proximity to Water Bodies

- **Nearest Significant Water Bodies:** The Salt River, which flows west through Phoenix, is approximately 2–5 miles from the downtown core depending on location. Lake Pleasant is ~45 miles north; Lake Havasu is ~200 miles west on the Colorado River. These distances are too great to provide meaningful thermal moderation to the urban core.
- **Thermal Moderating Effect:** Minimal. The Salt River is often dry or reduced to a trickle during summer months due to upstream water extraction for irrigation and municipal supply. When flowing, its limited volume and narrow riparian corridor provide negligible evaporative cooling to the broader urban area. The lack of a large proximate water body is a primary reason Phoenix experiences extreme UHI intensity.
- **Seasonal Variation:** Summer (June–August) is when the Salt River is most depleted, eliminating any potential evaporative cooling benefit. Winter flows are slightly higher but still insufficient to moderate the urban heat island.
- **Wind and Heat Transport:** Prevailing winds in Phoenix are generally from the west and southwest in summer. The absence of a nearby water body means these winds do not carry maritime moderation; instead, they transport warm, dry air from the desert interior, exacerbating heat stress in the urban area.



Sources:

- U.S. Bureau of Reclamation water management data for the Salt River Project
- NOAA wind climatology for Phoenix
- Arizona Department of Water Resources hydrologic records

4. Green Spaces & Vegetation

- **Type and Extent:** Phoenix's urban canopy is fragmented. Major parks include Desert Botanical Garden (~140 acres), South Mountain Park (~16,000 acres, partially within city limits), and numerous smaller neighborhood parks. Street trees are present but unevenly distributed, concentrated in older neighborhoods and along major corridors.
- **Estimated Canopy Coverage:** Approximately 3–5% citywide (estimated based on typical low-density sprawl patterns in the Southwest). This is significantly below the 20–30% canopy coverage recommended by urban forestry standards and well below values in temperate cities (10–15% typical for comparable U.S. cities).
- **Vegetation Type:** Predominantly native desert shrubs (creosote, palo verde, acacia) and non-native ornamental palms and date palms in landscaped areas. Deciduous trees (ash, cottonwood) are limited to riparian zones and irrigated parks. Evergreen conifers are rare. The sparse, low-stature native vegetation provides minimal shade; ornamental plantings in residential areas offer some localized cooling but require irrigation in the arid climate.
- **Urban Greening Initiatives:** Phoenix has promoted tree-planting programs (e.g., Million Trees initiative) and cool-roof ordinances, but implementation remains limited relative to the city's sprawling footprint. Canopy gains have been modest.
- **Cooling Contribution:** Estimated at 1–3°F reduction in ambient temperature within and immediately adjacent to vegetated areas (parks, tree-lined streets) compared to surrounding built environment. The citywide effect is negligible due to low overall canopy coverage.

Sources:

- U.S. Forest Service i-Tree Canopy assessment methodology
- City of Phoenix Parks and Recreation department data
- Sonoran Desert ecology and native plant physiology literature
- Urban heat island mitigation research for arid regions

5. Land Cover Type

- **Dominant Surface Materials:** The urban core and suburban sprawl are dominated by asphalt (roads, parking lots, driveways) and concrete (buildings, sidewalks, hardscape). Bare soil and desert scrub occupy interstices and undeveloped parcels. Vegetation coverage is minimal (see Section 4).
- **Thermal Properties:** Asphalt has an albedo of 0.05–0.15 (very dark, absorbs ~85–95% of incident solar radiation) and a thermal conductivity that allows rapid heating and re-radiation. Concrete has an albedo of 0.20–0.35 (slightly lighter) but still absorbs 65–80% of solar energy. Both materials have high thermal mass and retain heat well into the night, contributing significantly to the nocturnal UHI effect. Surface temperatures of asphalt and dark concrete can exceed air temperature by 30–50°F under intense summer sun.
- **Heat-Reflective Materials and Programs:** Cool-roof ordinances (reflective coatings with albedo >0.65) have been adopted for new commercial construction and some municipal buildings, but penetration is limited. Cool-pavement pilots exist but are not widespread due to cost and maintenance concerns. Estimated adoption rate: <10% of total impervious surface area.

Sources:

- USGS spectral reflectance and thermal properties of urban materials
- Lawrence Berkeley National Laboratory cool-roof and cool-pavement research
- City of Phoenix Building and Fire Code cool-roof requirements
- Urban heat island effect literature (Oke, 1982; EPA UHI mitigation guidance)

6. Building Density & Height

- **Building Density Characterization:** Phoenix exhibits a mixed profile: a high-rise commercial core (downtown, ~10–40 stories), mid-rise office and hotel corridors along major avenues, and extensive low-rise (1–3 story) single-family residential sprawl covering the majority of the metropolitan area. Overall building density is moderate to low compared to older U.S. cities, but concentrated in the urban core.
- **Typical Building Heights:** Downtown Phoenix averages 15–25 stories; suburban areas are predominantly 1–2



stories. The vertical massing in the core creates pronounced street canyon effects (see Section 8) and contributes to localized UHI intensification. The sprawling low-density periphery offers minimal shade and maximum solar exposure to individual structures.

- **Roofing and Facade Materials:** Older buildings (pre-1990s) typically feature dark asphalt shingles or tar roofs (albedo ~0.05–0.10) and light-colored stucco facades (albedo ~0.30–0.40). Newer commercial buildings increasingly use reflective membranes or metal roofing (albedo ~0.40–0.70). Residential properties are mixed; many feature dark tile roofs (albedo ~0.20–0.30). Cool-roof adoption remains below 20% of total roofed area.
- **Anthropogenic Heat Sources:** Estimated at 15–25 W/m² in the urban core (from HVAC exhaust, vehicle traffic, industrial processes, and human metabolism). In residential areas, estimated at 5–10 W/m². On a hot August day with peak cooling demand, air-conditioning systems operate at maximum capacity, exhausting hot air into street canyons and contributing 2–4°F to local air temperatures. Vehicle traffic on major corridors (I-10, I-17, Loop 101) adds continuous heat; estimated vehicle density in peak hours exceeds 2,000 vehicles/hour/lane on major freeways.

Sources:

- City of Phoenix zoning and building density data
- USGS spectral reflectance of roofing materials
- Anthropogenic heat flux research (Ichinose et al., 1999; Sailor, 2011)
- Arizona Department of Transportation traffic volume data

7. Shadow Coverage

- **Shadow Coverage Assessment:** At 12:00 hours (solar noon) on August 23 in Phoenix (latitude 33.45°N), the solar altitude angle is approximately 75–80° above the horizon. At this steep angle, shadows are short and minimal. Estimated shadow coverage from buildings and structures in the urban core: 10–15%. In suburban single-family areas with scattered trees: 5–10%. Overall citywide shadow coverage at noon: ~8–10%.
- **Solar Angle Calculation:** Using standard solar geometry for latitude 33.45°N on August 23 (approximately 235 days into the year), the solar declination is ~11°N. The solar altitude angle $h = \arcsin[\sin(\text{lat}) \times \sin(\text{dec}) + \cos(\text{lat}) \times \cos(\text{dec}) \times \cos(\text{hour angle})]$. At solar noon (hour angle = 0°), $h \approx 78^\circ$. This steep angle minimizes shadow length and reduces shading benefit from vertical structures.
- **Quantitative Impact of Shading:** Where shade is present (parks, tree-lined streets, building overhangs), surface temperatures are reduced by 15–25°F relative to unshaded surfaces. However, ambient air temperature reduction is modest: 1–3°F in shaded areas due to limited canopy coverage and the dominance of unshaded impervious surfaces. Nighttime cooling is more significantly affected by daytime shade (see Section 8).
- **Permanent vs. Seasonal Shade:** Permanent shade from buildings and structures is concentrated in the downtown core and along major commercial corridors. Seasonal shade from deciduous trees is minimal due to low canopy coverage; evergreen palms provide year-round but limited shade. The lack of substantial deciduous canopy means summer cooling benefit is not offset by winter solar gain, a missed opportunity in the desert climate.

Sources:

- NOAA solar position calculator and solar geometry equations
- Urban heat island and shading research (Taha, 1997; Akbari et al., 2001)
- Building shadow modeling and GIS-based canopy assessment

8. Urban Geometry & Street Canyon Effects

- **Street Canyon Characteristics:** Downtown Phoenix features typical urban canyons with height-to-width (H/W) ratios of 0.5–1.5 (buildings 10–25 stories, street widths 60–120 feet). Suburban areas have much lower H/W ratios (0.1–0.3) due to low-rise buildings and wide streets/parking lots. In high H/W canyons, longwave radiation is trapped between building facades, reducing nighttime radiative cooling. Estimated nighttime temperature reduction in deep canyons: 1–2°F less cooling compared to open areas. In low H/W suburban areas, radiative cooling is more efficient, but daytime heating is intense due to wide exposure to solar radiation.
- **Wind Corridor Presence:** Phoenix's street grid is predominantly regular (orthogonal) in older neighborhoods and downtown, transitioning to organic, curvilinear patterns in newer suburban developments. The regular grid in downtown and mid-city areas allows some wind channeling along major avenues (e.g., Central Avenue, Van Buren Street), which can enhance convective cooling on windy days. However, summer wind speeds in Phoenix are generally low (average 6–8 mph), limiting the cooling benefit. Suburban cul-de-sac patterns inhibit wind flow and create stagnant air pockets, exacerbating local heat accumulation.
- **Street Layout and Solar Exposure:** The regular grid layout in downtown and older neighborhoods means streets run N–S and E–W. E–W streets have one facade in full sun for much of the day (south-facing in the Northern



Hemisphere), while N–S streets distribute solar load more evenly. Suburban areas with curved streets and irregular layouts create variable solar exposure, but the dominance of low-rise buildings means most surfaces receive direct sun regardless of orientation.

- **Sky View Factor (SVF) Estimation:** Downtown Phoenix canyons with H/W ~1.0 have estimated SVF of 0.4–0.6 (40–60% of sky visible). Suburban low-rise areas have SVF of 0.7–0.9. Higher SVF (more open sky) allows more efficient radiative cooling at night but also permits more solar heating during the day. The trade-off favors cooler nighttime temperatures in open suburban areas, but daytime heating is more intense. The urban core's lower SVF reduces nighttime cooling efficiency, contributing to sustained elevated temperatures through the night and into the following day.

Sources:

- Urban canyon radiation and heat transfer modeling (Oke, 1987; Arnfield, 2003)
- Sky View Factor calculation and nocturnal cooling research
- City of Phoenix street network GIS data and urban morphology studies
- NOAA wind climatology for Phoenix

Environmental Factors Analysis

1. Air Quality & Atmospheric Opacity

Typical AQI Range and EPA Classification

- Phoenix metropolitan area (33.45°N, 112.07°W) in August typically experiences Moderate to Unhealthy for Sensitive Groups (USG) AQI conditions
- Typical August AQI range: 80–150 (Moderate to USG); peak afternoon values often reach 120–160 during heat events
- EPA classification: Moderate (51–100) on cooler days; USG (101–150) on heat-driven ozone episodes

Primary Pollutants and Sources

- Ozone (O₃): dominant concern in summer; formed via photochemical reactions of NO_x and volatile organic compounds (VOCs) under intense solar radiation
- PM_{2.5} and PM₁₀: elevated from dust storms, vehicle emissions, and industrial activity; Phoenix basin geography traps pollutants
- NO₂ and CO: primary emissions from vehicular traffic and power generation
- Sources: vehicle emissions (dominant), power plants, industrial facilities, dust mobilization from arid soils and construction

Air Quality Influence on Local Temperature

- Aerosol radiative forcing: suspended particulates and smog reduce direct solar transmittance by 5–15%, lowering surface insolation but trapping outgoing longwave radiation
- Net effect: reduced peak daytime temperature but enhanced nighttime warming and suppressed nocturnal cooling
- Smog layer acts as a thermal blanket, reducing diurnal temperature range by approximately 2–4°F

Seasonal and Industrial Factors

- August peak: maximum solar radiation, thermal convection, and photochemical ozone production
- Phoenix's rapid urban expansion and vehicle-dependent sprawl amplify NO_x and VOC emissions
- Cooling season HVAC load (peak in August) contributes anthropogenic heat and increases demand for electricity, driving power plant emissions

Heat-Pollution Feedback Loop

- High temperatures accelerate ozone formation: each 1°C rise increases ozone production by ~3–5%
- Elevated ozone concentrations suppress vegetation photosynthesis and transpiration, reducing evaporative cooling
- Reduced evapotranspiration further elevates surface temperatures, intensifying the UHI and amplifying pollutant stagnation



Sources:

- EPA AQI standards and air quality data for Phoenix metropolitan area
 - NOAA air quality and atmospheric composition research
 - Peer-reviewed literature on photochemical ozone formation and aerosol radiative forcing
-

2. Climate Classification & Historical Weather

Köppen Climate Classification

- Classification: BWh (hot desert climate)
- Characteristics: annual precipitation <10 inches; mean annual temperature >64°F; extremely hot summers with minimal moisture
- Defining feature: intense solar radiation, low humidity, minimal cloud cover, and extreme diurnal temperature variation in spring/fall

Historical Climate Normals for August 23

- Typical high: 108–110°F
- Typical low: 82–85°F
- Mean (average of high and low): 95–97°F
- Provided average temperature: 112°F

Comparison to Normals

- The provided 112°F average is 2–4°F above the typical high for this date, indicating a heat event or anomalously warm conditions
- This reading suggests either a prolonged heatwave, peak afternoon measurement, or an exceptionally hot year relative to 1991–2020 normals
- Within the range of observed extremes but notably elevated

Extreme Temperature Records

- Phoenix all-time record high: 122°F (June 26, 1990)
- August record high: 120°F (August 12, 1990)
- Consecutive days $\geq 120^\circ\text{F}$: 19 days (June–July 1990)
- The 112°F reading is well below extreme records but represents a strong heat event for late August

Long-Term Climate Profile and UHI Behavior

- Desert climate with minimal vegetation and high surface albedo variability creates strong daytime heating and rapid nighttime cooling in rural areas
- Urban areas (Phoenix city proper) exhibit pronounced UHI: 5–10°F warmer than surrounding desert at night
- Sparse precipitation and low soil moisture limit evaporative cooling potential, making sensible heat the dominant cooling mechanism
- Extreme continentality (large DTR) typical of deserts, but urban surfaces reduce this range by trapping heat

Sources:

- NOAA climate normals for Phoenix Sky Harbor International Airport (1991–2020)
 - Köppen climate classification system
 - NOAA National Centers for Environmental Information (NCEI) extreme temperature records
-

3. Climate Trends & Projections

Observed Temperature and Humidity Trends



- Phoenix warming rate (1970–2020): approximately 0.3–0.4°F per decade, consistent with Southwest regional trends
- Trend acceleration post-2000: warming rate increased to ~0.5°F per decade
- Relative humidity: slight declining trend (~0.2–0.3% per decade) due to earlier snowmelt and reduced spring moisture
- Heatwave frequency: number of days $\geq 100^\circ\text{F}$ has increased by ~15–20 days per decade since 1990

Urban Expansion and Land-Use Change

- Phoenix metropolitan area population growth: ~3.5 million (2020), with continued sprawl into surrounding desert
- Urban footprint expansion: ~1–2% per year, converting bare desert and sparse vegetation to impervious surfaces
- Consequence: UHI intensification, reduced evaporative cooling from lost vegetation, increased sensible heat flux
- Cooling degree days (CDD, base 65°F): increased from ~3,000 CDD/year (1970s) to ~3,500+ CDD/year (2020s)

Climate Change Projections (2030s and 2050s)

- Near-term (2030s): +1.5–2.0°F warming relative to 1991–2020 baseline; heatwave frequency increase of 20–30%
- Mid-century (2050s): +2.5–3.5°F warming; heatwaves becoming more intense and longer-duration; potential for 140+ days $\geq 100^\circ\text{F}$ annually
- Monsoon precipitation: high uncertainty; models suggest slight increases in summer rainfall but increased drought risk in spring
- Cooling degree days (2050s): projected 4,500–5,000 CDD/year, representing ~40–50% increase in cooling demand

Regional Climate Drivers

- Sea surface temperature warming in the Pacific and Gulf of California influences monsoon intensity and timing
- Reduced Colorado River flow due to warming and drought reduces irrigation availability, further limiting evaporative cooling
- Dust aerosol trends: uncertain; potential for increased dust mobilization under more frequent drought conditions

Sources:

- NOAA climate trend analysis and regional climate centers
- U.S. Geological Survey (USGS) Southwest climate change assessments
- Intergovernmental Panel on Climate Change (IPCC) AR6 projections for North America
- NASA GISS temperature records and trend analysis

4. Soil Moisture & Permeability

Typical Soil Types and Permeability

- Dominant soil types: sandy loam and loamy sand (Sonoran Desert soils); some clay-rich horizons in basin areas
- Permeability: high in sandy soils (>2 inches/hour), moderate in loamy soils (0.5–2 inches/hour)
- Urban areas: sealed by asphalt and concrete, effectively zero permeability; reduces infiltration and groundwater recharge

Expected Soil Moisture Conditions (August)

- Natural desert soils: very dry; volumetric water content typically $<5\%$ in upper 12 inches
- Monsoon influence: late July–August brings occasional convective rainfall; soil moisture may spike briefly to 10–15% after events
- Typical August condition (without recent rain): $<3\%$ volumetric water content; rapid drying within 24–48 hours of precipitation
- Irrigated urban landscapes: soil moisture maintained at 15–25% through supplemental watering

Soil Characteristics and Heat Dynamics

- Low soil moisture reduces latent heat flux (evaporation); sensible heat becomes dominant energy pathway
- Sandy soils have low thermal conductivity (~0.2–0.3 W/m·K); heat is concentrated near surface, creating steep



temperature gradients

- Bare soil albedo: 0.25–0.35; absorbs 65–75% of incident solar radiation
- Ground-level temperature on bare soil: typically 15–25°F above air temperature under peak solar load

Urbanization and Soil Sealing

- Phoenix urban core: ~60–70% impervious surface coverage (asphalt, concrete, buildings)
- Consequence: eliminated soil evaporation, suppressed groundwater recharge, reduced evapotranspiration from vegetation
- Heat retention: sealed soils and surfaces store thermal energy, releasing it slowly at night and suppressing nocturnal cooling
- Feedback: reduced moisture availability further stresses vegetation, reducing transpiration and increasing bare surface exposure

Groundwater Table and Moisture Availability

- Phoenix basin groundwater table: typically 100–300 feet below surface in urban areas, deeper in surrounding desert
- Limited capillary rise: groundwater contributes minimally to surface soil moisture in arid conditions
- Consequence: surface moisture availability depends almost entirely on precipitation and irrigation
- Declining water table (due to over-extraction) reduces long-term moisture availability and evaporative cooling potential

Sources:

- USDA Natural Resources Conservation Service (NRCS) soil survey data for Maricopa County
- Soil Science Society of America soil properties and thermal conductivity data
- NOAA precipitation and drought monitoring
- U.S. Geological Survey groundwater and aquifer assessments for Arizona

5. Heat Retention Capacity of Surfaces

Dominant Surface Materials

- Urban core (Phoenix city proper): asphalt (40–50%), concrete (20–30%), buildings/roofs (15–25%), vegetation (5–10%)
- Suburban areas: concrete, asphalt, low-density vegetation, some bare soil
- Surrounding desert: bare soil, sparse shrubs, minimal vegetation cover

Comparative Heat Retention and Surface Temperatures

- Asphalt surface temperature under peak solar load (noon, August): 140–160°F; air temperature ~112°F; differential ~28–48°F
- Concrete surface temperature: 120–140°F; differential ~8–28°F (lighter color reduces absorption)
- Vegetation (grass/shrubs): 80–95°F; differential -17 to -32°F (cooler than air due to evapotranspiration)
- Bare soil: 110–130°F; differential -2 to +18°F (depends on moisture and color)

Thermal Admittance and Albedo

- Asphalt: albedo 0.05–0.10 (very dark); thermal admittance ~1,800 J/(m²·K·s^{0.5}); high heat storage
- Concrete: albedo 0.30–0.40 (medium); thermal admittance ~1,500–2,000 J/(m²·K·s^{0.5}); moderate-to-high heat storage
- Vegetation: albedo 0.20–0.30; thermal admittance ~500–800 J/(m²·K·s^{0.5}); low heat storage, high latent cooling
- Reflective coatings (cool roofs): albedo 0.60–0.80; reduce surface temperature by 20–40°F relative to standard materials

Contribution to Urban Heat Island Intensity

- Phoenix UHI magnitude: 5–10°F at night (urban vs. rural); 2–5°F during peak afternoon (reduced by strong sensible



heat flux)

- Primary driver: high thermal mass of asphalt and concrete, combined with reduced vegetation and evapotranspiration
- Secondary driver: anthropogenic heat from air conditioning, vehicles, and industrial activity (~50–100 W/m² in dense urban areas)
- Cumulative effect: urban surfaces absorb ~10–15% more solar energy than surrounding desert due to lower albedo

Known Cooling Infrastructure

- Cool roofs: increasing adoption in Phoenix; reflective coatings reduce roof temperature by 30–50°F and building cooling load by 10–30%
- Reflective pavements: pilot programs in some neighborhoods; limited widespread adoption due to cost and maintenance
- Urban tree canopy: ~10–15% coverage in Phoenix (below recommended 25–30%); trees provide 5–15°F local cooling under canopy
- Green infrastructure: limited; some parks and green roofs in downtown Phoenix, but not widespread

Sources:

- Lawrence Berkeley National Laboratory (LBNL) cool roof and cool pavement research
 - EPA Heat Island Effect mitigation strategies and surface albedo data
 - ASHRAE thermal properties of building materials
 - Peer-reviewed literature on urban surface temperatures and UHI intensity
-

6. Humidity Levels

Typical Relative Humidity Range

- Phoenix August at 12:00 hours (noon): typical relative humidity 15–25%
- Daily range: morning (6:00 AM) ~40–50%; peak afternoon (2:00–4:00 PM) ~10–20%; evening (6:00 PM) ~25–35%
- Monsoon influence (late July–August): humidity can spike to 30–50% on days with convective activity or moisture influx from Gulf of California
- Post-monsoon (September): humidity typically 20–30%

Dew Point Temperature and Moisture Indicator

- Typical August dew point at noon: 35–45°F (very low; indicates very dry air)
- Dew point is more stable than RH and directly indicates absolute moisture content
- Dew point <45°F: air is extremely dry; rapid evaporation occurs from skin and surfaces
- Dew point >60°F: humidity begins to suppress evaporative cooling; discomfort increases
- Dew point >75°F: dangerous heat stress threshold; evaporative cooling becomes ineffective; rare in Phoenix but possible during monsoon extremes

Humidity and Perceived Temperature (Heat Index)

- At 112°F and 20% RH: heat index ~114–116°F (minimal increase; dry air permits efficient evaporative cooling)
- At 112°F and 40% RH: heat index ~120–125°F (moderate increase; evaporative cooling less efficient)
- At 112°F and 60% RH: heat index ~135–145°F (severe increase; evaporative cooling significantly suppressed)
- Phoenix's typical low humidity means heat index is usually only 2–5°F above actual temperature, unlike humid regions

Seasonal Humidity Patterns

- Winter (December–February): RH 30–50%; higher due to cooler temperatures and occasional frontal systems
- Spring (March–May): RH 10–20%; extremely dry; dust storms common
- Summer pre-monsoon (June–mid-July): RH 10–25%; very dry; heat stress severe
- Monsoon (mid-July–September): RH 20–40% on average; spikes to 50–70% during convective events



Humidity-Driven Heat Stress Phenomena

- Nocturnal cooling suppression: high humidity (RH >50%) at night traps outgoing longwave radiation; reduces cooling rate by 2–4°F
- Consecutive hot nights: when monsoon moisture persists, nighttime lows may stay above 85°F; prevents thermal recovery and amplifies heat stress
- Dew point >75°F threshold: occurs rarely in Phoenix (typically only during extreme monsoon events); represents dangerous heat stress (wet-bulb temperature >32°C)
- Typical August: humidity is low enough that evaporative cooling remains effective; heat stress is primarily from absolute temperature, not humidity

Sources:

- NOAA climate data and relative humidity normals for Phoenix
 - National Weather Service heat index calculation methodology
 - Peer-reviewed literature on dew point thresholds for heat stress and wet-bulb temperature
 - EPA thermal comfort and humidity relationships
-

7. Solar Radiation Intensity

Expected Global Horizontal Irradiance (GHI)

- Phoenix August 23 at 12:00 hours: estimated GHI ~950–1,000 W/m²
- Clear-sky GHI (no clouds): ~1,050–1,100 W/m² (near theoretical maximum for this latitude and season)
- Typical atmospheric conditions (with aerosols and minor cloud cover): 900–950 W/m²
- Provided air quality (Moderate to USG AQI): aerosol optical depth reduces GHI by ~5–10% relative to pristine conditions

Solar Elevation Angle and Radiation Intensity

- Solar elevation angle at 33.45°N on August 23 at 12:00 hours (solar noon): approximately 75–78° above horizon
- High elevation angle (summer maximum ~82° at summer solstice, declining by August) concentrates solar energy on horizontal surfaces
- At 75° elevation: direct normal irradiance (DNI) ~900–950 W/m²; direct component dominates over diffuse
- Radiation intensity peaks within ±2 hours of solar noon; thermal lag of 2–4 hours means peak air temperature occurs ~2:00–4:00 PM

Peak Sunlight Hours and Thermal Lag

- Effective peak sunlight hours (GHI >800 W/m²): ~6–7 hours per day in August
- Thermal lag: surfaces and air mass continue heating after peak radiation due to thermal inertia; peak air temperature typically 2–4 hours after solar noon
- For August 23 at 12:00 hours: this is mid-peak radiation period; air temperature likely still rising toward daily maximum
- Provided 112°F average may represent a measurement near peak heating, not the daily mean

Terrain, Urban Structures, and Cloud Cover Modulation

- Phoenix basin terrain: relatively flat; minimal shading from topography in most urban areas
- Urban canyon effects: tall buildings can shade street-level surfaces by 20–40% during morning and evening; minimal effect at solar noon
- Typical August cloud cover: 10–20% (clear skies); monsoon clouds (mid-July–September) can reduce GHI by 20–50% on convective days
- Dust and aerosols: reduce direct beam by ~10–15%; increase diffuse component slightly

Differential Heat Absorption by Surface Materials

- Asphalt (albedo 0.05–0.10): absorbs 900–950 W/m² of incident 950 W/m² GHI; surface temperature rise ~3–5°F per



hour under peak load

- Concrete (albedo 0.30–0.40): absorbs 570–665 W/m²; surface temperature rise ~2–3°F per hour
- Vegetation (albedo 0.20–0.30): absorbs 665–760 W/m²; most energy partitioned to latent heat (evapotranspiration); sensible temperature rise <1°F per hour
- Cumulative effect: urban surfaces with low albedo accumulate thermal energy faster, contributing to UHI

Sources:

- NOAA solar radiation data and clear-sky models
 - NASA POWER project solar irradiance data
 - NREL solar radiation resource assessment for Arizona
 - Peer-reviewed literature on solar elevation angle and surface heating
-

8. Nighttime Cooling Rates

Typical Diurnal Temperature Range (DTR)

- Phoenix August typical DTR: 25–30°F (high, typical of desert climate)
- Example: if high is 110°F, low is typically 80–85°F
- Urban areas: DTR reduced to 20–25°F due to thermal mass and anthropogenic heat retention
- Rural/desert areas: DTR can exceed 35°F, with lows dropping to 75°F or below

Surface Thermal Mass and Urban Geometry Effects on Nocturnal Cooling

- Asphalt and concrete: high thermal mass (~1.5–2.0 MJ/m³·K); release stored heat slowly over 8–12 hours post-sunset
- Street canyon geometry: narrow streets (building height-to-width ratio >1) trap longwave radiation; reduces cooling by 2–5°F
- Building materials: masonry and concrete walls continue radiating heat through the night; peak heat release occurs 4–8 hours after sunset
- Consequence: urban nighttime temperatures remain elevated; cooling rate ~1–2°F per hour (vs. 3–4°F per hour in rural desert)

Nighttime Cooling Strength and Heat Stress Implications

- Phoenix typically exhibits moderate-to-strong nighttime cooling; lows usually drop 20–25°F from daily highs
- Consecutive hot nights (lows >85°F): occur on ~5–10 days per August; associated with monsoon moisture or sustained high pressure
- Heat stress amplification: when nighttime lows remain >85°F, thermal recovery is incomplete; next day's heat stress is compounded
- Vulnerable populations (elderly, outdoor workers): consecutive hot nights increase risk of heat-related illness even during moderate daytime temperatures

Factors Suppressing Nocturnal Cooling

- Cloud cover: reduces longwave radiation loss to space by 30–50%; each 10% cloud cover increase suppresses cooling by ~1°F
- Humidity: high RH (>50%) traps outgoing radiation; dew point >60°F can suppress cooling by 3–5°F
- Thermal mass: urban surfaces continue releasing stored heat; reduces cooling rate by 1–2°F per hour
- Street canyon geometry: reduces radiative sky view factor; suppresses cooling by 2–5°F
- Anthropogenic heat: air conditioning waste heat, vehicle emissions, and industrial activity add 50–100 W/m² in dense urban areas; suppresses cooling by 1–3°F

Urban vs. Rural Nighttime Temperature Differential

- Phoenix UHI nighttime intensity: 5–10°F (urban core vs. surrounding desert)
- Example: urban low 85°F; rural low 75–78°F
- Mechanism: reduced vegetation, high thermal mass, street canyon geometry, and anthropogenic heat



- Seasonal variation: UHI is strongest in summer (when thermal mass is most effective) and weakest in winter

Sources:

- NOAA diurnal temperature range climate normals
 - Peer-reviewed literature on urban heat island nocturnal effects
 - EPA urban heat island mitigation strategies and cooling rate data
 - Thermal properties of building materials (ASHRAE)
-

9. Thermal Comfort Index

Most Applicable Thermal Comfort Metric

- Primary metric: Heat Index (HI); standard for U.S. National Weather Service heat stress warnings
- Justification: HI incorporates air temperature and relative humidity; designed for outdoor heat stress in moderate wind conditions; widely recognized and operationally applied
- Secondary metrics: Wet-Bulb Globe Temperature (WBGT) for occupational heat stress; Universal Thermal Climate Index (UTCI) for more comprehensive biometeorological assessment
- For Phoenix August conditions (low humidity, high temperature): HI and WBGT yield similar results; UTCI provides additional context on wind and radiation effects

Heat Index Calculation and Component Interactions

- Heat Index formula: combines air temperature (T) and relative humidity (RH) to estimate perceived temperature
- At 112°F and 20% RH: HI = 114–116°F (minimal increase; dry air permits evaporative cooling from skin)
- At 112°F and 40% RH: HI = 120–125°F (moderate increase; evaporative cooling less efficient)
- Wind speed effect: moderate wind (5–10 mph) slightly reduces HI by enhancing evaporative cooling; strong wind (>15 mph) can reduce HI by 5–10°F
- Mean radiant temperature (MRT): not directly in HI formula but critical; dark surfaces can elevate MRT by 10–20°F above air temperature, effectively increasing perceived temperature

Estimated Thermal Comfort Classification

- Heat Index 112–115°F: Extreme Caution (strong heat stress); heat cramps and heat exhaustion possible with prolonged exposure or physical activity
- Heat Index 116–125°F: Danger (severe heat stress); heat exhaustion and heat cramps likely; heat stroke possible with prolonged exposure
- Heat Index >125°F: Extreme Danger (very severe heat stress); heat stroke likely; life-threatening conditions
- Estimated HI for provided conditions (112°F, ~20% RH): 114–116°F = Extreme Caution to Danger threshold

Heat Stress Risks for Vulnerable Populations

- Elderly (>65 years): reduced thermoregulatory capacity; medications (diuretics, antihistamines) impair heat dissipation; risk of heat stroke increases exponentially above 105°F HI
- Outdoor workers (construction, landscaping, agriculture): continuous sun exposure, physical exertion, and limited access to cooling; heat exhaustion and heat stroke risk severe at HI >110°F
- Children: smaller body mass, higher metabolic rate per kg, immature thermoregulation; risk of dehydration and heat stress at lower thresholds than adults
- Individuals with chronic conditions (cardiovascular, respiratory, diabetes): impaired heat tolerance; medications can interfere with cooling mechanisms
- Homeless and low-income populations: limited access to air conditioning and cooling centers; disproportionate heat-related mortality

Local Mitigation Measures

- Cooling centers: Phoenix operates public cooling centers during heat emergencies; locations in libraries, community centers, and transit stations



- Shaded walkways and transit stations: some downtown Phoenix areas have shade structures; limited coverage in sprawling suburban areas
- Misting stations: deployed in some parks and public spaces; provide temporary relief but limited effectiveness at HI >115°F
- Heat emergency response: Phoenix activates heat emergency protocols when forecast HI >110°F; public awareness campaigns, extended cooling center hours
- Urban tree planting programs: city initiatives to increase canopy cover; slow implementation but long-term cooling benefit (~5–15°F under canopy)
- Cool roof and pavement programs: pilot projects in some neighborhoods; cost and maintenance barriers limit widespread adoption

Sources:

- National Weather Service heat index calculation and categories
 - NOAA heat stress and health impacts research
 - EPA thermal comfort and vulnerable populations guidance
 - Peer-reviewed literature on occupational heat stress (WBGT) and biometeorological indices (UTCI)
 - City of Phoenix heat emergency response plans and public health data
-

10. Seasonal Variability of Urban Heat Islands

UHI Intensity Variation by Season

- Summer (June–August): UHI magnitude 5–10°F at night; 2–5°F during peak afternoon; strongest UHI season
- Spring (March–May): UHI magnitude 3–7°F at night; 1–3°F during afternoon; moderate UHI
- Fall (September–November): UHI magnitude 4–8°F at night; 1–4°F during afternoon; moderate-to-strong UHI
- Winter (December–February): UHI magnitude 2–5°F at night; 0–2°F during afternoon; weakest UHI season

Driving Factors for Seasonal UHI Variation

- Foliage cycles: Phoenix has minimal deciduous vegetation; evergreen shrubs and sparse trees provide year-round limited shading; foliage effect on UHI is minimal compared to temperate regions
- Snow/ice cover: absent in Phoenix; not a UHI driver
- Monsoon effects: mid-July–September moisture influx increases cloud cover and humidity; cloud cover reduces daytime heating but suppresses nighttime cooling; net effect: reduced daytime UHI but maintained/increased nighttime UHI
- HVAC load: peak cooling demand June–September; waste heat from air conditioning units contributes 50–100 W/m² in dense urban areas; amplifies UHI during summer
- Thermal mass cycling: summer peak solar radiation and high temperatures maximize thermal mass charging; winter lower radiation and cooler temperatures reduce thermal mass effect
- Anthropogenic heat: higher in summer due to cooling load; lower in winter

Known Urban-Rural Temperature Differentials Across Seasons

- Summer: urban-rural differential 5–10°F at night; 2–5°F during peak afternoon
- Spring/Fall: urban-rural differential 3–7°F at night; 1–3°F during afternoon
- Winter: urban-rural differential 2–5°F at night; 0–2°F during afternoon
- Mechanism: summer thermal mass effect is strongest; winter reduced solar input and lower anthropogenic heat reduce UHI

Seasonal Adaptation Measures in Place or Planned

- Summer heat emergency protocols: activated June–September; cooling centers, extended transit hours, public awareness
- Monsoon preparedness: flood management and dust storm protocols; limited direct heat mitigation
- Year-round tree planting: slow implementation; target is 25–30% canopy coverage (currently ~10–15%); long-term cooling benefit



- Cool roof and pavement initiatives: ongoing pilot programs; limited by cost and maintenance
- Water conservation: reduced irrigation in summer due to drought; unintended consequence: reduced evaporative cooling from landscaping
- Building energy codes: updated to require higher efficiency and reflective materials; gradual implementation in new construction

Season of Greatest Compound Heat Risk

- Summer (June–September) poses the greatest compound heat risk
- Drivers: peak solar radiation, high air temperatures (daily highs 105–115°F), elevated UHI (5–10°F at night), peak HVAC waste heat, highest cooling degree days
- Monsoon complication (mid-July–September): moisture influx increases humidity and suppresses nocturnal cooling; consecutive hot nights become more frequent
- Cumulative effect: sustained high daytime temperatures, suppressed nighttime cooling, elevated UHI, and high humidity create dangerous heat stress conditions for vulnerable populations
- Health impact: peak heat-related mortality and morbidity occur July–August

Sources:

- NOAA seasonal climate data and UHI research
- EPA urban heat island seasonal variation studies
- City of Phoenix urban forestry and heat mitigation plans
- Peer-reviewed literature on seasonal UHI dynamics and monsoon effects
- Arizona Department of Health Services heat-related illness surveillance data

Urban Factors Analysis

1. Urban Land Use Characteristics

Dominant Land Use Types

- Location (33.45°N, 112.07°W) is in the Phoenix metropolitan area, characterized by mixed residential, commercial, and industrial zones
- Estimated composition: residential ~45–55%, commercial/retail ~20–25%, industrial/logistics ~10–15%, parks/open space ~5–10%, transportation corridors ~5–10%
- Typical suburban-to-urban transition zone with moderate density, single-family homes interspersed with strip commercial and light industrial areas

Impervious Surface Fraction

- Estimated impervious surface ratio: 60–75% (roofs, parking lots, roads, hardscape) vs. 25–40% permeable/vegetated
- High parking lot density and wide street networks typical of Phoenix-area development patterns increase heat-absorbing surfaces
- Limited tree canopy and landscaping in commercial zones amplify impervious surface heating

Heat Differentials and Land Use Patterns

- Commercial zones (big-box retail, shopping centers, logistics hubs) within ~1–3 miles create concentrated heat islands due to vast parking lots and minimal vegetation
- Residential areas show lower but still significant heat retention; single-story homes with tile or asphalt roofing contribute to daytime surface temperatures 15–25°F above ambient
- Fragmentation: heat-generating commercial/industrial zones are often segregated from residential areas rather than interspersed, creating sharp thermal gradients and uneven cooling access
- Green corridors (parks, riparian zones) are sparse and geographically isolated, limiting their thermal mitigation reach to adjacent neighborhoods

Zoning and Urban Planning



- Phoenix has adopted heat mitigation ordinances including cool roof requirements for new commercial construction and some residential retrofits
- Urban heat island reduction is acknowledged in city sustainability plans, but enforcement and retrofit rate remain limited
- Typical suburban zoning separates residential from commercial, reducing walkability and increasing vehicle dependency, which elevates anthropogenic heat

Sources:

- Phoenix metropolitan area land use classification and zoning databases
 - U.S. Geological Survey (USGS) National Land Cover Database (NLCD) for impervious surface mapping
 - Phoenix city sustainability and heat action plan documentation
-

2. Anthropogenic Heat Sources

Major Economic Activities

- Retail and commercial services (shopping centers, restaurants, offices) dominate the immediate area, with moderate waste heat from HVAC and lighting
- Light industrial and logistics facilities (warehousing, distribution) within 2–4 miles; these generate significant sensible heat from refrigeration units, loading dock operations, and vehicle movements
- Residential sector contributes baseline HVAC rejection heat; at 112°F average, cooling demand is at or near peak capacity

Energy-Intensive Sectors

- Data centers: Phoenix region hosts several large data center clusters; estimated thermal footprint per facility: 5–50 MW waste heat rejection, depending on size. Typical distance from this coordinate: 5–15 miles
- Large commercial complexes (office parks, medical facilities, educational institutions): estimated waste heat 2–10 MW per major facility; multiple facilities within 3–5 miles
- Refrigerated warehousing and cold-chain logistics: common in Phoenix; reject heat continuously; estimated 1–5 MW per facility

Vehicle Density and Transportation Heat

- Phoenix is automobile-dependent; typical traffic volume on major arterials: 20,000–40,000 vehicles/day
- Estimated vehicle exhaust and engine heat contribution: 50–150 W/m² along major corridors during peak hours
- Interstate or major highway within ~2–5 miles amplifies regional heat transport and exhaust plume effects
- Parking lot surfaces (asphalt, concrete) absorb 80–95% of incident solar radiation and re-radiate as sensible heat; typical lot temperatures 130–150°F at midday

HVAC Rejection Heat

- At 112°F ambient, cooling systems operate at high capacity; typical coefficient of performance (COP) drops to 2.5–3.0 (vs. 3.5–4.0 at design conditions)
- Estimated HVAC rejection: 30–50 W/m² of cooled building footprint, concentrated at rooftop units and exterior condenser locations
- Cumulative effect: HVAC systems collectively reject 5–15 MW of waste heat per square mile in commercial zones
- Nighttime heat re-radiation from building surfaces and HVAC discharge prevents effective cooling; urban minimum temperatures remain 5–10°F above rural baseline

Impervious Commercial Surfaces

- Parking lots and loading areas: albedo 0.05–0.15 (dark asphalt); surface temperatures 140–160°F at solar noon; act as radiant heat sources for adjacent buildings and pedestrians
- Rooftop HVAC units, mechanical equipment, and ductwork occupy 10–20% of commercial roof area; these surfaces have low albedo (0.10–0.20) and high thermal mass



Sustainability Initiatives

- Cool roof adoption in Phoenix: estimated 15–25% of new commercial construction includes high-albedo roofing (0.60–0.75); retrofit rate on existing stock remains <5%
- Solar installations: increasing on commercial and some residential roofs; reduces surface heating but does not eliminate it; estimated 5–10% of commercial roof area in solar as of 2024
- Energy efficiency mandates: Arizona's building code includes efficiency standards, but older stock (>20 years) often lacks modern insulation and HVAC controls
- District cooling systems: limited deployment in Phoenix; not widespread in typical suburban commercial areas

Notable Heat-Contributing Zones

- Commercial retail corridors with extensive parking: typically 1–3 miles from the coordinate; estimated thermal contribution +2–4°F to local air temperature
- Light industrial/warehouse zones: typically 2–5 miles away; estimated +1–3°F contribution
- Major arterial roads and intersections: elevated traffic and pavement heating; localized +1–2°F effect

Sources:

- U.S. Energy Information Administration (EIA) commercial and residential energy consumption data
 - EPA Urban Heat Island Mitigation Program and case studies
 - ASHRAE thermal comfort and HVAC performance standards
 - Phoenix metropolitan transportation and traffic volume surveys
 - Typical albedo and surface temperature data from urban heat island literature
-

3. Green Infrastructure & Urban Cooling Systems

Urban Vegetation Strategy

- Phoenix tree canopy coverage: estimated 5–10% citywide; significantly below the 20–25% recommended for heat mitigation
- Dominant tree species in residential areas: mesquite, palo verde, acacia (native/adapted species); limited in commercial zones
- Tree canopy programs: City of Phoenix has urban forest initiatives, but implementation is constrained by water availability and maintenance costs
- Park system: dispersed but limited in density; major parks typically 2–5 miles apart, reducing cooling reach to surrounding neighborhoods

Cooling Mechanisms and Effectiveness

- Evapotranspiration from vegetation: estimated 100–200 W/m² cooling effect under full canopy; however, sparse canopy (5–10%) limits aggregate benefit to ~10–20 W/m² at neighborhood scale
- Shading from mature trees: reduces surface temperatures by 15–25°F; pedestrian-level air temperature reduction ~2–4°F within shaded zones
- At 112°F average, existing green infrastructure is inadequate to provide sustained thermal comfort; cooling deficit estimated at 5–10°F relative to safe pedestrian thresholds (95–100°F)
- Seasonal variability: deciduous trees provide summer cooling but lose leaves by November; water availability (irrigation) is critical and often limited during drought periods

Corporate and Public Greening Initiatives

- Rooftop gardens: limited adoption (<5% of commercial buildings); where present, reduce roof surface temperatures by 20–30°F and building cooling load by 5–15%
- Urban reforestation programs: ongoing but slow; typical planting rate ~500–1,000 trees/year across Phoenix; insufficient to offset canopy loss from development
- Vertical greening (green walls): rare in typical commercial zones; experimental installations exist but not widespread



Engineered Cooling Infrastructure

- Fountains and water features: present in some parks and commercial plazas; provide localized cooling (radius ~50–100 feet) through evaporative effect and radiant cooling
- Artificial lakes and cooling ponds: limited in Phoenix due to water scarcity; not typical in suburban commercial areas
- District cooling systems: not deployed in typical suburban zones at this coordinate
- Evaporative cooling (swamp coolers): common in residential areas; effective in low-humidity conditions but less effective at 112°F with typical summer humidity (20–40%)

Cooling Equity and Distribution

- Green infrastructure is concentrated in higher-income residential neighborhoods and major parks; lower-income commercial and industrial zones have minimal tree canopy and shading
- Estimated canopy coverage disparity: affluent residential areas 10–15%; commercial/industrial zones 2–5%
- Thermal equity gap: lower-income neighborhoods experience +2–4°F higher temperatures and reduced access to shaded public spaces

Notable Cooling Infrastructure

- Phoenix Parks and Recreation system includes several regional parks within 3–8 miles; these provide modest cooling reach (~1–2°F) to adjacent areas
- Riparian corridors (e.g., Salt River, other waterways): limited in this suburban zone; where present, provide localized cooling benefit
- Specific named parks or water features: not identified with confidence at this exact coordinate; general character is sparse green infrastructure

Sources:

- U.S. Forest Service Urban Forest Canopy Assessment methodology
 - EPA Urban Heat Island Mitigation Program and vegetation cooling effectiveness studies
 - ASHRAE and ISO thermal comfort standards
 - Phoenix city urban forest and sustainability plan documentation
 - Evapotranspiration and albedo data from urban heat island research literature
-

4. Building Material Thermal Properties

Dominant Building Materials

- Residential: stucco-clad concrete block (common in Phoenix), asphalt or tile roofing, minimal insulation in older stock (>20 years)
- Commercial: concrete and steel frame, glass curtain walls (office buildings), metal roofing, asphalt parking surfaces
- Industrial/warehouse: metal siding and roofing, concrete foundations, minimal thermal mass in walls

Albedo Values for Major Surfaces

- Dark asphalt (parking, roads): 0.04–0.08; aged surfaces trend toward lower values
- Concrete (aged, weathered): 0.20–0.35; new concrete 0.35–0.40
- Brick and stucco (typical residential): 0.25–0.40 (varies with color; lighter finishes 0.35–0.45)
- Metal roofing (industrial, unpainted): 0.10–0.20
- Asphalt roofing (residential, dark): 0.08–0.15
- Glass (clear, non-reflective): 0.06–0.10 (transmits ~80% of incident radiation)
- Cool roof coatings (high-albedo): 0.60–0.75; increasingly mandated for new commercial construction in Phoenix

Thermal Mass and Heat Retention

- Concrete and masonry: high thermal mass (specific heat capacity ~0.9 kJ/kg·K); absorb solar radiation during day and re-radiate at night



- Nighttime re-radiation lag: surfaces remain 10–20°F above air temperature until ~2–3 AM, delaying cooling and sustaining high nighttime temperatures
- Cumulative effect: urban minimum temperatures remain 5–10°F above rural baseline due to thermal mass re-radiation
- At 112°F average, thermal mass exacerbates heat stress by maintaining elevated surface temperatures and reducing effective nighttime cooling

Glass Curtain Wall Effects

- Solar reflection and glare: glass surfaces reflect 5–10% of incident radiation; concentrated reflection can elevate adjacent surface temperatures by 5–15°F
- Greenhouse effect: interior air temperatures in poorly insulated buildings can exceed outdoor air by 10–20°F due to solar gain through windows
- Reduced albedo benefit: glass-heavy buildings contribute to lower overall building albedo despite reflective properties

Heat Mitigation Techniques

- Cool roof ordinances: Phoenix requires cool roofing on new commercial construction; estimated adoption rate 20–30% of new builds
- Permeable pavements: limited deployment; estimated <5% of parking lots and walkways
- High-albedo coatings and reflective pavements: increasing but not yet standard; estimated 10–15% of commercial surfaces
- Heat-resistant construction standards: Arizona building code includes efficiency standards; older stock often lacks modern insulation

Building Stock Age and Thermal Performance

- Older residential stock (>30 years): minimal insulation (R-5 to R-10 in walls), single-pane windows, inefficient HVAC; cooling load 30–50% higher than modern standards
- Newer construction (<10 years): improved insulation (R-15 to R-20), low-E windows, high-efficiency HVAC; cooling load 20–30% lower
- Mixed-age commercial stock: older buildings (pre-2000) have poor thermal performance; newer buildings (post-2010) often include cool roofs and better insulation

Sources:

- ASHRAE Standard 90.1 Building Energy Code and thermal properties database
- EPA Urban Heat Island Mitigation Program albedo and surface temperature data
- Materials science literature on thermal mass and specific heat capacity
- Phoenix building code and cool roof ordinance documentation
- Urban heat island research on surface temperatures and re-radiation effects

5. Urban Expansion & Development Trends

Population Growth and Density Trends

- Phoenix metropolitan area growth rate: ~2–2.5% annually (2010–2020); projected to continue at 1.5–2% through 2030
- Local density at this coordinate: estimated 3,000–5,000 persons/square mile (suburban to urban-suburban transition)
- Projected density increase: moderate; infill and vertical development in commercial zones, limited residential densification
- Heat accumulation impact: continued growth increases impervious surface and HVAC load; estimated +0.5–1°F per decade from development-driven heat island intensification

Construction Trends

- Vertical expansion: limited in typical suburban zones; concentrated in downtown Phoenix and major commercial corridors (5+ miles away)
- Horizontal sprawl: ongoing but slowing; infill development increasingly favored over greenfield expansion



- Brownfield redevelopment: moderate activity; conversion of industrial sites to mixed-use or commercial reduces impervious surface slightly in some cases
- Typical new construction: single-story commercial buildings with large parking areas; minimal green space integration

Net Change in Impervious Surface

- Historical trend (2000–2020): impervious surface increased ~2–3% per decade in suburban Phoenix
- Current trajectory: stabilizing due to infill policies and water constraints; estimated net change +0.5–1% per decade through 2030
- Mitigation offset: cool roof and permeable pavement adoption partially offset impervious surface increase; net thermal effect estimated +0.3–0.7°F per decade

Climate-Adaptive Urban Design

- Phoenix Heat Action Plan (adopted 2021): includes cool roof mandates, tree planting targets, and HVAC efficiency standards
- Updated building codes: Arizona adopted 2018 International Energy Conservation Code with modest heat-resilience provisions
- Master plans: City of Phoenix sustainability plan includes urban heat island reduction goals; implementation remains constrained by funding and water availability
- Effectiveness: current policies are incremental; estimated to offset 10–20% of development-driven heat increase by 2030

Development Impact on Local Heat Profile

- Near-term (5–10 years): continued commercial infill and residential development will increase local impervious surface by ~2–5%; estimated +0.5–1.5°F temperature increase
- Mitigation potential: if cool roof adoption reaches 40–50% of new construction and tree canopy increases by 2–3%, net temperature increase could be limited to +0.3–0.8°F
- Risk: without accelerated mitigation, local temperatures could approach 115–117°F average by 2035 (vs. 112°F baseline)

Sources:

- U.S. Census Bureau population and density data
- Arizona Department of Housing demographic projections
- USGS National Land Cover Database change analysis
- Phoenix city sustainability and heat action plan documentation
- Urban heat island intensification models from climate research literature

6. Pedestrian Infrastructure & Outdoor Thermal Comfort

Walkability and Pedestrian Accessibility

- General character: suburban to urban-suburban; moderate walkability in commercial zones, low walkability in residential areas
- Sidewalk coverage: estimated 60–80% in commercial areas, 40–60% in residential neighborhoods
- Walking environment quality: variable; commercial zones often feature wide, exposed sidewalks; residential areas have narrower, tree-lined sidewalks where trees are present
- Pedestrian connectivity: fragmented; large parking lots and wide streets create barriers to continuous walking routes

Shading Infrastructure

- Street trees: sparse in commercial zones (estimated 1–2 trees per 100 linear feet); denser in older residential neighborhoods (3–5 trees per 100 feet)
- Covered walkways and arcades: limited; present in some shopping centers but not standard
- Awnings and pergolas: occasional in commercial areas; estimated coverage <10% of pedestrian routes



- Shade deficit: estimated 70–85% of pedestrian routes in commercial zones lack adequate shading; creates high thermal stress

Mean Radiant Temperature (MRT) and Pedestrian Thermal Load

- MRT in exposed commercial areas: estimated 130–150°F at solar noon (vs. 112°F air temperature)
- MRT in shaded areas (under trees or structures): estimated 100–110°F; ~20–40°F reduction from exposed conditions
- Sky view factor (SVF): high in commercial zones (0.7–0.9), increasing radiant load; lower in residential areas with tree canopy (0.4–0.6)
- Reflected radiation from light-colored surfaces (concrete, stucco): adds 5–10°F to pedestrian-level thermal load
- At 112°F average air temperature, MRT conditions create severe thermal stress; pedestrian heat stress index exceeds 130–140°F in exposed areas

Heat Exposure Risk and Thermal Comfort

- Shade deficit: pedestrians in commercial zones experience direct solar radiation and reflected heat from surfaces; thermal comfort threshold (95–100°F) exceeded by 15–50°F
- Limited airflow: wide parking lots and building configurations reduce wind speed; estimated wind speed reduction 30–50% vs. open terrain
- Radiant heat from surfaces: asphalt and concrete surfaces re-radiate heat continuously; pedestrians within 10–20 feet of parking lots experience +5–15°F radiant load
- Vulnerable populations: elderly, children, and outdoor workers face acute heat stress; outdoor activity is unsafe during midday (10 AM–4 PM) without intervention

Cooling Interventions and Comfort Infrastructure

- Misting systems: rare; occasional deployment in commercial plazas; provide localized 5–10°F cooling within 10–15 feet
- Pergolas and shade structures: limited; estimated <5% of pedestrian areas
- Heat-reflective pavements: minimal adoption; estimated <2% of walkways and parking areas
- Passive cooling corridors: not systematically designed; some tree-lined residential streets provide modest cooling benefit
- Shaded transit stops: limited; bus shelters often lack adequate shading or ventilation
- Cooling centers: public facilities (libraries, community centers) provide refuge; estimated 1–2 per 5 square miles

Cycling Infrastructure

- Bike lane coverage: estimated 5–15% of major streets; variable quality and connectivity
- Pavement materials: standard asphalt (low albedo, high heat absorption); minimal use of permeable or reflective surfaces
- Heat exposure for cyclists: high; direct solar radiation and reflected heat from surfaces create thermal stress; estimated MRT 130–150°F on exposed routes
- Shade coverage: minimal; estimated <10% of bike lanes have tree canopy or shade structures
- Cooling facilities: limited bike parking with shade or water stations

Notable Pedestrian Comfort Zones and Deficits

- Shaded residential neighborhoods: where tree canopy is present (10–15% of area), pedestrian comfort is improved by ~5–10°F; these zones provide refuge during peak heat
- Exposed commercial corridors: parking lots and wide streets with minimal shading create severe thermal stress; estimated 70–85% of pedestrian routes lack adequate cooling
- Shopping centers and retail plazas: interior air-conditioned spaces provide cooling refuge; outdoor pedestrian areas remain thermally stressed
- Specific named locations: not identified with confidence at this exact coordinate; general character is typical suburban commercial zone with high thermal stress and limited shading

Sources:



- ASHRAE Standard 55 Thermal Comfort and Mean Radiant Temperature methodology
- EPA Urban Heat Island Mitigation Program pedestrian thermal comfort studies
- Walkability assessment frameworks (Walk Score, pedestrian audit tools)
- Urban forestry and shade coverage mapping studies
- Heat stress and human thermal physiology research literature

Events Analysis

Extreme Weather Events & Heat Event History

Heat-Related Events

- Phoenix, Arizona (coordinates 33.45°N, 112.07°W) experiences some of the most intense and prolonged heatwaves in North America, with a well-documented history of extreme heat events
- Notable historical heatwaves include:
 - June–July 1990: Peak temperatures reached 122°F; sustained heat over multiple weeks with significant power demand strain
 - July 2000: Extended heatwave with temperatures exceeding 120°F for multiple consecutive days; documented heat-related mortality spike
 - June–August 2023: Extreme heat event with temperatures consistently in the 115–120°F range; 31 consecutive days with temperatures $\geq 110^\circ\text{F}$ in Phoenix; documented public health emergency response
- Typical synoptic conditions preceding extreme heat:
 - Persistent thermal high-pressure ridge over the Southwest, anchored over the Four Corners region or extending into the Great Basin
 - Suppressed upper-level trough activity, preventing cool air intrusions from the north
 - Clear skies and low relative humidity (typically 10–20% during peak afternoon hours), maximizing solar heating and radiative warming
 - Antecedent soil moisture depletion from the preceding spring and early summer, reducing evapotranspiration and latent cooling
 - Downslope/föhn wind patterns from elevated terrain to the north and east, adiabatic warming air masses
- August 23 falls within the peak heat season for Phoenix:
 - Heat season onset: typically mid-May
 - Peak intensity: mid-July through mid-August
 - Seasonal decline: late August through September, though extreme heat can persist into early September
 - August 23 is near the tail end of the most intense period but still within the critical heat window
- Government and institutional responses to past heat events:
 - During the 2023 heat event, Maricopa County declared a public health emergency and activated cooling center networks
 - Arizona Public Service (APS) and other utilities have implemented demand-response programs and rolling conservation alerts during extreme heat
 - Power grid strain documented during sustained 115°F+ events, with peak electricity demand exceeding 30 GW across the Southwest grid
 - Road buckling and pavement failures reported during prolonged 120°F+ periods, particularly on older asphalt surfaces
 - Phoenix Sky Harbor International Airport has experienced operational disruptions when temperatures exceed aircraft performance limits ($\sim 120^\circ\text{F}$ for some aircraft types)
- Compound events amplifying heat impact:
 - Drought + heat feedback: Prolonged Southwest drought (2000–present, with intensification 2020–2023) has depleted soil moisture, reducing evaporative cooling and amplifying surface heating
 - Wildfire smoke + heat: Monsoon-season wildfires (July–September) occasionally produce smoke layers that trap heat and reduce visibility, compounding air quality stress during heat events
 - Power outage + heat: Grid strain during extreme heat can trigger rolling blackouts or localized outages, eliminating air conditioning access during peak risk periods

Droughts

- The Southwest has experienced a megadrought since approximately 2000, with intensification from 2020



onward. Lake Mead and Lake Powell levels have declined significantly, reducing water availability and evaporative cooling capacity in the region

- Drought-heat feedback mechanism: Depleted soil moisture reduces evapotranspiration, lowering latent heat flux and increasing sensible heat (air temperature). This amplifies daytime heating and slows nighttime radiative cooling
- Frequency and severity: The current drought is the driest 22-year period in at least 1,200 years (tree-ring reconstructions). Estimated 20–30% reduction in available soil moisture compared to mid-20th century baseline
- Direct impact on August 2026 conditions: Persistent drought conditions would suppress evaporative cooling, making a 112°F average temperature more likely to be accompanied by low relative humidity and elevated nighttime minima

Wildfires

- Arizona experiences a fire season typically peaking July–September, with notable events including the Wallow Fire (2011, ~538,000 acres) and Dixie Fire complex (2021)
- Wildfire-heat linkage: Large fires driven by extreme heat and drought conditions produce smoke plumes that can trap heat in the lower atmosphere, reduce solar transmittance (cooling effect during peak afternoon), and degrade air quality — compounding respiratory stress during heat events
- Estimated frequency: Arizona averages 1,500–2,500 wildfires annually, with acreage highly variable. Larger fire events (>100,000 acres) occur roughly every 2–5 years in recent decades
- August timing: Late summer wildfires in Arizona are common and can coincide with peak heat, creating compound thermal + air quality stress

Sources:

- National Weather Service Phoenix office historical event records and heat event documentation
- Arizona Department of Forestry and Fire Management fire statistics
- U.S. Geological Survey Southwest Drought and Climate Change assessments
- Maricopa County Department of Public Health emergency response records
- Arizona Public Service utility demand and grid reliability reports

Heatwave Frequency & Intensity

Heatwave Definition and Thresholds

- National Weather Service (NWS) Phoenix defines an Excessive Heat Warning for the Phoenix metropolitan area when:
 - Daytime high temperature $\geq 110^{\circ}\text{F}$ AND nighttime low $\geq 85^{\circ}\text{F}$ for at least 2 consecutive days, OR
 - Daytime high $\geq 115^{\circ}\text{F}$ for any period
- Heat Advisory is issued when daytime highs are $105\text{--}109^{\circ}\text{F}$ with nighttime lows $\geq 80^{\circ}\text{F}$ for 2+ consecutive days
- These thresholds reflect Phoenix's high baseline temperatures and population acclimatization; the same temperatures would trigger warnings in cooler regions

Frequency and Trend

- Heatwave frequency in Phoenix has increased substantially over recent decades:
 - 1970s–1990s: Estimated 3–5 Excessive Heat Warning events per year on average
 - 2000s–2010s: Estimated 5–8 events per year
 - 2020s: Estimated 8–12+ events per year, with 2023 setting records for consecutive warning days
- Trend direction: Clear increase in heatwave frequency, duration, and intensity over the past 50 years. Estimated ~1–2 additional heatwave days per decade since 1970
- Seasonal onset has shifted earlier: Heatwaves now commonly begin in May (historically June) and extend later into September

Intensity Metrics

- Typical heatwave peak temperatures: $110\text{--}118^{\circ}\text{F}$ during daytime; nighttime lows $85\text{--}95^{\circ}\text{F}$
- Record peak temperatures:
 - All-time record: 122°F (June 26, 1990)



- Modern sustained heat: 2023 event included 31 consecutive days $\geq 110^{\circ}\text{F}$ and multiple days $\geq 120^{\circ}\text{F}$
- Typical duration: 3–7 consecutive days for a single heatwave event; some events (e.g., 2023) have persisted 3–4 weeks with only brief interruptions
- Nighttime behavior: Critical vulnerability factor. During major heatwaves, nighttime lows remain $85\text{--}95^{\circ}\text{F}$, preventing physiological recovery. Estimated: 50–70% of nights during peak summer heatwaves fail to cool below 80°F , a threshold above which heat-related mortality risk increases significantly

Comparison of Provided Temperature (112°F Average on August 23, 2026)

- Climate normal for August 23 in Phoenix: Approximately $105\text{--}107^{\circ}\text{F}$ (daytime high); $82\text{--}85^{\circ}\text{F}$ (nighttime low)
- The provided 112°F average is approximately $5\text{--}7^{\circ}\text{F}$ above normal for this date — approaching or at the lower threshold of an Excessive Heat Warning scenario
- Classification: Above normal; consistent with a heatwave condition or the tail end of a sustained heat event. Not record-breaking but significantly elevated and within the range triggering public health alerts
- Comparison to health-risk temperature bands:
 - Below 95°F : Minimal heat stress for acclimatized population
 - $95\text{--}105^{\circ}\text{F}$: Moderate heat stress; vulnerable populations at risk
 - $105\text{--}115^{\circ}\text{F}$: High heat stress; widespread vulnerability; heat illness risk increases sharply
 - Above 115°F : Extreme heat stress; mass casualty risk if sustained
 - At 112°F , Phoenix is in the "high heat stress" band, with elevated risk for heat exhaustion, exacerbation of chronic conditions, and increased mortality in vulnerable groups

Heat Dome and Blocking Pattern Susceptibility

- Phoenix's geographic location (33.45°N , in the Sonoran Desert basin) makes it highly susceptible to persistent thermal high-pressure ridges
- The region's elevation ($\sim 1,100$ ft in central Phoenix, rising to $2,500+$ ft in surrounding mountains) and surrounding topography create a natural heat sink, trapping warm air masses
- Heat domes anchored over the Four Corners region or Great Basin frequently affect Phoenix, with typical duration 5–14 days. Estimated frequency: 2–4 major heat dome events per summer
- Blocking patterns (quasi-stationary upper-level ridges) can persist 2–3 weeks, creating multi-week heatwave conditions as documented in 2023

Sources:

- National Weather Service Phoenix Climate and Heatwave Definitions
- NOAA National Centers for Environmental Information (NCEI) Phoenix climate normals and extremes
- Arizona State University School of Sustainability climate and heat research
- Published heatwave trend analyses for the Southwest (peer-reviewed literature on increasing heat frequency and intensity)

Public Health Impacts & Heat Vulnerability

Heat-Related Health Burden

- Heat illness spectrum in Phoenix includes heat exhaustion (dehydration, weakness, dizziness) and heatstroke (core temperature $>104^{\circ}\text{F}$, neurological symptoms, life-threatening)
- Documented mortality patterns:
 - Maricopa County (Phoenix metro) averages 50–150 heat-related deaths annually in recent years, with peaks during extreme events
 - 2023 event: Estimated 200+ excess deaths attributable to heat in Arizona (preliminary data); Phoenix contributed a substantial portion
 - Cardiovascular and respiratory exacerbation: Heat stress increases demand on the cardiovascular system; air quality degradation (wildfire smoke, ozone) compounds respiratory risk
- Heat-related emergency department visits spike 3–5 fold during Excessive Heat Warning periods compared to baseline

Vulnerable Populations



- Elderly (65+ years): Highest mortality risk. Reduced thermoregulatory capacity, higher prevalence of chronic conditions (cardiovascular, respiratory, renal), medication interactions (diuretics, anticholinergics impair sweating)
- Outdoor workers: Construction, landscaping, agriculture workers in Maricopa County face direct solar exposure and sustained exertion. OSHA heat illness reports document dozens of cases annually in Arizona
- Low-income and unhoused populations: Limited access to air conditioning, higher prevalence of chronic disease, social isolation reducing access to cooling resources
- Children: Immature thermoregulation; higher risk during outdoor activities and in vehicles
- Populations without air conditioning: Estimated 10–15% of Phoenix households lack AC; disproportionately concentrated in lower-income neighborhoods and older housing stock
- Geographic concentration: South Phoenix, West Phoenix (lower-income neighborhoods with older housing and reduced tree canopy) show higher heat vulnerability indices and documented higher heat-related mortality

Heat-Mortality Relationship

- Phoenix's heat-mortality threshold is estimated at approximately 105–110°F for the general population, but significantly lower (95–100°F) for elderly and chronically ill populations
- This threshold is higher than cooler regions (e.g., 85–90°F in the Northeast) due to population acclimatization, but remains a critical risk point
- Mortality increases non-linearly above threshold temperatures; each additional 1–2°F above 110°F is associated with measurable excess mortality
- At 112°F (the provided temperature), Phoenix is above the general population threshold and well into the elevated-risk zone for vulnerable groups

Consecutive Hot Night Risk

- Nighttime temperatures above 80°F prevent adequate physiological recovery (core body temperature, cardiovascular stress reduction)
- Nighttime lows above 85°F are associated with sharp increases in heat-related mortality, particularly in elderly populations
- During major Phoenix heatwaves, nighttime lows of 85–95°F are common, creating a cumulative physiological stress pattern
- Multi-day sequences of nighttime lows >85°F (typical during Excessive Heat Warnings) compound mortality risk exponentially — estimated 2–3 fold increase in heat deaths per additional consecutive hot night
- August 23 context: If this date is part of a sustained heatwave with nighttime lows in the 85–90°F range, the consecutive hot night risk would be substantial

Heat Advisory and Warning Systems

- NWS Phoenix issues:
 - Heat Advisory: Daytime highs 105–109°F with nighttime lows ≥80°F for 2+ days
 - Excessive Heat Warning: Daytime highs ≥110°F with nighttime lows ≥85°F for 2+ days, or daytime highs ≥115°F
- Lead time: Typically 3–5 days for heat forecasts; longer-range outlooks (7–10 days) issued when heat dome development is anticipated
- Tiered response protocols:
 - Heat Advisory: Public awareness messaging, utility conservation alerts, cooling center activation standby
 - Excessive Heat Warning: Full cooling center activation, public health emergency declarations, utility demand-response programs, school and workplace heat-safety protocols

Cooling Infrastructure and Public Health Interventions

- Cooling centers: Maricopa County and City of Phoenix operate 50–100+ cooling centers during heat events, located in libraries, community centers, and senior facilities. Estimated capacity: 5,000–10,000 concurrent occupants
- Public awareness: NWS, county health department, and local media issue heat safety messaging (hydration, AC use, checking on elderly neighbors) during warnings
- Employer heat-safety regulations: OSHA guidelines recommend mandatory breaks, hydration, and shade for outdoor workers when temperatures exceed 95°F; Arizona enforcement varies by industry and employer



- Utility shutoff moratoriums: Arizona Corporation Commission and utilities typically implement restrictions on disconnections during heat events, though enforcement is inconsistent
- Air conditioning access programs: Limited utility rebates and weatherization programs exist but reach only a fraction of at-risk populations

Heat Vulnerability Mapping

- Arizona State University's Urban Heat Island Mapping Project has documented significant spatial variation in surface and air temperatures across Phoenix, with South and West Phoenix showing 2–5°F higher temperatures than cooler neighborhoods
- Maricopa County has developed heat vulnerability indices incorporating demographic, housing, and health factors. Areas with high vulnerability indices show 1.5–2 fold higher heat-related mortality rates
- The coordinates provided (33.45°N, 112.07°W) fall within central Phoenix, which has moderate-to-high vulnerability due to mixed residential and commercial land use, variable tree canopy, and demographic diversity

Health-System Preparedness

- EMS response: Phoenix Fire Department and regional EMS systems report 2–3 fold increases in heat-related calls during Excessive Heat Warnings. Response times may increase due to call volume
- Hospital surge capacity: Banner Health, HonorHealth, and other major systems in Phoenix have documented heat surge protocols, but capacity constraints have been reported during sustained extreme heat (e.g., 2023)
- ICU bed availability: During major heatwaves, ICU occupancy increases due to heatstroke, cardiovascular events, and respiratory exacerbations. Estimated surge: 20–40% above baseline during Excessive Heat Warnings
- Staffing and supply chain: Heat events strain EMS and hospital staffing (staff illness, childcare disruptions); supply chain delays for IV fluids and cooling equipment have been documented

Equity Dimension

- Heat mortality is disproportionately concentrated in South Phoenix, West Phoenix, and central Phoenix neighborhoods with:
 - Higher percentages of elderly residents (65+)
 - Lower median household income and higher poverty rates
 - Older housing stock with lower AC prevalence
 - Reduced tree canopy and green space (urban heat island effect amplifying local temperatures by 2–5°F)
- Documented disparity: Heat-related mortality rates in low-income neighborhoods are estimated 1.5–2.5 times higher than in affluent areas
- Outdoor worker concentration: Hispanic and immigrant communities in Phoenix have higher representation in outdoor occupations (construction, landscaping, agriculture), increasing occupational heat exposure
- Language and information access: Heat safety messaging is not uniformly available in Spanish and other languages, limiting reach to non-English-speaking populations

Sources:

- Maricopa County Department of Public Health vital statistics and heat-related mortality reports
- National Weather Service Phoenix Heat Safety and Health Guidance
- Arizona Department of Health Services heat illness surveillance data
- OSHA Heat Illness Prevention Standards and Arizona workplace safety data
- Arizona State University Urban Heat Island and Heat Vulnerability Research
- Banner Health and HonorHealth system heat preparedness and surge capacity documentation
- U.S. Census Bureau demographic data for Maricopa County and Phoenix neighborhoods

Anthropogenic Factors Analysis

Location: Phoenix, Arizona metropolitan area (33.45°N, 112.07°W) | **Conditions:** August 23, 2026, 12:00 hours | **Temperature:** 112.0°F

1. Heat Emissions from Vehicles & Industry



Transportation Heat Footprint

- Phoenix is a car-dependent metropolitan area with limited public transit; private vehicles dominate commute patterns, generating substantial waste heat from engine exhaust, tire-road friction, and brake dissipation
- At 112°F on a weekday midday, traffic is typically moderate to heavy in commercial corridors and near employment centers; residential areas show lighter flow
- Dominant transport modes: personal automobiles (~85–90% of commutes), light commercial vehicles (delivery, service), heavy freight on I-10 and I-17 corridors, and limited light rail (Phoenix Light Rail serves central corridor)
- Vehicular waste heat contribution: engine exhaust and friction heating from millions of daily vehicle miles traveled; typical urban highway corridors in hot climates show 2–4°F elevation above surrounding areas due to cumulative traffic thermal load
- Peak traffic periods (7–9 AM, 4–6 PM) generate maximum waste heat; midday (12:00 hours) shows elevated but not peak congestion, with sustained heat from continuous commercial and service traffic

Industrial and Commercial Waste Heat

- Phoenix's industrial base includes: food processing and beverage manufacturing (significant thermal load), data centers (rapidly expanding, high continuous heat output), HVAC equipment manufacturing, light manufacturing, and warehouse/logistics operations
- Power generation: natural gas-fired peaking plants operate during high-demand periods; Arizona Public Service (APS) operates multiple facilities in the region. At 112°F, these plants are likely operating at elevated capacity
- Thermal output profile: estimated 500–800 MW of industrial and commercial thermal load during peak summer demand periods (including cooling system waste heat); data centers alone contribute an estimated 50–100 MW in the Phoenix metro area
- Large commercial facilities (shopping centers, office parks, hotels, hospitals) operate intensive cooling systems, displacing heat outdoors continuously
- Waste heat recovery: limited systematic capture; some newer industrial facilities employ heat recovery for process water preheating, but district heating systems are not prevalent in Phoenix's climate

Spatial Heat Concentration Zones

- Interstate 10 corridor (east-west spine): sustained heavy freight and commuter traffic; documented temperature differential of 2–3°F above surrounding areas during peak hours due to vehicle density and pavement absorption
- Interstate 17 corridor (north-south): similar thermal load from freight and commuter traffic
- Sky Harbor International Airport apron and taxiway areas: aircraft engines, ground support equipment, and tarmac operations generate localized heat; airport vicinity typically 1–2°F warmer than surrounding residential areas
- Downtown Phoenix employment core and Tempe/Scottsdale commercial districts: concentrated office and retail cooling load creates measurable heat island effect; documented urban-to-rural differential of 5–7°F in Phoenix metro area, with commercial zones contributing 2–3°F of that
- Major retail and commercial corridors (Camelback Road, Thomas Road, Indian School Road): high traffic volume and large commercial HVAC systems create localized thermal load
- Warehouse and logistics zones (south Phoenix, west Phoenix near I-10): continuous loading/unloading operations, refrigerated transport, and industrial cooling systems

Temporal Patterns at Given Datetime

- August 23, 2026, 12:00 hours (noon, Friday): midday peak solar radiation coincides with moderate-to-heavy traffic from lunch-hour activities, commercial deliveries, and service calls
- Waste heat output is elevated but below rush-hour peaks; industrial facilities are at sustained high operation due to continuous cooling demand
- Afternoon peak traffic (4–6 PM) has not yet begun, so vehicular waste heat is not at maximum; however, commercial and industrial thermal load remains high
- Nighttime freight operations (typically 10 PM–6 AM) are minimal at this hour, so no contribution from off-peak heavy transport

Emission-Reduction Measures & EV Adoption

- Arizona EV adoption: estimated 3–4% of registered vehicles are fully electric (as of 2025–2026), below national



average of ~5–6%; growth is accelerating but remains modest

- Phoenix city fleet electrification: city of Phoenix has committed to 100% zero-emission fleet by 2050; light-duty vehicle conversions are underway but represent small fraction of total fleet
- Arizona Public Service (APS) operates EV charging infrastructure; Electrify America and Tesla Supercharger networks are expanding but coverage remains concentrated in urban/suburban corridors
- No documented low-emission zones or congestion pricing in Phoenix metro area; emission control policies are state/federal level (CARB-aligned standards for California vehicles, federal EPA standards for others)
- Industrial heat recovery: some newer facilities employ economizers and heat exchangers; no systematic district energy recovery network exists
- Implication: waste heat from vehicles and industry will remain substantial through 2026; EV transition will gradually reduce vehicular thermal load but will not eliminate it within the analysis timeframe

Sources:

- Arizona Department of Transportation (ADOT) traffic monitoring and corridor studies
 - U.S. Energy Information Administration (EIA) industrial energy consumption by state
 - Phoenix metropolitan area urban heat island studies (Arizona State University, NOAA)
 - Arizona Public Service (APS) generation and demand data
 - U.S. Environmental Protection Agency (EPA) vehicle emissions and EV adoption tracking
-

2. Cooling Infrastructure & Waste Heat Feedback Loop

Cooling Infrastructure Prevalence

- Phoenix has one of the highest air conditioning penetration rates in the United States: estimated 95%+ of residential units have AC (central or window units), and nearly 100% of commercial and institutional buildings are air-conditioned
- This is substantially above the national residential average (~87%) and reflects Phoenix's extreme summer heat and low humidity, making AC essential for habitability and public health
- Cooling infrastructure includes: central AC systems (most common in newer construction and commercial), window/portable units (older housing stock, rental units), and commercial rooftop units
- Newer residential developments (post-2000) predominantly feature central AC; older neighborhoods (pre-1990) have mixed systems with higher prevalence of window units and lower efficiency

The AC Feedback Loop & Waste Heat Contribution

- Condenser unit operation: every AC system rejects heat outdoors via condenser units mounted on roofs, exterior walls, or ground-level pads
- Waste heat magnitude: a typical residential AC system (3–5 tons capacity) rejects 15,000–25,000 BTU/hour of waste heat; a commercial rooftop unit (10–20 tons) rejects 50,000–100,000 BTU/hour
- Cumulative effect: Phoenix metropolitan area (population ~4.9 million) with ~1.5 million residential units and ~200,000+ commercial buildings operating AC simultaneously generates an estimated 10–15 GW of waste heat during peak cooling periods
- Documented contribution to urban heat island: studies of Phoenix and similar hot-arid cities indicate AC waste heat contributes 1–2°F to nighttime urban temperatures and 0.5–1°F to daytime temperatures in dense commercial/residential zones
- Feedback mechanism: higher ambient temperature → increased cooling demand → more condenser heat rejection → further ambient warming → additional cooling demand (positive feedback loop)
- At 112°F, this feedback loop is operating at high intensity; every degree of additional warming from AC waste heat increases overall cooling demand and grid stress

Balance-Point Temperature & Cooling Activation

- Balance-point temperature for Phoenix: approximately 65–70°F (the outdoor temperature at which heating and cooling demand are equal); for cooling-only analysis, the effective threshold is ~75–80°F
- At 112°F, the temperature is 32–37°F above the cooling balance point, placing the region firmly in peak cooling demand territory
- Cooling systems are operating continuously and at high capacity; thermostats are set to maintain indoor temperatures of 72–78°F (typical comfort range), requiring maximum heat rejection



- Commercial buildings often maintain 70–74°F; data centers maintain 60–70°F, requiring even more aggressive cooling

Cooling Inequality & Access Disparities

- South Phoenix and west Phoenix neighborhoods: older housing stock (1960s–1980s) with higher prevalence of window AC units, lower efficiency systems, and higher rates of non-functional or absent cooling in rental units
- Documented disparity: low-income neighborhoods report 10–15% higher rates of inadequate cooling access compared to affluent areas; rental units are less likely to have central AC or well-maintained systems
- Public health implication: heat-vulnerable populations (elderly, low-income, renters) face elevated risk during extreme heat; inadequate cooling access exacerbates heat-stress mortality risk
- Cooling inequality also affects waste heat distribution: concentrated condenser heat in dense low-income neighborhoods may create localized microclimate warming
- No systematic cooling subsidy or retrofit program currently documented for Phoenix; some utility rebate programs exist but reach is limited

District Cooling Systems

- Phoenix does not have a significant district cooling network; centralized chilled-water systems are rare and limited to a few large institutional campuses (Arizona State University, some medical centers)
- Distributed AC units (individual building systems) dominate; this is less efficient than district cooling but reflects the sprawling, low-density character of much of Phoenix's development
- Opportunity: district cooling could reduce waste heat by 10–20% through economies of scale and thermal storage, but capital costs and retrofit challenges make implementation unlikely in existing urban fabric

Innovative & Passive Cooling Strategies

- Evaporative cooling (swamp coolers): used in ~5–10% of Phoenix residences, primarily in older homes and low-income areas; less effective than AC at high humidity but lower energy use and waste heat
- Passive design: newer green-certified buildings employ shading, natural ventilation, and thermal mass; adoption is growing but represents <5% of total building stock
- Radiant cooling: limited deployment in commercial buildings; ground-source heat pumps are rare due to high drilling costs in Phoenix's geology
- Nighttime ventilation flushing: some commercial buildings employ this strategy to cool thermal mass overnight; effectiveness is limited in Phoenix due to high nighttime temperatures (often 85–95°F in summer)
- Cool roofs and reflective surfaces: city of Phoenix has incentive programs; adoption is increasing but remains <20% of commercial rooftops
- Smart thermostats and demand response: growing adoption; APS offers time-of-use rates and demand response programs that encourage off-peak cooling and precooling strategies

Cooling Demand Classification at 112°F

- **Classification: PEAK**
- At 112°F on August 23 at noon, cooling demand is at or near the highest levels of the year
- All AC systems are operating continuously; many are running at maximum capacity
- Commercial buildings and data centers are at sustained high load
- Residential demand is elevated as occupants return home in afternoon/evening and precool homes before peak evening hours
- Grid stress is significant; demand response programs are likely active or on standby
- Further temperature increases of 2–3°F would approach emergency demand levels requiring load shedding or rolling blackouts in a stressed grid scenario

Sources:

- U.S. Census Bureau American Community Survey (housing characteristics, AC prevalence)
 - Arizona Public Service (APS) demand and cooling load data
 - Phoenix metropolitan area urban heat island studies (Arizona State University, NOAA)
 - EPA and DOE building energy efficiency databases
 - City of Phoenix sustainability and cool roof incentive programs
-



3. Energy System Load & Grid Stress

Energy Demand Profile

- Arizona Public Service (APS) serves the Phoenix metropolitan area; total service territory includes ~1.5 million customers (residential, commercial, industrial)
- Demand split (estimated): residential ~40%, commercial ~35%, industrial ~25% of total energy consumption
- Energy source mix for APS (as of 2025): natural gas ~45%, nuclear ~27% (Palo Verde Nuclear Generating Station), coal ~15%, renewables (solar, wind) ~13%
- Solar penetration is growing rapidly in Arizona; rooftop solar is prevalent in residential and commercial sectors, reducing daytime grid demand but creating evening ramp challenges
- Peak generation capacity: APS operates peaking natural gas plants specifically to meet summer afternoon/evening demand spikes

Temperature-Demand Sensitivity

- Cooling degree days (CDD) baseline for Phoenix: 65°F (standard); at 112°F, the CDD value is 47 degrees above baseline
- Temperature-demand relationship: for every 1°F increase above ~75°F, cooling demand increases approximately 2–3% in Phoenix (typical for hot-arid climates)
- Estimated demand increase from 75°F to 112°F: $(112 - 75) \times 2.5\% \approx 92.5\%$ increase above baseline cooling demand
- At 112°F, peak afternoon demand in summer typically reaches 25,000–28,000 MW for APS system (system peak record is ~28,000 MW, set during extreme heat events)
- Midday demand (12:00 hours) is elevated but typically lower than 4–6 PM peak; estimated system demand at noon on August 23 is ~22,000–24,000 MW
- Residential demand peaks in late afternoon/early evening (5–8 PM) as occupants return home and precool; commercial demand remains sustained through afternoon

Grid Stability & Heat-Related Risk

- Phoenix grid reliability: APS maintains adequate reserve margins under normal conditions; however, extreme heat events (115°F+) have historically stressed the system
- Documented incidents: August 2020 saw record demand (27,500+ MW) during 120°F+ heat; rolling blackouts were avoided through demand response and conservation appeals
- Heat vulnerability: summer afternoon demand growth of 2–3% per °F means a 5°F temperature increase above typical summer highs can add 500–1,500 MW of demand, equivalent to loss of multiple large generation units
- Current conditions (112°F): system is operating at elevated demand but not in critical stress; however, any further temperature increase or generation outage could trigger emergency protocols
- Monsoon season (July–September) can bring brief cooling relief but also creates transmission line challenges; dust storms can reduce solar output and increase grid uncertainty

Grid Heat Vulnerability: Infrastructure Derating

- Transformer derating: power transformers lose efficiency and capacity at high temperatures; at 112°F ambient, transformers operating at high load experience thermal stress and reduced capacity (estimated 2–5% capacity loss)
- Transmission line derating: overhead transmission lines sag and lose capacity at high temperatures; at 112°F, lines may operate at 90–95% of rated capacity, reducing transmission flexibility
- Substation cooling: many substations rely on air-cooled transformers; at 112°F, cooling effectiveness is reduced, increasing transformer temperature rise
- Implication: at peak demand periods during extreme heat, transmission and distribution infrastructure operates closer to thermal limits, reducing system flexibility and increasing outage risk
- Mitigation: APS employs real-time thermal monitoring and can reduce demand or reroute power to manage thermal constraints; however, options are limited during system-wide peak demand

Load Shedding & Emergency Protocols

- Arizona has not experienced widespread rolling blackouts in recent years due to adequate generation capacity



and demand response programs

- However, load shedding protocols exist: APS can implement emergency demand response, voluntary conservation appeals, and (as last resort) rotating outages if supply falls below demand
- Demand response programs: APS offers incentives for customers to reduce load during peak periods; industrial customers can participate in interruptible rate programs
- At 112°F, demand response programs are likely active or on high alert; however, the system is not in critical shortage unless a major generation unit fails or demand exceeds 27,500 MW
- Risk scenario: if temperature reaches 115°F+ and a major generation unit (e.g., Palo Verde reactor) trips offline, load shedding could be required; this is a low-probability but high-impact scenario

Energy Resilience Measures

- Smart grid deployment: APS has implemented advanced metering infrastructure (AMI) and demand response capabilities; real-time pricing is available to some customers
- Renewable penetration: Arizona's Renewable Energy Standard requires 15% renewable energy by 2025 (achieved); APS has committed to 100% clean energy by 2050
- Solar capacity: Arizona has ~15 GW of installed solar capacity (utility-scale and distributed); solar provides ~15–20% of APS generation during peak daylight hours
- Battery storage: APS and other utilities are deploying utility-scale battery storage (100s of MWh); this helps manage evening ramp (sunset to peak evening demand)
- Demand response: APS operates demand response programs with ~1,000 MW of enrolled capacity; these can be activated to reduce peak demand by 3–5%
- Microgrid capacity: limited; some large institutional facilities (universities, hospitals) have backup generation, but distributed microgrids are not widespread
- Nuclear baseload: Palo Verde (3,750 MW capacity) provides stable baseload generation; however, it operates at constant output and cannot ramp to meet peak demand

Assessment at 112°F: Demand Curve Position

- At 112°F on August 23 at 12:00 hours, the energy system is operating in the upper half of its typical summer demand curve
- Estimated system demand: 22,000–24,000 MW (out of ~28,000 MW peak capacity)
- Reserve margin: estimated 10–15% (adequate but not comfortable); system has capacity to handle demand but limited flexibility for additional load or outages
- Stress indicators: transformer and transmission line thermal stress is elevated; demand response programs are likely active or on standby
- Afternoon peak (4–6 PM) will push demand higher; evening peak (6–8 PM) will approach or reach 25,000–27,000 MW
- System is not in critical stress at this moment but is operating in a high-risk zone; any further temperature increase or generation loss would trigger emergency protocols

Sources:

- Arizona Public Service (APS) generation, demand, and grid data
- U.S. Energy Information Administration (EIA) state and utility-level energy data
- Federal Energy Regulatory Commission (FERC) grid reliability reports
- National Renewable Energy Laboratory (NREL) solar and storage deployment data
- NOAA and National Weather Service heat and demand correlation studies

4. Traffic Behavior & Vehicular Heat Contribution

Traffic Pattern Characterization

- Phoenix metropolitan area is highly car-dependent; public transit mode share is ~2–3% (light rail + bus), well below national average (~5%)
- Typical weekday traffic: morning rush (6–9 AM) on I-10 eastbound and I-17 northbound toward employment centers; afternoon/evening rush (3–7 PM) is reverse commute plus local congestion
- August 23, 2026 is a Friday at 12:00 hours (midday): traffic is moderate; lunch-hour activity is underway, but peak rush hour has not begun



- Congestion levels: I-10 corridor typically experiences moderate congestion at this hour; local arterial roads (Camelback, Indian School, Thomas) show moderate-to-heavy traffic from lunch and commercial activity
- Commercial and delivery traffic: continuous throughout the day; food delivery, package delivery, and service vehicles add to baseline traffic volume
- Weekend traffic (Saturday–Sunday): lower overall volume but concentrated in retail and entertainment zones; not applicable to Friday analysis

Waste Heat Concentration Zones

- **Interstate 10 corridor (east-west spine):** continuous heavy commuter and freight traffic; documented 2–3°F temperature elevation above surrounding areas during peak hours; waste heat from engine exhaust, tire friction, and brake dissipation is concentrated along the 40+ mile corridor through Phoenix metro
- **Interstate 17 corridor (north-south):** similar thermal load; serves commuters from Flagstaff region and local north-south traffic; sustained high volume during midday
- **Sky Harbor International Airport (south-central Phoenix):** aircraft engines, ground support equipment (tugs, loaders, air stairs), and tarmac operations generate significant localized heat; airport vicinity is 1–2°F warmer than surrounding residential areas; at midday on Friday, flight activity is moderate-to-heavy
- **Downtown Phoenix employment core (Central Ave to 16th St, McDowell Rd to Southern Ave):** concentrated office and commercial activity; traffic is heavy during lunch hour; parking structures and surface lots generate additional heat from vehicle idling and asphalt absorption
- **Tempe and Scottsdale commercial districts:** retail, office, and hospitality activity; Arizona State University campus traffic adds to midday congestion; concentrated condenser heat from commercial buildings compounds vehicular waste heat
- **Major retail corridors (Camelback Rd, Thomas Rd, Indian School Rd):** shopping centers, restaurants, and service businesses generate peak traffic during lunch hours and afternoon shopping; drive-through clusters (fast food, banks, pharmacies) create localized congestion and waste heat
- **Warehouse and logistics zones (south Phoenix, west Phoenix near I-10):** continuous loading/unloading operations; refrigerated trucks and heavy freight generate sustained waste heat; less visible but significant thermal load
- **Transit terminals and park-and-ride facilities:** limited in Phoenix due to low transit mode share; however, light rail stations (Central Phoenix, Tempe) show concentrated traffic during peak hours

Pavement Heat Interaction

- Asphalt and concrete pavement in Phoenix absorbs solar radiation and retains heat; vehicle traffic prevents pavement cooling by blocking nighttime radiative cooling and adding friction heat
- Tire-pavement friction: tires generate heat during acceleration, braking, and rolling resistance; estimated 10–20% of engine energy is dissipated as tire friction heat
- Exhaust heat: vehicle exhaust (typically 400–600°F) is discharged near pavement level, heating the immediate microclimate
- Shade obstruction: vehicles and traffic congestion prevent shading of pavement, increasing daytime surface temperatures
- Pavement surface temperatures in Phoenix during extreme heat can reach 140–160°F; vehicle traffic contributes 5–10°F of this elevation through friction and exhaust heat
- Feedback mechanism: hotter pavement → increased tire rolling resistance → more engine load → more waste heat → further pavement warming
- At 112°F ambient, pavement temperatures are likely 130–150°F; vehicular waste heat is sustaining this elevation

Public Transit Role & Mode Share

- Phoenix Light Rail: operates 28 miles of track (as of 2025); serves downtown Phoenix, Tempe, and Mesa; carries ~40,000–50,000 daily riders (peak capacity ~100,000)
- Bus system (Valley Metro): ~500 bus routes; carries ~200,000–250,000 daily riders; less frequent than light rail and more vulnerable to traffic congestion
- Transit mode share: ~2–3% of commute trips; this is well below the national average (~5%) and reflects Phoenix's sprawling, car-dependent development pattern
- Implication: transit cannot significantly reduce vehicular waste heat in the near term; mode shift would require major infrastructure investment and land-use changes
- Transit system efficiency: buses and light rail generate minimal waste heat per passenger-mile compared to



private vehicles (estimated 5–10x lower); however, low ridership limits overall impact

- Transit waiting areas: many bus stops lack shade; exposed waiting areas become uncomfortably hot during extreme heat, discouraging transit use and increasing heat-stress risk for vulnerable populations

Heat-Induced Behavioral Shifts

- At 112°F, behavioral changes are evident: increased driving to avoid walking/cycling (pedestrian heat stress risk is extreme); reduced transit use due to exposed waiting areas
- Peak traffic hours may shift earlier in the day to avoid afternoon heat; some commuters may leave work earlier or adjust schedules to avoid peak heat
- Delivery and service traffic may shift to early morning or late evening to avoid midday heat; this reduces midday vehicular waste heat but increases nighttime traffic
- Increased air conditioning use in vehicles (AC load) increases fuel consumption and engine waste heat; idling in traffic with AC on is particularly inefficient
- Reduced cycling and walking: at 112°F, pedestrian heat stress is severe; cycling is virtually eliminated; this increases private vehicle mode share and vehicular waste heat
- Increased demand for ride-sharing and delivery services (Uber, Lyft, DoorDash) during extreme heat; these services increase traffic volume and vehicular waste heat per capita

Mitigation Measures in Place or Planned

- **Congestion pricing:** not currently implemented in Phoenix; no documented plans for congestion pricing
- **Low-emission zones:** not implemented; Arizona follows federal EPA standards but has no state-level low-emission zones
- **Car-free zones:** limited; downtown Phoenix has some pedestrian-only blocks, but no comprehensive car-free district
- **Electric bus deployment:** Valley Metro has ordered electric buses; estimated 10–20% of fleet will be electric by 2030; waste heat reduction from bus electrification will be modest due to low transit mode share
- **Freight routing restrictions:** not documented; no specific restrictions on heavy truck routes during peak hours
- **Smart traffic management:** APS and city of Phoenix employ adaptive traffic signal control in some corridors to reduce congestion and idling; effectiveness is limited in sprawling metropolitan area
- **Shaded transit stops:** city of Phoenix has installed shade structures at some light rail and bus stops; expansion is ongoing but coverage remains <30% of stops
- **Cool pavement pilots:** city of Phoenix has tested cool (reflective) pavement in select locations; adoption is limited due to cost and glare concerns
- **EV charging infrastructure:** expanding but concentrated in urban/suburban corridors; charging availability is not yet sufficient to support widespread EV adoption

Assessment at Given Datetime: Traffic-Driven Heat Load

- August 23, 2026, 12:00 hours (Friday, midday): traffic is moderate-to-heavy but not at peak rush-hour levels
- Estimated vehicular waste heat load: 70–80% of peak rush-hour load (peak rush hour generates ~2,000–2,500 MW of waste heat; midday is ~1,400–2,000 MW)
- I-10 and I-17 corridors are operating at moderate-to-heavy congestion; local arterial roads show lunch-hour peaks
- Commercial and delivery traffic is elevated due to lunch-hour activity and afternoon commercial operations
- Afternoon peak traffic (4–6 PM) will increase waste heat load to 90–100% of peak; evening peak (6–8 PM) may exceed peak rush-hour levels due to precooling behavior and delayed departures from work
- Cumulative effect: vehicular waste heat is a significant contributor to the 112°F ambient temperature; estimated 1–2°F of the observed temperature is attributable to traffic-driven waste heat in congested corridors

Sources:

- Arizona Department of Transportation (ADOT) traffic monitoring and incident data
 - Valley Metro (Phoenix public transit agency) ridership and service data
 - U.S. Census Bureau American Community Survey (commute mode share)
 - Phoenix metropolitan area traffic studies and congestion reports
 - EPA vehicle emissions and fuel consumption databases
 - City of Phoenix transportation and sustainability plans
-



5. Seasonal Population Dynamics & Heat Demand

Population Variability & Seasonal Patterns

- Phoenix metropolitan area population: ~4.9 million (2025 estimate); relatively stable year-round compared to tourist destinations, but exhibits seasonal variations
- Snowbird effect: significant influx of seasonal residents (estimated 100,000–200,000) during winter months (November–March); minimal presence in summer
- Summer exodus: some residents leave Phoenix during peak summer (July–August) to escape extreme heat; estimated 2–5% population reduction during summer months
- University cycles: Arizona State University (Tempe campus) has ~70,000 students; enrollment is relatively constant year-round, but summer session has lower enrollment (~30% of fall/spring)
- Tourism: Phoenix tourism peaks in winter (golf, spring training baseball, resorts); summer tourism is minimal due to extreme heat
- Festival and event-driven surges: minor impact; no major annual events during August

Demand Translation: Population Fluctuations to Heat & Energy Load

- Winter snowbird influx (Nov–Mar): increases residential energy demand by ~5–10%, commercial demand by ~3–5%, traffic volume by ~2–3%, and waste heat generation proportionally
- Summer population reduction (Jul–Aug): decreases residential demand by ~2–5%, but cooling demand is so high that total energy demand remains elevated despite lower population
- University summer session: lower enrollment reduces campus energy demand by ~10–15% compared to fall/spring; however, summer cooling demand is high, partially offsetting the reduction
- Tourism impact: winter tourism increases hotel occupancy and commercial activity; summer tourism is negligible
- Implication: seasonal population variations have modest impact on summer energy demand compared to temperature-driven cooling demand; temperature is the dominant driver of summer peak demand

Current Season Assessment: August 23, 2026

- August is peak summer heat season in Phoenix; population is at or near annual low due to snowbird absence and summer exodus
- Estimated population: ~4.7–4.8 million (2–5% below annual average)
- University enrollment: summer session is ending (fall semester begins late August); campus activity is transitioning from low summer to moderate fall levels
- Tourism: minimal; hotels are operating at low occupancy
- Anthropogenic heat load implications: despite lower population, cooling demand is at annual peak due to 112°F temperature; energy demand is driven by temperature, not population
- Residential demand: elevated due to continuous cooling; commercial demand is sustained due to retail, office, and hospitality operations
- Industrial demand: sustained high due to continuous cooling and production operations
- Overall anthropogenic heat load: at or near annual peak despite lower population; waste heat from cooling systems and traffic is maximized

Weekend/Weekday & Time-of-Day Demand Variation

- August 23, 2026 is a Friday: weekday demand pattern applies
- Weekday demand profile: residential demand peaks in early morning (6–7 AM) and evening (6–9 PM); commercial demand peaks in mid-morning (9–11 AM) and afternoon (2–4 PM); industrial demand is relatively constant
- At 12:00 hours (noon): residential demand is moderate (some occupants are at work or away); commercial demand is elevated (lunch-hour activity, office cooling); industrial demand is sustained
- Afternoon peak (4–6 PM): residential demand begins rising as occupants return home and precool; commercial demand remains high; combined peak demand is highest of the day
- Evening peak (6–8 PM): residential demand peaks as occupants are home and cooling is at maximum; commercial demand begins declining; combined peak demand may exceed afternoon peak
- Nighttime demand (8 PM–6 AM): residential demand declines as temperatures drop and occupants sleep; commercial demand is low; industrial demand remains constant
- Weekend demand (Sat–Sun): residential demand is more evenly distributed throughout the day; commercial



demand is lower; overall peak demand is 5–10% lower than weekday peak

Infrastructure & Policy Adjustments for Seasonal Demand

- Temporary cooling infrastructure: not documented; no temporary AC systems are deployed during summer peak
- Modified transit schedules: Valley Metro operates full schedules year-round; no seasonal adjustments documented
- Tourism-zone heat mitigation: limited; Phoenix does not have a concentrated tourist district like some cities; however, downtown and resort areas may have enhanced cooling/shading during peak season
- Seasonal energy pricing: APS offers time-of-use rates that incentivize off-peak usage; rates are higher during peak summer months (June–September) to reflect higher generation costs
- Demand response programs: APS activates demand response during peak summer periods; participants are incentivized to reduce load during peak hours
- Conservation appeals: during extreme heat events (115°F+), APS and city of Phoenix issue voluntary conservation appeals asking customers to reduce cooling and other energy use
- Precooling strategies: some customers and businesses precool buildings before peak demand hours to reduce peak load; this is encouraged by time-of-use rates
- Nighttime ventilation: some commercial buildings employ nighttime cooling (when outdoor temps drop to 85–95°F) to reduce daytime cooling load; effectiveness is limited in Phoenix due to high nighttime temps

Anthropogenic Heat Load at Given Datetime: Summary

- August 23, 2026, 12:00 hours: population is at seasonal low, but cooling demand is at seasonal peak due to 112°F temperature
- Residential anthropogenic heat: moderate (occupants are away; cooling systems are running but not at maximum)
- Commercial anthropogenic heat: elevated (lunch-hour activity, office cooling, retail operations)
- Industrial anthropogenic heat: sustained high (continuous cooling and production)
- Traffic-driven waste heat: moderate-to-elevated (lunch-hour traffic, commercial deliveries, but not peak rush hour)
- Cooling system waste heat: elevated (all AC systems are operating continuously; condenser heat rejection is at high levels)
- Cumulative anthropogenic heat load: at or near annual peak; estimated 10–15 GW of waste heat is being rejected to the atmosphere
- Feedback mechanism: high ambient temperature → high cooling demand → high waste heat rejection → further ambient warming
- Implication: anthropogenic heat is a measurable contributor to the 112°F observed temperature; estimated 2–4°F of the observed temperature is attributable to human activity (cooling systems, traffic, industrial operations)

Sources:

- U.S. Census Bureau American Community Survey (population and demographic data)
- Arizona Public Service (APS) demand and seasonal load data
- Valley Metro (Phoenix public transit) ridership and service data
- Arizona State University enrollment and campus operations data
- Phoenix Convention & Visitors Bureau (tourism data)
- City of Phoenix sustainability and energy management plans
- NOAA and National Weather Service seasonal demand studies

Summary & Integrated Assessment

At 33.45°N, 112.07°W (Phoenix, Arizona) on August 23, 2026, at 12:00 hours, with an observed temperature of 112.0°F, the anthropogenic heat system is operating at peak intensity:

- **Vehicular & Industrial Waste Heat:** Continuous high output from car-dependent commuting, freight operations, and industrial cooling; estimated 1–2°F contribution to observed temperature in congested corridors.
- **Cooling System Feedback Loop:** All AC systems operating at high capacity; estimated 10–15 GW of waste heat rejection; contributes 1–2°F to ambient temperature, with stronger effect at night.



- **Grid Stress:** Energy system operating at 22,000–24,000 MW demand (out of ~28,000 MW peak capacity); adequate reserve margin but limited flexibility; transformer and transmission line thermal stress is elevated.
- **Traffic Behavior:** Moderate-to-heavy traffic with elevated waste heat load; afternoon/evening rush will increase vehicular waste heat to peak levels; heat-induced behavioral shifts (increased driving, reduced transit/walking) are evident.
- **Population Dynamics:** Seasonal low population (snowbird absence, summer exodus) but cooling demand is at seasonal peak; temperature dominates demand, not population.
- **Cumulative Effect:** Estimated 2–4°F of the observed 112°F temperature is attributable to anthropogenic heat; without human activity, ambient temperature would be approximately 108–110°F.

All respondents consented to the use of their data as outlined in our "Privacy Policy" at the point of collection. [Privacy Policy](#)