

Lynx | TL-519 ★ Most Popular

Capacity 5,512 lbs | Max Height 19.7 ft | Max Reach 7.1 ft

| LIFTING                 |                        | DIMENSIONS             |                                   |
|-------------------------|------------------------|------------------------|-----------------------------------|
| Rated Capacity          | 5,512 lbs (2,500 kg)   | Machine Weight         | 12,787 lbs (5,800 kg)             |
| Max Lifting Height      | 19.7 ft (6.0 m)        | Overall Length         | 13.1 ft (4.0 m)                   |
| Max Outreach            | 7.1 ft (2.16 m)        | Overall Width / Height | 6.6 ft (2.02 m) / 6.7 ft (2.05 m) |
| PERFORMANCE             |                        | Wheelbase              | 9.2 ft (2.8 m)                    |
| Max Travel Speed        | 21.7 mph (35 km/h)     | Ground Clearance       | 9.1 in (0.23 m)                   |
| Steering Modes          | 2WD / 4WD / Crab       | Turning Radius         | 14.8 ft (4.5 m)                   |
| POWERTRAIN & CAPACITIES |                        |                        |                                   |
| Engine                  | Cummins / FPT EPA 4    | Fuel Tank              | 21.1 gal (80 L)                   |
| Transmission            | Torque Converter 4F/4R | Hydraulic Tank         | 44.9 gal (170 L)                  |
| Tires                   | 12-16.5 Pneumatic      | Hydraulic Flow         | 85 L/min @ 220 bar                |

TL-623

Capacity 6,614 lbs | Max Height 23.0 ft | Max Reach 10.5 ft

| LIFTING                 |                        | DIMENSIONS             |                       |
|-------------------------|------------------------|------------------------|-----------------------|
| Rated Capacity          | 6,614 lbs (3,000 kg)   | Machine Weight         | 16,755 lbs (7,600 kg) |
| Max Lifting Height      | 23.0 ft (7.0 m)        | Overall Length         | 15.3 ft (4.65 m)      |
| Max Outreach            | 10.5 ft (3.2 m)        | Overall Width / Height | N/A / 8.4 ft (2.55 m) |
| PERFORMANCE             |                        | Wheelbase              | 10.3 ft (3.15 m)      |
| Max Travel Speed        | 21.7 mph (35 km/h)     | Ground Clearance       | 13.8 in (0.35 m)      |
| Steering Modes          | 2WD / 4WD / Crab       | Turning Radius         | 13.9 ft (4.25 m)      |
| POWERTRAIN & CAPACITIES |                        |                        |                       |
| Engine                  | Cummins / FPT EPA 4    | Fuel Tank              | 51.5 gal (195 L)      |
| Transmission            | Torque Converter 4F/4R | Hydraulic Tank         | 44.9 gal (170 L)      |
| Tires                   | 16/70-20 Pneumatic     | Hydraulic Flow         | 120 L/min             |

TL-723

Capacity 7,716 lbs | Max Height 23.0 ft | Max Reach 10.5 ft

| LIFTING                 |                        | DIMENSIONS             |                                  |
|-------------------------|------------------------|------------------------|----------------------------------|
| Rated Capacity          | 7,716 lbs (3,500 kg)   | Machine Weight         | 16,755 lbs (7,600 kg)            |
| Max Lifting Height      | 23.0 ft (7.0 m)        | Overall Length         | 15.3 ft (4.65 m)                 |
| Max Outreach            | 10.5 ft (3.2 m)        | Overall Width / Height | 7.2 ft (2.2 m) / 8.4 ft (2.55 m) |
| PERFORMANCE             |                        | Wheelbase              | 10.3 ft (3.15 m)                 |
| Max Travel Speed        | 21.7 mph (35 km/h)     | Ground Clearance       | 13.8 in (0.35 m)                 |
| Steering Modes          | 2WD / 4WD / Crab       | Turning Radius         | 13.9 ft (4.25 m)                 |
| POWERTRAIN & CAPACITIES |                        |                        |                                  |
| Engine                  | Cummins / FPT EPA 4    | Fuel Tank              | 51.5 gal (195 L)                 |
| Transmission            | Torque Converter 4F/4R | Hydraulic Tank         | 44.9 gal (170 L)                 |
| Tires                   | 16/70-20 Pneumatic     | Hydraulic Flow         | 120 L/min                        |

TL-733

Capacity 7,716 lbs | Max Height 32.8 ft | Max Reach 20.0 ft

| LIFTING                 |                        | DIMENSIONS             |                                  |
|-------------------------|------------------------|------------------------|----------------------------------|
| Rated Capacity          | 7,716 lbs (3,500 kg)   | Machine Weight         | 20,944 lbs (9,500 kg)            |
| Max Lifting Height      | 32.8 ft (10.0 m)       | Overall Length         | 19.0 ft (5.8 m)                  |
| Max Outreach            | 20.0 ft (6.1 m)        | Overall Width / Height | 7.2 ft (2.2 m) / 8.4 ft (2.55 m) |
| PERFORMANCE             |                        | Wheelbase              | 10.3 ft (3.15 m)                 |
| Max Travel Speed        | 21.7 mph (35 km/h)     | Ground Clearance       | 13.8 in (0.35 m)                 |
| Steering Modes          | 2WD / 4WD / Crab       | Turning Radius         | 13.9 ft (4.25 m)                 |
| POWERTRAIN & CAPACITIES |                        |                        |                                  |
| Engine                  | Cummins / FPT EPA 4    | Fuel Tank              | 51.5 gal (195 L)                 |
| Transmission            | Torque Converter 4F/4R | Hydraulic Tank         | 44.9 gal (170 L)                 |
| Tires                   | 16/70-20 Pneumatic     | Hydraulic Flow         | 120 L/min                        |

TL-739

Capacity 7,716 lbs | Max Height 39.4 ft | Max Reach 24.9 ft

| LIFTING                 |                        | DIMENSIONS             |                                  |
|-------------------------|------------------------|------------------------|----------------------------------|
| Rated Capacity          | 7,716 lbs (3,500 kg)   | Machine Weight         | 22,487 lbs (10,200 kg)           |
| Max Lifting Height      | 39.4 ft (12.0 m)       | Overall Length         | 21.7 ft (6.6 m)                  |
| Max Outreach            | 24.9 ft (7.6 m)        | Overall Width / Height | 7.2 ft (2.2 m) / 8.5 ft (2.60 m) |
| PERFORMANCE             |                        | Wheelbase              | 10.3 ft (3.15 m)                 |
| Max Travel Speed        | 21.7 mph (35 km/h)     | Ground Clearance       | 15.7 in (0.4 m)                  |
| Steering Modes          | 2WD / 4WD / Crab       | Turning Radius         | 13.9 ft (4.25 m)                 |
| POWERTRAIN & CAPACITIES |                        |                        |                                  |
| Engine                  | Cummins / FPT EPA 4    | Fuel Tank              | 51.5 gal (195 L)                 |
| Transmission            | Torque Converter 4F/4R | Hydraulic Tank         | 44.9 gal (170 L)                 |
| Tires                   | 16/70-24 Pneumatic     | Hydraulic Flow         | 120 L/min                        |

TL-823

Capacity 8,818 lbs | Max Height 23.0 ft | Max Reach 10.5 ft

| LIFTING                 |                        | DIMENSIONS             |                                  |
|-------------------------|------------------------|------------------------|----------------------------------|
| Rated Capacity          | 8,818 lbs (4,000 kg)   | Machine Weight         | 17,857 lbs (8,100 kg)            |
| Max Lifting Height      | 23.0 ft (7.0 m)        | Overall Length         | 15.3 ft (4.65 m)                 |
| Max Outreach            | 10.5 ft (3.2 m)        | Overall Width / Height | 7.2 ft (2.2 m) / 8.4 ft (2.55 m) |
| PERFORMANCE             |                        | Wheelbase              | 10.3 ft (3.15 m)                 |
| Max Travel Speed        | 21.7 mph (35 km/h)     | Ground Clearance       | 13.8 in (0.35 m)                 |
| Steering Modes          | 2WD / 4WD / Crab       | Turning Radius         | 13.9 ft (4.25 m)                 |
| POWERTRAIN & CAPACITIES |                        |                        |                                  |
| Engine                  | Cummins / FPT EPA 4    | Fuel Tank              | 51.5 gal (195 L)                 |
| Transmission            | Torque Converter 2F/2R | Hydraulic Tank         | 44.9 gal (170 L)                 |
| Tires                   | 16/70-20 Pneumatic     | Hydraulic Flow         | 150 L/min                        |

TL-835

Capacity 8,818 lbs | Max Height 34.8 ft | Max Reach 20.0 ft

| LIFTING                 |                        | DIMENSIONS             |                                  |
|-------------------------|------------------------|------------------------|----------------------------------|
| Rated Capacity          | 8,818 lbs (4,000 kg)   | Machine Weight         | 22,707 lbs (10,300 kg)           |
| Max Lifting Height      | 34.8 ft (10.6 m)       | Overall Length         | 19.0 ft (5.8 m)                  |
| Max Outreach            | 20.0 ft (6.1 m)        | Overall Width / Height | 7.2 ft (2.2 m) / 8.4 ft (2.55 m) |
| PERFORMANCE             |                        | Wheelbase              | 10.3 ft (3.15 m)                 |
| Max Travel Speed        | 21.7 mph (35 km/h)     | Ground Clearance       | 13.8 in (0.35 m)                 |
| Steering Modes          | 2WD / 4WD / Crab       | Turning Radius         | 13.9 ft (4.25 m)                 |
| POWERTRAIN & CAPACITIES |                        |                        |                                  |
| Engine                  | Cummins / FPT EPA 4    | Fuel Tank              | 51.5 gal (195 L)                 |
| Transmission            | Torque Converter 4F/4R | Hydraulic Tank         | 44.9 gal (170 L)                 |
| Tires                   | 400/70-24 Tubeless     | Hydraulic Flow         | 150 L/min                        |

TL-845

Capacity 8,818 lbs | Max Height 45.3 ft | Max Reach 23.0 ft

| LIFTING                 |                        | DIMENSIONS             |                                   |
|-------------------------|------------------------|------------------------|-----------------------------------|
| Rated Capacity          | 8,818 lbs (4,000 kg)   | Machine Weight         | 28,660 lbs (13,000 kg)            |
| Max Lifting Height      | 45.3 ft (13.8 m)       | Overall Length         | 21.0 ft (6.4 m)                   |
| Max Outreach            | 23.0 ft (7.0 m)        | Overall Width / Height | 7.7 ft (2.35 m) / 8.4 ft (2.55 m) |
| PERFORMANCE             |                        | Wheelbase              | 11.8 ft (3.6 m)                   |
| Max Travel Speed        | 24.9 mph (40 km/h)     | Ground Clearance       | 15.0 in (0.38 m)                  |
| Steering Modes          | 2WD / 4WD / Crab       | Turning Radius         | 13.5 ft (4.1 m)                   |
| POWERTRAIN & CAPACITIES |                        |                        |                                   |
| Engine                  | Cummins / FPT EPA 4    | Fuel Tank              | 51.5 gal (195 L)                  |
| Transmission            | Torque Converter 4F/4R | Hydraulic Tank         | 44.9 gal (170 L)                  |
| Tires                   | 440/80-24 Tubeless     | Hydraulic Flow         | 150 L/min                         |

Leopard | TL-858 ★ Most Popular

Capacity 8,818 lbs | Max Height 57.7 ft | Max Reach 42.0 ft

| LIFTING                 |                        | DIMENSIONS             |                                   |
|-------------------------|------------------------|------------------------|-----------------------------------|
| Rated Capacity          | 8,818 lbs (4,000 kg)   | Machine Weight         | 6,614 lbs (3,000 kg)              |
| Max Lifting Height      | 57.7 ft (17.6 m)       | Overall Length         | 21.0 ft (6.4 m)                   |
| Max Outreach            | 42.0 ft (12.8 m)       | Overall Width / Height | 7.7 ft (2.35 m) / 8.4 ft (2.55 m) |
| PERFORMANCE             |                        | Wheelbase              | 11.8 ft (3.6 m)                   |
| Max Travel Speed        | 24.9 mph (40 km/h)     | Ground Clearance       | 15.0 in (0.38 m)                  |
| Steering Modes          | 2WD / 4WD / Crab       | Turning Radius         | 13.5 ft (4.1 m)                   |
| POWERTRAIN & CAPACITIES |                        |                        |                                   |
| Engine                  | Cummins / FPT EPA 4    | Fuel Tank              | 51.5 gal (195 L)                  |
| Transmission            | Torque Converter 4F/4R | Hydraulic Tank         | 44.9 gal (170 L)                  |
| Tires                   | 440/80-24 Tubeless     | Hydraulic Flow         | 150 L/min                         |

TL-1132

Capacity 11,023 lbs | Max Height 32.2 ft | Max Reach 16.4 ft

| LIFTING                 |                        | DIMENSIONS             |                                   |
|-------------------------|------------------------|------------------------|-----------------------------------|
| Rated Capacity          | 11,023 lbs (5,000 kg)  | Machine Weight         | 28,219 lbs (12,800 kg)            |
| Max Lifting Height      | 32.2 ft (9.8 m)        | Overall Length         | 21.0 ft (6.4 m)                   |
| Max Outreach            | 16.4 ft (5.0 m)        | Overall Width / Height | 7.7 ft (2.35 m) / 8.4 ft (2.55 m) |
| PERFORMANCE             |                        | Wheelbase              | 11.8 ft (3.6 m)                   |
| Max Travel Speed        | 24.9 mph (40 km/h)     | Ground Clearance       | 15.0 in (0.38 m)                  |
| Steering Modes          | 2WD / 4WD / Crab       | Turning Radius         | 13.5 ft (4.1 m)                   |
| POWERTRAIN & CAPACITIES |                        |                        |                                   |
| Engine                  | Cummins / FPT EPA 4    | Fuel Tank              | 51.5 gal (195 L)                  |
| Transmission            | Torque Converter 4F/4R | Hydraulic Tank         | 44.9 gal (170 L)                  |
| Tires                   | 16/70-24 Semi-Solid    | Hydraulic Flow         | 150 L/min                         |

TL-1145

Capacity 11,023 lbs | Max Height 45.3 ft | Max Reach 26.2 ft

| LIFTING                 |                        | DIMENSIONS             |                                   |
|-------------------------|------------------------|------------------------|-----------------------------------|
| Rated Capacity          | 11,023 lbs (5,000 kg)  | Machine Weight         | 29,982 lbs (13,600 kg)            |
| Max Lifting Height      | 45.3 ft (13.8 m)       | Overall Length         | 21.7 ft (6.6 m)                   |
| Max Outreach            | 26.2 ft (8.0 m)        | Overall Width / Height | 7.7 ft (2.35 m) / 8.4 ft (2.55 m) |
| PERFORMANCE             |                        | Wheelbase              | 11.8 ft (3.6 m)                   |
| Max Travel Speed        | 24.9 mph (40 km/h)     | Ground Clearance       | 15.0 in (0.38 m)                  |
| Steering Modes          | 2WD / 4WD / Crab       | Turning Radius         | 13.5 ft (4.1 m)                   |
| POWERTRAIN & CAPACITIES |                        |                        |                                   |
| Engine                  | Cummins / FPT EPA 4    | Fuel Tank              | 51.5 gal (195 L)                  |
| Transmission            | Torque Converter 4F/4R | Hydraulic Tank         | 50.2 gal (190 L)                  |
| Tires                   | 440/80-24 Tubeless     | Hydraulic Flow         | 150 L/min                         |

Lion | TL-1158 ★ Most Popular

Capacity 11,023 lbs | Max Height 57.6 ft | Max Reach 36.7 ft

| LIFTING                 |                        | DIMENSIONS             |                                   |
|-------------------------|------------------------|------------------------|-----------------------------------|
| Rated Capacity          | 11,023 lbs (5,000 kg)  | Machine Weight         | 31,086 lbs (14,100 kg)            |
| Max Lifting Height      | 57.6 ft (17.55 m)      | Overall Length         | 21.7 ft (6.6 m)                   |
| Max Outreach            | 36.7 ft (11.2 m)       | Overall Width / Height | 7.7 ft (2.35 m) / 8.7 ft (2.65 m) |
| PERFORMANCE             |                        | Wheelbase              | 11.8 ft (3.6 m)                   |
| Max Travel Speed        | 24.9 mph (40 km/h)     | Ground Clearance       | 15.0 in (0.38 m)                  |
| Steering Modes          | 2WD / 4WD / Crab       | Turning Radius         | 13.5 ft (4.1 m)                   |
| POWERTRAIN & CAPACITIES |                        |                        |                                   |
| Engine                  | Cummins / FPT EPA 4    | Fuel Tank              | 51.5 gal (195 L)                  |
| Transmission            | Torque Converter 4F/4R | Hydraulic Tank         | 50.2 gal (190 L)                  |
| Tires                   | 440/80-24 Tubeless     | Hydraulic Flow         | 150 L/min                         |

TL-1358

Capacity 13,228 lbs | Max Height 57.7 ft | Max Reach 39.4 ft

| LIFTING                 |                        | DIMENSIONS             |                                  |
|-------------------------|------------------------|------------------------|----------------------------------|
| Rated Capacity          | 13,228 lbs (6,000 kg)  | Machine Weight         | 37,479 lbs (17,000 kg)           |
| Max Lifting Height      | 57.7 ft (17.6 m)       | Overall Length         | 22.6 ft (6.9 m)                  |
| Max Outreach            | 39.4 ft (12.0 m)       | Overall Width / Height | 8.9 ft (2.7 m) / 9.1 ft (2.76 m) |
| PERFORMANCE             |                        | Wheelbase              | 11.8 ft (3.6 m)                  |
| Max Travel Speed        | 24.9 mph (40 km/h)     | Ground Clearance       | 19.7 in (0.50 m)                 |
| Steering Modes          | 2WD / 4WD / Crab       | Turning Radius         | 13.5 ft (4.1 m)                  |
| POWERTRAIN & CAPACITIES |                        |                        |                                  |
| Engine                  | Cummins / FPT EPA 4    | Fuel Tank              | 51.5 gal (195 L)                 |
| Transmission            | Torque Converter 4F/4R | Hydraulic Tank         | 44.9 gal (170 L)                 |
| Tires                   | 17.5-25 Tubeless       | Hydraulic Flow         | 180 L/min                        |

TL-1558

Capacity 15,432 lbs | Max Height 57.7 ft | Max Reach 39.4 ft

| LIFTING                 |                        | DIMENSIONS             |                                  |
|-------------------------|------------------------|------------------------|----------------------------------|
| Rated Capacity          | 15,432 lbs (7,000 kg)  | Machine Weight         | 38,581 lbs (17,500 kg)           |
| Max Lifting Height      | 57.7 ft (17.6 m)       | Overall Length         | 27.2 ft (8.3 m)                  |
| Max Outreach            | 39.4 ft (12.0 m)       | Overall Width / Height | 8.5 ft (2.6 m) / 9.4 ft (2.85 m) |
| PERFORMANCE             |                        | Wheelbase              | 11.8 ft (3.6 m)                  |
| Max Travel Speed        | 24.9 mph (40 km/h)     | Ground Clearance       | 19.7 in (0.50 m)                 |
| Steering Modes          | 2WD / 4WD / Crab       | Turning Radius         | 13.5 ft (4.1 m)                  |
| POWERTRAIN & CAPACITIES |                        |                        |                                  |
| Engine                  | Cummins / FPT EPA 4    | Fuel Tank              | 34.3 gal (130 L)                 |
| Transmission            | Torque Converter 4F/4R | Hydraulic Tank         | 44.9 gal (170 L)                 |
| Tires                   | 17.5-25 Tubeless       | Hydraulic Flow         | 180 L/min                        |