



Chapter 4



Dates, Times, Locales, and Resource Bundles



1

Content

1Z0-809 Chapter 4

- Dates, Times and Locales
- Dealing with Time Zones and Daylight Savings
- Formatting Dates and Times
- Properties Files
- Resource Bundles

M. Romdhani, 2020

2

2

Dates, Times, and Locales

3

1Z0-809 Chapter 4

Working with Dates and Times

■ Here's an overview of how the classes in `java.time` are organized

- **Local dates and times**
 - These dates and times are local to your time zone and so don't have time-zone information associated with them. These are represented by classes `java.time.LocalDate`, `java.time.LocalDateTime`, and `java.time.LocalTime`.
- **Zoned dates and times**
 - These dates and times include time-zone information. They are represented by classes `java.time.ZonedDateTime` and `java.time.OffsetDateTime`.
- **Formatters for dates and times**
 - With `java.time.format.DateTimeFormatter`, you can parse and print dates and times with patterns and in a variety of styles.
- **Adjustments to dates and times**
 - With `java.time.temporal.TemporalAdjusters` and `java.time.temporal.ChronoUnit`, you can adjust and manipulate dates and times by handy increments.
- **Periods, Durations, and Instants**
 - `java.time.Periods` and `java.time.Durations` represent an amount of time, periods for days or longer and durations for shorter periods like minutes or seconds. `java.time.Instants` represent a specific instant in time, so you can, say, compute the number of minutes between two instants.

M. Romdhani, 2020

4

4

Using the LocalDate class

■ java.time.LocalDate represents a date without time or time zone.

- LocalDate is represented in the ISO-8601 calendar system in a year-month-day format (YYYY-MM-DD): for example, 2019-03-26.
- Here's an example that uses LocalDate:

```
LocalDate today = LocalDate.now();
System.out.println("Today's date is: " + today);
```

- This code printed the following when we ran it: Today's date is: **2019-03-26**

■ Important Methods in the LocalDate Class

Method	Short Description	Example Code
LocalDate now(Clock clock)	Returns a LocalDate object with the current date using the passed clock or zone argument	// assume today's date is 26 Oct 2015 LocalDate.now(Clock.systemDefaultZone()); // returns current date as 2015-10-26 LocalDate.now(ZoneId.of("Asia/Kolkata")); // returns current date as 2015-10-26 LocalDate.now(ZoneId.of("Asia/Tokyo")); // returns current date as 2015-10-27
LocalDate ofYearDay(int year, int dayOfYear)	Returns the LocalDate from the year and dayOfYear passed as arguments	LocalDate.ofYearDay(2016, 100); // returns date as 2016-04-09
LocalDate parse(CharSequence dateString)	Returns the LocalDate from the dateString passed as the argument	LocalDate.parse("2015-10-26"); // returns a LocalDate corresponding to the passed string argument; hence it // returns date as 2015-10-26
LocalDate ofEpochDay(Long epochDay)	Returns the LocalDate by adding the number of days to the epoch starting day (the epoch starts in 1970)	LocalDate.ofEpochDay(10); // returns 1970-01-11;

M. Romdhani, 2020

;

5

Using the LocalTime class

■ The java.time.LocalTime class is similar to LocalDate except that LocalTime represents time without dates or time zones.

- The time is in the ISO-8601 calendar system format: HH:MM:SS.millisecond.
- Here is an example that uses LocalTime:

```
LocalTime currTime = LocalTime.now();
System.out.println("Current time is: " + currTime);
```

- When we executed it, it printed the following: Current time is: **12:23:05.072**

■ Important methods in LocalTime Class

Method	Short Description	Example Code
LocalTime now(Clock clock)	Returns a LocalTime object with the current time using the passed clock or zone argument	LocalTime.now(Clock.systemDefaultZone()); // returns current time as 18:30:35.744 LocalTime.now(ZoneId.of("Asia/Tokyo")); // returns current time as 22:00:35.193
LocalTime ofSecondOfDay(long daySeconds)	Returns the LocalTime from daySeconds passed as the argument (note that a 24-hour day has 86,400 seconds)	LocalTime.ofSecondOfDay(66620); // returns 18:30:20 because // 66620 seconds have elapsed
LocalTime parse(CharSequence timeString)	Returns the LocalTime from the dateString passed as the argument	LocalTime.parse("18:30:05"); // returns a LocalTime object // corresponding to the given String // hence it prints: 18:30:05

M. Romdhani, 2020

6

6

Using the LocalDateTime Class

- The class `java.time.LocalDateTime` represents both date and time without time zones.

- You can think of `LocalDateTime` as a logical combination of the `LocalTime` and `LocalDate` classes. The date and time formats use the ISO-8601 calendar system: `YYYY-MM-DD HH:MM:SS.millisecond`.

- Here is a simple example that prints today's date and the current time:

```
LocalDateTime currDateTime = LocalDateTime.now();
System.out.println("Today's date and current time is: " +
    currDateTime);
```

- This prints : Today's date and current time is: **2019-03-26T21:04:36.376**

In this output, note that the character **T** stands for time, and it separates the date and time components.

- Similar to `LocalDate` and `LocalTime` the methods, `LocalDateTime` has methods such as `now()`, `of()`, and `parse()`. Again, similar, this class also provides methods to add or subtract years, months, days, hours, minutes, seconds, and nanoseconds.

Instant, Period, Duration Classes

- The `Instant` values began on January 1, 1970, at 00:00:00 hours (known as the Unix epoch).

- The `Instant` class internally uses a long variable that holds the number of seconds since the start of the Unix epoch

- The `java.time.Period` class is used to measure an amount of time in terms of years, months, and days.

- Assume that you have bought some expensive medicine and want to use it before it expires. Here is how you can find out when it will expire:

```
LocalDate manufacturingDate = LocalDate.of(2016, Month.JANUARY, 1);
LocalDate expiryDate = LocalDate.of(2018, Month.JULY, 18);
```

```
Period expiry = Period.between(manufacturingDate, expiryDate);
```

```
System.out.printf("Medicine will expire in: %d years, %d months, and %d days (%s)\n",
    expiry.getYears(), expiry.getMonths(), expiry.getDays(), expiry)
```

- `Duration` is the time equivalent of `Period`. The `Duration` class represents time in terms of hours, minutes, seconds, and so on.

- It is suitable for measuring machine time or when working with `Instant` objects. Similar to the `Instant` class, the `Duration` class stores the seconds component as a long value and nanoseconds using an `int` value.

Dealing with Time Zones and Daylight Savings

9

1Z0-809 Chapter 4

Using Time Zone–Related Classes

- There are three important classes related to time zones that you need to know in order to work with dates and times across time zones: **ZoneId**, **ZoneOffset**, and **ZonedDateTime**

- Using the **ZoneId** Class

- Time zones are typically identified using an offset from Greenwich Mean Time (GMT, also known as UTC/Greenwich).
 - `System.out.println("My zone id is: " + ZoneId.systemDefault());`
This prints: My zone id is: US/Pacific, if you are in US Pacific zone.

- Using the **ZoneOffset** Class

- **ZoneId** identifies a time zone, such as Asia/Kolkata. Another class, **ZoneOffset**, represents the time-zone offset from UTC/Greenwich. For example, zone ID "Asia/Kolkata" has a zone offset of +05:30 (plus 5 hours and 30 minutes) from UTC/Greenwich.

- Using the **ZonedDateTime** Class

- What if you want all three—date, time, and time zone—together? For that, you can use the **ZonedDateTime** class:

```
LocalDate currentDate = LocalDate.now();
LocalTime currentTime = LocalTime.now();
ZoneId myZone = ZoneId.systemDefault();
ZonedDateTime zonedDateTime = ZonedDateTime.of(currentDate, currentTime, myZone);
System.out.println(zonedDateTime);
```

Here is the result: 2015-11-05T11:38:40.647+05:30[Asia/Kolkata]

M. Romdhani, 2020

10

10

Dealing with Daylight Savings

- **With daylight savings time (DST), the clock is set one hour earlier or later to make the best use of the daylight.**

```
Zoneld kolkataZone = Zoneld.of("Asia/Kolkata");
Duration kolkataDST = kolkataZone.getRules().getDaylightSavings(Instant.now());
System.out.printf("Kolkata zone DST is: %d hours %n", kolkataDST.toHours());
```

```
Zoneld aucklandZone = Zoneld.of("Pacific/Auckland");
Duration aucklandDST = aucklandZone.getRules().getDaylightSavings(Instant.now());
System.out.printf("Auckland zone DST is: %d hours", aucklandDST.toHours());
```

Here is the result (when executed on November 5, 2015):

```
Kolkata zone DST is: 0 hours
Auckland zone DST is: 1 hours
```

- The call `zoneld.getRules().getDaylightSavings(Instant.now());` returns a Duration object based on whether DST is in effect at that time.
 - If `Duration.isZero()` is false, DST is in effect in that zone; otherwise, it is not. In this example, the Kolkata time zone does not have DST in effect, but the Auckland time zone has +1 hour of DST.

Formatting Dates and Times

The DateTimeFormatter class

■ The `DateTimeFormatter` class provides many predefined constants for formatting date and time values.

- Here is a list of a few such predefined formatters (with sample output values):

- `ISO_DATE` (2015-11-05)
- `ISO_TIME` (11:25:47.624)
- `RFC_1123_DATE_TIME` (Thu, 5 Nov 2015 11:27:22 +0530)
- `ISO_ZONED_DATE_TIME` (2015-11-05T11:30:33.49+05:30[Asia/Kolkata])

■ Here is a simple example that uses the predefined `ISO_TIME` of type `DateTimeFormatter`:

```
LocalTime wakeupTime = LocalTime.of(6, 0, 0);  
System.out.println("Wake up time: " +  
    DateTimeFormatter.ISO_TIME.format(wakeupTime));
```

- This printed the following: Wake up time: 06:00:00

- If you want to use a custom format instead of any of the predefined formats? To do so, you can use the `ofPattern()` method in the `DateTimeFormatter` class:

```
DateTimeFormatter customFormat = DateTimeFormatter.ofPattern("dd  
    MMM yyyy");  
System.out.println(customFormat.format(LocalDate.of(2016,  
    Month.JANUARY, 01)));
```

- Here is the result: 01 Jan 2016

Properties Files

What are Property files

- **Property files are typically used to externally store configuration settings and operating parameters for your applications. In the Java world, there are at least three variations on property files:**

1. There is a system-level properties file that holds system information like hardware info, software versions, classpaths, and so on.
 - The `java.lang.System` class has methods that allow you to update this file and view its contents. This property file is not on the exam.
2. There is a class called `java.util.Properties` that makes it easy for a programmer to create and maintain property files for whatever applications the programmer chooses.
3. There is a class called `java.util.ResourceBundle` that can—optionally—use `java.util.Properties` files to make it easier for a programmer to add localization and/or internationalization features to applications.

- **Structure of Property files**

- Property files can define key/value pairs in any of the following formats:

```
key=value
key:value
key value
```

- Property files can use two styles of commenting: `!` Comment or `#` comment

M. Romdhani, 2020

15

15

Creating a Property File

- **Here's some code that creates a new `Properties` object, adds a few properties, and then stores the contents of the `Properties` object to a file on disk:**

```
import java.util.*;
import java.io.*;
class Props1 {
    public static void main(String[] args) {
        Properties p = new Properties();
        p.setProperty("k1", "v1");
        p.setProperty("k2", "v2");
        p.list(System.out);           // what's in the object
        try {
            // creates or replaces file
            FileOutputStream out = new FileOutputStream("myProps1.props");
            p.store(out, "test-comment"); // adds header comment
            out.close();
        } catch (IOException e) {
            System.out.println("exc 1");
        }
    }
}
```

M. Romdhani, 2020

16

16

Reading a Property file

- Now let's run a second program that opens up the file we just created, adds a new key/value pair, then saves the result to a second file on disk:

```
import java.util.*;
import java.io.*;
class Props2 {
    public static void main(String[] args) {
        Properties p2 = new Properties();
        try {
            FileInputStream in = new FileInputStream("myProps1.props");
            p2.load(in);
            p2.list(System.out);
            p2.setProperty("newProp", "newData");
            p2.list(System.out);
            FileOutputStream out = new FileOutputStream("myProps2.props");
            p2.store(out, "myUpdate");
            in.close();
            out.close();
        } catch (IOException e) {
            System.out.println("exc 2");
        }
    }
}
```

M. Romdhani, 2020

17


17

Resource Bundles

18

What are ResourceBundle

- In Java, resource bundles provide a solution to customize the application locale-specific needs.
- A resource bundle is a set of classes or property files that help define a set of keys and map those keys to locale specific values.
 - The abstract class `java.util.ResourceBundle` provides an abstraction of resource bundles in Java. It has two derived classes: `java.util.PropertyResourceBundle` and `java.util.ListResourceBundle`



M. Romdhani, 2020

19

19

Using PropertyResourceBundle

- If you design your application with localization in mind using property files, you can add support for new locales to the application **without changing anything in the code** !

■ Example : LocalizedHello

```

import java.util.Locale;
import java.util.ResourceBundle;

public class LocalizedHello {
    public static void main(String args[]) {
        Locale currentLocale = Locale.getDefault();
        ResourceBundle resBundle =
            ResourceBundle.getBundle("ResourceBundle", currentLocale);
        System.out.printf(resBundle.getString("Greeting"));
    }
}
  
```

```

D:\> type ResourceBundle.properties
Greeting=Hello
  
```

```

D:\> type ResourceBundle_ar.properties
Greeting=As-Salamu Alaykum
  
```

```

D:\> type ResourceBundle_it.properties
Greeting=Ciao
  
```

- Using the LocalizedHello

D:\> java LocalizedHello, prints Hello

D:\> java -Duser.language=it LocalizedHello, prints Ciao

D:\> java -Duser.language=ar LocalizedHello, prints As-Salamu Alaykum

M. Romdhani, 2020

20

20

Using ListResourceBundle

- Support for a new locale can be added using ListResourceBundle by extending it.

- While extending the ListResourceBundle, you need to override the abstract method getContents(); the signature of this method is:

- protected Object[][] getContents();

- ListResourceBundle example

```
// default US English version
public class ResourceBundle {
    public Object[][] getContents() {
        return contents;
    }
    static final Object[][] contents = {
        { "MovieName", "Avatar" },
        { "GrossRevenue", (Long) 2782275172L }, // in US dollars
        { "Year", (Integer) 2009 }
    };
}
```

- Now, let's define a ResourceBundle for the Italian locale. You give the class the suffix "_it_IT"

```
// Italian version
public class ResourceBundle_it_IT extends ListResourceBundle {
    public Object[][] getContents() {
        return contents;
    }
    static final Object[][] contents = {
        { "MovieName", "Che Bella Giornata" },
        { "GrossRevenue", (Long) 43000000L }, // in euros
        { "Year", (Integer) 2011 }
    };
}
```

M. Romdhani, 2020

21

21

Using ListResourceBundle

- Now let's see how to use our resource bundles.

- While extending the ListResourceBundle, you need to override the abstract method getContents(); the signature of this method is:

```
public class LocalizedBoxOfficeHits {
    public void printMovieDetails(ResourceBundle resBundle) {
        String movieName = resBundle.getString("MovieName");
        Long revenue = (Long) (resBundle.getObject("GrossRevenue"));
        Integer year = (Integer) resBundle.getObject("Year");

        System.out.println("Movie " + movieName + "(" + year + ")" + " grossed "
            + revenue);
    }
    public static void main(String args[]) {
        LocalizedBoxOfficeHits localizedHits = new LocalizedBoxOfficeHits();
        // print the largest box-office hit movie for default (US) locale
        Locale locale = Locale.getDefault();
        localizedHits.printMovieDetails(ResourceBundle.getBundle("ResBundle", locale));

        // print the largest box-office hit movie for Italian locale
        locale = new Locale("it", "IT", "");
        localizedHits.printMovieDetails(ResourceBundle.getBundle("ResBundle", locale));
    }
}
```

- It prints the following:

```
Movie Avatar (2009) grossed 2782275172
Movie Che Bella Giornata (2011) grossed 43000000
```

M. Romdhani, 2020

22

22

ResourceBundle Hints

- A call to `Resource.getBundle` MUST include the full package qualified package + class name. IF the resource is not in the same folder of the package that the program is in.
- If you have `Buggy_en.java` and `Buggy_en.properties` and `Buggy.java`, the code will search and skip looking in `Buggy_en.properties`: it prefers the Java resource and then looks in the default resource after that.
 - Java does not allow looking in a properties file resource bundle once it has matched a Java class resource bundle.
- You can call methods `getString()`, `getObject()`, `keySet()`, `getKeys()`, and `getStringArray()` from class `ResourceBundle` to access its keys and values.
- The order in which Java searches for a matching:
 1. `bundle_localeLang_localeCountry_localeVariant`
 2. `bundle_localeLang_localeCountry`
 3. `bundle_localeLang`
 4. `bundle_defaultLang_defaultCountry_defaultVariant`
 5. `bundle_defaultLang_defaultCountry`
 6. `bundle_defaultLang`
 7. `Bundle`
 - If there's no matching resource bundle for the target language, neither a default resource bundle, then the application throws a `MissingResourceException` at runtime.

M. Romdhani, 2020

23