

CS585
Database Systems
Summer 2006
Final Exam

Name: _____
Student ID: _____

	Maximum	Received
Problem 1	10	
Problem 2	15	
Problem 3	15	
Problem 4	15	
Problem 5	15	
Problem 6	15	
Problem 7	15	

1) 10 pts

True/False questions

1. ___F___ Elements are **defined** within an XML schema.
2. ___F___ Attribute groups are **declared** within an XML schema.
3. ___T___ Types are **defined** within an XML schema.
4. ___T___ XQuery has some programming language features but SQL has not.
5. ___F___ **SQL** and XQuery are used to query data and considered functional languages.
6. ___T___ SQL and XQuery have Update capability.
7. ___F___ A distributed database requires distributed processing.
8. ___T___ Distributed database systems communicate with one another through a communication network.
9. ___F___ Thru query optimization, distributed databases always find the most efficient method of processing for a given query.
10. ___F___ Transaction data such as sales orders or inventory information is always aggregated before storing into OLAP cubes.

2) 20 pts

Short answer questions. Please answer briefly and to the point. 3-5 sentences will be enough to answer for each question.

a. Describe how and under what circumstances a distributed spatial database could have better performance than a central spatial database when computing the following query:

```
SELECT city.name FROM city WHERE city.center INSIDE California.region
```

If it is central it is costly to go through all the cities in US.

b. Give two reasons why you would replicate or not replicate the data at local nodes in a distributed database.

Reasons to replicate

1) improved reliability

2) better performance(I/O performance, parallelism)

Reasons not to replicate

1) write more than read

2) Save storage

c. What is the difference between data mining and decision support using OLAP?

GOOGLE 得到。。。 (不确定。。。)

OLAP provides summary data and generates rich calculations. For example, OLAP answers questions like "How do sales of mutual funds in North America for this quarter compare with sales a year ago? What can we predict for sales next quarter? What is the trend as measured by percent change?" **Data mining** is the computational process of discovering patterns in large data sets involving methods at the intersection of artificial intelligence, machine learning, statistics, and database systems. The overall goal of the data mining process is to extract information from a data set and transform it into an understandable structure for further use. •discovers hidden patterns in data. Data mining operates at a detail level instead of a summary level. Data mining answers questions like "Who is likely to buy a mutual fund in the next six months, and what are the characteristics of these likely buyers?"

d. Can we express “if conditions” in XML language? Justify your answer.

XML 包含 XQuery, and XQuery has “if condition”

3) 15 pts

Write a DTD that describes the following XML data:

```
<bib>
  <vendor id="id0_1">
    <name>Amazon</name>
    <email>webmaster@amazon.com</email>
    <phone>1-800-555-9999</phone>
    <book>
      <title>Unix Network Programming</title>
      <publisher>Addison Wesley</publisher>
      <year>1995</year>
      <author>
        <firstname>Richard</firstname>
        <lastname>Stevens</lastname>
      </author>
      <price>38.68</price>
    </book>
    <book>
      <title>An Introduction to O-O Design</title>
      <publisher>Addison Wesley</publisher>
      <year>1996</year>
      <author>
        <firstname>Jo</firstname>
        <lastname>Levin</lastname>
      </author>
      <author>
        <firstname>Harold</firstname>
        <lastname>Perry</lastname>
      </author>
      <price>11.55</price>
    </book>
  </vendor>
</bib>
```

Additional Space.

```
<!ELEMENT bib(vendor)>
<!ELEMENT vendor(name, email, phone, book*)>
<!ELEMENT book(title, publisher?, year, author+, price)>
<!ELEMENT author(firstname, lastname)>
<!ATTLIST vendor id CDATA #REQUIRED>
<!ELEMENT title(#PCDATA)>
<!ELEMENT publisher(#PCDATA)>
<!ELEMENT firstname(#PCDATA)>
<!ELEMENT lastname(#PCDATA)>
<!ELEMENT price(#PCDATA)>
```

4) 15 pts

Consider the following XML document type definition (DTD) for a product catalog:

```
<!DOCTYPE CATALOG [  
  <!ELEMENT CATALOG (TOOL | TOY)+>  
  <!ELEMENT TOOL (NAME,SPECIFICATIONS+,OPTIONS?)>  
  <!ELEMENT NAME (#PCDATA)>  
  <!ELEMENT SPECIFICATIONS (#PCDATA)>  
  <!ELEMENT OPTIONS (#PCDATA)>  
  <!ELEMENT TOY (NAME,PRICE?)>  
  <!ELEMENT PRICE (#PCDATA)+>  
>
```

We designed a relational database schema that captures the same information as the Catalog DTD as below:

```
Tools(toolid: integer, name: string, options: string)  
Specifications(toolid: integer, specno: integer, spec: string)  
Toys(toyid: integer, name: string, price: string)
```

a. Given your relational database schema, translate the following SQL query into an equivalent

XML query:

```
SELECT S.spec  
FROM Tools T, Specifications S  
WHERE T.toolid = S.toolid AND S.specno = 1 AND T.name = "Hammer"
```

```
/CATALOG/TOOL[NAME="Hammer"]/SPECIFICATIONS
```

```
for $i in document(CATALOG)//TOOL[NAME="Hammer"]
```

```
let
```

```
return <SPECIFICATIONS > $i/SPECIFICATIONS </SPECIFICATIONS >
```

b. Given your relational database schema, translate the following SQL query into an equivalent XML query:

```
SELECT name FROM Tools
UNION
SELECT name FROM Toys
```


5) 15 pts

Consider the following XML Schema . Is the following allowed according to the XML schema specification rules? If not, list all errors and explain what rules are violated.

```
<xsd:complexType name="ssnType" minOccurs="1">
  <xsd:restriction base="xsd:string">
    <xsd:pattern value="\d{3}-\d{2}-\d{4}"/>
    <xsd:pattern value="\d{9}"/>
  </xsd:restriction>
</xsd:complexType>


<xsd:element name="Company">
  <xsd:complexType>
    <xsd:sequence>
      <xsd:element name="Employee" type="xsd:string"
        maxOccurs="unbounded">
        <xsd:complexType>
          <xsd:sequence>
            <xsd:element name="SSN" type="ssnType"/>
            <xsd:element name="name" type="xsd:string" />
            <xsd:element name="BirthDate" type="xsd:gDate" use="optional"/>
            <xsd:element name="address" minOccurs="0">
              <xsd:simpleType>
                <xsd:attribute name="city" type="xsd:string" maxOccurs="1"/>
                <xsd:attribute name="state" type="xsd:string" maxOccurs="1"/>
                <xsd:attribute name="zip" type="xsd:integer" maxOccurs="1"/>
              </xsd:simpleType>
            </xsd:element>
          </xsd:sequence>
        </xsd:complexType>
      </xsd:element>
    </xsd:sequence>
  </xsd:complexType>
</xsd:element>
```

Comment [晓阳1]: sequence 和 attribute 并列
这里改 complexType

Comment [晓阳2]: 删掉

```
</xsd:sequence>  
</xsd:complexType>  
</xsd:element>
```

Additional space



6) 15 pts

Given the distributed database design below:

Actors (Name: String,
 Gender: String,
 Agent: String)

Actors relation split across 4 nodes with

- Node 1 keeps male actors with Name < "M"
- Node 2 keeps males actors with Name >= "M"
- Node 3 keeps female actors with Name < "M"
- Node 4 keeps females actors with Name >= "M"

AppearsIn(Name: String,
 Title: String)

AppearsIn relation split across 2 nodes

- Node 5 keeps tuples with Name < "M"
- Node 6 keeps tuples with Name >= "M"

Movies (Title: String,
 Producer: String,
 Year: Integer,
 Cost: Integer,
 Location: String,
 Director: String)

Movies relation split across 2 nodes

- Node 7 keeps movies with Year > 1980
- Node 8 keeps movies with Year <= 1980

And the query

```
SELECT    Actors.Agent
FROM      Actors, AppearsIn, Movies
WHERE     Actors.Name=AppearsIn.Name AND
          Movies.Title=AppearsIn.Title AND
          Movies.Cost > 30,000,000 AND
          Movies.Location="LA"
```

And the following assumptions:

- AppearsIn relation is of size 3000
- Actors relation is of size 1000
- Movies relation is of size 200
- Costs are between \$100,000 and \$200,000,000
- 10% of movies are made in LA

Specify an efficient order of operations for the above query. You must also show all transfer of data from site to site. State any additional assumptions you need to make.

7) 15 pts

Given the relation

Movies (Title: String,
 Producer: String,
 Year: Integer,
 Cost: Integer,
 Director: String)

And the queries

q1: SELECT Title FROM Movies

q2: SELECT Producer, Year FROM Movies

q3: SELECT Title, Cost FROM Movies

q4: SELECT Director FROM Movies


With the following access frequency from sites 1 to 3

	S1	S2	S3
q1	20	0	5
q2	0	10	0
q3	5	5	20
q4	0	10	5

a- Create the attribute affinity matrix

b- Determine an optimal vertical fragmentation of this relation into 3 fragments.

Additional Space



Additional Space

