




PRESSURE REDUCING & RELIEF  
VALVES



[Products](#) > [Pressure Reducing & Relief Valves](#)

## Pressure Relief Valve



<b>SIZE RANGE</b>	50mm to 300mm
<b>BODY PATTERN</b>	Globe, Angle
<b>PRESSURE RATINGS</b>	Class 150 – 12.0 Bar Max, Class 300 – 20.6 Bar Max
<b>MAXIMUM WORKING TEMPERATURE</b>	Up to 82°C (180°F)
<b>CONNECTION TYPES</b>	Threaded, Flanged or Grooved
<b>MATERIAL</b>	Ductile Iron - ASTM A536
<b>FINISH</b>	Red Epoxy Coated
<b>APPROVALS</b>	FM Approved, UL Listed

### Sizes

### Connection Type

### Type

### Quantity

[ADD TO PROJECT LIST](#)

[Email](#)

### Description

### Technical Specifications

### Download

#### Valve Capacity Table

Valve Size mm	50	65	80	100	150	200	250	300
NFPA 20 Maximum Recommended LPM (litres per Min)	787	1136	1893	3785	9464	18927	41640	60567

#### Dimensions

Value Size (mm)	50	65	80	100	150	200	250	300
Threaded Ends	238	279	318	-	-	-	-	-
A 150 Flanged	238	279	305	381	508	645	756	864
300 Flanged	254	295	337	397	533	670	790	902
300 x 150	-	-	327	389	522	657	773	883
B	84	102	116	146	200	254	330	356
C	305	311	318	330	363	414	457	522
D	38	43	65	81	109	135	235	273
Threaded Ends	121	140	159	-	-	-	-	-
E 150 Flanged	121	140	152	191	254	324	378	432
300 Flanged	127	149	162	200	267	337	395	451
Threaded Ends	83	102	114	-	-	-	-	-
E 150 Flanged	83	102	102	127	152	203	219	349
300 Flanged	89	109	111	135	165	216	236	368

Related Products

104FF NRS Resilient Wedge Gate Valve



DN50 - DN300 (2" - 12"), UL Listed, FM Approved, CNBOP Certified

 [VIEW FULL DETAILS](#)

Pressure Relief Valve



Cla-Val Pressure Relief Valve Model 50B-4KG1 (Globe) / 2050B-4KG1 (Angle), ANSI, Grooved & PN16 Connections, Class 150 / 300,...

 [VIEW FULL DETAILS](#)

302 ANSI Swing Check Valve (Flanged)



Flanged Swing Check Valve with connection sizes 50mm - 300mm (2" - 12"), FM and LPCB Approved, UL Listed

 [VIEW FULL DETAILS](#)

702 ANSI Y-Type Strainer (Flanged)



Flanged Y-Type Strainer with connection sizes 50mm - 300mm (2" - 12") UL Listed

 [VIEW FULL DETAILS](#)