

Corporate

Application Fields

Products

Pumps Selection Program Documents

Products

Homepage > Fire Fighting Pumps

SNK UL/FM

Fire Fighting Pumps





Products

Fire Fighting Pumps

Request Form

#Fire Fighting Pumps

Design Features According to UL & FM

- All interior bolt or screw that are exposed to pumped liquid shall be of rolled bronze or corrosion resistant material
- · The pump shall be provided with automatic air-release valve, circulation relief valve and pressure gauges
- . Bearings shall have an L-10 rating of not less than 5000 hours at maximum load.
- The pumps shall be provided with at least four packing rings plus a lantern ring. The lantern ring may be permitted to replace one ring of packing.
- Impellers, wear rings, shafts, lantern rings, glands shall be made of corrosion resistant material.
- Following material specifications are applied to STANDART UL/FM fire pumps:

I Technical Information

Discharge Flange	ANSI B16.1 Class 250
Casing Pressure (Pmax)	16 bar
Operating Temperature (°C)	up to 40 °C
Speed	up to 3000 d/min

Download





m Name
m Name
ione
mail Address
otes
ZhVc7 C
Being informed in accordance with the Law on Personal Data Protection No. 6698, I hereby consent that my personal data that I share is processed, stored, shared with Standart Pompa and related persons within the context of regulations related to the purposes stated in the Information Form.





SDS / SDS-V

NFPA 20

ation

STANDART POMPA 'IN SOCIAL MEDIA











©Copyright 2018 | standartpompa.com

