
Home About Products Projects Accreditations Knowledge Base Events Contact Us Your Project





in



Products > Wet & Dry Risers and Hose Reels

DRV006 Dry Riser Landing Valve (Threaded - Male)

Q

SIZE	65mm (2 ½")		
VALVE TYPE	Gate pattern		
INLET CONNECTION	BSP Male Threaded		
OUTLET CONNECTION	BS336 Female		
WORKING PRESSURE	22 bar (319 psi)		
BODY MATERIAL	LG2 bronze		
STANDARDS	Manufactured in Accordance with BS5041 part 2 Flange manufactured to BS4504		

Dry Riser Landing Valve, Male BSP Threaded

Please Select

Quantity

1

ADD TO PROJECT LIST

Email

Description Technical Specifications Download

Specifications

Size	65mm (2 ½")
Material	LG2
Pressure Rating	Tested to 22 bar
Inlet Connection	BSP Male Threaded
Outlet Connection	BS336 Female
Manufactured in Accordance to	BS5041 Part 2

Material Specifications

Item	Part Description	Qty	Material
1	Body	1	LG2
2	Disc	1	Brass
3	Stem	1	Brass
4	Valve Cap O-ring	1	Rubber
5	Valve Cap	1	Brass
6	Nut	1	Brass
7	Valve Stem O-ring	1	Rubber
8	Nut	1	Brass
9	Handwheel	1	Brass
10	Handwheel Gasket	1	Steel
11	Nut M12	1	Steel
12	Tag	1	Brass
13	Spring	1	SUS304
14	Guard Knob	1	Brass
15	Nut M8	1	Steel
16	Сар	1	Plastic

17	Sealing Ring	1	Rubber	
18	Cap with Chain	1	Plastic (cover) Steel (chain)	

Related Products

DRV002 Dry Riser Landing Valve Flanged

DRV007 Dry Riser Landing Valve (Threaded - Female)

Dry Riser Vertical Outlet Full Cabinet



Dry Riser Landing Valve Flanged



Dry Riser Landing Valve Threaded - Female



Model: DRC008 (red) / DRC009 (stainless steel) Vertical Outlet Full Cabinet for Dry Riser Landing Valves









Copyright © 2023 Rapidrop Global Ltd. All rights reserved. Company Registered in the UK, No. 05503278
Registered address: Unit 1-3, Rutland Business Park, Newark Road, Peterborough, Cambridgeshire, PE1 5WA

Terms & Conditions | Privacy Policy | Site Map