





Products > Wet & Dry Risers and Hose Reels

DRV006 Dry Riser Landing Valve (Threaded -Male)

Q

SIZE	65mm (2 ½")
VALVE TYPE	Gate pattern
INLET CONNECTION	BSP Male Threaded
OUTLET CONNECTION	BS336 Female
WORKING PRESSURE	22 bar (319 psi)
BODY MATERIAL	LG2 bronze
STANDARDS	Manufactured in Accordance with BS5041 part 2 Flange manufactured to BS4504

Dry Riser Landing	Valve,	Male	BSP	Threaded
Diagon Coloct				

Please Select	*	
Quantity		
1		
ADD TO PROJECT LIST	✓ Email	

Description **Technical Specifications** Download

Dry riser landing valves are outlets from the riser main. The valves are situated on each floor of a high rise building and are usually housed in an outlet cabinet. Dry riser landing valves are available with PN16 inlet, Table D inlet, BSP threaded male inlet and BSP threaded female inlet. The outlets are to BS336 and come complete with cap & chain. Padlocks and straps are available on request.

Related Products

DRV002 Dry Riser Landing Valve Flanged

DRV007 Dry Riser Landing Valve (Threaded - Female)

Dry Riser Vertical Outlet Full Cabinet



Dry Riser Landing Valve Flanged




Dry Riser Landing Valve Threaded -



Model: DRC008 (red) / DRC009 (stainless steel) Vertical Outlet Full Cabinet for Dry Riser Landing Valves









Registered address. Onlit 1-5, Rolliand dosiness Park, Wewark Road, Peterborough, Cambridgeshire, PET 5WA	Terms & Conditions Privacy Policy Site Map