Forensic Analysis of Web Data

Erhard Dinhobl

Vienna University of Technology - Information and Software Engineering Group

5.10.2016

Introduction

- using collected data in surveys
- influence to known investigative models
- appropriate investigation model
- digital preservation
- legal issues
- deep web crawling
- format of data
- designing a deep web crawler

Table of contents


- base investigation model
- new investigation model
- "reduct" and "preserve" steps in detail
- underlying methodology (deep web crawler)
- usage

The Investigation S(RP)AP

- secure
- ▶ reduct
- preserve
- analyze
- present

Best for online crime investigation!

The Process



The Process (2)


- ▶ Where was the evidence stored?
- ▶ Who had obtained the evidence?
- ▶ What has been done to the evidence?

The Deep Web Crawler

Challenges:

- ▶ the use of AJAX technology in web pages
- the simulation of user interaction with HTML elements (e.g. forms)
- the use of Captchas in web pages

The Architecture



Simple Example

```
<?xml version="1.0"?>
<cratalis start-url="http://kurier.at"</pre>
    name="Kurier Crawling"
    start-action-sequence="1">
  <action-sequence id="1">
    <action type="StartAction" id="1"</pre>
        comment="start every link" save="true"
        action-sequence-id="3">
          .//a[@href and
          not(starts-with(@href, "#"))]
    </action>
  </action-sequence>
  <action-sequence id="3">
    <action type="SaveAction" id="3"
        comment="just save" save="true"/>
  </action-sequence>
</cratalis>
```

More complex example

```
<?xml version="1.0"?>
<cratalis start-url="http://www.studivz.de" name="StudiVZ" start-action-sequence="1"</pre>
      deml-file="studivz/studivz.xml">
  <action-sequence id="1">
    <action type="JavaScript" id="1" comment="filling out the login form"
          save="true" save-file="studivz/login-screen.html">
        var usernameInputs = document.evaluate(".//*[@id='Login_email']", ...);
        var usernameTextBox = usernameInputs.iterateNext():
        usernameTextBox.value = "forensicanalysis@vmail.com":
        var passwordInputs = document.evaluate(".//*[@id='Login_password']", ...);
        var passwordTextBox = passwordInputs.iterateNext();
        passwordTextBox.value = "gustav":
    </action>
    <action type="StartAction" id="2" save-file="studivz/home.html"....></action>
  </action-sequence>
  <action-sequence id="2">
    <action type="StartAction" id="3" save-file="studivz/inbox.html"></action>
  </action-sequence>
  <action-sequence id="3">
    <action type="JavaScript" id="4" comment="start other action to overview" save="fals
        var msgLinkList = document.evaluate(
              ".//div[contains(@class.'from-subject')]/div[contains(@class.'subject')]/a
        var msgLink;
        var count = 0;
        while(msgLink = msgLinkList.iterateNext()) {
            count++:
            msgLink.onclick.apply(msgLink);
            savePage('studivz/msg' + count + '.html');
    </action>
  </action-sequence>
</cratalis>
```

Usage

- investigative
 - collecting bitcoin addresses (clear and dark net)
 - saving evidence files from the web (also via Tor)
- non-investigative
 - collecting event data
 - ... person data (incl. friendship)
 - ... news
 - ... locations
 - ... bitcoin addresses and names
 - many others still done