

DataBridge Connector v2.4

User Manual

Document version 2.4.1 — October 2025

1. Introduction

DataBridge Connector is a lightweight middleware library that synchronises data between your application database and third-party APIs. It supports incremental sync, conflict resolution, and automatic retry on transient failures. This manual covers installation, configuration, and day-to-day operation of version 2.4.

2. System Requirements

Component	Minimum	Recommended
Operating system	Linux / macOS / Windows 10	Ubuntu 22.04 LTS
Python	3.10	3.12
RAM	512 MB	2 GB
Disk space	100 MB	500 MB
Network	Outbound HTTPS (443)	Low-latency connection

3. Installation

3.1 Installing via pip

Install DataBridge Connector from PyPI using pip:

```
pip install databridge-connector
```

3.2 Verifying the installation

```
python -c "import databridge; print(databridge.__version__)"
```

Expected output: 2.4.1

4. Configuration

All settings are loaded from a YAML configuration file. By default the connector looks for `databridge.yml` in the current working directory. An alternative path can be specified via the `DATABRIDGE_CONFIG` environment variable.

Minimal configuration example:

```
source:
  type: postgresql
  host: localhost
  port: 5432
  database: myapp

target:
```

```
type: rest_api
base_url: https://api.example.com/v1
auth: bearer

sync:
  interval_minutes: 15
  batch_size: 500
  conflict_strategy: source_wins
```

5. Running the Connector

Start a one-time sync:

```
databridge sync --once
```

Start the continuous sync daemon:

```
databridge sync --daemon
```

Logs are written to `databridge.log` in the working directory and rotated daily. The default log level is `INFO`; set `log_level: debug` in the config file for verbose output.

6. Troubleshooting

Symptom	Likely cause	Resolution
ConnectionRefusedError on startup	Database not reachable	Check host/port in config; confirm firewall rules
401 Unauthorized from target API	Expired or invalid bearer token	Refresh the token and update <code>databridge.yml</code>
Sync completes but no records transferred	Write mark table is missing	Run: <code>databridge init-schema</code>
High memory usage during large batch	<code>batch_size</code> too large	Reduce <code>batch_size</code> to 100 and retry

For additional help, open an issue at <https://github.com/example/databridge-connector>