

Computer Vision

Chapter 5: Image segmentation


Chapter 5. Segmentation

- Introduction to image segmentation
- Segmentation based on pixel classification
 - Thresholding
 - Clustering techniques
- Region-based segmentation
 - Region growing algorithm,
 - Split and merge algorithm
- Edge-based segmentation

Introduction


- Purpose:
 - to partition an image into meaningful regions with respect to a particular application
- Goal:
 - to cluster pixels into salient image regions, i.e., regions corresponding to individual surfaces, objects, or natural parts of objects.
- The segmentation is based on the feature measurements taken from the image:
 - grey level, color, texture, depth or motion...

Introduction



Introduction

- Entity can be extracted from images using mask



Source : Pascal Bertolino, Cours de Traitement d'images. LIS, INPG (France)

5


Applications

- Image segmentation**
 - is usually an initial and vital step in a series of processes aimed at overall image understanding of computer vision
- Segmentation applications:**
 - Object recognition;
 - Image retrieval;
 - Medical image analysis;
 - Boundary estimation within motion or stereo systems;
 - Tracking of objects in a video;
 - Classification of terrains visible in satellite images
 - ...



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

7



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

8

Approaches for image segmentation

- Segmentation is usually based on:
 - discontinuities:** edges
 - sudden changes, borders (frontiers) between regions...
 - homogeneous zones:** regions
 - same color, texture, intensity, ...




SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

9

Approaches for image segmentation


- Pixel-based approach
- Region-based approach:
 - look for **homogeneous** areas in the image
- Edge-based approach :
 - look for **discontinuities** in the image
 - **A closed edge is equivalent to a region**
- Hybrid (Dual) approach (region + edge)



Examples

Original images

Segmented images



Pixel-based approach

- Pixel-based approach
 - Thresholding
 - Clustering
- It is not a region segmentation technique
 - But we often in segmentation looking for regions
 - Need some post-processing

Thresholding


- Thresholding is a *simple and popular* method for object segmentation in digital images
- Thresholding can be
 - **Global**: one threshold for the whole image
 - **Local**: one threshold for a part of the image
 - **Adaptive**: one threshold adjusted according to each image or each image part

Basic global thresholding

- Basic thresholding (2 classes) – main idea :
 - IF value(pixel) \geq threshold THEN value(pixel) = 1 (or 255)
 - IF value(pixel) < threshold THEN value(pixel) = 0
- The result is a binary image
- It is also possible to use n thresholds to split the image in $n+1$ classes
- Problem: choosing the threshold(s)!

Basic global thresholding



- Find the threshold on histogram of gray level intensity (histogram thresholding)



$$g(x, y) = \begin{cases} 0, & f(x, y) < T \\ 1, & f(x, y) \geq T \end{cases}$$

Basic global thresholding

- Threshold value: not difficile if
 - Controlled environment
 - Industrial applications




Multi-thresholds

- n thresholds to split the image in $n+1$ classes:
 - IF value(pixel) < threshold_1
 - THEN value(pixel) = 0
 - IF value(pixel) \geq threshold_1 && value(pixel) < threshold_2
 - THEN value(pixel) = 1
 - ...
 - IF value(pixel) \geq threshold_n
 - THEN value(pixel) = n
- Problems: How many thresholds?

Multi-thresholds

$$g(x, y) = \begin{cases} 0, & f(x, y) < T_1 \\ 1, & T_2 > f(x, y) \geq T_1 \\ 2, & f(x, y) \geq T_2 \end{cases}$$




Threshold value

- Global thresholding: How to find the value of the threshold **T** ?
 - Value obtained by tests
 - The mean value of gray values
 - The median value between the min gray level and the max one
 - One value balancing both sections of the histogram
 - automatic thresholding

Choice of thresholds (optimal)

- 2 surfaces (background and object) in an image
 - We suppose mathematical models for distributions (gaussians, etc.)
 - We determine the probability of error in the classes 1 and 2 (surfaces 1 et 2)
 - We search for a threshold **T** resulting in a minimum error
 - Several methods for achieving this



Example: Global automatic thresholding

- One possible algorithm:
 - Choose an initial value for the threshold **T** (mean, median, ...)
 - We obtain 2 groups of pixels
 - G1 where $f(x,y) \geq T$ and G2 where $f(x,y) < T$
 - Compute the gray level means for G1 and G2 $\rightarrow \mu_1$ and μ_2
 - Compute a new value for **T**
 - $T = 1/2 (\mu_1 + \mu_2)$
 - Repeat until **T** is ~ constant
- There exist many other global automatic methods
 - Otsu, Kittler, K-means, ...
 - No solution on which one to use
 - Must be tested for each new application


Example: Otsu algorithm

- Sweep all possible threshold value for T
- For **each value of T** :
 - Compute the mean and variance for each class
 - We look for the intraclass variance

- Means: μ_1, μ_2
- Variances: σ_1^2, σ_2^2
- **Intra-class variance:**
 $\sigma_w^2 = P_1 * \sigma_1^2 + P_2 * \sigma_2^2$

- The optimal threshold is the one with the **minimum value for σ_w^2**

- It is based on the idea that classes are well defined and well grouped



$$\sigma_1^2 = \frac{1}{T} \sum_{i=0}^{T-1} (h(i) - \mu_1)^2$$


$$\sigma_2^2 = \frac{1}{256 - T} \sum_{i=T}^{255} (h(i) - \mu_2)^2$$

$$\mu_1 = \frac{1}{T} \sum_{i=0}^{T-1} h(i) \quad P_1 = \frac{1}{N} \sum_{i=0}^{T-1} h(i)$$

$$\mu_2 = \frac{1}{256 - T} \sum_{i=T}^{255} h(i) \quad P_2 = \frac{1}{N} \sum_{i=T}^{255} h(i)$$


Example: Otsu algorithm

- Threshold found by the algorithm:
 - $T = 125$




Global threshold: problem

- Problem:
 - Global thresholding cannot be used in that case
 - Solution: adaptive local thresholding




Example of adaptive thresholding

- Split the image in sub-images and process each sub-image with its own threshold
- The main decision is to choose the size of the sub-images
- Before processing each sub-image, check the variance to make sure that the sub-image contains two regions, and not only one.
 - Example: no thresholding for a sub-image if variance < 100



Example of adaptive thresholding



Example of adaptive thresholding




FIGURE 10.37
(a) Original image, (b) Image segmented by local thresholding. (Courtesy of IBM Corporation.)

Clustering-based segmentation


- Image is considered as a set of N image pixels.
- Attributes (property) of the pixels
 - gray level of single-band gray tone images,
 - color values of three-band color images: (r, g, b)
 - values of multi-band images, ...
- Based on the similar attribute, pixels classification operators partition an image into homogeneous regions.
 - Clustering provides a grouping of the pixels that is dependent on their values in the image but not necessarily on their locations in the image unless location is a specified property
 - Classifier provide the pixel classes which should be homogeneous regions.

Clustering algorithms


- Image segmentation approaches including:
 - Feature space clustering approaches
 - Graph-based approaches
- Clustering algorithms:
 - K-Means clustering
 - Mean-Shift Clustering
 - Expectation-Maximization Clustering
 - Watershed Segmentation
 - Graph Cuts (Spectral clustering)
 - Normalized cuts
 - ...

K-means Clustering

- Let $X = \{p_1, \dots, p_N\}$ be a set of N image pixels:
 - $V(p_i)$: the property vector associated with pixel p_i
 - The clustering algorithm is to partition the image into K clusters (K regions)
- The **K-means** algorithm:
 - Initialization step: An initial property vector of each class C_k is chosen randomly from the set of all property vector, note $\mu_k(0)$
 - Interactive step: Assignment of image pixels to K clusters




31



32

K-means Clustering



Input image


K-means on gray level

K-means on color

33

K-means Clust

K-means on color for 11 groups




34

Example



Example



Pixel-based approach: Pros & cons

- Pros
 - Simple, fast
- Cons: thresholding is mainly an operation on pixels
 - It does **not give connected regions** → can add more features
 - we need to « clean » the results
 - erase **lonely pixels**, keep regions
- Other segmentation methods exist
 - that can keep the integrity of regions (connected pixels)

Features for segmentation

- Intensity, Color?
- Position
- Texture
- ...

Segmentation as clustering

Depending on what we choose as the *feature space*, we can group pixels in different ways.

Grouping pixels based on **intensity** similarity



Feature space: intensity value (1-d)





SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

Slide credit: Kristen Grauman

Segmentation as clustering

Depending on what we choose as the *feature space*, we can group pixels in different ways.

Grouping pixels based on **intensity+position** similarity



Both regions are black, but if we also include **position (x,y)**, then we could group the two into distinct segments; way to encode both **similarity & proximity**.





Slide credit: Kristen Grauman

SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

Segmentation as clustering

Depending on what we choose as the *feature space*, we can group pixels in different ways.

Grouping pixels based on **texture** similarity



Filter bank of 24 filters

Feature space: filter bank responses (e.g., 24-d)




SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

Slide credit: Kristen Grauman

Segmentation with texture features

- Find "textons" by **clustering** vectors of filter bank outputs
- Describe texture in a window based on *texton histogram*




Malik, Belongie, Leung and Shi. IJCV 2001.

SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

Adapted from Lana Lazebnik

Image segmentation example



Slide credit: Kristen Grauman

Region-based segmentation

- Finding region based on the criterion of **homogeneity** and **connectivity** of pixels (region)
 - Each region is homogeneous (i.e., uniform in terms of the pixel attributes such as intensity, color, range, or texture, etc.)
 - and connected
- Algorithms:**
 - Region growing
 - Split and merge algorithm
 - Hierarchical clustering
 - ...



Region-based segmentation

- Region-based approaches provide :
 - All pixels must be assigned to regions
 - Each pixel must belong to a **single region** only
 - Each region must be **uniform**
 - Any **merged pair of adjacent regions** must be **non-uniform**
 - Each region must be a **connected set of pixels**
- Region-based approaches:
 - Different methods
 - Common point: **homogeneity criteria**


Region growing

- Start from a point (seed) and add neighbor pixels following a **given criteria**
- The seeds can be manually or automatically chosen
 - automatic seeds in very homogeneous zones for example




Region growing algorithm

- Algorithm:
 - Choose K random pixels in K regions
 - Use 8-connected and threshold to determine
 - Repeat a and b until almost points are K classified.
- Example illustrated:



Region growing with multi-seeds




Example

Simulation
of region
growing
(90% pixels)




Split-and-merge

- Split (step 1)
 - Recursively split all non-homogeneous regions following a given criteria
 - variance, max-min, ...
 - Dividing one region gives 4 subregions
 - Subregion attributes are re-computed
- Merge (step 2)
 - Group all homogeneous adjacent regions following a given criteria



Split-and-merge: split




Source : Jean-Christophe Baillie, Cours de segmentation, ENSTA ParisTech (France).

51

Split-and-merge: merge

Phase 1: Create homogeneous zones (split)
Phase 2: Group homogeneous zone (merge)



Source : Jean-Christophe Baillie, Cours de segmentation, ENSTA ParisTech (France).

52

Split-and-merge



Source : Jean-Christophe Baillie, Cours de segmentation, ENSTA ParisTech (France).

53

Edge-based segmentation

- Finding region based on edges



- Algorithms:**


- Basic Edge Detection
- The Marr-Hildreth edge detector (LoG)
- Short response Hilbert transform (SRHLT)
- Watersheds

Source : Jean-Christophe Baillie, Cours de segmentation, ENSTA ParisTech (France).

54

Watershed segmentation

- We consider the image as a 3D shape using the gray level as the third dimension




2D image

Visualization in 3D


Watershed segmentation

- After we reverse (upside down) the values to create « holes » in the shape




Watershed segmentation


- Next we fill in the holes with water




Watershed segmentation



Watershed segmentation



Watershed segmentation



Segmentation – advices

- Image segmentation
 - No method works for all images
 - No miracle, no warranty!
- One of the main problem is to define the **goal of segmentation**:
 - What exactly are we looking for in the image?
 - Global regions or small details?
 - Presence or not of persons details in the face?
- It is good to think in advance **what we will do with this segmentation results**
 - This helps to define the level of precision needed

Segmentation – advices

- Image Pre-processing:
 - **good selection** of sensors and energy source, and controled image acquisition conditions help to make segmentation easier and more efficient
- For some applications, we realize today that we can **avoid to segment** the image. It is often better like this.

Limits of segmentation

Image segmentation alone cannot find all image objects as we can interpret them




SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

63

Segmentation vs. grouping

- Term 'segmentation' :
 - less used
 - segmentation, which let think about an exact image splitting into regions
- 'Pixel grouping'
 - which refers only to a notion of similarity between pixels without relation on the content of regions.



Source : [Malik 2001].



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

64

Motion segmentation



Input sequence



Image Segmentation



Motion Segmentation



Input sequence



Image Segmentation



Motion Segmentation

A.Barbu, S.C. Zhu. Generalizing Swendsen-Wang to sampling arbitrary posterior probabilities, *IEEE Trans. PAMI*, August 2005.

Credit: Kristen Grauman, UT Austin



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY



Thank you for
your attention!

soict.hust.edu.vn / fb.com/groups/soict

