HUMPHREY VIRTUAL FARMS LLC // WP-3: SITE PLC, 60HZ SCADA, & SAE J1939 CAN-BUS ICD
Entity: Humphrey Virtual Farms LLC (CAGE: 1AHA8 | SAM.gov UEI: S1M4ENLHTDH5)
Controlling Authority: Jeffery Humphrey, Founder, CEO, & Principal Sovereign Architect
Plug-In Module: CLIN 0029 (WP-3 Site Interface Adapter) | Enclave Tier: PUBLIC
Host Ebony Baseline Merkle Root:
cc1ee1c8d29b2ae5e856fc0fcb672a52e7e49d50369499febe14e18e9150949a

==========

1. 60Hz Microgrid Substation Relay Binding (CLIN 0003 -- IEEE C37.118 / Modbus / DNP3)
- Measured Bus Frequency: 59.985 Hz (Deviation: 0.0150 Hz | Limit: <= 0.50 Hz)
- Rate-of-Change-of-Frequency (RoCoF): -0.12 Hz/s (Limit: <= 1.50 Hz/s)
- PCC Islanding Breaker Trip State: False
- Hardware Register Map: [REDACTED_MODBUS_DNP3_REGISTER_MAP_DFARS_252_227_7018]

==========

2. 480V 3-Phase Grain Silo Contactor & Plenum PLC Binding (CLIN 0009 -- NEMA MG-1)
- 3-Phase RMS Voltage Average: 480.00 V AC
- NEMA MG-1 Phase Voltage Unbalance: 0.2500% (Limit: <= 2.00%)
- Contactor Interlock Safe: True | Command: ENERGIZE_480V_CONTACTOR
- PLC Coil & Register Map: [REDACTED_480V_PLC_COIL_MAP_DFARS_252_227_7018]

==========

3. SAE J1939 29-Bit Tactical CAN-Bus Decoder (CLIN 0008 -- PGN 61444 EEC1)
- 29-Bit Extended CAN Identifier: 0x0CF00400 (Priority: 3 | PGN: 61444 | Source: 0)
- Decoded Engine Speed (SPN 190): 1800.00 RPM
- CAN-Bus Physical & Scaling Binding: [REDACTED_J1939_SPN_SCALING_DFARS_252_227_7018]

==========
WORM WP-3 Interface Control Document Seal (SHA-256):
3a7f92d1f670ff1dbdc9e4259d1b60e0fa14c54e46c1ed37ad484fbcb042a343