



Agent/Client Protocol

Ben Brandt, Zed
Sergey Ignatov, JetBrains



JETBRAINS



Zed

agent-client-protocolmain

1 ChangeStage All

agent.rsReview: Capabilities for Agent Client ProtocolUncommitted Changes

Tracked

README.md

README.md

Jump To Fileg space

1StageRestore

2

3

4

5# Agent Client Protocol

6

7The Agent Client Protocol (ACP) standardizes communication between _code editors_ (interactive programs for viewing and editing source code) and _coding agents_ (programs that use generative AI to autonomously modify code).

8

9Learn more at agentclientprotocol.com.

10

11## Integrations

12

13- [Schema](./schema/schema.json)

14### Official Libraries

15- **Kotlin**: [`acp-kotlin`](https://github.com

Capabilities for Agent Client Protocol

Protocol Suggestions: If you'd like to propose additions or

License

License

By contributing, you agree that your contributions will be license

This project is licensed under the Apache 2.0 License. By contribu

I've cleaned up the README with the following improvements:

Changes made:

1. Fixed spacing in the HTML anchor tag

2. Changed italics to bold for key terms (code editors, coding agents) for better emphasis

3. Reorganized the Integrations section with clearer subsections:

- “Official Libraries” prominently listed first
- “Community Resources” for schema, agents, clients, and community libraries

4. Standardized punctuation – used en-dashes (–) consistently and changed “See” to lowercase “see” for consistency

5. Moved “Schema” to “Protocol Schema” for clarity and moved it under Community Resources

6. Improved wording – changed “we follow” semicolon to period for better readability

7. Made “License” a top-level section (## instead of ###) since it's not really part of Contributing

8. Enhanced the license text to make it clearer that the project itself is licensed under Apache 2.0

Edits · 1 file

Reject Allcmd-shift-nKeep Allcmd-shift-y

Message the Zed Agent – @ to include context

11k / 200kWriteClaude Sonnet 4.5

1:1 -- NORMAL --

Project

build_registry.py

generate_mintlify_agents.py

update-versions.yml

update_versions.py

upload-s3.yml

verify_agents.py

.idea

_not_yet_unsupported

auggie

claude-code-acp

- agent.json
- icon.svg

codex-acp

dist

factory-droid

- agent.json
- icon.svg

gemini

- agent.json
- icon.svg

github-copilot

mistral-vibe

opencode

qwen-code

.gitignore

agent.schema.json

M+ AGENTS.md

M+ AUTHENTICATION.md

M+ CODE_OF_CONDUCT.md

M+ CONTRIBUTING.md

M+ FORMAT.md

LICENSE

M+ README.md

registry.schema.json

External Libraries

Scratches and Consoles

- Extensions
- Scratches

registry – AGENTS.md

CLAUDE.md

This file provides guidance to Claude Code (claude.ai/code) when working with code in this repository.

Build Commands

```
'''bash
# Build registry (validates all agents and outputs to dist/)
uv run --with jsonschema .github/workflows/build_registry.py

# Build without schema validation (if jsonschema not available)
python .github/workflows/build_registry.py
'''
```

Architecture

This is a registry of ACP (Agent Client Protocol) agents and extensions. The structure is:

```
<id>/
├── agent.json      # Agent metadata and distribution info
├── extension.json  # OR extension metadata (same schema as agent.json)
└── icon.svg       # Icon: 16x16 SVG, monochrome with currentColor (optional)
```

Each directory contains either `agent.json` (for agents) or `extension.json` (for extensions), but not both

Build process (`.github/workflows/build\_registry.py`):
1. Scans directories for `agent.json` or `extension.json` files
2. Validates against `agent.schema.json` (JSON Schema)
3. Validates icons (16x16 SVG, monochrome with `currentColor`)
4. Aggregates into `dist/registry.json` with separate `agents` and `extensions` arrays
5. Copies icons to `dist/<id>.svg`

CI/CD (`.github/workflows/build-registry.yml`):
- PRs: Runs validation only
- Push to main: Validates, then publishes versioned + `latest` GitHub releases

Validation Rules

- `id`: lowercase, hyphens only, must match directory name
- `version`: semantic versioning (e.g., `1.0.0`)
- `distribution`: at least one of `binary`, `npm`, `uvx`
- `icon.svg`: must be SVG format, 16x16, monochrome using `currentColor` (enables theming)
- **URL validation**: All distribution URLs must be accessible (binary archives, npm/PyPI packages)

Junie

Junie

Junie is a Coding Agent.
It understands the context of the whole project.
This makes it autonomous, and gives it ability to solve big coding tasks.

Type your task here, press ⌘

+

Auto

Brave Mode

Think More

→

Use Junie From a Single AI Chat

You can now work with Junie and other AI features from a single chat interface.

Try New AI Experience

Learn More ↗

Ask Junie to:

1. Generate project-specific guidelines

2. Write/update a README.md file for this project

3. Based on the last 2-5 git commits, generate a CHANGELOG.md file

4. Develop a "specific feature" using a Test-Driven Development (TDD) approach

Mastering Junie

Junie Getting Started Guide ↗

Coding Guidelines for Your AI Agents ↗

1:1

LF

UTF-8

4 spaces

zed on **main** [\$] via **orbstack** via **v1.90.0**
 > claude

Claude Code v2.0.27
 Sonnet 4.5 · API Usage Billing
 /Users/benbrandt/github/zed

> /status
 [Status dialog dismissed

> /help

Claude Code v2.0.27 **general**ds comman custom-com (tab to mands cycle)

Claude understands your codebase, makes edits with your permission, and executes commands – right from your terminal.

Shortcuts

! for	double tap esc to	ctrl + _ to
bash mode	clear input	undo
/ for	shift + tab to	ctrl + z to
commands	ctrl + o for dits	suspend
@ for	verbose output	ctrl + v to
file	ctrl + t to show	paste images
paths	tab to toggle	
# to	thinking	
memorize	shift + ↵ for	
	newline	

For more help: <https://docs.claude.com/en/docs/claude-code/overview>

Esc to exit

>_ **OpenAI Codex** (v0.46.0)

model: gpt-5-codex /model to change
 directory: ~/github/zed

To get started, describe a task or try one of these commands:

/init - create an AGENTS.md file with instructions for Codex
 /status - show current session configuration
 /approvals - choose what Codex can do without approval
 /model - choose what model and reasoning effort to use
 /review - review any changes and find issues

> Summarize recent commits

100% context left · ? for shortcuts



v0.8.0-nightly.20250925
 .b1da8c21

Tips for getting started:

1. Ask questions, edit files, or run commands.
2. Be specific for the best results.
3. **/help** for more information.

> /help

Basics:

Add context: Use @ to specify files for context (e.g., @src/myFile.ts) to target specific files or folders.

Shell mode: Execute shell commands via ! (e.g., !npm run start) or use natural language (e.g. start server).

Commands:

/about - show version info
/auth - change the auth method
/bug - submit a bug report
/chat - Manage conversation history.
 list - List saved conversation checkpoints
 save - Save the current conversation as a checkpoint. Usage: /chat save <tag>
 resume - Resume a conversation from a checkpoint. Usage: /chat resume <tag>
 delete - Delete a conversation checkpoint. Usage: /chat delete <tag>
 share - Share the current conversation to a markdown or json file. Usage: /chat share <file>
/clear - clear the screen and conversation history

LSP

Use the tools you like
in the editor you love ♥

ACP

Use the **agents** you like
in the editor you love ♥



Agent/Client
Protocol

JSON RPC Spec

```
{ "method": "initialize", "params": {"protocolVersion": 1, "clientCapabilities": {"fs": {"readTextFile": true}}, "prompt": "You are a helpful assistant." },  
  { "result": {"agentCapabilities": {"loadSession": true, "mcpCapabilities": {"http": true, "sse": false}, "prompt": "You are a helpful assistant." }},  
  { "method": "session/new", "params": {"cwd": "/Users/ignatov/src/intellij-erlang", "mcpServers": []} },  
  { "result": {"models": {"availableModels": [], "currentModelId": ""}, "modes": {"availableModes": [{"description": "You are a helpful assistant."}]}},  
  { "method": "session/update", "params": {"sessionId": "01de191d-968e-4068-a801-e7e68f1b760f", "update": {"agentCapabilities": {"loadSession": true, "mcpCapabilities": {"http": true, "sse": false}, "prompt": "You are a helpful assistant." }},  
  { "method": "initialize", "params": {"protocolVersion": 1, "clientCapabilities": {"fs": {"readTextFile": true}}, "prompt": "You are a helpful assistant." },  
  { "result": {"protocolVersion": 1, "agentCapabilities": {"loadSession": true, "resumeSession": true, "sessionCapabilities": {"fs": {"readTextFile": true}}},  
  { "method": "session/new", "params": {"cwd": "/Users/ignatov/src/intellij-erlang", "mcpServers": []} },  
  { "result": {"sessionId": "298948c1-41e4-4f46-9497-0ae97d11b8fd", "models": {"availableModels": [{"modelId": "gpt-4o", "description": "You are a helpful assistant."}]}},  
  { "method": "session/set_mode", "params": {"sessionId": "298948c1-41e4-4f46-9497-0ae97d11b8fd", "modeId": "gpt-4o"},  
  { "method": "session/update", "params": {"sessionId": "298948c1-41e4-4f46-9497-0ae97d11b8fd", "update": {"agentCapabilities": {"loadSession": true, "mcpCapabilities": {"http": true, "sse": false}, "prompt": "You are a helpful assistant." }},  
  { "method": "session/set_model", "params": {"sessionId": "298948c1-41e4-4f46-9497-0ae97d11b8fd", "modelId": "gpt-4o"},  
  { "method": "session/prompt", "params": {"sessionId": "298948c1-41e4-4f46-9497-0ae97d11b8fd", "prompt": [{"text": "Hello"}]},  
  { "method": "session/update", "params": {"sessionId": "298948c1-41e4-4f46-9497-0ae97d11b8fd", "update": {"agentCapabilities": {"loadSession": true, "mcpCapabilities": {"http": true, "sse": false}, "prompt": "You are a helpful assistant." }},  
  { "result": {"stopReason": "end_turn"} } }
```


acp-rust-sdk

add-session-close

←

→

t.rs

agent.rs src

Uncommitted Changes

Cargo.toml

lib.rs

settings.json

ACP: codex-acp

Changes since origin/main

hi!

↑ initialize

{ "protocolVersion": 1, "clientCapabilities": { "fs": { "readTextFile": true, "writeTextFile": true }, "terminal": true, "_meta": { "terminal_outpu

↓ initialize

{ "protocolVersion": 1, "agentCapabilities": { "loadSession": true, "promptCapabilities": { "image": true, "audio": false, "embeddedContext": true

↑ session/new

{ "cwd": "/Users/benbrandt/github/acp-rust-sdk", "mcpServers": [] }

↓ session/new

{ "sessionId": "019cdcd6-a497-76c2-9e7a-654792a6c7b8", "modes": { "currentModeId": "read-only", "availableModes": [{ "id": "read-only", "name": "Re

↓ session/update

{ "sessionId": "019cdcd6-a497-76c2-9e7a-654792a6c7b8", "update": { "sessionUpdate": "available_commands_update", "availableCommands": [{ "name": "r

↑ session/list

{ }

↓ session/list

{ "sessions": [{ "sessionId": "019cd43d-c0ab-7fa1-aae0-5d966522a886", "cwd": "/Users/benbrandt/github/zed", "title": "We aren't notifying users of :

↑ session/prompt

{ "sessionId": "019cdcd6-a497-76c2-9e7a-654792a6c7b8", "prompt": [{ "type": "text", "text": "hi!" }] }

↓ session/update

{ "sessionId": "019cdcd6-a497-76c2-9e7a-654792a6c7b8", "update": { "sessionUpdate": "agent_message_chunk", "content": { "type": "text", "text": "Hi

↓ session/update

{ "sessionId": "019cdcd6-a497-76c2-9e7a-654792a6c7b8", "update": { "sessionUpdate": "agent_message_chunk", "content": { "type": "text", "text": "."

↓ session/update

{ "sessionId": "019cdcd6-a497-76c2-9e7a-654792a6c7b8", "update": { "sessionUpdate": "agent_message_chunk", "content": { "type": "text", "text": " W

↓ session/update

hi!

Hi. What do you need help with in /Users/benbrandt/github/acp-rust-sdk?

Message Codex CLI – @ to include context, / for commands

Read Only gpt-5.4 Xhigh

-- INSERT --

Current status



Amp
ACP wrapper for Amp - the frontier coding agent
0.7.0



Auggie CLI
Augment Code's powerful software agent, backed by industry-leading context engine
0.18.1



Autohand Code
Autohand Code - AI coding agent powered by Autohand AI
0.2.1



Claude Agent
ACP wrapper for Anthropic's Claude
0.21.0



Cline
Autonomous coding agent CLI - capable of creating/editing files, running commands, using the browser, and more
2.6.1



Codebuddy Code
Tencent Cloud's official intelligent coding tool
2.56.1



Codex CLI
ACP adapter for OpenAI's coding assistant
0.9.5



Corust Agent
Co-building with a seasoned Rust partner.
0.3.7



crow-cli
Minimal ACP Native Coding Agent
0.1.14



Cursor
Cursor's coding agent
0.1.0



DimCode
A coding agent that puts leading models at your command.
0.0.16



Factory Droid
Factory Droid - AI coding agent powered by Factory AI
0.71.0



fast-agent
Code and build agents with comprehensive multi-provider support
0.5.9



Gemini CLI
Google's official CLI for Gemini
0.32.1



GitHub Copilot
GitHub's AI pair programmer
1.0.3



goose
A local, extensible, open source AI agent that automates engineering tasks
1.27.2



Junie
AI Coding Agent by JetBrains
888.180.0



Kilo
The open source coding agent
7.0.41



Kimi CLI
Moonshot AI's coding assistant
1.18.0



Minion Code
An enhanced AI code assistant built on the Minion framework with rich development tools
0.1.39



Mistral Vibe
Mistral's open-source coding assistant
2.4.0



Nova
Nova by Compass AI - a fully-fledged software engineer at your command
1.0.76



OpenCode
The open source coding agent
1.2.24



pi ACP
ACP adapter for pi coding agent
0.0.22



Qoder CLI
AI coding assistant with agentic capabilities
0.1.30



Qwen Code
Alibaba's Qwen coding assistant
0.12.0



Stakpak
Open-source DevOps agent in Rust with enterprise-grade security
0.3.67

30+ Agents



Zed

Native ACP support with real-time editing, syntax highlighting, and agent following.



JetBrains

Full ACP integration coming soon to IntelliJ IDEA, PyCharm, and other JetBrains IDEs.

In Progress



Sidequery

Browser-based development environment with ACP support coming soon.



AionUi

Modern editor with integrated ACP support for seamless agent interaction.



Emacs

Agent-shell.el plugin brings ACP agents to Emacs through a native shell interface.



marimo

Python notebook environment with integrated ACP agent support for data science workflows.

Via Plugin



Neovim


Through two available plugins: CodeCompanion & yetone/avante.nvim.

Via Plugin



Obsidian

Bring your AI agents directly into Obsidian. Chat with Claude Code, Codex, and others from your vault.



aizen

Manage multiple Git branches simultaneously with dedicated terminals and agents in parallel.



DeepChat


A feature-rich open-source AI chat platform supporting multiple cloud and local LLMs.



Tidewave

The coding agent for full-stack web app development. Integrate agents with your web app at every layer.

Via AI SDK Adapter




Web Browser

AI SDK-powered browser client with ACP support via @mcpc/acp-ai-provider.

40+ Clients

Your coding agent knows your code. Now it knows your web app too.

Connect Claude Code, Codex, or Copilot to your running app: database, logs, and live UI. Point to any element to reference it. Your agent sees what you see.

[↓ Install Tidewave](#)[🗨️ Join our Discord](#)



Q Search...



Get Started

Introduction

Architecture

Agents

Clients

ACP Registry

Protocol

Overview

Initialization

Session Setup

Session List

Prompt Turn

Content

Tool Calls

File System

Terminals

Agent Plan

Session Modes

Session Config Options

Protocol

RFDs

Community

Publications

Updates

Brand

Get Started

ACP Registry

Copy page



The easiest way to find and install ACP-compatible agents.

Overview

The ACP Registry is an easy way for developers to distribute their ACP-compatible agents to any client that speaks the protocol.

This is a curated set of agents, including only the ones that support authentication.

Visit [the registry repository on GitHub](#) to learn more about it.

Available Agents



Amp

ACP wrapper for Amp - the frontier coding agent

0.7.0





Auggie CLI

Augment Code's powerful software agent, backed by industry-leading context engine

0.18.1

Session History



The vision

Clients:

More choice for your users,
without custom integrations.

Agents:

Distribute your agent where
your users do their work.

Developers:

Use the best agent for the job
with tools you already love.

The future

**Work in progress,
short-term**


Auth support

Interactive login

Asking from ENV

Terminal as a backup plan

OAuth 2.0



Next Edit Suggestion

```
> public boolean isNew() { return this.id == null; }
```

Tab ▾ to complete Next Edit Suggestions powered by GitHub Copilot




```
public static void foo() { ~ Tab to complete 👍 🗨 no usages
```

```
    System.out.println("foo");
```

```
}
```

Enterprise registry

Tools > AI Assistant > Agents



Search agents...



GitHub Copilot v1.448.0

GitHub's AI pair programmer

GitHub ↗

Uninstall





Junie v888.117.0

AI Coding Agent by JetBrains

JetBrains ↗

Install

Remote agents



Keeping on par with TUI

MCP-style elicitation

Agenting-driven tasks follow ups

Skills completion & suggestion

Session management

delete/close

store/restore

fork/join

Async communication: steering & queuing

Telemetry

MCP over ACP

**What can we build
on top of standard
communication
patterns with agents?**

Spare parts

The registry

SDKs

TS / Rust / Kotlin / Java / Python

Go / Swift / Dart / .Net

Agentic frameworks

LangChain with deepagents

Koog

LlamaIndex

Thinkwell




Chat connectors

Slack

Discord

Telegram

Product examples





3

ignatovs_bot

bot

1

- richer per-status summaries instead of only supported/authRequired/methodNotFound/other
- protocolSignatures for session/new and the post-init methods
- consistencyChecks such as:
 - advertisedButMissing
 - worksButNotAdvertised
 - authBoundaryChanged
 - responseShapeChanged
- a Protocol Drift Warnings section in the markdown report

If you want to go further without auth

There are two additional options:

- **agent test mode**: a special env var that enables fake authenticated behavior in CI
- **reference/mock agents**: dedicated conformance targets to validate the probe engine itself

That still is not real auth, but it does let you validate post-auth protocol shape in a controlled way.



Message



issue comment or proposal text in English.

🔍 Search tasks



+ New Task

Running

🔄 Search config housekeeping 📄
Running quick format and l... +34 -0

🔄 Add search suggestions drop... 📄
Extend API for partial queri... +12 -0

🔄 Implement GET /search handler
Inspecting existing handlers...

Done

✅ Build SearchBox component
Done +242 -0

✅ Add /api/demo-search
Done +39 -0

Perform a search config housekeeping — keep existing indexes and add commented demo section for local testing

I'll help you perform housekeeping on the search-config.json file and add a commented demo section for local testing. Let me first examine the current config structure and then create a clean version with a demo section.

✓ Read `search-config.json`

Perfect! Now I have the complete search-config.json structure. Let me update my todo and create the cleaned up version with proper housekeeping and a demo section.

`search-config.json` +11 -0

Next, I'll make sure the new section doesn't break JSON parsing when comments are stripped. For that, I'll generate a quick Node validation script.

`validate-search-config.ts` +23 -0

Now let me run the script to confirm the config parses correctly:

✓ Successfully validated

Config looks good — now I'll run format and lint checks to confirm everything meets style rules.

▼ PLAN 3/4

- ✓ Read and parse current config structure
- ✓ Add commented demo section at the bottom
- ✓ Validate JSON after removing comments
- 🔄 Run quick format and lint checks

Follow-up on this task, @ for mentions, / for commands

+ | ✨ Sonnet 4 ▼

Ask Permission ▼





Post



Peter Steinberger

@steipete




acp subagents are lit

7:08 pm · 7 Mar 2026 · **44.5K** Views

Research

<https://symposium.dev>

niquola/agentic-workspace



Agent Client Protocol (ACP)

A protocol for connecting any editor to any agent

Verified

 127 followers  <https://agentclientprotocol.com/>

Follow

README .md



Agent/Client Protocol

Agent Client Protocol

The Agent Client Protocol (ACP) standardizes communication between *code editors* (interactive programs for viewing and editing source code) and *coding agents* (programs that use generative AI to autonomously modify code).

Learn more at agentclientprotocol.com.

Integrations

- [Schema](#)
- [Agents](#)
- [Clients](#)
- Official Libraries
 - Kotlin: [acp-kotlin](#) - Supports JVM, other targets are in progress
 - Python: [python-sdk](#) - See [examples](#)
 - Rust: [agent-client-protocol](#) - See [examples/agent.rs](#) and [examples/client.rs](#)
 - TypeScript: [@agentclientprotocol/sdk](#) - See [examples/](#)
- [Community Libraries](#)

 View as: **Public** ▼

You are viewing the README and pinned repositories as a public user.

[Get started with tasks](#) that most successful organizations complete.

Top discussions this past month

 **Support for questions and "wizards" like AskUserQuestionTool**
↑ 4  4 

 **Remote ACP Agents**
↑ 2  0 

 **How to "always approve" tool calls for specific MCP server**
↑ 1  0 

[View all discussions](#)

Top languages

● Rust ● MDX ● Java ● Kotlin

● TypeScript

Most used topics Manage

acp ai agent-client-protocol
agentclientprotocol agents



Requests for Dialog (RFDs)

Copy page

Our process for introducing changes to the protocol

A “Request for Dialog” (RFD) is ACP’s version of the RFC process. RFDs are the primary mechanism for proposing new features, collecting community input on an issue, and documenting design decisions.

When to write an RFD

You should consider writing an RFD if you intend to make a “substantial” change to ACP or its documentation. What constitutes a “substantial” change is evolving based on community norms and varies depending on what part of the ecosystem you are proposing to change.

Some changes do not require an RFD:

- Rephrasing, reorganizing or refactoring
- Addition or removal of warnings
- Additions that strictly improve objective, numerical quality criteria (speedup, better browser support)
- Fixing objectively incorrect behavior

The RFD Process

1. Propose by opening a PR

Fork the repo and copy `docs/rfds/TEMPLATE.md` to `docs/rfds/my-feature.md` (using kebab-case naming). The RFD can start minimal -just an elevator pitch and status quo are enough to begin dialog. Pull requests