

Package ‘FunCC’

May 11, 2020

Title Functional Cheng and Church Bi-clustering

Version 0.0.0.9000

Author Agostino Torti [aut, cre], Marta Galvani [aut, cre], Alessandra Menafoglio [aut], Simone Vantini[aut]

Description The FunCC package allows to apply the funCC algorithm to simultaneously cluster the rows and the columns of a data matrix whose inputs are functions.

Depends R (>= 3.5.1)

License GPL (>= 3)

Encoding UTF-8

LazyData true

RoxygenNote 7.0.2

Imports narray,
biclust,
reshape,
RColorBrewer,
ggplot2

R topics documented:

find_best_delta	2
funCCdata	3
funcc_biclust	3
funcc_show_bicluster_coverage	4
funcc_show_bicluster_dimension	5
funcc_show_bicluster_hscore	5
funcc_show_block_matrix	6
funcc_show_results	6
Index	8

find_best_delta

*Functional Cheng and Church Algorithm varying the delta value***Description**

The find_best_delta function evaluate the results of FunCC algorithm in terms of total H-score value, the number of obtained bi-clusters and the number of not assigned elements when varying the delta value

Usage

```
find_best_delta(
    fun_mat,
    delta_min,
    delta_max,
    num_delta = 10,
    template.type = "mean",
    theta = 1.5,
    number = 100,
    alpha = 0,
    beta = 0,
    const_alpha = F,
    const_beta = F,
    shift.alignement = F,
    shift.max = 0.1,
    max.iter.align = 100
)
```

Arguments

fun_mat	The data array (n x m x T) where each entry corresponds to the measure of one observation i, i=1,...,n, for a functional variable m, m=1,...,p, at point t, t=1,...,T
delta_min	scalar: Maximum value of the maximum of accepted score, should be a real value > 0
num_delta	integer: number of delta to be evaluated between delta_min and delta_max
template.type	character: type of template required. If template.type='mean' the template is evaluated as the average function, if template.type='medoid' the template is evaluated as the medoid function.
theta	scalar: Scaling factor should be a real value > 1
number	integer: Maximum number of iterations
alpha	binary: if alpha=1 row shift is allowed, if alpha=0 row shift is avoided
beta	binary: if beta=1 row shift is allowed, if beta=0 row shift is avoided
const_alpha	logical: indicates if row shift is contrained as constant
shift.alignement	logical: If shift.alignement=True the shift alignent is performed, if shift.alignement=False no alignment is performed
shift.max	scalar: shift.max controls the maximal allowed shift, at each iteration, in the alignment procedure with respect to the range of curve domains. t.max must be such that 0<shift.max<1

`max.iter.align` integer: maximum number of iteration in the alignment procedure
`const_b` logical: indicates if col shift is constrained as constant

Value

a dataframe containing for each evaluated delta: `Htot_sum` (the sum of totale H-score), `num_clust` (the number of found Bi-clusters), `not_assigned` (the number of not assigned elements)

funCCdata	<i>Simulated data</i>
-----------	-----------------------

Description

`funCC.data` is a functional dataset displaying block structure

Usage

```
data(funCCdata)
```

Format

An object of class array of dimension 30 x 7 x 240.

Examples

```
data(funCCdata)
```

funcc_biclust	<i>Functional Cheng and Church algorithm</i>
---------------	--

Description

The `funCC` algorithm allows to simultaneously cluster the rows and the columns of a data matrix where each entry of the matrix is a function or a time series

Usage

```
funcc_biclust(
  fun_mat,
  delta,
  theta = 1,
  template.type = "mean",
  number = 100,
  alpha = 0,
  beta = 0,
  const_alpha = F,
  const_beta = F,
  shift.alignement = F,
  shift.max = 0.1,
  max.iter.align = 100
)
```

Arguments

fun_mat	The data array (n x m x T) where each entry corresponds to the measure of one observation i, i=1,...,n, for a functional variable m, m=1,...,p, at point t, t=1,...,T
delta	scalar: Maximum of accepted score, should be a real value > 0
theta	scalar: Scaling factor should be a real value > 1
template.type	character: type of template required. If template.type='mean' the template is evaluated as the average function, if template.type='medoid' the template is evaluated as the medoid function.
number	integer: Maximum number of iteration
alpha	binary: if alpha=1 row shift is allowed, if alpha=0 row shift is avoided
beta	binary: if beta=1 row shift is allowed, if beta=0 row shift is avoided
const_alpha	logical: Indicates if row shift is constrained as constant.
shift.alignment	logical: If shift.alignment=True the shift alignment is performed, if shift.alignment=False no alignment is performed
shift.max	scalar: shift.max controls the maximal allowed shift, at each iteration, in the alignment procedure with respect to the range of curve domains. t.max must be such that 0<shift.max<1
max.iter.align	integer: maximum number of iteration in the alignment procedure
const_b	logical: Indicates if col shift is constrained as constant.

Value

a list of two elements containing respectively the Biclustresults and a dataframe containing the parameters setting of the algorithm

funcc_show_bicluster_coverage
plotting coverage of each bi-cluster

Description

funcc_show_bicluster_coverage graphically shows the coverage of each bi-cluster in terms of percentage of included functions

Usage

```
funcc_show_bicluster_coverage(
  fun_mat,
  res_input,
  not_assigned = T,
  max_coverage = 1
)
```

Arguments

fun_mat	The data array (n x m x T) where each entry corresponds to the measure of one observation i, i=1,...,n, for a functional variable m, m=1,...,p, at point t, t=1,...,T
res_input	An object produced by the funcc_biclust function
not_assigned	logical: if true also the cluster of not assigned elements is included
max_coverage	scalar: percentage of maximum cumulative coverage to be shown

Value

a figure representing for each bi-cluster the coverage in terms of percentage of included functions

funcc_show_bicluster_dimension
plotting dimensions of each bi-cluster

Description

funcc_show_bicluster_dimension graphically shows the dimensions of each bi-cluster (i.e. number of rows and columns)

Usage

```
funcc_show_bicluster_dimension(fun_mat, res_input)
```

Arguments

fun_mat	The data array (n x m x T) where each entry corresponds to the measure of one observation i, i=1,...,n, for a functional variable m, m=1,...,p, at point t, t=1,...,T
res_input	An object produced by the funcc_biclust function

Value

a figure representing the dimensions of each bi-cluster (i.e. number of rows and columns)

funcc_show_bicluster_hscore
plotting hscore of each bi-cluster on bicluster dimension

Description

funcc_show_bicluster_hscore graphically shows the hscore vs the dimension (i.e. number of rows and columns) of each bi-cluster

Usage

```
funcc_show_bicluster_hscore(fun_mat, res_input)
```

Arguments

fun_mat	The data array (n x m x T) where each entry corresponds to the measure of one observation i, i=1,...,n, for a functional variable m, m=1,...,p, at point t, t=1,...,T
res_input	An object produced by the funcc_biclust function

Value

a figure representing the dimensions of each bi-cluster (i.e. number of rows and columns)

funcc_show_block_matrix

Plotting co-clustering results of funCC on the data matrix

Description

funcc_show_block_matrix graphically shows the bi-clusters positions in the original data matrix

Usage

```
funcc_show_block_matrix(fun_mat, res_input)
```

Arguments

fun_mat	The data array (n x m x T) where each entry corresponds to the measure of one observation i, i=1,...,n, for a functional variable m, m=1,...,p, at point t, t=1,...,T
res_input	An object produced by the funcc_biclust function

Value

a figure representing the bi-clusters positions in the original data matrix

funcc_show_results

Plotting co-clustering results of funCC

Description

funcc_show_results graphically shows the results of the bi-clustering

Usage

```
funcc_show_results(fun_mat, res_input, only.mean = F, aligned = F, warping = F)
```

Arguments

fun_mat	The data array (n x m x T) where each entry corresponds to the measure of one observation i, i=1,...,n, for a functional variable m, m=1,...,p, at point t, t=1,...,T
res_input	An object produced by the funcc_biclust function
only.mean	logical: if True only the template functions for each bi-cluster is displayed
aligned	logical: if True the alignemd functions are displayed
warping	logical: if True also a figure representing the warping functions are displayed

Value

a figure representing each bi-cluster in terms of functions contained in it or templates

Index

*Topic **datasets**

funCCdata, [3](#)

find_best_delta, [2](#)

funcc_biclust, [3](#)

funcc_show_bicluster_coverage, [4](#)

funcc_show_bicluster_dimension, [5](#)

funcc_show_bicluster_hscore, [5](#)

funcc_show_block_matrix, [6](#)

funcc_show_results, [6](#)

funCCdata, [3](#)