

README

April 6, 2019

```
In [1]: from IPython.display import display, HTML
```

```
display(HTML(data="""
<style>
    div#notebook-container    { width: 40%; }
    div#menubar-container    { width: 65%; }
    div#maintoolbar-container { width: 99%; }
</style>
"""))
```

<IPython.core.display.HTML object>

0.0.1 LAURENT Thomas

M2 IA

Apprentissage


```
In [2]: from main import *
        from PlotBuilder import *
```

- 'yielding_pas' mean how many **rows** you learn between each tests process.
- The data is readed in cycle.
- During all testing process we add an other point on the plot graph.


```
In [3]: MAX_PLOT_X_PERCEPTRON = 100
        MAX_PLOT_X = 4500
```

```
iris_X, iris_y = Data.load_iris_data()
mushroom_X, mushroom_y = Data.load_mushroom_data()
spambase_X, spambase_y = Data.load_spambase_data()
```


```
In [4]: Plot_builder.y_repartition(iris_y, title="repartition of Iris \
        (-1=others, 1=Iris_versicolor)")
```



In [5]: `Plot_builder.y_repartition(mushroom_y, title="repartition of Mushrooms\`
`(-1=poisonous, 1=edible)")`




```
In [6]: Plot_builder.y_repartition(spambase_y, title="repartition of Spambase \
      (-1=spam, 1=not a spam)")
```




1 Perceptron


```
In [7]: perceptron = Algo(iris_X, iris_y, algo=Perceptron, yielding_pas=10)
      perceptron.do_all(nb_iterations=MAX_PLOT_X_PERCEPTRON, name="perceptron iris",
      max_x=MAX_PLOT_X_PERCEPTRON)
```



```
In [8]: perceptron = Algo(mushroom_X, mushroom_y, algo=Perceptron, yielding_pas=10)
        perceptron.do_all(nb_iterations=MAX_PLOT_X_PERCEPTRON,
                          name="perceptron mushroom", max_x=MAX_PLOT_X_PERCEPTRON)
```




```
In [9]: perceptron = Algo(spambase_X, spambase_y, algo=Perceptron, yielding_pas=10)
        perceptron.do_all(nb_iterations=MAX_PLOT_X_PERCEPTRON,
                          name="perceptron spambase", max_x=MAX_PLOT_X_PERCEPTRON)
```




2 Descent gradient


```
In [10]: gradient_descent = Algo(iris_X, iris_y, algo=GradientDescent,
                                   yielding_pas=10, gradient_eta=2)
        gradient_descent.do_all(nb_iterations=MAX_PLOT_X,
                                name="gradient descent iris", max_x=MAX_PLOT_X)
```



```
In [11]: gradient_descent = Algo(mushroom_X, mushroom_y, algo=GradientDescent,  
                                yielding_pas=10, gradient_eta=2)  
gradient_descent.do_all(nb_iterations=MAX_PLOT_X,  
                        name="gradient descent mushroom", max_x=MAX_PLOT_X)
```






```
In [12]: gradient_descent = Algo(spambase_X, spambase_y, algo=GradientDescent,  
                                yielding_pas=10, gradient_eta=2)  
gradient_descent.do_all(nb_iterations=MAX_PLOT_X,  
                        name="gradient descent spambase", max_x=MAX_PLOT_X)
```





3 searching for best ETA


```
In [15]: for eta in [-1000,1,-1000]:
          gradient_descent = Algo(mushroom_X, mushroom_y,
                                algo=GradientDescent, yielding_pas=10,
                                gradient_eta=eta)
          gradient_descent.do_all(nb_iterations=MAX_PLOT_X,
                                name="gradient descent mushroom",
                                max_x=MAX_PLOT_X)
```



```
In [16]: for eta in [-1000,1,1000]:  
    gradient_descent = Algo(spambase_X, spambase_y, algo=GradientDescent,  
                           yielding_pas=10, gradient_eta=eta)  
    gradient_descent.do_all(nb_iterations=MAX_PLOT_X,  
                           name="gradient descent mushroom",  
                           max_x=MAX_PLOT_X)
```





Nothing change, i tried to test with $\eta = (0.7, 0.2, -0.2, -0.07)$ and $\text{range}(1, 10000, 100)$