

Untitled

March 27, 2019

```
In [1]: from main import *  
        from PlotBuilder import *
```

- 'yielding_pas' mean how many **rows** you learn between each testing process.


the data is readed in cycle.

during all testing process we add an other point on the plot graph.


```
In [2]: MAX_PLOT_X_PERCEPTRON = 100  
        MAX_PLOT_X = 4500
```

```
iris_X, iris_y = Data.load_iris_data()  
mushroom_X, mushroom_y = Data.load_mushroom_data()  
spambase_X, spambase_y = Data.load_spambase_data()
```


```
In [3]: Plot_builder.y_repartition(iris_y, title="repartition of Iris (-1=others, 1=Iris_versicolor)
```



```
In [4]: Plot_builder.y_repartition(mushroom_y, title="repartition of Mushrooms (-1=poisonous, 1=edible),
```




```
In [5]: Plot_builder.y_repartition(spambase_y, title="repartition of Spambase (-1=spam, 1=not a spam),
```




1 Perceptron


```
In [6]: perceptron = Algo(iris_X, iris_y, algo=Perceptron, yielding_pas=10)
        perceptron.do_all(nb_iterations=MAX_PLOT_X_PERCEPTRON, name="perceptron iris", max_x=MAX_PLOT_X_PERCEPTRON)
```



```
In [7]: perceptron = Algo(mushroom_X, mushroom_y, algo=Perceptron, yielding_pas=10)
        perceptron.do_all(nb_iterations=MAX_PLOT_X_PERCEPTRON,name="perceptron mushroom", max_
```




```
In [8]: perceptron = Algo(spambase_X, spambase_y, algo=Perceptron, yielding_pas=10)
        perceptron.do_all(nb_iterations=MAX_PLOT_X_PERCEPTRON,name="perceptron spambase", max_x=MAX_PLOT_X)
```




2 Descent gradient


```
In [9]: gradient_descent = Algo(iris_X, iris_y, algo=GradientDescent, yielding_pas=10, gradient_descent)
        gradient_descent.do_all(nb_iterations=MAX_PLOT_X,name="gradient descent iris", max_x=MAX_PLOT_X)
```



```
In [10]: gradient_descent = Algo(mushroom_X, mushroom_y, algo=GradientDescent, yielding_pas=10)
gradient_descent.do_all(nb_iterations=MAX_PLOT_X,name="gradient descent mushroom", max
```







```
In [11]: gradient_descent = Algo(spambase_X, spambase_y, algo=GradientDescent, yielding_pas=10)
        gradient_descent.do_all(nb_iterations=MAX_PLOT_X,name="gradient descent spambase", ma
```




3 searching for best ETA

```
In [15]: for eta in range(100,1000,200):
        gradient_descent = Algo(mushroom_X, mushroom_y, algo=GradientDescent, yielding_pa
        gradient_descent.do_all(nb_iterations=MAX_PLOT_X,name="gradient descent mushroom"
```











3.1 notting change



```
In [18]: for eta in [-1000,-500,-100]:  
    gradient_descent = Algo(mushroom_X, mushroom_y, algo=GradientDescent, yielding_pa  
    gradient_descent.do_all(nb_iterations=MAX_PLOT_X,name="gradient descent mushroom")
```






```
In [19]: for eta in [0.2, 0.8, -0.3, -0.7]:
          gradient_descent = Algo(mushroom_X, mushroom_y, algo=GradientDescent, yielding_pa
          gradient_descent.do_all(nb_iterations=MAX_PLOT_X,name="gradient descent mushroom")
```







Still the same.