Example SyntaxColorizing: All script steps and all options

```
## NEVER run the contents of this script!
Exit Script [ ]
## Doc
If [ 1 ]
    #@purpose: The primary purpose of this script is to provide a test bed for script steps. It contains every script step with more or less every combination of possible parameters.
    #@author: @mrwatson-de

    #It is specifically used by @mrwatson-de to check the output of fmCheckMate's Print Script Step XSLT transformation function (which converts a FileMaker clipboard script or script step fmxmlsnippet to FileMaker script text)

    #It is also available in @mirslavkos's Ooe-fm (One of Everything FileMaker) file as a test bed for SaXML & co.

    #To test fmCheckMate's Print Script Step XSLT transformation you need

    #- the latest version of FileMaker Pro
    #- this script (from Ooe-fm or fmSyntaxColorizer)
    #- fmWorkMate
    #- fmCheckMate-XSLT
    #- BaseElements plugin
    #- MBS plugin
    #- a Mac

    #Setup the test environment needed to test the Print Script Step XSLT transformation

    #1. Download and setup FileMaker Pro
    #2. Download and setup BaseElements plugin
    #   - Setup:
    #     - install plugin
    #3. Download and setup MBS plugin
    #   - Setup:
    #     - install plugin
    #     - licence, if necessary
    #4. Download and setup fmWorkMate
    #   - Setup:
    #     - move the fmWorkMate folder to Applications folder
    #     - rename folder to just `fmWorkMate`, if necessary
    #5. Download and setup the fmCheckMate-XSLT Library
    #   - Setup:
    #     - move the fmCheckMate-XSLT folder to the **Documents** folder
    #     - rename folder to just `fmCheckMate`
    #6. Download and setup fmSyntaxColorizer
    #   - Setup:
    #     - move the fmSyntaxColorizer folder next to the fmWorkMate folder
    #     - rename folder to just `fmSyntaxColorizer`, if necessary

    #Method to test fmCheckMate's Print Script Step XSLT transformation

    #1. Prepare the test environment as above
    #2. Diff the function results with the actual script text
    #   a. Open fmSyntaxColorizer (or Ooe-fm) and copy all steps from this script (CMD+A, CMD+C)
    #   b. Open fmWorkMate > fmTextDiff and add the clipboard contents to the diff (CMD+7, CMD+7)
    #   c. Return to fmSyntaxColorizer and copy the selected step text (Right Click > Copy Selected // MBS function)
    #   d. In fmTextDiff add the clipboard contents to the diff (CMD+7)
    #3. Inspect the results
    #   - Only difference's should be
```

- empty comment steps (because MBS shows empty lines as `#` instead of ``)

- documented steps that contain internal state not available on the clipboard

#20250815 @mrwatson-de Update started for FM22

#20250630 @mrwatson-de Updated for FM21

#20170516 MrW Script sorted alphabetically within categories for fm16

End If

Vars

If [1]

#@var $$fjhsd.gfd.jhsgf.dshg.fshgf $abc $AccountName $AudioPath $BaseModel $BCC $BeaconName $Body $calculation $CC $Code $Command $container $continuous $cURL_Options

#@var $data $DataSource $date $DefaultLocation $Delay $DlgMessage $DlgTitle $Endpoint $Ersetzen

#@var $FensterBreite $FensterHoehe $FensterLinks $FensterName $FensterNameAlt $FensterNameNeu $FensterOben $FieldName $file $FileContents $FileExists $FileID $FilePath $FileSize $FolderPath $format

#@var $i $InputFile $JSONOptions $KeineSourceVar $yKontoname $Latitude $LayoutName $LayoutNr $LayoutNumber $Longitude

#@var $Major $MBS_Command_Results $Message $Minor $Model $MoreComplexName $MyRagAccount $MySecretApiKey $n $name $Name $Nr $number $Objektname

#@var $p1 $P1 $p2 $P2 $P3 $P4 $Param $Parameters $Passwort $Path $Path1 $PathXML $PathXSL $PathXSLT $PdfPath $Pos $price $Prompt $PromptTemplateName $Radius $RagAcccount $RecordIDs $Rep $ResponseTarget

#@var $ScriptParameter $ScriptResult $Secret $source $SourceFile $SourceFileName $SourceURL $SourceVar $SpaceID $Subject $Suchen $Target $TargetDump $TargetFileContents $TargetVar $TargetWebContent $TemplateName $test $text $time $timeout $timestamp $Title $To $TrainingDataFilePath

#@var $UpdatedModel $url $UserPrompt $UseSetVariable $UUID $var $Volume $WebContent $window $windowname

Set Variable [$FileID; Value:""]

Set Variable [$FileExists; Value:""]

Set Variable [$FileSize; Value:""]

Set Variable [$PathXSLT; Value:""]

Set Variable [$target; Value:""]

Set Variable [$data; Value:""]

Set Variable [$pos; Value:""]

Set Variable [$window; Value:""]

Set Variable [$name; Value:""]

Set Variable [$windowname; Value:""]

Set Variable [$Parameters; Value:""]

Set Variable [$secret; Value:""]

End If

Control

If [1]

Allow User Abort [On]

Allow User Abort [Off]

#Commit Transaction - see Open Transaction

Configure Local Notification [Action: Queue]

Configure Local Notification [Action: Clear]

Configure Local Notification [Action: Clear; Name: "Name"]

Configure Local Notification [Action: Queue; Name: $Name]

Configure Local Notification [Action: Queue; Script: “Hello world”; Name: $Name]

Configure Local Notification [Action: Queue; Script: “Hello world”; Parameter: $Param; Name: $Name]

Configure Local Notification [Action: Queue; Script: “Hello world”; Name: $Name; Delay: $Delay]

Configure Local Notification [Action: Queue; Script: “Hello world”; Name: $Name; Delay: $Delay; Title: $Title]

Configure Local Notification [Action: Queue; Script: “Hello world”; Name: $Name; Delay: $Delay; Title: $Title; Body: $Body]

Configure Local Notification [Action: Queue; Script: “Hello world”; Name: $Name; Delay: $Delay; Title: $Title; Body: $Body; Button 1 Label: "Button 1 label"]

Configure Local Notification [Action: Queue; Script: “Hello world”; Name: $Name; Delay: $Delay; Title: $Title; Body: $Body; Button 1 Label: "Button 1 label"; Button 2 Label: "Button 2 label"]

Configure Local Notification [Action: Queue; Script: “Hello world”; Name: $Name; Delay: $Delay; Title: $Title; Body: $Body; Button 1 Label: "Button 1 label"; Button 2 Label: "Button 2 label"; Button 3 Label: "Button 3 label"]

Configure Local Notification [Action: Queue; Script: “Hello world”; Name: $Name; Delay: $Delay; Title: $Title; Body: $Body; Button 1 Label: "Button 1 label"; Button 2 Label: "Button 2 label"; Button 3 Label: "Button 3 label"; Button 1 Foreground: "Button 1 foreground"]

Configure Local Notification [Action: Queue; Script: “Hello world”; Name: $Name; Delay: $Delay; Title: $Title; Body: $Body; Button 1 Label: "Button 1 label"; Button 2 Label: "Button 2 label"; Button 3 Label: "Button 3 label"; Button 1 Foreground: "Button 1 foreground"; Button 2 Foreground: "Button 2 foreground"]

Configure Local Notification [Action: Queue; Script: “Hello world”; Name: $Name; Delay: $Delay; Title: $Title; Body: $Body; Button 1 Label: "Button 1 label"; Button 2 Label: "Button 2 label"; Button 3 Label: "Button 3 label"; Button 1 Foreground: "Button 1 foreground"; Button 2 Foreground: "Button 2 foreground"; Button 3 Foreground: "Button 3 foreground"]

Configure Local Notification [Action: Queue; Script: “Hello world”; Name: $Name; Delay: $Delay; Title: $Title; Body: $Body; Button 1 Label: "Button 1 label"; Button 2 Label: "Button 2 label"; Button 3 Label: "Button 3 label"; Button 1 Foreground: "Button 1 foreground"; Button 2 Foreground: "Button 2 foreground"; Button 3 Foreground: "Button 3 foreground"; Show when app in foreground: True]

Configure Local Notification [Action: Queue; Script: “Hello world”; Name: $Name; Delay: $Delay; Title: $Title; Body: $Body; Button 1 Foreground: "Button 1 foreground"; Button 2 Foreground: "Button 2 foreground"; Button 3 Foreground: "Button 3 foreground"; Show when app in foreground: True]

Configure Local Notification [Action: Queue; Script: “Hello world”; Name: $Name; Delay: $Delay; Title: $Title; Body: $Body; Button 1 Foreground: "Button 1 foreground"; Button 2 Foreground: "Button 2 foreground"; Button 3 Foreground: "Button 3 foreground"; Show when app in foreground: True]

Configure NFC Reading [Action: Cancel]

Configure NFC Reading [Action: Read]

Configure NFC Reading [Action: Read; Script: “Hello world”]

Configure NFC Reading [Action: Read; Script: “Hello world”; Timeout: $Timeout]

Configure NFC Reading [Action: Read; Script: “Hello world”; Timeout: $Timeout; Continuous Reading: $Continuous]

Configure NFC Reading [Action: Read; Script: “Hello world”; Parameter: $Param; Timeout: $Timeout; Continuous Reading: $Continuous; Format Result as JSON: $format]

Configure NFC Reading [Action: Read; Script: “Hello world”; Format Result as JSON: $Format]

Configure NFC Reading [Action: Read; Timeout: $timeout; Continuous Reading: $continuous; Format Result as JSON: $Format]

Configure NFC Reading [Action: Read; Continuous Reading: $Continuous; Format Result as JSON: $Format]

Configure NFC Reading [Action: Read; Format Result as JSON: $Format]

Configure NFC Reading [Action: Read]

Configure NFC Reading [Action: Read; Script: “Hello world”; Format Result as JSON: $Format]

Configure Region Monitor Script [Monitor: iBeacon]

Configure Region Monitor Script [Monitor: iBeacon; Name: "foobar"]

Configure Region Monitor Script [Monitor: iBeacon; Name: "foobar"; UUID: $UUID]

Configure Region Monitor Script [Monitor: iBeacon; UUID: $UUID]

Configure Region Monitor Script [Monitor: iBeacon; Script: “Hello world” from file: “Self”; Parameter: 1; Name: $BeaconName; UUID: $UUID; Major: $Major; Minor: $Minor]

Configure Region Monitor Script [Monitor: iBeacon; Script: “Hello world” from file: “Self”; Parameter: 1; Name: $BeaconName; UUID: $UUID]

Configure Region Monitor Script [Monitor: iBeacon; Script: “Hello world” from file: “Self”; Parameter: 1; Name: 123; UUID: $UUID]

Configure Region Monitor Script [Monitor: Geofence; Script: “Hello world”; Parameter: 1; Name: $BeaconName; Latitude: $Latitude; Longitude: $Longitude; Radius: $Radius]

If [1=0]
Else If [1=1]
    If [ ]
    Else If [ ]
    End If
Else [ ]
End If

Exit Script [ ]
Exit Script [Result: $ScriptResult]
Exit Script [Result: "nix"]

Halt Script

Install OnTimer Script [ ]
Install OnTimer Script [“<unknown>”; Interval: 123]
Install OnTimer Script [“All script steps sorted by category”; $Param; Interval: 1+2]

Loop [Flush: Always]
    Exit Loop If [1=1]
    Loop [Flush: Defer]
        Exit Loop If [1=1]
        Loop [Flush: Minimum]
            Exit Loop If [1=1]
        End Loop
    End Loop
End Loop

Open Transaction [ ]
    Revert Transaction [Condition: 1=1; Error Code: 5000; Error Message: "Broken"]
Commit Transaction
Open Transaction [ ]
    [Skip data entry validation]
    Revert Transaction [Condition: 1=1; Error Code: 5000]
    Revert Transaction [Condition: 1=1; Error Code: 5000]
    Revert Transaction [Condition: 1=1]
Commit Transaction
Open Transaction [ ]
    [Override ESS locking conflicts]
    Revert Transaction [Error Code: 5000; Error Message: "Broken"]
Commit Transaction
Open Transaction [ ]
    [Skip data entry validation; Override ESS locking conflicts]
    Revert Transaction [Condition: 1=1; Error Code: 1; Error Message: "Broken"]
Commit Transaction
Open Transaction [ ]
    [Skip data entry validation; Skip auto-enter options; Override ESS locking conflicts]
Commit Transaction

Pause/Resume Script [Indefinitely]
Pause/Resume Script [Duration (seconds): 1]

Perform Script [“All script steps sorted by category”]

Perform Script [<unknown>]
Perform Script [“All script steps sorted by category”; Parameter: $ScriptParameter]
Perform Script [By name; "All script steps and all options"; Parameter: $ScriptParameter]
Perform Script [<unknown> from file: “” (file not open)]
#Two error cases for fmSyntaxColorizer:
Perform Script [“All script steps sorted by category”; Parameter: /* commented out */]
Perform Script [“All script steps sorted by category”; Parameter: "/* not only commented out, but also stringified! */"]

Perform Script on Server [<unknown>]
[Wait for completion]

Perform Script on Server [<unknown>]

Perform Script on Server with Callback [<unknown>; Callback script: <unknown>; State: “Continue”]

Perform Script on Server with Callback [“<unknown>”; Callback script: <unknown>; State: “Continue”]

Perform Script on Server with Callback [“A typical script”; Callback script: <unknown>; State: “Continue”]

Perform Script on Server with Callback [“A typical script” from file: “Self”; Callback script: <unknown>; State: “Continue”]

Perform Script on Server with Callback [“A typical script”; Parameter: "Param"; Callback script: “Undefined variables”; Parameter: "Param"; State: “Continue”]

Perform Script on Server with Callback [“A typical script” from file: “Self”; Parameter: "ParamOver"; Callback script: “Undefined variables” from file: “Self”; Parameter: "ParamBack"; State: “Continue”]

Perform Script on Server with Callback [“A typical script”; Parameter: "Param"; Callback script: “Undefined variables”; Parameter: "Param"; State: “Continue”]

Perform Script on Server with Callback [“A typical script”; Parameter: "Param"; Callback script: “All script steps and all options” from file: “Self”; Parameter: "Param"; State: “Continue”]

#Revert Transaction - see Open Transaction

Set Error Capture [On]

Set Error Capture [Off]

Set Error Logging [On ; Custom debug info:]

Set Error Logging [Off ; Custom debug info:]

Set Error Logging [On ; Custom debug info: Get (CurrentHostTimestamp)]

Set Layout Object Animation [On]

Set Layout Object Animation [Off]

Set Revert Transaction on Error [Off]

Set Revert Transaction on Error [On]

Set Variable [ ]

Set Variable [$var]

Set Variable [$var; Value:<Function Missing>(2) + 4]

Set Variable [$var; Value:1+Test(1) & "string" & ($$fjhsd.gfd.jhsgf.dshg.fshgf)]

Set Variable [$MBS_Command_Results; Value:Let(
[

$text = TestTable::TextField1 ;
$number = TestTable::NumberField1 ;
$date = TestTable::DateField1;
$time = TestTable::TimeField1;
$timestamp = TestTable::TimestampField1 ;
$container = TestTable::ContainerField1 ;
$calculation = TestTable::CalcField1_c ;
$summary = TestTable::SummaryField1

];

List(
$text ;
$number ;
$date ;
$time ;
$timestamp ;
$container ;
$calculation ;

```
        $summary
        )

        ) ]


    Trigger Claris Connect Flow [  Flow: MrWatsonWebhook ; JSON Data: JSONSetElement ( ""
    ; ["whatever" ; "foo" ; JSONString]
    ; ["whatever" ; "bar" ; JSONString]
    ; ["whatever" ; "baz" ; JSONString]
    ; ["whatever" ; "too much" ; JSONString]
    ) ; URL: "https://bmi8au.apps.connect.claris.com/api/webhook/v1/mrwatsonwebhook/catch" ; AppID:APIKey for Webhooks:    ;
        Target: $Target ]
    Trigger Claris Connect Flow [  Flow: <unknown> ; JSON Data: JSONSetElement ( "" ; "whatever" ; "foo" ; JSONString ) ;
        URL:    ; AppID:APIKey for Webhooks: $APIKEY ; Target: $Target ]
    Trigger Claris Connect Flow [  Flow: <unknown> ; JSON Data: JSONSetElement ( "" ; "whatever" ; "foo" ; JSONString ) ;
        URL:    ; AppID:APIKey for Webhooks: $APIKEY ; Target: $Target ]
    Trigger Claris Connect Flow [  Flow: <unknown> ; JSON Data: JSONSetElement ( "" ; "whatever" ; "foo" ; JSONString ) ;
        URL:    ; AppID:APIKey for Webhooks: $appIdKey ; Target: TestTable::TextField1 ]
End If
## Navigation
If [ 1 ]
    Close Popover


    Enter Browse Mode
        [ Pause ]
    Enter Browse Mode


    Enter Find Mode [  ]
        [ Pause ]
    Enter Find Mode [  ]
    Enter Find Mode [ Specified Find Requests: Find Records; Criteria: TestTable::TextField1: “ScriptStep” AND TestTable::
    TextField_lotsTurnedOn: “1”
        Omit Records; Criteria: TestTable_Contacts::ID: “*” ]
        [ Restore; Pause ]


    Enter Preview Mode
        [ Pause ]
    Enter Preview Mode


    Go to Field [ <Table Missing> ]
    Go to Field [ <Table Missing> ]
        [ Select/perform ]
    Go to Field [  ]
        [ Select/perform ]
    Go to Field [ <Table Missing>[2+3] ]
    Go to Field [ <Table Missing> ]


    Go to Layout [ original layout ]
    Go to Layout [ $LayoutName ]
    Go to Layout [ $LayoutNumber ]
    Go to Layout [ "Test" ]
    Go to Layout [ “File Open” (_Home) ]
    Go to Layout [ “File Open” (_Home); Animation: Slide in from Left ]
    Go to Layout [ “File Open” (_Home); Animation: Slide in from Right ]
    Go to Layout [ “File Open” (_Home); Animation: Slide in from Bottom ]
    Go to Layout [ “File Open” (_Home); Animation: Slide out to Left ]
    Go to Layout [ “File Open” (_Home); Animation: Slide out to Right ]
    Go to Layout [ “File Open” (_Home); Animation: Slide out to Bottom ]
```

Go to Layout [“File Open” (_Home); Animation: Flip from Left]
Go to Layout [“File Open” (_Home); Animation: Flip from Right]
Go to Layout [“File Open” (_Home); Animation: Zoom In]
Go to Layout [“File Open” (_Home); Animation: Zoom Out]
Go to Layout [“File Open” (_Home); Animation: Cross Dissolve]

#Some error cases for fmSyntaxColorizer
Go to Layout [<unknown>]
Go to Layout [<Function Missing>]
Go to Layout [/*cf_LayoutName*/]
#and undefined variables
Go to Layout [$LayoutName]
Go to Layout [$LayoutNr]

#FM22
Go to List of Records [Using layout: <Current Layout>]
Go to List of Records [List of record IDs:$RecordIDs; Using layout: <Current Layout>]
Go to List of Records [List of record IDs:$RecordIDs; Using layout: “My Layout for TestTable” (TestTable)]
Go to List of Records [List of record IDs:$RecordIDs; Using layout: “My Layout for TestTable” (TestTable); Animation: Slide in from Left]
Go to List of Records [List of record IDs:$RecordIDs; Using layout: “My Layout for TestTable” (TestTable); Animation: Slide in from Right]
Go to List of Records [List of record IDs:$RecordIDs; Using layout: “My Layout for TestTable” (TestTable); Animation: Slide in from Bottom]
Go to List of Records [List of record IDs:$RecordIDs; Using layout: “My Layout for TestTable” (TestTable); Animation: Slide out to Left]
Go to List of Records [List of record IDs:$RecordIDs; Using layout: “My Layout for TestTable” (TestTable); Animation: Slide out to Right]
Go to List of Records [List of record IDs:$RecordIDs; Using layout: “My Layout for TestTable” (TestTable); Animation: Slide out to Bottom]
Go to List of Records [List of record IDs:$RecordIDs; Using layout: “My Layout for TestTable” (TestTable); Animation: Flip from Left]
Go to List of Records [List of record IDs:$RecordIDs; Using layout: “My Layout for TestTable” (TestTable); Animation: Flip from Right]
Go to List of Records [List of record IDs:$RecordIDs; Using layout: “My Layout for TestTable” (TestTable); Animation: Zoom In]
Go to List of Records [List of record IDs:$RecordIDs; Using layout: “My Layout for TestTable” (TestTable); Animation: Zoom Out]
Go to List of Records [List of record IDs:$RecordIDs; Using layout: “My Layout for TestTable” (TestTable); Animation: Cross Dissolve]
Go to List of Records [List of record IDs:$RecordIDs; Using layout: “My Layout for TestTable” (TestTable)]
[New window]
Go to List of Records [List of record IDs:$RecordIDs; Using layout: $LayoutNumber]
Go to List of Records [List of record IDs:$RecordIDs; Using layout: $LayoutName]
Go to List of Records [List of record IDs:$RecordIDs; Using layout: $LayoutName]
[New window]
Go to List of Records [List of record IDs:$RecordIDs; Using layout: $LayoutName]
[New window]
Go to List of Records [List of record IDs:$RecordIDs; Using layout: $LayoutName]
[New window]
Go to List of Records [List of record IDs:$RecordIDs; Using layout: $LayoutName]
[New window]
#/FM22

Go to Next Field

Go to Object [Repetition: 1]

Go to Object [Object Name: "RepField"; Repetition: $Rep]

Go to Object [Object Name: $Objektname; Repetition: 1]

Go to Portal Row
[Select; First]

Go to Portal Row
[Last]

Go to Portal Row
[Previous; Exit after last]

Go to Portal Row
[Previous]

Go to Portal Row
[Next; Exit after last]

Go to Portal Row
[Next]

Go to Portal Row [$abc]

Go to Portal Row [Get(CurrentDate)]

Go to Portal Row [1+1]
[No dialog]

Go to Previous Field

Go to Record/Request/Page
[First]

Go to Record/Request/Page
[Last]

Go to Record/Request/Page
[Previous; Exit after last]

Go to Record/Request/Page
[Previous]

Go to Record/Request/Page
[Next; Exit after last]

Go to Record/Request/Page
[Next]

Go to Record/Request/Page [1+1]
[No dialog]

Go to Record/Request/Page [Get(LayoutNumber) + 1]
[No dialog]

Go to Record/Request/Page [$Nr]

#Some error cases for fmSyntaxColorizer

Go to Record/Request/Page [<Function Missing> + 1]

Go to Record/Request/Page [/*cf_LayoutNumber + 1*/]

Go to Related Record [From table: “TestTable”; Using layout: <Current Layout>]

Go to Related Record [From table: “TestTable”; Using layout: <Current Layout>]
[Show only related records]

Go to Related Record [From table: “TestTable_Contacts”; Using layout: <Current Layout>]
[Show only related records]

Go to Related Record [From table: “TestTable”; Using layout: “My Layout for TestTable” (TestTable)]
[Show only related records]

Go to Related Record [From table: “TestTable”; Using layout: “My Layout for TestTable” (TestTable); Animation: Slide in from Left]
[Show only related records]

Go to Related Record [From table: “TestTable”; Using layout: “My Layout for TestTable” (TestTable); Animation: Slide in from Right]
[Show only related records]

Go to Related Record [From table: “TestTable”; Using layout: “My Layout for TestTable” (TestTable); Animation: Slide in from Bottom]
[Show only related records]

Go to Related Record [From table: “TestTable”; Using layout: “My Layout for TestTable” (TestTable); Animation: Slide out to Left]
[Show only related records]

Go to Related Record [From table: “TestTable”; Using layout: “My Layout for TestTable” (TestTable); Animation: Slide out to Right]
[Show only related records]

Go to Related Record [From table: “TestTable”; Using layout: “My Layout for TestTable” (TestTable); Animation: Slide out to Bottom]
[Show only related records]

Go to Related Record [From table: “TestTable”; Using layout: “My Layout for TestTable” (TestTable); Animation: Flip from Left]
[Show only related records]

Go to Related Record [From table: “TestTable”; Using layout: “My Layout for TestTable” (TestTable); Animation: Flip from Right]
[Show only related records]

Go to Related Record [From table: “TestTable”; Using layout: “My Layout for TestTable” (TestTable); Animation: Zoom In]
[Show only related records]

Go to Related Record [From table: “TestTable”; Using layout: “My Layout for TestTable” (TestTable); Animation: Zoom Out]
[Show only related records]

Go to Related Record [From table: “TestTable”; Using layout: “My Layout for TestTable” (TestTable); Animation: Cross Dissolve]
[Show only related records]

Go to Related Record [From table: “TestTable_Contacts”; Using layout: “Contacts” (Contacts)]
[Show only related records; Match found set; New window]

Go to Related Record [From table: “TestTable_Contacts”; Using layout: “Contacts” (Contacts)]
[Show only related records; Match found set; New window]

Go to Related Record [From table: “TestTable_Contacts”; Using layout: “Contacts” (Contacts)]
[Show only related records; Match found set; New window]

Go to Related Record [From table: “TestTable_Ooe”; External; Using layout: “My Layout for TestTable” (TestTable)]
[Show only related records; Match found set; New window]

Go to Related Record [From table: <unknown>; Using layout: <unknown>]
[Show only related records]

End If

Editing

If [1]

Clear [ ]
[Select]

Clear [<Table Missing>]
[Select]

Clear [TestTable::TextField1]

Clear [TestTable::ID]
[Select]

Copy [ ]
[Select]

Copy [<Table Missing>]
[Select]

Cut [ ]
[Select]

Cut [<Table Missing>]

#FM21 Bug: No style is reversed

Paste [ ]
[Select; No style]

Paste [ ]
[Select]

Paste [<Table Missing>]
[Select]

Paste [<Table Missing>]
[Select; No style]

Paste [TestTable::NumberField1[$Rep]]

Paste [TestTable::TextField1[$Rep]]
[No style]

Perform Find/Replace [Search operation: Find Next; Search settings: Forward; Search across: All records/requests; Search within: All fields]

Perform Find/Replace [Search operation: Find Next; Search settings: Forward; Search across: All records/requests; Search within: All fields]
[No dialog]

Perform Find/Replace [Find: $Suchen; Replace: $Ersetzen; Search operation: Replace; Search settings: All, Match case, Match whole words only; Search across: All records/requests; Search within: All fields]

Perform Find/Replace [Find: $Suchen; Replace: $Ersetzen; Search operation: Find Next; Search settings: Backward, Match case, Match whole words only; Search across: Current record/request; Search within: Current field]
[No dialog]

Perform Find/Replace [Find: $Suchen; Replace: $Ersetzen; Search operation: Replace & Find; Search settings: All, Match case, Match whole words only; Search across: All records/requests; Search within: All fields]
[No dialog]

Perform Find/Replace [Find: $Suchen; Replace: $Ersetzen; Search operation: Replace All; Search settings: All, Match case, Match whole words only; Search across: All records/requests; Search within: All fields]
[No dialog]

Select All

Set Selection [<Table Missing>; Start Position1; End Position12]

Undo/Redo
[Toggle]

Undo/Redo
[Undo]

Undo/Redo
[Redo]

End If

Fields

If [1]

Export Field Contents [Create folders:No]

Export Field Contents [TestTable::ContainerField1; Create folders:No]

Export Field Contents [<Table Missing>; “file:file.txt”; Automatically open; Create email; Create folders:No]

Export Field Contents [“file:file.txt”; Automatically open; Create email; Create folders:No]

Insert Audio/Video [ ]

Insert Audio/Video [“$AudioPath”]
[Reference]

Insert Audio/Video [“$AudioPath”]

#Extended in fm16: TARGET = VARIABLE

Insert Calculated Result [ ]

Insert Calculated Result [$TargetVar]

Insert Calculated Result [$SourceVar]

Insert Calculated Result [$TargetVar; $SourceVar]

Insert Calculated Result [$TargetVar]
[Select]

Insert Calculated Result [$SourceVar]
[Select]

Insert Calculated Result [$TargetVar; $SourceVar]
[Select]

Insert Calculated Result [$TargetVar; "Value"]
[Select]

Insert Calculated Result [TestTable::MyGlobal_g; TestTable::ContactNameList_u]

[Select]

Insert Calculated Result [TestTable::TextField1; "hello"]
[Select]

Insert Calculated Result [<Table Missing>; 1+2]
[Select]

Insert Calculated Result [$Target]
[Select]

Insert Calculated Result [$UseSetVariable; "Value"]
[Select]

Insert Current Date [ ]

Insert Current Date [ ]
[Select]

Insert Current Date [$UseSetVariable]

Insert Current Date [$UseSetVariable]
[Select]

Insert Current Date [TestTable::MyGlobal_g]
[Select]

Insert Current Date [$UseSetVariable]
[Select]

Insert Current Time [ ]

Insert Current Time [ ]
[Select]

Insert Current Time [$UseSetVariable]

Insert Current Time [$UseSetVariable]
[Select]

Insert Current Time [TestTable::MyGlobal_g[$Rep]]
[Select]

Insert Current Time [$UseSetVariable]
[Select]

Insert Current User Name [$UseSetVariable]
[Select]

Insert Current User Name [TestTable::TimeField1]
[Select]

Insert Current User Name [$UseSetVariable]
[Select]

Insert File [ ]

Insert File [“$Path”]

Insert File [$Target; “$Path”]
[*Custom title:* $Title]
[*Storage method:* Let user choose]
[*Display icon*]
[*Compression:* Let user choose]

Insert File [$Target; “$Path”]
[*Custom title:* $Title]
[*Storage method:* Let user choose]
[*Display icon*]
[*Compression:* Never compress]

Insert File [$Target; “$Path”]
[*Custom title:* $Title]
[*Storage method:* Let user choose]
[*Display icon*]
[*Compression:* Compress when possible]

Insert File [$Target; “$Path”]
[*Custom title:* "Hello World"]
[*Storage method:* Let user choose]
[*Display content*]

[*Compression:* Never compress]

Insert File [$Target; “$Path”]
[*Custom title:* $Title]
[*Storage method:* Let user choose]
[*Display content*]
[*Compression:* Compress when possible]

Insert File [$Target; “$Path”]
[*Custom title:* $Title]
[*Storage method:* Insert]
[*Display icon*]
[*Compression:* Let user choose]

Insert File [$Target; “$Path”]
[*Custom title:* $Title]
[*Storage method:* Insert]
[*Display icon*]
[*Compression:* Never compress]

Insert File [$Target; “$Path”]
[*Custom title:* $Title]
[*Storage method:* Insert]
[*Display icon*]
[*Compression:* Compress when possible]

Insert File [$Target; “$Path”]
[*Custom title:* $Title]
[*Storage method:* Insert]
[*Display content*]
[*Compression:* Never compress]

Insert File [$Target; “$Path”]
[*Custom title:* $Title]
[*Storage method:* Insert]
[*Display content*]
[*Compression:* Compress when possible]

Insert File [$Target; “$Path”]
[*Custom title:* $Title]
[*Storage method:* Reference]
[*Display icon*]
[*Compression:* Never compress]

Insert File [$Target; “$Path”]
[*Custom title:* $Title]
[*Storage method:* Reference]
[*Display content*]
[*Compression:* Never compress]

Insert File [$Target; “$Path”]
[*Custom title:* $Title]
[*Filters*]
  [*"Video":* (mov; mpg; mpeg; mp4; m4v; wmv; avi)]
[*Storage method:* Let user choose]
[*Display icon*]
[*Compression:* Never compress]

Insert File [$Target; “$Path”]
[*Custom title:* $Title]
[*Filters*]
  [*"Video":* (mov; mpg; mpeg; mp4; m4v; wmv; avi)]
[*Storage method:* Let user choose]
[*Display icon*]
[*Compression:* Compress when possible]

Insert File [$Target; “$Path”]
[*Custom title:* "Hello World"]
[*Filters*]
  [*"Images":* (png; jpg; gif; bmp; tif; tiff)]
[*Storage method:* Let user choose]
[*Display content*]
[*Compression:* Never compress]

Insert File [$Target; “$Path”]
[*Custom title:* $Title]
[*Filters*]
  [*"Video":* (mov; mpg; mpeg; mp4; m4v; wmv; avi)]
[*Storage method:* Let user choose]
[*Display content*]
[*Compression:* Compress when possible]

Insert File [$Target; “$Path”]
[*Custom title:* $Title]
[*Filters*]

[*"Audio":* (mp3; wav; aiff; m4a; wma)]
[*"Images":* (png; jpg; gif; bmp; tif; tiff)]
[*Storage method:* Insert]
[*Display icon*]
[*Compression:* Let user choose]

Insert File [$Target; “$Path”]
[*Custom title:* $Title]
[*Filters*]
[*"Video":* (mov; mpg; mpeg; mp4; m4v; wmv; avi)]
[*Storage method:* Insert]
[*Display icon*]
[*Compression:* Never compress]

Insert File [$Target; “$Path”]
[*Custom title:* $Title]
[*Filters*]
[*"Video":* (mov; mpg; mpeg; mp4; m4v; wmv; avi)]
[*Storage method:* Insert]
[*Display icon*]
[*Compression:* Compress when possible]

Insert File [$Target; “$Path”]
[*Custom title:* $Title]
[*Filters*]
[*"Video":* (mov; mpg; mpeg; mp4; m4v; wmv; avi)]
[*Storage method:* Insert]
[*Display content*]
[*Compression:* Never compress]

Insert File [$Target; “$Path”]
[*Custom title:* $Title]
[*Filters*]
[*"Video":* (mov; mpg; mpeg; mp4; m4v; wmv; avi)]
[*Storage method:* Insert]
[*Display content*]
[*Compression:* Compress when possible]

Insert File [$Target; “$Path”]
[*Custom title:* $Title]
[*Filters*]
[*"Audio":* (mp3; wav; aiff; m4a; wma)]
[*"Images":* (png; jpg; gif; bmp; tif; tiff)]
[*Storage method:* Reference]
[*Display icon*]
[*Compression:* Never compress]

Insert File [$Target; “$Path”]
[*Custom title:* $Title]
[*Filters*]
[*"Audio":* (mp3; wav; aiff; m4a; wma)]
[*"Images":* (png; jpg; gif; bmp; tif; tiff)]
[*Storage method:* Reference]
[*Display content*]
[*Compression:* Never compress]

Insert File [$TargetFileContents; “file:some file somewhere”]
[*Storage method:* Let user choose]
[*Display icon*]
[*Compression:* Let user choose]

Insert File [$TargetFileContents; “file:some file somewhere/$SourceFileName”]
[*Storage method:* Let user choose]
[*Display icon*]
[*Compression:* Let user choose]

Insert File [“$Path1” OR “$Path2”]
[*Storage method:* Insert]
[*Display icon*]
[*Compression:* Never compress]

Insert File [“$Path1” OR “$Path2”]
[*Storage method:* Reference]
[*Display icon*]
[*Compression:* Never compress]

Insert File [“$Path1” OR “$Path2”]

Insert File [ ]
[*Custom title:* "Choose image"]
[*Filters*]
[*"Images":* (png; jpg; gif; bmp; tif; tiff)]
[*Storage method:* Let user choose]
[*Display icon*]

[*Compression:* Let user choose]

Insert File [TestTable::ID]
[*Custom title:* "Choose image"]
[*Filters*]
[*"Images":* (png; jpg; gif; bmp; tif; tiff)]
[*Storage method:* Let user choose]
[*Display icon*]
[*Compression:* Let user choose]

Insert File [TestTable::ID; “$Path”]
[*Custom title:* "Choose image"]
[*Filters*]
[*"Images":* (png; jpg; gif; bmp; tif; tiff)]
[*Storage method:* Let user choose]
[*Display icon*]
[*Compression:* Let user choose]

Insert File [$FileContents; “file:some file somewhere”]
[*Storage method:* Let user choose]
[*Display icon*]
[*Compression:* Let user choose]

Insert from Device [Type: Music Library]

Insert from Device [TestTable::MyGlobal_g; Type: Photo Library]

Insert from Device [TestTable::MyGlobal_g; Type: Camera; Camera: Back; Resolution: Full]

Insert from Device [TestTable::MyGlobal_g; Type: Camera; Camera: Front; Resolution: Full]

Insert from Device [TestTable::MyGlobal_g; Type: Camera; Camera: Front; Resolution: Large]

Insert from Device [TestTable::MyGlobal_g; Type: Camera; Camera: Front; Resolution: Medium]

Insert from Device [TestTable::MyGlobal_g; Type: Camera; Camera: Front; Resolution: Small]

Insert from Device [TestTable::MyGlobal_g; Type: Video Camera; Camera: Back; Resolution: Full; Max duration: 60; Start immediately]

Insert from Device [TestTable::MyGlobal_g; Type: Video Camera; Camera: Front; Resolution: Small; Max duration: 5; Start immediately]

Insert from Device [TestTable::MyGlobal_g; Type: Microphone; Max duration: 12; Start immediately]

Insert from Device [TestTable::MyGlobal_g; Type: Barcode; Camera: Back; Resolution: Full; Types: Code 39, Code 93, Code 128, EAN-8, EAN-13, EAN/UPC Composite, GS1 2-Digit Add-On, GS1 5-Digit Add-On, GS1 DataBar Limited, GS1 DataBar Expanded, GS1 DataBar (RSS), Interleaved 2 of 5, ISBN-10 (from EAN-13), ISBN-13 (from EAN-13), QR Code, UPC-A, UPC-E]

Insert from Device [TestTable::MyGlobal_g; Type: Barcode; Scan from: TestTable::<Field Missing>; Types: Code 39, Code 93, Code 128, EAN-8, EAN-13, EAN/UPC Composite, GS1 2-Digit Add-On, GS1 5-Digit Add-On, GS1 DataBar Limited, GS1 DataBar Expanded, GS1 DataBar (RSS), Interleaved 2 of 5, ISBN-10 (from EAN-13), ISBN-13 (from EAN-13), QR Code, UPC-A, UPC-E]

Insert from Device [TestTable::MyGlobal_g; Type: Photo Library]

Insert from Device [TestTable::MyGlobal_g; Type: Signature; Title: "Title"; Message: "Message"; Prompt: "Prompt"; Presentation: Full Screen]

Insert from Device [TestTable::MyGlobal_g; Type: Signature; Title: "Title"; Message: "Message"; Prompt: "Prompt"; Presentation: Overlay]

Insert from Device [TestTable::MyGlobal_g; Type: Signature; Title: "Title"; Message: "Message"; Prompt: "Prompt"; Presentation: Embedded]

Insert from Index [ ]

Insert from Index [TestTable::MyGlobal_g]

Insert from Index [TestTable::MyGlobal_g]
[Select]

Insert from Index [ ]
[Select]

Insert from Last Visited [ ]

Insert from Last Visited [TestTable::MyGlobal_g]

Insert from Last Visited [TestTable::MyGlobal_g]
[Select]

Insert from Last Visited [ ]
[Select]

Insert from URL [ ]
[No dialog]

Insert from URL [ ]

Insert from URL [TestTable::MyGlobal_g]

Insert from URL [TestTable::ContainerField1; $URL]
[Do not automatically encode URL; No dialog; Verify SSL Certificates]

Insert from URL [$WebContent]
[Select]

Insert from URL [TestTable::TextField1; $url]
[Select]

Insert from URL [TestTable::TextField1; $url]
[Do not automatically encode URL; Select]

Insert from URL [TestTable::TextField1; $url]
[Select; No dialog]

Insert from URL [cURL options: "-X PUT"]
[Select]

Insert from URL [TestTable::TextField1; $URL; cURL options: $curl_options]
[Select; No dialog; Verify SSL Certificates]

#ONLY ONE Param => Assume Source Var

#The following INFREQUENT form has no target -> NEEDS a currently selected layout field

Insert from URL [$URL]
[No dialog]

Insert from URL [$TargetWebContent; "someurl"]
[No dialog]

Insert from URL [$TargetWebContent; $SourceURL]
[No dialog]

#TODO: MBS must interpret first var as Target when 2 Vars between 'With dialog' and 'cURL options': Target Variable + URL Variable

Insert from URL [$TargetWebContent; $URL; cURL options: $cURL_Options]

#EGIT - in cURL options ist es GEMISCHT: MANCHE Vars sind Target Vars, manche QUELL Vars

Insert from URL [TestTable::DateField1; "http://www.mrwatson.de"; cURL options: "
--trace $TargetDump
--uploadOrWhatever $SourceFile
"]
[Do not automatically encode URL; No dialog]

Insert PDF [ ]

Insert PDF [“$PdfPath”]

Insert PDF [“$PdfPath”]
[Reference]

Insert PDF [ ]
[Reference]

Insert PDF [ ]
[Reference]

Insert Picture [ ]

Insert Picture [“image:Bild.png”]

Insert Picture [“image:Bild.png”]
[Reference]

Insert Picture [ ]
[Reference]

Insert Text [ ]

Insert Text [ ]

Insert Text [$Code]

Insert Text [$Code]

[Select]

Insert Text [ ]

Insert Text [$TargetVar]

Insert Text [<Table Missing>; “1+2”]
[Select]

Insert Text [TestTable::NumberField1; “foo bar baz”]
[Select]

Insert Text [$Code]
[Select]

Insert Text [$Code]

Insert Text [$Code]

Insert Text [$Code]

Insert Text [$Code]

Insert Text [ ]
[Select]

Relookup Field Contents [ ]

Relookup Field Contents [TestTable::TextField1]
[No dialog]

Replace Field Contents [<Table Missing>]

Replace Field Contents [Replace with calculation: 123456]

Replace Field Contents [TestTable::MyGlobal_g; Current contents]

#Custom Values: 1+1

Replace Field Contents [TestTable::SerialNumberOnCreationIncBy1; Replace with serial numbers: Custom values; Initial value: 1; Increment value: 1]
[No dialog]

#Custom Values: 100+10

Replace Field Contents [TestTable::SerialNumberOnCreationIncBy1; Replace with serial numbers: Custom values; Initial value: 100; Increment value: 10]
[Update Entry Options]

#Entry Options (+1)

Replace Field Contents [TestTable::SerialNumberOnCreationIncBy1; Replace with serial numbers: Entry option values; Increment value: 0]
[No dialog]

#Entry Options (+10)

Replace Field Contents [TestTable::SerialNumberOnCommitIncBy10; Replace with serial numbers: Entry option values; Increment value: 0]
[No dialog]

#Entry Options (+1) ; Update Serial Number in Entry Options

Replace Field Contents [TestTable::SerialNumberOnCreationIncBy1; Replace with serial numbers: Entry option values; Increment value: 0]
[No dialog; Update Entry Options]

#Custom Values: 1+1 ; Update Serial Number in Entry Options

Replace Field Contents [TestTable::SerialNumberOnCreationIncBy1; Replace with serial numbers: Custom values; Initial value: 1; Increment value: 1]
[No dialog; Update Entry Options]

Replace Field Contents [TestTable::NumberField1; Replace with serial numbers: Custom values; Initial value: 100; Increment value: 10]
[Update Entry Options]

Replace Field Contents [TestTable::TextField1; Replace with calculation: "Calc"]

#FM22 - New option: Skip auto-enter options

Replace Field Contents [Replace with calculation: 123456; Skip auto-enter options]

Replace Field Contents [TestTable::TextField1; Current contents; Skip auto-enter options]

Replace Field Contents [TestTable::TextField1; Replace with calculation: "Calc"; Skip auto-enter options]

#/FM22

Set Field [<Table Missing>; 1+2]

Set Field [<Table Missing>[2+1]; 1+2]
Set Field [_Color::<Field Missing>; 1+2]
Set Field [TestTable::ID[2]; 1+2]
Set Field [TestTable::TextField_lotsTurnedOn; "Tabelle nicht vorhanden"]
Set Field [TestTable::NumberField1; "<Tabelle nicht vorhanden>"]

Set Field By Name ["Test::Egal"; 1+2]
Set Field By Name [$FieldName; "Value"]

Set Next Serial Value [1]
Set Next Serial Value [<Table Missing>; 1]
Set Next Serial Value [TestTable::ContactNameList_u; 1]

#OBSOLETE STEPS
#[OBSOLETE] Insert Object
#[OBSOLETE] Insert QuickTime
End If
Records
If [1]
Commit Records/Requests
Commit Records/Requests
[No dialog]
Commit Records/Requests
[Skip data entry validation]
Commit Records/Requests
[Skip data entry validation; No dialog]
Commit Records/Requests
[Skip data entry validation; No dialog; Force Commit]

Copy All Records/Requests

Copy Record/Request

Delete All Records
Delete All Records
[No dialog]

Delete Portal Row
Delete Portal Row
[No dialog]

Delete Record/Request
Delete Record/Request
[No dialog]

Duplicate Record/Request

Export Records [Create folders:No]
Export Records [Create folders:No; Character Set: “Macintosh”; Field Order: TestTable::TextField1]
[Format output using current layout]
Export Records [Create folders:No; Character Set: “Windows (ANSI)”; Field Order: TestTable::TextField1]
Export Records [Create folders:No; Character Set: “Macintosh”; Field Order: TestTable::TextField1]
Export Records [File Name: “file:file.txt”; Create folders:No; Character Set: “Macintosh”; Field Order: TestTable::TextField1]
Export Records [File Name: “file:file.txt”; Automatically open; Create email; Create folders:No; Character Set: “Unicode (UTF-8)”; Field Order: TestTable::TextField1
TestTable::NumberField1

TestTable::DateField1
TestTable::TimeField1
TestTable::TimestampField1
TestTable::ContainerField1
TestTable::CalcField1_c
TestTable::SummaryField1
TestTable::ID
TestTable::TextField_lotsTurnedOn
TestTable::ContactNameList_u
TestTable::ContainerField1_RC
TestTable::MyGlobal_g
TestTable::ContainerField1_RC_dynamicPath
TestTable::CreationTimestamp]

Export Records [File Name: “file:file.txt”; Automatically open; Create email; Create folders:No; Character Set: “Macintosh”; Field Order: TestTable::TextField1]
[No dialog]

Export Records [File Name: “file:file.txt”; Automatically open; Create email; Create folders:No; Character Set: “Unicode (UTF-8)”; Field Order: TestTable::TextField1]
[No dialog; Format output using current layout]

Export Records [File Name: “file:file.txt”; Automatically open; Create email; Create folders:No; Character Set: “Unicode (UTF-16)”; Field Order: TestTable::TextField1]
[No dialog; Format output using current layout]

Export Records [File Name: “file:file.txt”; Automatically open; Create email; Create folders:No; Character Set: “Windows (ANSI)”; Field Order: TestTable::TextField1
TestTable::NumberField1
TestTable::DateField1
TestTable::TimeField1
TestTable::TimestampField1
TestTable::ContainerField1
TestTable::CalcField1_c
TestTable::SummaryField1
TestTable::ID
TestTable::TextField_lotsTurnedOn
TestTable::ContactNameList_u
TestTable::ContainerField1_RC
TestTable::MyGlobal_g
TestTable::ContainerField1_RC_dynamicPath
TestTable::CreationTimestamp]
[No dialog]

Export Records [File Name: “file:file.txt”; Automatically open; Create email; Create folders:No; Character Set: “ASCII (DOS)”; Field Order: TestTable::TextField1
TestTable::NumberField1
TestTable::DateField1
TestTable::TimeField1
TestTable::TimestampField1
TestTable::ContainerField1
TestTable::CalcField1_c
TestTable::SummaryField1
TestTable::ID
TestTable::TextField_lotsTurnedOn
TestTable::ContactNameList_u
TestTable::ContainerField1_RC
TestTable::MyGlobal_g
TestTable::ContainerField1_RC_dynamicPath
TestTable::CreationTimestamp]
[No dialog]

Export Records [File Name: “file:file.txt”; Automatically open; Create email; Create folders:No; Character Set: “Macintosh”; Field Order: TestTable::TextField1
TestTable::NumberField1
TestTable::DateField1
TestTable::TimeField1
TestTable::TimestampField1
TestTable::ContainerField1
TestTable::CalcField1_c
TestTable::SummaryField1
TestTable::ID
TestTable::TextField_lotsTurnedOn
TestTable::ContactNameList_u
TestTable::ContainerField1_RC
TestTable::MyGlobal_g

TestTable::ContainerField1_RC_dynamicPath
TestTable::CreationTimestamp]
[No dialog]

Export Records [File Name: “file:file.txt”; Automatically open; Create email; Create folders:No; Character Set: “Japanese (Shift-JIS)”; Field Order: TestTable::TextField1
TestTable::NumberField1
TestTable::DateField1
TestTable::TimeField1
TestTable::TimestampField1
TestTable::ContainerField1
TestTable::CalcField1_c
TestTable::SummaryField1
TestTable::ID
TestTable::TextField_lotsTurnedOn
TestTable::ContactNameList_u
TestTable::ContainerField1_RC
TestTable::MyGlobal_g
TestTable::ContainerField1_RC_dynamicPath
TestTable::CreationTimestamp]
[No dialog]

Export Records [File Name: “file:file.txt”; Automatically open; Create email; Create folders:No; Character Set: “Simplified Chinese (GB)”; Field Order: TestTable::TextField1
TestTable::NumberField1
TestTable::DateField1
TestTable::TimeField1
TestTable::TimestampField1
TestTable::ContainerField1
TestTable::CalcField1_c
TestTable::SummaryField1
TestTable::ID
TestTable::TextField_lotsTurnedOn
TestTable::ContactNameList_u
TestTable::ContainerField1_RC
TestTable::MyGlobal_g
TestTable::ContainerField1_RC_dynamicPath
TestTable::CreationTimestamp]
[No dialog]

Export Records [File Name: “file:file.txt”; Automatically open; Create email; Create folders:No; Character Set: “Traditional Chinese (Big-5)”; Field Order: TestTable::TextField1
TestTable::NumberField1
TestTable::DateField1
TestTable::TimeField1
TestTable::TimestampField1
TestTable::ContainerField1
TestTable::CalcField1_c
TestTable::SummaryField1
TestTable::ID
TestTable::TextField_lotsTurnedOn
TestTable::ContactNameList_u
TestTable::ContainerField1_RC
TestTable::MyGlobal_g
TestTable::ContainerField1_RC_dynamicPath
TestTable::CreationTimestamp]
[No dialog]

Export Records [File Name: “file:file.txt”; Automatically open; Create email; Create folders:No; Character Set: “Korean (EUC-KR)”; Field Order: TestTable::TextField1
TestTable::NumberField1
TestTable::DateField1
TestTable::TimeField1
TestTable::TimestampField1
TestTable::ContainerField1
TestTable::CalcField1_c
TestTable::SummaryField1
TestTable::ID
TestTable::TextField_lotsTurnedOn
TestTable::ContactNameList_u
TestTable::ContainerField1_RC
TestTable::MyGlobal_g
TestTable::ContainerField1_RC_dynamicPath
TestTable::CreationTimestamp]
[No dialog]

Example SyntaxColorizing: All script steps and all options

Export Records [File Name: “file:file.txt”; Automatically open; Create email; Create folders:No; Character Set: “Macintosh”; Field Order: TestTable::TextField1
TestTable::NumberField1
TestTable::DateField1
TestTable::TimeField1
TestTable::TimestampField1
TestTable::ContainerField1
TestTable::CalcField1_c
TestTable::SummaryField1
TestTable::SummaryField1; Summarize by: _Syntax::ColorName
TestTable::ID
TestTable::TextField_lotsTurnedOn
TestTable::ContactNameList_u
TestTable::ContainerField1_RC
TestTable::MyGlobal_g
TestTable::ContainerField1_RC_dynamicPath
TestTable::CreationTimestamp]
[No dialog; Format output using current layout]

Import Records [Source: “file:fmSyntaxColorizer.fmp12”; Target: “TestTable”; Method: Add; Character Set: “Mac Roman”; Field Mapping: Source field 1 import to TestTable::TextField1;
Source field 2 import to TestTable::NumberField1;
Source field 3 import to TestTable::DateField1;
Source field 4 import to TestTable::TimeField1;
Source field 5 import to TestTable::TimestampField1;
Source field 6 import to TestTable::ContainerField1;
Source field 9 import to TestTable::ID(Do Auto-Enter);
Source field 10 import to TestTable::TextField_lotsTurnedOn(Do Auto-Enter);
Source field 12 import to TestTable::ContainerField1_RC;
Source field 13 import to TestTable::MyGlobal_g;
Source field 14 import to TestTable::ContainerField1_RC_dynamicPath;
Source field 15 import to TestTable::CreationTimestamp(Do Auto-Enter);
TestTable::SerialNumberOnCreationIncBy1(Do Auto-Enter);
TestTable::SerialNumberOnCommitIncBy10(Do Auto-Enter);]
[No dialog]

Import Records [Source: “file:file.txt”]

Import Records [Source: “file:file.fmp12”]

Import Records [Source: “file:file.tab”; Fields Name Row: 0; Predefined: No]

Import Records [Source: “file:file.tab”; Fields Name Row: -1; Predefined: No]

Import Records [Source: “file:file.csv”; Fields Name Row: 0; Predefined: No]

Import Records [Source: “file:file.csv”; Fields Name Row: -1; Predefined: No]

Import Records [Source: “file:file.mer”]

Import Records [Source: “file:file.dbf”]

Import Records ["file:file.xls"; Worksheet: ""; Fields Name Row: 0]

Import Records ["file:file.xls"; Worksheet: ""; Fields Name Row: -1]

Import Records ["file:file.xlsx"; Worksheet: ""; Fields Name Row: 0]

Import Records ["file:file.xlsx"; Worksheet: ""; Fields Name Row: -1]

Import Records [Folder Name: folder; Include all enclosed folders; File Type: Picture and movie files; Import only a reference; Target: “TestTable”; Method: Add; Character Set: “Mac Roman”; Field Mapping: Source field 1 import to TestTable::TextField1;
Source field 2 import to TestTable::NumberField1;
Source field 3 import to TestTable::DateField1;
Source field 4 import to TestTable::TimeField1;
Source field 5 import to TestTable::TimestampField1;
Source field 6 import to TestTable::ContainerField1;
Source field 9 import to TestTable::ID(Do Auto-Enter);
Source field 10 import to TestTable::TextField_lotsTurnedOn(Do Auto-Enter);
Source field 12 import to TestTable::ContainerField1_RC;
Source field 13 import to TestTable::MyGlobal_g;
Source field 14 import to TestTable::ContainerField1_RC_dynamicPath;
Source field 15 import to TestTable::CreationTimestamp(Do Auto-Enter);
TestTable::SerialNumberOnCreationIncBy1(Do Auto-Enter);
TestTable::SerialNumberOnCommitIncBy10(Do Auto-Enter);]
[Verify SSL Certificates]

Import Records [Folder Name: folder; Include all enclosed folders; File Type: Picture and movie files; Import only a reference]

Import Records [Folder Name: folder; File Type: Picture and movie files]

Import Records [Folder Name: folder; File Type: Text files]

Import Records [Folder Name: folder; File Type: Text files]

Import Records [Folder Name: folder; File Type: Text files; Target: “TestTable”; Method: Add; Character Set: “Mac Roman”; Field Mapping: Source field 1 import to TestTable::TextField1;
Source field 2 import to TestTable::NumberField1;
Source field 3 import to TestTable::DateField1;
Source field 4 import to TestTable::TimeField1;
Source field 5 import to TestTable::TimestampField1;
Source field 6 import to TestTable::ContainerField1;
Source field 9 import to TestTable::ID(Do Auto-Enter);
Source field 10 import to TestTable::TextField_lotsTurnedOn(Do Auto-Enter);
Source field 12 import to TestTable::ContainerField1_RC;
Source field 13 import to TestTable::MyGlobal_g;
Source field 14 import to TestTable::ContainerField1_RC_dynamicPath;
Source field 15 import to TestTable::CreationTimestamp(Do Auto-Enter);
TestTable::SerialNumberOnCreationIncBy1(Do Auto-Enter);
TestTable::SerialNumberOnCommitIncBy10(Do Auto-Enter);]
[Data contains column names]

Import Records [Folder Name: folder; File Type: Text files; Target: “TestTable”; Method: Replace; Character Set: “Mac Roman”; Field Mapping: Source field 1 import to TestTable::TextField1;
Source field 2 import to TestTable::NumberField1;
Source field 3 import to TestTable::DateField1;
Source field 4 import to TestTable::TimeField1;
Source field 5 import to TestTable::TimestampField1;
Source field 6 import to TestTable::ContainerField1;
Source field 9 import to TestTable::ID(Do Auto-Enter);
Source field 10 import to TestTable::TextField_lotsTurnedOn(Do Auto-Enter);
Source field 12 import to TestTable::ContainerField1_RC;
Source field 13 import to TestTable::MyGlobal_g;
Source field 14 import to TestTable::ContainerField1_RC_dynamicPath;
Source field 15 import to TestTable::CreationTimestamp(Do Auto-Enter);
TestTable::SerialNumberOnCreationIncBy1(Do Auto-Enter);
TestTable::SerialNumberOnCommitIncBy10(Do Auto-Enter);]
[Data contains column names]

Import Records [Folder Name: folder; File Type: Text files; Target: “TestTable”; Method: Update; Character Set: “Mac Roman”; Field Mapping: Source field 1 match with TestTable::TextField1;
Source field 2 import to TestTable::NumberField1;
Source field 3 import to TestTable::DateField1;
Source field 4 import to TestTable::TimeField1;
Source field 5 import to TestTable::TimestampField1;
Source field 6 import to TestTable::ContainerField1;
Source field 9 import to TestTable::ID(Do Auto-Enter);
Source field 10 import to TestTable::TextField_lotsTurnedOn(Do Auto-Enter);
Source field 12 import to TestTable::ContainerField1_RC;
Source field 13 import to TestTable::MyGlobal_g;
Source field 14 import to TestTable::ContainerField1_RC_dynamicPath;
Source field 15 import to TestTable::CreationTimestamp(Do Auto-Enter);
TestTable::SerialNumberOnCreationIncBy1(Do Auto-Enter);
TestTable::SerialNumberOnCommitIncBy10(Do Auto-Enter);]

Import Records [Folder Name: folder; File Type: Text files; Target: “TestTable”; Method: Update; Character Set: “Mac Roman”; Field Mapping: Source field 1 match with TestTable::TextField1;
Source field 2 import to TestTable::NumberField1;
Source field 3 import to TestTable::DateField1;
Source field 4 import to TestTable::TimeField1;
Source field 5 import to TestTable::TimestampField1;
Source field 6 import to TestTable::ContainerField1;
Source field 9 import to TestTable::ID(Do Auto-Enter);
Source field 10 import to TestTable::TextField_lotsTurnedOn(Do Auto-Enter);
Source field 12 import to TestTable::ContainerField1_RC;
Source field 13 import to TestTable::MyGlobal_g;
Source field 14 import to TestTable::ContainerField1_RC_dynamicPath;
Source field 15 import to TestTable::CreationTimestamp(Do Auto-Enter);
TestTable::SerialNumberOnCreationIncBy1(Do Auto-Enter);
TestTable::SerialNumberOnCommitIncBy10(Do Auto-Enter);]

Import Records [Folder Name: folder; File Type: Text files; Target: “TestTable”; Method: Update; Character Set: “Windows ANSI”; Field Mapping: Source field 1 match with TestTable::TextField1;
Source field 2 import to TestTable::NumberField1;
Source field 3 import to TestTable::DateField1;
Source field 4 import to TestTable::TimeField1;

Source field 5 import to TestTable::TimestampField1;
Source field 6 import to TestTable::ContainerField1;
Source field 9 import to TestTable::ID(Do Auto-Enter);
Source field 10 import to TestTable::TextField_lotsTurnedOn(Do Auto-Enter);
Source field 12 import to TestTable::ContainerField1_RC;
Source field 13 import to TestTable::MyGlobal_g;
Source field 14 import to TestTable::ContainerField1_RC_dynamicPath;
Source field 15 import to TestTable::CreationTimestamp(Do Auto-Enter);
TestTable::SerialNumberOnCreationIncBy1(Do Auto-Enter);
TestTable::SerialNumberOnCommitIncBy10(Do Auto-Enter);]

Import Records [Folder Name: folder; Include all enclosed folders; File Type: Text files; Target: “TestTable”; Method: Update; Character Set: “DOS OEM”; Field Mapping: Source field 1 match with TestTable::TextField1;
Source field 2 import to TestTable::NumberField1;
Source field 3 import to TestTable::DateField1;
Source field 4 import to TestTable::TimeField1;
Source field 5 import to TestTable::TimestampField1;
Source field 6 import to TestTable::ContainerField1;
Source field 9 import to TestTable::ID(Do Auto-Enter);
Source field 10 import to TestTable::TextField_lotsTurnedOn(Do Auto-Enter);
Source field 12 import to TestTable::ContainerField1_RC;
Source field 13 import to TestTable::MyGlobal_g;
Source field 14 import to TestTable::ContainerField1_RC_dynamicPath;
Source field 15 import to TestTable::CreationTimestamp(Do Auto-Enter);
TestTable::SerialNumberOnCreationIncBy1(Do Auto-Enter);
TestTable::SerialNumberOnCommitIncBy10(Do Auto-Enter);]

Import Records [Folder Name: folder; File Type: Text files; Target: “TestTable”; Method: Update; Character Set: “Unicode”; Field Mapping: Source field 1 match with TestTable::TextField1;
Source field 2 import to TestTable::NumberField1;
Source field 3 import to TestTable::DateField1;
Source field 4 import to TestTable::TimeField1;
Source field 5 import to TestTable::TimestampField1;
Source field 6 import to TestTable::ContainerField1;
Source field 9 import to TestTable::ID(Do Auto-Enter);
Source field 10 import to TestTable::TextField_lotsTurnedOn(Do Auto-Enter);
Source field 12 import to TestTable::ContainerField1_RC;
Source field 13 import to TestTable::MyGlobal_g;
Source field 14 import to TestTable::ContainerField1_RC_dynamicPath;
Source field 15 import to TestTable::CreationTimestamp(Do Auto-Enter);
TestTable::SerialNumberOnCreationIncBy1(Do Auto-Enter);
TestTable::SerialNumberOnCommitIncBy10(Do Auto-Enter);]

Import Records [Folder Name: folder; File Type: Text files; Target: “TestTable”; Method: Update; Character Set: “Unicode (big endian)”; Field Mapping: Source field 1 match with TestTable::TextField1;
Source field 2 import to TestTable::NumberField1;
Source field 3 import to TestTable::DateField1;
Source field 4 import to TestTable::TimeField1;
Source field 5 import to TestTable::TimestampField1;
Source field 6 import to TestTable::ContainerField1;
Source field 9 import to TestTable::ID(Do Auto-Enter);
Source field 10 import to TestTable::TextField_lotsTurnedOn(Do Auto-Enter);
Source field 12 import to TestTable::ContainerField1_RC;
Source field 13 import to TestTable::MyGlobal_g;
Source field 14 import to TestTable::ContainerField1_RC_dynamicPath;
Source field 15 import to TestTable::CreationTimestamp(Do Auto-Enter);
TestTable::SerialNumberOnCreationIncBy1(Do Auto-Enter);
TestTable::SerialNumberOnCommitIncBy10(Do Auto-Enter);]

Import Records [Folder Name: folder; File Type: Text files; Target: “TestTable”; Method: Update; Character Set: “UTF-8”; Field Mapping: Source field 1 match with TestTable::TextField1;
Source field 2 import to TestTable::NumberField1;
Source field 3 import to TestTable::DateField1;
Source field 4 import to TestTable::TimeField1;
Source field 5 import to TestTable::TimestampField1;
Source field 6 import to TestTable::ContainerField1;
Source field 9 import to TestTable::ID(Do Auto-Enter);
Source field 10 import to TestTable::TextField_lotsTurnedOn(Do Auto-Enter);
Source field 12 import to TestTable::ContainerField1_RC;
Source field 13 import to TestTable::MyGlobal_g;
Source field 14 import to TestTable::ContainerField1_RC_dynamicPath;
Source field 15 import to TestTable::CreationTimestamp(Do Auto-Enter);
TestTable::SerialNumberOnCreationIncBy1(Do Auto-Enter);
TestTable::SerialNumberOnCommitIncBy10(Do Auto-Enter);]

Import Records [Folder Name: folder; File Type: Text files; Target: “TestTable”; Method: Update; Character Set: “Shift JIS”; Field Mapping: Source field 1 match with TestTable::TextField1;
Source field 2 import to TestTable::NumberField1;
Source field 3 import to TestTable::DateField1;
Source field 4 import to TestTable::TimeField1;
Source field 5 import to TestTable::TimestampField1;
Source field 6 import to TestTable::ContainerField1;
Source field 9 import to TestTable::ID(Do Auto-Enter);
Source field 10 import to TestTable::TextField_lotsTurnedOn(Do Auto-Enter);
Source field 12 import to TestTable::ContainerField1_RC;
Source field 13 import to TestTable::MyGlobal_g;
Source field 14 import to TestTable::ContainerField1_RC_dynamicPath;
Source field 15 import to TestTable::CreationTimestamp(Do Auto-Enter);
TestTable::SerialNumberOnCreationIncBy1(Do Auto-Enter);
TestTable::SerialNumberOnCommitIncBy10(Do Auto-Enter);]

Import Records [Folder Name: folder; File Type: Text files; Target: “TestTable”; Method: Update; Character Set: “Simplified Chinese (GB)”; Field Mapping: Source field 1 match with TestTable::TextField1;
Source field 2 import to TestTable::NumberField1;
Source field 3 import to TestTable::DateField1;
Source field 4 import to TestTable::TimeField1;
Source field 5 import to TestTable::TimestampField1;
Source field 6 import to TestTable::ContainerField1;
Source field 9 import to TestTable::ID(Do Auto-Enter);
Source field 10 import to TestTable::TextField_lotsTurnedOn(Do Auto-Enter);
Source field 12 import to TestTable::ContainerField1_RC;
Source field 13 import to TestTable::MyGlobal_g;
Source field 14 import to TestTable::ContainerField1_RC_dynamicPath;
Source field 15 import to TestTable::CreationTimestamp(Do Auto-Enter);
TestTable::SerialNumberOnCreationIncBy1(Do Auto-Enter);
TestTable::SerialNumberOnCommitIncBy10(Do Auto-Enter);]

Import Records [Folder Name: folder; File Type: Text files; Target: “TestTable”; Method: Update; Character Set: “Traditional Chinese (Big-5)”; Field Mapping: Source field 1 match with TestTable::TextField1;
Source field 2 import to TestTable::NumberField1;
Source field 3 import to TestTable::DateField1;
Source field 4 import to TestTable::TimeField1;
Source field 5 import to TestTable::TimestampField1;
Source field 6 import to TestTable::ContainerField1;
Source field 9 import to TestTable::ID(Do Auto-Enter);
Source field 10 import to TestTable::TextField_lotsTurnedOn(Do Auto-Enter);
Source field 12 import to TestTable::ContainerField1_RC;
Source field 13 import to TestTable::MyGlobal_g;
Source field 14 import to TestTable::ContainerField1_RC_dynamicPath;
Source field 15 import to TestTable::CreationTimestamp(Do Auto-Enter);
TestTable::SerialNumberOnCreationIncBy1(Do Auto-Enter);
TestTable::SerialNumberOnCommitIncBy10(Do Auto-Enter);]

Import Records [Folder Name: folder; File Type: Text files; Target: “TestTable”; Method: Update; Character Set: “Korean (EUC-KR)”; Field Mapping: Source field 1 match with TestTable::TextField1;
Source field 2 import to TestTable::NumberField1;
Source field 3 import to TestTable::DateField1;
Source field 4 import to TestTable::TimeField1;
Source field 5 import to TestTable::TimestampField1;
Source field 6 import to TestTable::ContainerField1;
Source field 9 import to TestTable::ID(Do Auto-Enter);
Source field 10 import to TestTable::TextField_lotsTurnedOn(Do Auto-Enter);
Source field 12 import to TestTable::ContainerField1_RC;
Source field 13 import to TestTable::MyGlobal_g;
Source field 14 import to TestTable::ContainerField1_RC_dynamicPath;
Source field 15 import to TestTable::CreationTimestamp(Do Auto-Enter);
TestTable::SerialNumberOnCreationIncBy1(Do Auto-Enter);
TestTable::SerialNumberOnCommitIncBy10(Do Auto-Enter);]

Import Records [Source: “file:Import.log”; Fields Name Row: 0; Predefined: Yes; Delimiter: “ ”; Target: “{New table}”; Method: Add; Character Set: “UTF-8”; Field Mapping: Source field 1 import to target field 1;
Source field 2 import to target field 2;
Source field 3 import to target field 3;
Source field 4 import to target field 4;]
[No dialog]

Import Records [ ]
[No dialog]

Import Records [XML (from http): http://xslt.com/xsl.xml]
[No dialog]

Import Records [XML (from http): http://xslt.com/xsl.xml; XSL (from file): xsl.xsl]
[No dialog]

Import Records [XML (from http): http://xslt.com/xsl.xml; XSL (from calculation): $PathXSL]
[No dialog]

Import Records [XML (from http): http://xslt.com/xsl.xml; XSL (from http): http://xslt.com/xsl.xsl; Target: “Home.Syntax_ALL”; Method: Replace; Add remaining; Character Set: “Mac Roman”; Field Mapping: Source field 1 import to Home.Syntax_ALL::Sort(Do Auto-Enter);
Source field 2 import to Home.Syntax_ALL::Command_EN(Do Auto-Enter);
Source field 3 import to Home.Syntax_ALL::ColorName;
Source field 4 import to Home.Syntax_ALL::MBS_Command_Results(Do Auto-Enter);
Source field 6 import to Home.Syntax_ALL::On;
Source field 9 import to Home.Syntax_ALL::_ID_Palette(Do Auto-Enter);
Source field 10 import to Home.Syntax_ALL::_gID_ActivePalette;
Source field 11 import to Home.Syntax_ALL::__ID(Do Auto-Enter);
Source field 14 import to Home.Syntax_ALL::Selector(Do Auto-Enter);
Source field 17 import to Home.Syntax_ALL::Comment(Do Auto-Enter);
Source field 22 import to Home.Syntax_ALL::IsMarked;
Source field 23 import to Home.Syntax_ALL::FM_internal_ID;
Source field 24 import to Home.Syntax_ALL::FM_Version(Do Auto-Enter);]
[No dialog; Data contains column names]

Import Records [XML (from file): xml.xml; XSL (from http): http://xslt.com/xsl.xsl; Target: “Home.Syntax_ALL”; Method: Replace; Add remaining; Character Set: “Mac Roman”; Field Mapping: Source field 1 import to Home.Syntax_ALL::Sort(Do Auto-Enter);
Source field 2 import to Home.Syntax_ALL::Command_EN(Do Auto-Enter);
Source field 3 import to Home.Syntax_ALL::ColorName;
Source field 4 import to Home.Syntax_ALL::MBS_Command_Results(Do Auto-Enter);
Source field 6 import to Home.Syntax_ALL::On;
Source field 9 import to Home.Syntax_ALL::_ID_Palette(Do Auto-Enter);
Source field 10 import to Home.Syntax_ALL::_gID_ActivePalette;
Source field 11 import to Home.Syntax_ALL::__ID(Do Auto-Enter);
Source field 14 import to Home.Syntax_ALL::Selector(Do Auto-Enter);
Source field 17 import to Home.Syntax_ALL::Comment(Do Auto-Enter);
Source field 22 import to Home.Syntax_ALL::IsMarked;
Source field 23 import to Home.Syntax_ALL::FM_internal_ID;
Source field 24 import to Home.Syntax_ALL::FM_Version(Do Auto-Enter);]
[No dialog; Data contains column names]

Import Records [XML (from calculation): $PathXML; XSL (from http): http://xslt.com/xsl.xsl; Target: “Home.Syntax_ALL”; Method: Replace; Add remaining; Character Set: “Mac Roman”; Field Mapping: Source field 1 import to Home.Syntax_ALL::Sort(Do Auto-Enter);
Source field 2 import to Home.Syntax_ALL::Command_EN(Do Auto-Enter);
Source field 3 import to Home.Syntax_ALL::ColorName;
Source field 4 import to Home.Syntax_ALL::MBS_Command_Results(Do Auto-Enter);
Source field 6 import to Home.Syntax_ALL::On;
Source field 9 import to Home.Syntax_ALL::_ID_Palette(Do Auto-Enter);
Source field 10 import to Home.Syntax_ALL::_gID_ActivePalette;
Source field 11 import to Home.Syntax_ALL::__ID(Do Auto-Enter);
Source field 14 import to Home.Syntax_ALL::Selector(Do Auto-Enter);
Source field 17 import to Home.Syntax_ALL::Comment(Do Auto-Enter);
Source field 22 import to Home.Syntax_ALL::IsMarked;
Source field 23 import to Home.Syntax_ALL::FM_internal_ID;
Source field 24 import to Home.Syntax_ALL::FM_Version(Do Auto-Enter);]
[No dialog; Data contains column names]

New Record/Request

Open Record/Request

Revert Record/Request

Revert Record/Request
[No dialog]

Save Records as Excel [Create folders:No]

Save Records as Excel [Create folders:No]
[No dialog]

Save Records as Excel [File Name: “$Path”; Automatically open; Create email; Create folders:No; Records being browsed; Use field names as column names; Worksheet: $WKS1; Title: $Title; Subject: $Subject; Author: $Author]
[Restore; No dialog]

Save Records as Excel [File Name: “$Path”; Automatically open; Create email; Create folders:No; Current record; Use field names as column names; Worksheet: $WKS1; Title: $Title; Subject: $Subject; Author: $Author]
[Restore; No dialog]

Save Records as JSONL [Format for fine-tuning:Off; Create folders:Off]

Save Records as JSONL [Format for fine-tuning:Off; Create folders:On]

Save Records as JSONL [Format for fine-tuning:On; Create folders:Off]

Save Records as JSONL [Format for fine-tuning:On; System Prompt:$SystemPrompt; User Prompt:$UserPrompt; Assistant Prompt:$AssistantPrompt; Create folders:Off]

Save Records as JSONL [Format for fine-tuning:On; Table: “TestTable”; System Prompt:$SystemPrompt; User Prompt: $UserPrompt; Assistant Prompt:$AssistantPrompt; “$OutputFilePath”; Create folders:Off]

Save Records as JSONL [Format for fine-tuning:On; Table: “TestTable”; System Prompt:$SystemPrompt; User Prompt: $UserPrompt; Assistant Prompt:$AssistantPrompt; “$OutputFilePath”; Automatically open; Create folders:On]

Save Records as PDF [Create folders:No]

Save Records as PDF [Create folders:No; Records being browsed]
[*Document* -]
[*Pages* - Number Pages From: 1; Include: All pages]
[*Security* - Printing: High Resolution; Editing: Any except extracting pages; Enable copying; Enable Screen Reader]
[*Initial View* - Show: Pages Panel and Page; Page Layout: Single Page; Magnification: 100%]
[Restore]

Save Records as PDF [Create folders:No; Current record]
[*Document* -]
[*Pages* - Number Pages From: 1; Include: All pages]
[*Security* - Printing: High Resolution; Editing: Any except extracting pages; Enable copying; Enable Screen Reader]
[*Initial View* - Show: Pages Panel and Page; Page Layout: Single Page; Magnification: 100%]
[Restore]

Save Records as PDF [Create folders:No]

Save Records as PDF [File Name: “$Path”; Automatically open; Create email; Create folders:No; Records being browsed]
[*Document* -]
[*Pages* - Number Pages From: 1; Include: All pages]
[*Security* - Printing: High Resolution; Editing: Any except extracting pages; Enable copying; Enable Screen Reader]
[*Initial View* - Show: Pages Panel and Page; Page Layout: Single Page; Magnification: 100%]
[Restore; Append; No dialog]

Save Records as PDF [File Name: “$Path”; Automatically open; Create email; Create folders:No; Current record]
[*Document* -]
[*Pages* - Number Pages From: 1; Include: All pages]
[*Security* - Printing: High Resolution; Editing: Any except extracting pages; Enable copying; Enable Screen Reader]
[*Initial View* - Show: Pages Panel and Page; Page Layout: Single Page; Magnification: 100%]
[Restore; Append; No dialog]

Save Records as PDF [File Name: “$Path”; Automatically open; Create email; Create folders:No; Blank record, as formatted]
[*Document* -]
[*Pages* - Number Pages From: 1; Include: All pages]
[*Security* - Printing: High Resolution; Editing: Any except extracting pages; Enable copying; Enable Screen Reader]
[*Initial View* - Show: Pages Panel and Page; Page Layout: Single Page; Magnification: 100%]
[Restore; Append; No dialog]

Save Records as PDF [File Name: “$Path”; Automatically open; Create email; Create folders:No; Blank record, with boxes]
[*Document* -]
[*Pages* - Number Pages From: 1; Include: All pages]
[*Security* - Printing: High Resolution; Editing: Any except extracting pages; Enable copying; Enable Screen Reader]
[*Initial View* - Show: Pages Panel and Page; Page Layout: Single Page; Magnification: 100%]
[Restore; Append; No dialog]

Save Records as PDF [File Name: “$Path”; Automatically open; Create email; Create folders:No; Blank record, with underlines]
[*Document* -]
[*Pages* - Number Pages From: 1; Include: All pages]
[*Security* - Printing: High Resolution; Editing: Any except extracting pages; Enable copying; Enable Screen Reader]
[*Initial View* - Show: Pages Panel and Page; Page Layout: Single Page; Magnification: 100%]
[Restore; Append; No dialog]

Save Records as PDF [File Name: “$Path”; Automatically open; Create email; Create folders:No; Blank record, with placeholder text]
[*Document* -]
[*Pages* - Number Pages From: 1; Include: All pages]
[*Security* - Printing: High Resolution; Editing: Any except extracting pages; Enable copying; Enable Screen Reader]
[*Initial View* - Show: Pages Panel and Page; Page Layout: Single Page; Magnification: 100%]
[Restore; Append; No dialog]

Save Records as PDF [File Name: “$Path”; Automatically open; Create email; Create folders:No; Records being browsed]

[*Document* - Title: $Title; Subject: $Subject; Author: $Author; Keywords: $Keywords]
[*Pages* - Number Pages From: 1; Include: All pages]
[*Security* - Password to open; Password to print/edit; Printing: Low Resolution; Editing: Inserting, deleting and rotating pages; Enable Screen Reader]
[*Initial View* - Show: Page Only; Page Layout: Single Page; Magnification: 800%]
[Restore; Append; No dialog]

Save Records as Snapshot Link [Create folders:No; Records being browsed]

Save Records as Snapshot Link [File Name: “$Path”; Create email; Create folders:No; Records being browsed]

Save Records as Snapshot Link [File Name: “$Path”; Create email; Create folders:No; Current record]

Truncate Table [Table: <Current Table>]

Truncate Table [No dialog; Table: “TestTable”]

Truncate Table [No dialog; Table: <Table Missing>]

End If

Found Sets

If [1]

Constrain Found Set [ ]

Constrain Found Set [Specified Find Requests: Find Records; Criteria: TestTable::TextField1: “one”
Omit Records; Criteria: TestTable::TextField1: “a”]
[Restore]

Constrain Found Set [Specified Find Requests: Find Records; Criteria: TestTable::TextField1: “one”
Omit Records; Criteria: TestTable::TextField1: “a”]
[Restore; Find without indexes]

Constrain Found Set [ ]
[Find without indexes]

Extend Found Set [ ]

Extend Found Set [Specified Find Requests: Find Records; Criteria: TestTable::TextField1: “one”
Omit Records; Criteria: TestTable::TextField1: “a”]
[Restore]

Find Matching Records [Replace; TestTable::TextField1]

Find Matching Records [Constrain; TestTable::TextField1]

Find Matching Records [Extend; TestTable::TextField1]

Modify Last Find

Omit Multiple Records [ ]

Omit Multiple Records [123]
[No dialog]

Omit Record

Perform Find [ ]

Perform Find [Specified Find Requests: Find Records; Criteria: TestTable::TextField1: “one”
Omit Records; Criteria: TestTable::TextField1: “a”]
[Restore]

Perform Quick Find [ ]

Perform Quick Find ["Hello"]

Show All Records

Show Omitted Only

Sort Records [ ]

[No dialog]

Sort Records [ ]

Sort Records [ ]

#Don't keep sorted

Sort Records [Specified Sort Order: TestTable::TextField1; ascending]
[Restore; No dialog]

#Keep sorted

Sort Records [Keep records in sorted order; Specified Sort Order: TestTable::TextField1; ascending]
[Restore; No dialog]

#Descending

Sort Records [Specified Sort Order: TestTable::TextField1; descending]
[Restore; No dialog]

#Everything

Sort Records [Specified Sort Order: _Syntax::Command_EN; ascending
_Syntax::On; ascending
_Syntax::IsMarked; descending
_Syntax::ColorName; based on value list: “Colors”
_Syntax::_k1; descending
Syntax.GUISyntax::Command; ascending; reorder based on summary field: Syntax.GUISyntax::_s1; override language: “German”
TestTable::TextField1; ascending
TestTable::NumberField1; descending]
[Restore; No dialog]

Sort Records by Field [Ascending; TestTable::ID]

Sort Records by Field [Descending; TestTable::ID]

Sort Records by Field [Associated value list; TestTable::ID]

Unsort Records

End If

Windows

If [1]

Adjust Window
[Resize to Fit]

Adjust Window
[Maximize]

Adjust Window
[Minimize]

Adjust Window
[Restore]

Adjust Window
[Hide]

Arrange All Windows
[Tile Horizontally]

Arrange All Windows
[Tile Vertically]

Arrange All Windows
[Cascade Window]

Arrange All Windows
[Bring All To Front]

Close Window [Current Window]

Close Window [Name: $FensterName; Current file]

Freeze Window

Move/Resize Window [Current Window]

Move/Resize Window [Name: $FensterName; Current file; Height: $FensterHoehe; Width: $FensterBreite; Top: $FensterOben; Left: $FensterLinks]

New Window [Style: Document; Name: "Window"; Using layout: <Current Layout>; Close: Yes; Minimize: Yes; Maximize: Yes; Resize: Yes; Menu Bar: Yes; Dim parent window: No; Toolbars: Yes]

New Window [Style: Document; Using layout: “Home” (_Home); Height: 1; Width: 2; Top: 3; Left: 4; Close: Yes; Minimize: Yes; Maximize: Yes; Resize: Yes; Menu Bar: Yes; Dim parent window: No; Toolbars: Yes]

New Window [Style: Document; Name: $FensterName; Using layout: <Current Layout>; Height: $FensterHoehe; Width: $FensterBreite; Top: $FensterOben; Left: $FensterLinks; Close: Yes; Minimize: Yes; Maximize: Yes; Resize: Yes]

New Window [Style: Floating Document; Name: $FensterName; Using layout: <Current Layout>; Height: $FensterHoehe; Width: $FensterBreite; Top: $FensterOben; Left: $FensterLinks; Close: Yes; Minimize: Yes; Maximize: Yes; Resize: Yes]

New Window [Style: Dialog; Name: $FensterName; Using layout: <Current Layout>; Height: $FensterHoehe; Width: $FensterBreite; Top: $FensterOben; Left: $FensterLinks; Close: No; Minimize: No; Maximize: No; Resize: No]

New Window [Style: Dialog; Name: $FensterName; Using layout: <Current Layout>; Height: $FensterHoehe; Width: $FensterBreite; Top: $FensterOben; Left: $FensterLinks; Close: Yes; Minimize: No; Maximize: Yes; Resize: Yes; Menu Bar: Yes; Dim parent window: No; Toolbars: Yes]

New Window [Style: Card; Name: $FensterName; Using layout: <Current Layout>; Height: $FensterHoehe; Width: $FensterBreite; Top: $FensterOben; Left: $FensterLinks; Close: Yes; Minimize: No; Maximize: No; Resize: No; Menu Bar: No; Dim parent window: Yes; Toolbars: No]

New Window [Style: Card; Name: $FensterName; Using layout: $LayoutName; Height: $FensterHoehe; Width: $FensterBreite; Top: $FensterOben; Left: $FensterLinks; Close: Yes; Minimize: No; Maximize: No; Resize: No; Menu Bar: No; Dim parent window: Yes; Toolbars: No]

Refresh Window

Refresh Window
[Flush cached join results; Flush cached external data]

Scroll Window
[Home]

Scroll Window
[End]

Scroll Window
[Page Up]

Scroll Window
[Page Down]

Scroll Window
[To Selection]

Select Window [Current Window]

Select Window [Name: $FensterName; Current file]

#[OBSOLETE] Set Allowed Orientations [Portrait:On; Portrait Upside Down:On; Landscape Left:On; Landscape Right:On]

#[OBSOLETE] Set Allowed Orientations [Portrait:Off; Portrait Upside Down:Off; Landscape Left:Off; Landscape Right:On]

#[OBSOLETE] Set Allowed Orientations [Portrait:On; Portrait Upside Down:Off; Landscape Left:Off; Landscape Right:Off]

Set Window Title [Current Window; New Title: $FensterNameNeu]

Set Window Title [Of Window: $FensterNameAlt; Current file; New Title: $FensterNameNeu]

Set Zoom Level [Lock; 25%]

Set Zoom Level [Lock; 50%]

Set Zoom Level [Lock; 75%]

Set Zoom Level [Lock; 100%]

Set Zoom Level [Lock; 150%]

Set Zoom Level [Lock; 200%]

Set Zoom Level [Lock; 300%]

Set Zoom Level [Lock; 400%]

Set Zoom Level [Lock; Zoom In]

Set Zoom Level [Lock; Zoom Out]

Show/Hide Menubar
[Lock; Toggle]
Show/Hide Menubar
[Lock; Hide]
Show/Hide Menubar
[Lock; Show]

Show/Hide Text Ruler
[Toggle]
Show/Hide Text Ruler
[Show]
Show/Hide Text Ruler
[Hide]

Show/Hide Toolbars
[Toggle]
Show/Hide Toolbars
[Lock; Show]
Show/Hide Toolbars
[Include Edit Record Toolbar; Lock; Hide]
Show/Hide Toolbars
[Include Edit Record Toolbar; Lock; Toggle]

View As
[Cycle]
View As
[View as Form]
View As
[View as List]
View As
[View as Table]

End If

Files

If [1]

Close Data File [File ID: ; File ID:]
Close Data File [File ID: $FileID]

Close File [Current File]
Close File [“Self”]

Convert File [Method: Add; Character Set: “Mac Roman”; Field Mapping: Source field 1 import to ;]
Convert File [Method: Add; Character Set: “Mac Roman”; Field Mapping: Source field 1 import to ;]
[No dialog]
Convert File [Method: Add; Character Set: “Mac Roman”; Field Mapping: Source field 1 import to ;]
[No dialog; Verify SSL Certificates]
Convert File [Skip index creation for FileMaker files; Method: Add; Character Set: “Mac Roman”; Field Mapping: Source field 1 import to ;]
Convert File [Skip index creation for FileMaker files; Method: Add; Character Set: “Mac Roman”; Field Mapping: Source field 1 import to ;]
[Verify SSL Certificates]
Convert File [Skip index creation for FileMaker files; Source: “$DataSource” OR “file:../../../fmIDE_keyboard_buffer.txt”; Fields Name Row: -1; Predefined: No; Method: Add; Character Set: “Mac Roman”; Field Mapping: Source field 1 import to ;]
[No dialog; Verify SSL Certificates]
Convert File [Skip index creation for FileMaker files; Method: Add; Character Set: “Mac Roman”; Field Mapping: Source field 1 import to ;]
[No dialog; Verify SSL Certificates]
Convert File [Open file after conversion]
Convert File [Open file after conversion]
[No dialog]
Convert File [Open file after conversion; Skip index creation for FileMaker files]

[No dialog]

Convert File [Open file after conversion; Skip index creation for FileMaker files; Source: “$DataSource” OR “file:../../..
/fmIDE_keyboard_buffer.txt”; Fields Name Row: -1; Predefined: No; Method: Add; Character Set: “Mac Roman”; Field Mapping: Source field 1 import to ;]
[No dialog]

Convert File [Open file after conversion; Skip index creation for FileMaker files; XML (from http): http:xml; XSL (from calculation): $XsltFilePath; Method: Add; Character Set: “Mac Roman”]
[No dialog; Data contains column names]

Convert File [Open file after conversion; Skip index creation for FileMaker files; XML (from file): RESULTSET.xml; XSL (from file): FMPXMLRESULT_XSLT_CreateXMLImportTemplate.xsl; Method: Add; Character Set: “Mac Roman”; Field Mapping: Source field 1 import to ;
Source field 2 import to ;
Source field 3 import to ;
Source field 4 import to ;
Source field 5 import to ;
Source field 6 import to ;
Source field 7 import to ;
Source field 8 import to ;
Source field 9 import to ;
Source field 10 import to ;
Source field 11 import to ;
Source field 12 import to ;
Source field 13 import to ;
Source field 14 import to ;
Source field 15 import to ;
Source field 16 import to ;
Source field 17 import to ;
Source field 18 import to ;
Source field 19 import to ;
Source field 20 import to ;
Source field 21 import to ;
Source field 22 import to ;
Source field 23 import to ;
Source field 24 import to ;
Source field 25 import to ;
Source field 26 import to ;
Source field 27 import to ;
Source field 28 import to ;
Source field 29 import to ;
Source field 30 import to ;]
[No dialog; Verify SSL Certificates; Data contains column names]

Convert File [Open file after conversion; Skip index creation for FileMaker files; Source: “$DataSource” OR “file:../../..
/fmIDE_keyboard_buffer.txt”; Fields Name Row: -1; Predefined: No; Method: Add; Character Set: “Mac Roman”; Field Mapping: Source field 1 import to ;]
[No dialog; Verify SSL Certificates]

Convert File [Open file after conversion; XML (from http): http:xml; XSL (from file): $PathXSLT]

Create Data File [; Create folders: Off]

Create Data File [; Create folders: On]

Create Data File [“abc.def” ; Create folders: Off]

Delete File [Target file:]

Delete File [Target file: “"byebye.csv"”]

Get Data File Position [File ID: ; Target:]

Get Data File Position [File ID: $FileID ; Target: $Pos]

Get Data File Position [File ID: $FileID ; Target: TestTable::TextField1]

Get File Exists [; Target:]

Get File Exists [“abc.fmp12” ; Target: $FileExists]

Get File Size [; Target:]

Get File Size [“abc.fmp12” ; Target: $FileSize]

New File

Open Data File [; Target:]

Open Data File [“abc.def” ; Target: TestTable::NumberField1]

Open File [<unknown>]
[Open hidden]

Open File [“Self”]
[Open hidden]

Open File [“Self”]
[Open hidden]

Print [ ]

Print [ ]
[No dialog]

Print [Records being browsed; All Pages; Orientation: Portrait; Paper size: 8,5" x 11"]
[Restore: drucker.werkheim-hamburg.de; No dialog]

Print [Records being browsed; All Pages; Orientation: Portrait; Paper size: 8,5" x 11"]
[Restore: 192.168.1.1]

Print [Records being browsed; All Pages; Orientation: Portrait; Paper size: 8,5" x 11"]
[Restore: printer.fmworkmate.com]

Print [Records being browsed; All Pages; Orientation: Portrait; Paper size: 8,5" x 11"]
[Restore: drücker.günther.com]

#FM Print options

Print [Records being browsed; All Pages; Orientation: Portrait; Paper size: 8,26" x 11,69"]
[Restore: hp psc 1310 series USB]

Print [Current record; All Pages; Orientation: Portrait; Paper size: 8,26" x 11,69"]
[Restore: hp psc 1310 series USB]

Print [Blank record, as formatted; All Pages; Orientation: Portrait; Paper size: 8,26" x 11,69"]
[Restore: hp psc 1310 series USB]

Print [Blank record, with boxes; All Pages; Orientation: Portrait; Paper size: 8,26" x 11,69"]
[Restore: hp psc 1310 series USB]

Print [Blank record, with underlines; All Pages; Orientation: Portrait; Paper size: 8,26" x 11,69"]
[Restore: hp psc 1310 series USB]

Print [Blank record, with placeholder text; All Pages; Orientation: Portrait; Paper size: 8,26" x 11,69"]
[Restore: hp psc 1310 series USB]

#Layout Print options

Print [Records being browsed; Pages: 2 to 2; Orientation: Portrait; Paper size: 8,26" x 11,69"]
[Restore: hp psc 1310 series USB]

Print [Records being browsed; Pages: 2 to 2; Number of copies: 4; collated; Orientation: Portrait; Paper size: 8,26" x 11,69"]
[Restore: hp psc 1310 series USB]

Print [Records being browsed; All Pages; Number pages from: 20; Orientation: Portrait; Paper size: 8,26" x 11,69"]
[Restore: hp psc 1310 series USB]

Print Setup [ ]

Print Setup [Orientation: Portrait; Paper size: 8,26" x 11,69"]
[Restore]

Print Setup [Orientation: Portrait; Paper size: 11,69" x 16,54"]
[Restore; No dialog]

Print Setup [Orientation: Landscape; Paper size: 8,27" x 11,69"; Scaling: 50%]
[Restore]

Read from Data File [File ID: ; Amount (bytes): ; Target: ; Read as: Bytes]

Read from Data File [File ID: ; Amount (bytes): ; Target: ; Read as: UTF-8]

Read from Data File [File ID: ; Amount: ; Target: ; Read as: UTF-16]

Read from Data File [File ID: $FileID ; Amount: 123 ; Target: TestTable::MyGlobal_g ; Read as: UTF-16]

Read from Data File [File ID: $FileID ; Amount (bytes): 123 ; Target: $target ; Read as: UTF-8]

Read from Data File [File ID: $FileID ; Amount (bytes): 123 ; Target: $target ; Read as: Bytes]

Recover File [ ]
Recover File [ ]
[No dialog]
Recover File [“$file”]
[No dialog]

Rename File [Source file: ; New name:]
Rename File [Source file: “$source” ; New name:]
Rename File [Source file: “$source” ; New name: "New Name"]
Rename File [Source file: ; New name: "New Name"]

Save a Copy as [Create folders:No]
[copy of current file]
Save a Copy as [Create folders:No]
[clone (no records)]
Save a Copy as [Create folders:No]
[compacted copy (smaller)]
Save a Copy as [Create folders:No]
[self-contained copy (single file)]
Save a Copy as [“$test”; Automatically open; Create email; Create folders:No]
[copy of current file]
Save a Copy as [“file:Test.fmp12”; Create folders:No]
[clone (no records)]

Save a Copy as XML [Window name: ; Destination file: <unknown>]
Save a Copy as XML [Window name: $window ; Destination file: <unknown>]
Save a Copy as XML [Window name: $window ; Destination file: “there”]
Save a Copy as XML [Window name: $window ; Destination file: “there” ; Include details for analysis tools]
Save a Copy as XML [Window name: $window ; Destination file: “there” ; Include details for analysis tools]
Save a Copy as XML [Window name: "window" ; Destination file: “$file” ; Include details for analysis tools]

Set Data File Position [File ID: ; New position:]
Set Data File Position [File ID: $FileID ; New position:]
Set Data File Position [File ID: ; New position: 123]
Set Data File Position [File ID: $FileID ; New position:]
Set Data File Position [File ID: $FileID ; New position: $Pos]

Set Multi-User [On]
Set Multi-User [On (Hidden)]
Set Multi-User [Off]

Set Use System Formats [On]
Set Use System Formats [Off]

Write to Data File [File ID: ; Data source: ; Write as: UTF-16 ; Append line feed: On]
Write to Data File [File ID: ; Data source: ; Write as: UTF-16 ; Append line feed: On]
Write to Data File [File ID: $FileID ; Data source: TestTable::TextField1 ; Write as: UTF-8 ; Append line feed: Off]
Write to Data File [File ID: $FileID ; Data source: $data ; Write as: UTF-16 ; Append line feed: On]
End If
Accounts
If [1]
Add Account [Privilege Set: <unknown>]
Add Account [Privilege Set: <unknown>]
Add Account [Authenticate via: FileMaker; Account Name: $AccountName; Privilege Set: USER]
Add Account [Authenticate via: FileMaker; Account Name: "aaa"; Privilege Set: [Read-Only Access]]
Add Account [Authenticate via: FileMaker; Account Name: "Privilege Set deleted"; Privilege Set: <unknown>]

Add Account [Authenticate via: FileMaker; Account Name: "acc"; Privilege Set: [Read-Only Access]]

Add Account [Authenticate via: FileMaker; Account Name: $Kontoname; Password: $Passwort; Privilege Set: [Data Entry Only]]
[Expire password]

Add Account [Authenticate via: FileMaker; Account Name: $Kontoname; Password: $Passwort; Privilege Set: [Read-Only Access]]
[Expire password]

Add Account [Authenticate via: FileMaker; Account Name: $Kontoname; Password: $Passwort; Privilege Set: USER]
[Expire password]

Add Account [Authenticate via: External Server; Group Name:$Groupname; Privilege Set: USER]

Add Account [Authenticate via: Apple Account; Account Name: $Kontoname; Privilege Set: USER]

Add Account [Authenticate via: Amazon; Account Name: $Kontoname; Privilege Set: USER]

Add Account [Authenticate via: Google; Account Name: $Kontoname; Privilege Set: USER]

Add Account [Authenticate via: Microsoft Entra ID; Account Name: $Kontoname; Privilege Set: USER]

Add Account [Authenticate via: Microsoft Entra ID; Group Name:$Groupname; Privilege Set: USER]

Add Account [Authenticate via: Custom OAuth; Account Name: $Username; Privilege Set: USER]

Add Account [Authenticate via: Custom OAuth; Group Name:$Groupname; Privilege Set: USER]

Change Password [ ]

Change Password [ ]
[No dialog]

Change Password [Old Password: "old"]
[No dialog]

Change Password [Old Password: $PasswortAlt; New Password: $PasswortNeu]

Change Password [Old Password: $PasswortAlt; New Password: $PasswortNeu]
[No dialog]

Delete Account [ ]

Delete Account [Account Name: $Kontoname]

Enable Account [ ]
[Activate]

Enable Account [Account Name: $Kontoname]
[Activate]

Enable Account [Account Name: $Kontoname]
[Deactivate]

Re-Login [ ]
[No dialog]

Re-Login [Password: "PW"]
[No dialog]

Re-Login [Account Name: $Kontoname; Password: $Passwort]
[No dialog]

Reset Account Password [ ]

Reset Account Password [ ]
[Expire password]

Reset Account Password [Account Name: "acc"; New Password: "New Password"]

Reset Account Password [Account Name: $Kontoname; New Password: $PasswortNeu]
[Expire password]

End If

Artificial Intelligence

If [1]

Configure AI Account

Configure AI Account [Model Provider: OpenAI]

Configure AI Account [Account Name:"MyChatGPT"; Model Provider: OpenAI; API key:$Secret]

Configure AI Account [Account Name:"MyCohere"; Model Provider: Cohere; API key:$Secret]

Configure AI Account [Account Name:"MyCustomAI"; Model Provider: Custom; Endpoint:"http://example.com/endpoint"; API key:$Secret]

Configure AI Account [Account Name:"MyCustomAI"; Model Provider: Custom; Endpoint:"http://example.com/endpoint"; API key:$Secret]

Configure AI Account [Account Name:"MyChatGPT"; Model Provider: Custom; API key:$Secret]

Configure Machine Learning Model [Operation: Unload ; Name:]

Configure Machine Learning Model [Operation: General ; Name: "MyGeneral" ; From: TestTable::TextField1[2]]

Configure Machine Learning Model [Operation: General ; Name: "MyGeneral" ; From: TestTable::MyGlobal_g[$i]]

Configure Machine Learning Model [Operation: Vision ; Name: "MyVision" ; From: TestTable::TextField1[2]]

Configure Machine Learning Model [Operation: Unload ; Name: "MyModel"]

Configure Machine Learning Model [Operation: Vision ; Name: "MyVision" ; From:]

Configure Machine Learning Model [Operation: Vision ; Name: "MyVision" ; From:]

#FM22

Configure Prompt Template [Model Provider: OpenAI; Template Type: SQL Query]

Configure Prompt Template [Template Name:$TemplateName; Model Provider: Anthropic; Template Type: SQL Query]

Configure Prompt Template [Template Name:$TemplateName; Model Provider: Cohere; Template Type: SQL Query]

Configure Prompt Template [Template Name:$TemplateName; Model Provider: Custom; Template Type: SQL Query]

Configure Prompt Template [Template Name:$TemplateName; Model Provider: OpenAI; Template Type: SQL Query; SQL Prompt:"Generate a fully formed SQL query based on following rules:¶ 1. Enclose all table and field names in double quotes.¶ 2. Format dates as \"DATE 'YYYY-MM-DD'\", times as \"TIME 'HH:MM:SS'\" and timestamps as \"TIMESTAMP 'YYYY-MM-DD HH:MM:SS'\".¶ 3. Return queries in plain text (not JSON).¶ 4. Use \"FETCH FIRST n ROW ONLY\" instead of \"LIMIT\".¶ 5. Support single queries only.¶ 6. No semicolon is needed at the end of SQL query.¶ 7. Don't generate nested SQL queries.¶ 8. Use \"LIKE\" instead of \"ILIKE\".¶ 9. Keep all comparisons case-sensitive.¶ 10. Do not include fields that are not included in the question.¶ 11. Use unquoted ROWID in queries.¶ 12. Only utilize the following database schema:¶ :schema:"]

Configure Prompt Template [Template Name:$TemplateName; Model Provider: OpenAI; Template Type: SQL Query; Natural Language Prompt:"The answer should be returned in plain text, not in JSON.¶ Break down response if it is too long."]

Configure Prompt Template [Template Name:$TemplateName; Model Provider: OpenAI; Template Type: SQL Query; SQL Prompt:"Generate a fully formed SQL query based on following rules:¶ 1. Enclose all table and field names in double quotes.¶ 2. Format dates as \"DATE 'YYYY-MM-DD'\", times as \"TIME 'HH:MM:SS'\" and timestamps as \"TIMESTAMP 'YYYY-MM-DD HH:MM:SS'\".¶ 3. Return queries in plain text (not JSON).¶ 4. Use \"FETCH FIRST n ROW ONLY\" instead of \"LIMIT\".¶ 5. Support single queries only.¶ 6. No semicolon is needed at the end of SQL query.¶ 7. Don't generate nested SQL queries.¶ 8. Use \"LIKE\" instead of \"ILIKE\".¶ 9. Keep all comparisons case-sensitive.¶ 10. Do not include fields that are not included in the question.¶ 11. Use unquoted ROWID in queries.¶ 12. Only utilize the following database schema:¶ :schema:"; Natural Language Prompt:"The answer should be returned in plain text, not in JSON.¶ Break down response if it is too long."]

Configure Prompt Template [Template Name:$TemplateName; Model Provider: OpenAI; Template Type: Find Request]

Configure Prompt Template [Template Name:$TemplateName; Model Provider: OpenAI; Template Type: Find Request; Find Request Prompt:"Generate and only return a JSON layout query…"]

Configure Prompt Template [Template Name:$TemplateName; Model Provider: OpenAI; Template Type: RAG Prompt]

Configure Prompt Template [Template Name:$TemplateName; Model Provider: OpenAI; Template Type: RAG Prompt; RAG Prompt:"Provide a comprehensive and informative answer to the question…"]

Configure RAG Account

Configure RAG Account

Configure RAG Account [Account Name:$MyRagAccount; Endpoint:$Endpoint; API key:$MySecretApiKey]

Configure RAG Account [Account Name:$MyRagAccount; Endpoint:$Endpoint; API key:$MySecretApiKey; Verify SSL Certificates]

Configure RAG Account [Account Name:$MyRagAccount; API key:$MySecretApiKey; Verify SSL Certificates]

Configure RAG Account [Verify SSL Certificates]

Configure Regression Model

Configure Regression Model [Action: Train Model; Algorithm: Random Forest]

Configure Regression Model [Action: Train Model; Model Name:"Fred"; Algorithm: Random Forest; Training Vectors Field: TestTable::TextField1; Training Target Field: TestTable::TextField_lotsTurnedOn; Skip empty or invalid records; Parameters:$Parameters; Save Model To: TestTable::ContainerField1]

Configure Regression Model [Action: Save Model]

Configure Regression Model [Action: Save Model; Model Name:"Fred"; Save Model To: TestTable::ContainerField1]

Configure Regression Model [Action: Save Model; Model Name:"Fred"; Save Model To: $UpdatedModel[$Rep]]

Configure Regression Model [Action: Save Model; Model Name:"Fred"; Save Model To: TestTable::ContainerField1[$Rep]]

Configure Regression Model [Action: Load Model]

Configure Regression Model [Action: Load Model; Model Name:"Fred"; Load Model From: TestTable::ContainerField1]

Configure Regression Model [Action: Load Model; Model Name:"Fred"; Load Model From: TestTable::ContainerField1 [$Rep]]

Configure Regression Model [Action: Load Model; Model Name:"Fred"; Load Model From: $UpdatedModel[$Rep]]

Configure Regression Model [Action: Unload Model]

Configure Regression Model [Action: Unload Model; Model Name:"Fred"]

Configure Regression Model [Action: Train Model; Model Name:DeletedFields::<Field Missing>; Algorithm: Random Forest; Training Vectors Field: DeletedFields::<Field Missing>; Training Target Field: DeletedFields::<Field Missing>; Skip empty or invalid records; Parameters:DeletedFields::<Field Missing>; Save Model To: DeletedFields::<Field Missing>]

Fine-Tune Model

Fine-Tune Model [Training Data: Table]

Fine-Tune Model [Training Data: Table]

Fine-Tune Model [Training Data: File]

Fine-Tune Model [Training Data: Table]

Fine-Tune Model [Account Name:$Name; Base Model:$BaseModel; Training Data: Table]

Fine-Tune Model [Account Name:$Name; Base Model:$BaseModel; Training Data: Table; “TestTable”]

Fine-Tune Model [Account Name:$Name; Base Model:$BaseModel; Training Data: Table; “TestTable”; Completion Field: TestTable::TextField1]

Fine-Tune Model [Account Name:$Name; Base Model:$BaseModel; Training Data: Table; “TestTable”; Response Target: TestTable::MyGlobal_g]

Fine-Tune Model [Account Name:$Name; Base Model:$BaseModel; Training Data: Table; “TestTable”; Completion Field: TestTable::TextField1; Response Target: TestTable::MyGlobal_g]

Fine-Tune Model [Account Name:$Name; Base Model:$BaseModel; Training Data: Table; “TestTable”; Completion Field: TestTable::TextField1; Response Target: TestTable::MyGlobal_g[$Rep]]

Fine-Tune Model [Account Name:$Name; Base Model:$BaseModel; Training Data: Table; “TestTable”; Completion Field: TestTable::TextField1; Response Target: $ResponseTarget[$Rep]]

Fine-Tune Model [Account Name:$Name; Base Model:$BaseModel; Training Data: Table; “TestTable”; Completion Field: TestTable::TextField1; Response Target: $ResponseTarget[$Rep]; Parameters:$Param]

Fine-Tune Model [Account Name:$Name; Base Model:$BaseModel; Training Data: File]

Fine-Tune Model [Account Name:$Name; Base Model:$BaseModel; Training Data: File; “file:TrainingData.xyz”]

Fine-Tune Model [Account Name:$Name; Base Model:$BaseModel; Training Data: File; “$TrainingDataFilePath”]

Fine-Tune Model [Account Name:$Name; Base Model:$BaseModel; Training Data: File; “$TrainingDataFilePath”; Response Target: TestTable::MyGlobal_g]

Fine-Tune Model [Account Name:$Name; Base Model:$BaseModel; Training Data: File; “$TrainingDataFilePath”; Response Target: TestTable::MyGlobal_g; Parameters:JSONSetElement ("{}"
;["what_params" ; "don't know" ; JSONString]
)]

Fine-Tune Model [Account Name:$Name; Base Model:$BaseModel; Training Data: File; Response Target: TestTable::TextField1]

Fine-Tune Model [Account Name:$Name; Base Model:$BaseModel; Training Data: File; Response Target: TestTable::

MyGlobal_g; Parameters:JSONSetElement ("{}"
;["what_params" ; "don't know" ; JSONString]
)]

Fine-Tune Model [Account Name:$Name; Base Model:$BaseModel; Training Data: File; Parameters:JSONSetElement ("{}"
;["what_params" ; "don't know" ; JSONString]
)]

Fine-Tune Model [Account Name:$Name; Base Model:$BaseModel; Training Data: File]

Fine-Tune Model [Account Name:$Name; Base Model:$BaseModel; Training Data: File; Response Target: $TargetVar]

#Extra Label

Fine-Tune Model [Account Name:$Name; Base Model:$BaseModel; Training Data: File; “$TrainingDataFilePath”; Response Target: $ResponseTarget]

Fine-Tune Model [Account Name:$Name; Base Model:$BaseModel; Training Data: File]

Generate Response from Model [Agentic mode:Off; Stream:Off]

Generate Response from Model [Agentic mode:On; Stream:Off]

Generate Response from Model [Agentic mode:Off; Stream:On]

Generate Response from Model [Agentic mode:Off; Stream:On]

Generate Response from Model [Account Name:$AccountName; Model:$Model; User Prompt:$UserPrompt; Agentic mode:Off; Stream:Off]

Generate Response from Model [Account Name:$AccountName; Model:$Model; User Prompt:$UserPrompt; Agentic mode:On; Stream:Off]

Generate Response from Model [Account Name:$AccountName; Model:$Model; User Prompt:$UserPrompt; Agentic mode:On; Response:$TargetResponse; Tool Calls from Model: $TargetToolCallsFromModel; Instructions:$InstructionsCalculation; Messages: $TargetMessages; Save Message History To:$SaveMessageHistoryVariable[$Rep]; Message History Count:$SaveMessageHistoryCountCalc; Temperature:$TemparatureCalculation; Tool Definitions:$ToolDefinitionsCalc; Stream:On; Parameters:$Parameters; Web Viewer:$WebViewer; Function Name:$JavascriptFunctionName]

Generate Response from Model [Account Name:$AccountName; Model:$Model; Agentic mode:On; Response:$TargetResponse; Tool Calls from Model: $TargetToolCallsFromModel; Instructions:$InstructionsCalculation; Messages:$TargetMessages; Save Message History To:$SaveMessageHistoryVariable[$Rep]; Message History Count:$SaveMessageHistoryCountCalc; Temperature:$TemparatureCalculation; Tool Definitions:$ToolDefinitionsCalc; Stream:On; Parameters:$Parameters]

Generate Response from Model [Account Name:$AccountName; Model:$Model; Agentic mode:On; Response:$TargetResponse; Tool Calls from Model: $TargetToolCallsFromModel; Instructions:$InstructionsCalculation; Messages:$TargetMessages; Save Message History To:$SaveMessageHistoryVariable[$Rep]; Message History Count:$SaveMessageHistoryCountCalc; Stream:On]

Generate Response from Model [Account Name:$AccountName; Model:$Model; Agentic mode:On; Response:$TargetResponse; Tool Calls from Model: $TargetToolCallsFromModel; Messages: $TargetMessages; Save Message History To:$SaveMessageHistoryVariable[$Rep]; Message History Count:$SaveMessageHistoryCountCalc; Stream:On]

Generate Response from Model [Account Name:$AccountName; Model:$Model; Agentic mode:On; Response:$TargetResponse; Tool Calls from Model: $TargetToolCallsFromModel; Messages: $TargetMessages; Save Message History To:$SaveMessageHistoryVariable[$Rep]; Message History Count:$SaveMessageHistoryCountCalc; Stream:On]

Generate Response from Model [Agentic mode:On; Messages: $TargetMessages; Stream:Off]

#/FM22

Insert Embedding

Insert Embedding [ ]

Insert Embedding [Embedding Model:$EmbeddingModel]

Insert Embedding [Account Name:"MyChatGPT"; Embedding Model:TestTable::MyGlobal_g; Input:TestTable::TextField1]

Insert Embedding [Account Name:"MyChatGPT"; Embedding Model:TestTable::TextField1; Input:TestTable::TextField1; Target: TestTable::TextField1[$Rep]]

Insert Embedding [Account Name:"MyChatGPT"; Embedding Model:TestTable::TextField1; Input:TestTable::TextField1]

Insert Embedding [Account Name:"MyChatGPT"; Embedding Model:Contacts::Name; Input:TestTable::TextField1]

Insert Embedding [Account Name:"MyChatGPT"; Embedding Model:TestTable::TextField1; Input:TestTable::TextField1]

Insert Embedding [Account Name:"MyChatGPT"; Embedding Model:TestTable::TextField1; Input:TestTable::TextField1; Target: TestTable::TextField1[$Rep]]

Insert Embedding [Account Name:"MyChatGPT"; Embedding Model:TestTable::TextField1; Input:TestTable::TextField1]

Insert Embedding [Account Name:"MyChatGPT"; Embedding Model:Contacts::Name; Input:TestTable::TextField1]

Insert Embedding in Found Set

Insert Embedding in Found Set [ ]

Insert Embedding in Found Set [ ]

Insert Embedding in Found Set [Account Name:"MyChatGPT"; Embedding Model:TestTable::TextField_lotsTurnedOn]

Insert Embedding in Found Set [Account Name:"MyChatGPT"; Embedding Model:TestTable::TextField_lotsTurnedOn; Source Field: Contacts::Name]

Insert Embedding in Found Set [Account Name:"MyChatGPT"; Embedding Model:"Model"; Source Field: TestTable::TextField1; Target Field: Contacts::Name]

Insert Embedding in Found Set [Account Name:"MyChatGPT"; Embedding Model:"Model"; Source Field: TestTable::TextField1; Target Field: Contacts::Name; Replace target contents]

Insert Embedding in Found Set [Account Name:"MyChatGPT"; Embedding Model:"Model"; Source Field: TestTable::TextField1; Target Field: Contacts::Name; Replace target contents; Continue on error; Show summary; Parameters:"ParamsJSON"]

Insert Embedding in Found Set [Account Name:"MyChatGPT"; Embedding Model:"Model"; Source Field: Contacts::Name; Replace target contents; Parameters:"ParamsJSON"]

#FM22

Perform Find by Natural Language [Get: Found Set]

Perform Find by Natural Language [Get: Found Set as JSON]

Perform Find by Natural Language [Get: Find Request as JSON]

#Bug in fm22: Prompt Template Name is not passed to the clipboard

Perform Find by Natural Language [Account Name:$AccountName; Model:$Model; Prompt:$Prompt; Get: Found Set; Parameters:$Parameters; Template Name:$PromptTemplateName]

Perform Find by Natural Language [Account Name:$AccountName; Model:$Model; Prompt:$Prompt; Get: Found Set as JSON; Parameters:$Parameters; Response Target:TestTable::TextField1[$Rep]; Template Name: $PromptTemplateName]

Perform Find by Natural Language [Account Name:$AccountName; Model:$Model; Prompt:$Prompt; Get: Found Set as JSON; Parameters:$Parameters; Response Target:TestTable::TextField1[$Rep]; Template Name: $PromptTemplateName]

Perform Find by Natural Language [Account Name:$AccountName; Model:$Model; Prompt:$Prompt; Get: Found Set as JSON; Parameters:$Parameters; Response Target:TestTable::TextField1[$Rep]]

Perform Find by Natural Language [Account Name:$AccountName; Model:$Model; Prompt:$Prompt; Get: Found Set as JSON; Parameters:$Parameters; Response Target:TestTable::TextField1[$Rep]]

#RAG Action Add Data (From Text)

Perform RAG Action [Action: Add Data; RAG Data: From Text]

Perform RAG Action [Account Name:$RagAcccount; Action: Add Data; RAG Data: From Text]

Perform RAG Action [Account Name:$RagAcccount; Space ID:$SpaceID; Action: Add Data; RAG Data: From Text; "Rag data"]

#RAG Action Add Data (From File)

Perform RAG Action [Account Name:$RagAcccount; Space ID:$SpaceID; Action: Add Data; RAG Data: From File]

Perform RAG Action [Account Name:$RagAcccount; Space ID:$SpaceID; Action: Add Data; RAG Data: From File;

“$InputFile”]

#RAG Action Add Data (From File (Async))

Perform RAG Action [Account Name:$RagAcccount; Space ID:$SpaceID; Action: Add Data; RAG Data: From File (Async)]

Perform RAG Action [Account Name:$RagAcccount; Space ID:$SpaceID; Action: Add Data; RAG Data: From File (Async); “$InputFile”]

#RAG Action Add Data (From Container)

Perform RAG Action [Account Name:$RagAcccount; Space ID:$SpaceID; Action: Add Data; RAG Data: From Container]

Perform RAG Action [Account Name:$RagAcccount; Space ID:$SpaceID; Action: Add Data; RAG Data: From Container; TestTable::ContainerField1]

Perform RAG Action [Account Name:$RagAcccount; Space ID:$SpaceID; Action: Add Data; RAG Data: From Container; TestTable::ContainerField1_RC[$Rep]]

#RAG Action Add Data (From Container (Async))

Perform RAG Action [Account Name:$RagAcccount; Space ID:$SpaceID; Action: Add Data; RAG Data: From Container (Async)]

Perform RAG Action [Account Name:$RagAcccount; Space ID:$SpaceID; Action: Add Data; RAG Data: From Container (Async); TestTable::ContainerField1_RC]

Perform RAG Action [Account Name:$RagAcccount; Space ID:$SpaceID; Action: Add Data; RAG Data: From Container (Async); TestTable::ContainerField1[$Rep]]

#RAG Action Send Prompt

Perform RAG Action [Action: Send Prompt; Stream:Off]

Perform RAG Action [Account Name:$RagAcccount; Space ID:$SpaceID; Action: Send Prompt; "Prompt"; AI Account Name $AccountName; Model:$Model; Stream:Off]

Perform RAG Action [Account Name:$RagAcccount; Space ID:$SpaceID; Action: Send Prompt; "Prompt"; AI Account Name $AccountName; Model:$Model; Stream:On]

Perform RAG Action [Account Name:$RagAcccount; Space ID:$SpaceID; Action: Send Prompt; "Prompt"; AI Account Name $AccountName; Model:$Model; Stream:On; Prompt Template Name:$PromptTemplateName]

Perform RAG Action [Account Name:$RagAcccount; Space ID:$SpaceID; Action: Send Prompt; "Prompt"; AI Account Name $AccountName; Model:$Model; Stream:On; Prompt Template Name:$PromptTemplateName; Response Target: $ResponseTarget]

Perform RAG Action [Account Name:$RagAcccount; Space ID:$SpaceID; Action: Send Prompt; "Prompt"; AI Account Name $AccountName; Model:$Model; Stream:On; Prompt Template Name:$PromptTemplateName; Response Target: $ResponseTarget[$Rep]]

Perform RAG Action [Account Name:$RagAcccount; Space ID:$SpaceID; Action: Send Prompt; "Prompt"; AI Account Name $AccountName; Model:$Model; Stream:On; Prompt Template Name:$PromptTemplateName; Response Target: TestTable::ContainerField1[$Rep]; Parameters:$Parameters]

Perform RAG Action [Account Name:$RagAcccount; Space ID:$SpaceID; Action: Send Prompt; "Prompt"; AI Account Name $AccountName; Model:$Model; Stream:On; Prompt Template Name:$PromptTemplateName; Response Target: $ResponseTarget; Parameters:$Parameters]

Perform RAG Action [Account Name:$RagAcccount; Space ID:$SpaceID; Action: Send Prompt; "Prompt"; AI Account Name $AccountName; Model:$Model; Stream:On; Response Target:$ResponseTarget; Parameters:$Parameters]

#RAG Action Remove Data

Perform RAG Action [Action: Remove Data]

Perform RAG Action [Account Name:$RagAcccount; Space ID:$SpaceID; Action: Remove Data]

#The following steps have 'left overs' - a label or a hanging semicolon - caused be emptying a selected element - which is not detectable in the clipboard XML and which disappear if you copy paste the step

Perform RAG Action [Account Name:$RagAcccount; Space ID:$SpaceID; Action: Add Data; RAG Data: From File]

Perform RAG Action [Account Name:$RagAcccount; Space ID:$SpaceID; Action: Add Data; RAG Data: From File (Async)]

Perform RAG Action [Account Name:$RagAcccount; Space ID:$SpaceID; Action: Send Prompt; "Prompt"; AI Account Name $AccountName; Model:$Model; Stream:On; Response Target:$ResponseTarget]

Perform RAG Action [Account Name:$RagAcccount; Space ID:$SpaceID; Action: Send Prompt; "Prompt"; AI Account Name $AccountName; Model:$Model; Stream:On; Response Target:$ResponseTarget]

#Fixed:

Perform RAG Action [Account Name:$RagAcccount; Space ID:$SpaceID; Action: Add Data; RAG Data: From File]

Perform RAG Action [Account Name:$RagAcccount; Space ID:$SpaceID; Action: Add Data; RAG Data: From File (Async)]

Perform RAG Action [Account Name:$RagAcccount; Space ID:$SpaceID; Action: Send Prompt; "Prompt"; AI Account Name $AccountName; Model:$Model; Stream:On; Response Target:$ResponseTarget]

Perform RAG Action [Account Name:$RagAcccount; Space ID:$SpaceID; Action: Send Prompt; "Prompt"; AI Account Name $AccountName; Model:$Model; Stream:On; Response Target:$ResponseTarget]

#/FM22

If [1 // Perform Semantic Find]

Perform Semantic Find [All records]

Perform Semantic Find [Current found set]

Perform Semantic Find [All records]

Perform Semantic Find [All records]

Perform Semantic Find [All records]

Perform Semantic Find [Image:$MyImage; All records]

Perform Semantic Find [ ]

Perform Semantic Find [Condition: greater than]

Perform Semantic Find [Condition: less than]

Perform Semantic Find [Condition: equal to]

Perform Semantic Find [Condition: greater than or equal to]

Perform Semantic Find [Condition: less than or equal to]

Perform Semantic Find [Account Name:$AccountName; Embedding Model:$EmbeddingModel; Image:$MyImage; All records]

Perform Semantic Find [Image:$MyImage; All records]

Perform Semantic Find [Account Name:"MyChatGPT"; Embedding Model:"Model"; Text: TestTable::TextField1; All records]

Perform Semantic Find [Account Name:"MyChatGPT"; Embedding Model:"Model"; Text: TestTable::TextField1; Current found set]

Perform Semantic Find [Account Name:"MyChatGPT"; Embedding Model:"Model"; Text: TestTable::TextField1; Current found set; TestTable::TextField1]

Perform Semantic Find [Account Name:"MyChatGPT"; Embedding Model:"Model"; Text: TestTable::TextField1; Current found set; TestTable::TextField1; Return count: TestTable::TextField1]

Perform Semantic Find [Account Name:"MyChatGPT"; Embedding Model:"Model"; Text: TestTable::TextField1; Current found set; TestTable::TextField1; Return count: TestTable::TextField1; Condition: greater than]

Perform Semantic Find [Account Name:"MyChatGPT"; Embedding Model:"Model"; Text: TestTable::TextField1; Current found set; TestTable::TextField1; Return count: TestTable::TextField1; Condition: greater than]

Perform Semantic Find [Account Name:"MyChatGPT"; Embedding Model:"Model"; Text: TestTable::TextField1; Current found set; TestTable::TextField1; Return count: TestTable::TextField1; Condition: greater than; Value:1/2]

Perform Semantic Find [Account Name:"MyChatGPT"; Embedding Model:"Model"; Text: TestTable::TextField1; Current found set; TestTable::TextField1; Return count: TestTable::TextField1; Condition: greater than; Value:1/2]

Perform Semantic Find [Account Name:"MyChatGPT"; Embedding Model:"Model"; Text: TestTable::TextField1; Current found set; TestTable::TextField1; Return count: TestTable::TextField1; Value:1/2]

Perform Semantic Find [Account Name:"MyChatGPT"; Embedding Model:"Model"; Text: TestTable::TextField1; Current found set; TestTable::TextField1; Return count: TestTable::TextField1; Value:1/2]

Perform Semantic Find [Account Name:"MyChatGPT"; Embedding Model:"Model"; Text: TestTable::TextField1; Current found set; TestTable::TextField1; Return count: TestTable::TextField1; Condition: greater than; Value:1/2]

End If

#FM22

Perform SQL Query by Natural Language [Options specified: From list; Action: Query; Data Tables: From list; [ ]; Stream: Off]

#Stream

Perform SQL Query by Natural Language [Options specified: From list; Action: Query; Data Tables: From list; [ ]; Stream: On]

#Actions no params

Perform SQL Query by Natural Language [Account Name:$AccountName; Model:$Model; Prompt:$Prompt; Options specified: From list; Action: Query; Data Tables: From list; [ ]; Stream:Off]

Perform SQL Query by Natural Language [Account Name:$AccountName; Model:$Model; Prompt:$Prompt; Options specified: From list; Action: Query for Data Only; Data Tables: From list; [ ]; Stream:Off]

Perform SQL Query by Natural Language [Account Name:$AccountName; Model:$Model; Prompt:$Prompt; Options specified: From list; Action: Get SQL; Data Tables: From list; [ ]; Stream:Off]

Perform SQL Query by Natural Language [Account Name:$AccountName; Model:$Model; Prompt:$Prompt; Options specified: From list; Action: Get First SQL Only; Data Tables: From list; [ ]; Stream:Off]

Perform SQL Query by Natural Language [Account Name:$AccountName; Model:$Model; Prompt:$Prompt; Options specified: From list; Action: Get DDL; Data Tables: From list; [ ]; Stream:Off]

#Actions Data Tables from list full

Perform SQL Query by Natural Language [Account Name:$AccountName; Model:$Model; Prompt:$Prompt; Options specified: From list; Action: Query; Data Tables: From list; [Contacts; Contacts_TestTable; TestTable; TestTable_Contacts]; Stream:On; Prompt Template Name:$PromptTemplateName; Parameters:$Parameters; Response Target:TestTable::TextField1; Web Viewer:"WebViewer"; Function Name: "JavascriptFunction"]

Perform SQL Query by Natural Language [Account Name:$AccountName; Model:$Model; Prompt:$Prompt; Options specified: From list; Action: Query for Data Only; Data Tables: From list; [Contacts; Contacts_TestTable; TestTable; TestTable_Contacts]; Stream:On; Prompt Template Name:$PromptTemplateName; Parameters:$Parameters; Response Target:TestTable::TextField1; Web Viewer:"WebViewer"; Function Name: "JavascriptFunction"]

Perform SQL Query by Natural Language [Account Name:$AccountName; Model:$Model; Prompt:$Prompt; Options specified: From list; Action: Get SQL; Data Tables: From list; [Contacts; Contacts_TestTable; TestTable; TestTable_Contacts]; Stream:On; Prompt Template Name:$PromptTemplateName; Parameters:$Parameters; Response Target:TestTable::TextField1; Web Viewer:"WebViewer"; Function Name: "JavascriptFunction"]

Perform SQL Query by Natural Language [Account Name:$AccountName; Model:$Model; Prompt:$Prompt; Options specified: From list; Action: Get First SQL Only; Data Tables: From list; [Contacts; Contacts_TestTable; TestTable; TestTable_Contacts]; Stream:On; Prompt Template Name:$PromptTemplateName; Parameters:$Parameters; Response Target:TestTable::TextField1; Web Viewer:"WebViewer"; Function Name: "JavascriptFunction"]

Perform SQL Query by Natural Language [Account Name:$AccountName; Model:$Model; Prompt:$Prompt; Options specified: From list; Action: Get DDL; Data Tables: From list; [Contacts; Contacts_TestTable; TestTable; TestTable_Contacts]; Stream:On; Prompt Template Name:$PromptTemplateName; Parameters:$Parameters; Response Target:TestTable::TextField1; Web Viewer:"WebViewer"; Function Name: "JavascriptFunction"]

#Query Data Tables from list

Perform SQL Query by Natural Language [Account Name:$AccountName; Model:$Model; Prompt:$Prompt; Options specified: From list; Action: Query; Data Tables: From list; [Contacts; Contacts_TestTable; TestTable; TestTable_Contacts]; Stream:On; Prompt Template Name:$PromptTemplateName; Parameters:$Parameters; Response Target:TestTable::TextField1; Web Viewer:"WebViewer"; Function Name: "JavascriptFunction"]

#Query Data Tables By name

Perform SQL Query by Natural Language [Account Name:$AccountName; Model:$Model; Prompt:$Prompt; Options specified: From list; Action: Query; Data Tables: By name; Stream:On; Prompt Template Name:$PromptTemplateName; Parameters:$Parameters; Response Target:TestTable::TextField1; Web Viewer:"WebViewer"; Function Name: "JavascriptFunction"]

Perform SQL Query by Natural Language [Account Name:$AccountName; Model:$Model; Prompt:$Prompt; Options specified: From list; Action: Query; Data Tables: By name; List(
"Contacts" ;
"TestTable"
); Stream:On; Prompt Template Name:$PromptTemplateName; Parameters:$Parameters; Response Target:TestTable::TextField1; Web Viewer:"WebViewer"; Function Name: "JavascriptFunction"]

#Query Data Tables By DDL

Perform SQL Query by Natural Language [Account Name:$AccountName; Model:$Model; Prompt:$Prompt; Options

specified: From list; Action: Query; Data Tables: By DDL; Stream:On; Prompt Template Name:$PromptTemplateName; Parameters:$Parameters; Response Target:TestTable::TextField1; Web Viewer:"WebViewer"; Function Name: "JavascriptFunction"]

Perform SQL Query by Natural Language [Account Name:$AccountName; Model:$Model; Prompt:$Prompt; Options specified: From list; Action: Query; Data Tables: By DDL; "How from DDL?"; Stream:On; Prompt Template Name: $PromptTemplateName; Parameters:$Parameters; Response Target:TestTable::TextField1; Web Viewer:"WebViewer"; Function Name: "JavascriptFunction"]

#JSONOptions

Perform SQL Query by Natural Language [Account Name:$AccountName; Model:$Model; Prompt:$Prompt; Options specified: By JSON data]

Perform SQL Query by Natural Language [Account Name:$AccountName; Model:$Model; Prompt:$Prompt; Options specified: By JSON data; $JSONOptions]

#Removed stuff, where possible

Perform SQL Query by Natural Language [Options specified: From list; Action: Query; Data Tables: By DDL; Stream:On; Response Target:$ResponseTarget[$Rep]]

#/FM22

Set AI Call Logging [Off]

Set AI Call Logging [On]

Set AI Call Logging [On; Verbose]

Set AI Call Logging [On; Verbose; Truncate Messages]

Set AI Call Logging [On; Filename:"filename.ext"; Verbose; Truncate Messages]

Set AI Call Logging [On; Filename:"filename.ext"]

Set AI Call Logging [Off; Filename:"filename.ext"]

Set AI Call Logging [Off; Filename:"filename.ext"]

End If

Spelling

If [1]

Check Found Set

Check Record

Check Selection [ ]
[Select]

Check Selection [ ]

Check Selection [TestTable::TextField1]

Check Selection [<Table Missing>]
[Select]

Check Selection [TestTable::TextField1]
[Select]

Correct Word

Edit User Dictionary

Select Dictionaries

Set Dictionary [ ]
[Português (Brasil)]

Set Dictionary [ ]
[Português (Portugal)]

Set Dictionary [ ]
[Nederlands]

Set Dictionary [ ]

[Deutsch (Alte Regeln)]
Set Dictionary [ ]
[Español]
Set Dictionary [ ]
[Italiano]
Set Dictionary [ ]
[Français]
Set Dictionary [ ]
[US English (Medical)]
Set Dictionary [ ]
[Deutsch (Neue Regeln)]
Set Dictionary [ ]
[Schweizerdeutsch]
Set Dictionary [ ]
[US English]
Set Dictionary [ ]
[Svenska]
Set Dictionary [ ]
[UK English]
Set Dictionary [“file:MyBritishDictionary.ext”]
[UK English]

Spelling Options
End If
Open Menu item
If [1]
Open Edit Saved Finds
Open Favorites
Open File Options
Open Find/Replace
Open Help
Open Hosts
Open Manage Containers
Open Manage Data Sources
Open Manage Database
Open Manage Layouts
Open Manage Themes
Open Manage Value Lists
Open Script Workspace
Open Settings
Open Sharing
Open Upload to Host
End If
Miscellaneous
If [1]
#BUG 1047 Applescript Prob. fixed
#FIXME please
#TODO next friday
#TEST this!
#NOTE there must be a space after the @ symbol:
#@ Christian: THANK YOU for the cool SyntaxColoring function in the MBS Plugin!

Allow Formatting Bar [On]
Allow Formatting Bar [Off]

AVPlayer Play [Object: <Active Object>]
AVPlayer Play [Object Name: "AVPlayer"; Repetition: 1]

AVPlayer Play [Object Name: "AVPlayer"; Repetition: $Rep]

AVPlayer Play [Field: TestTable::TextField1]

AVPlayer Play [Field: TestTable::TextField1[2]]

AVPlayer Play [Field: TestTable::TextField1[$Rep]]

AVPlayer Play [URL: $URL]

AVPlayer Play [Object Name: "AVPlayer"; Repetition: 1; Presentation: Start Full Screen; Disable Interaction: No; Hide Controls: No; Position: 123; Start Offset: 1; End Offset: 234]

AVPlayer Play [Object Name: "AVPlayer"; Repetition: 2; Presentation: Start Full Screen; Disable Interaction: No; Hide Controls: No; Position: 123; Start Offset: 1; End Offset: 234]

AVPlayer Play [Field: TestTable::TextField1; Presentation: Full Screen Only; Disable Interaction: No; Hide Controls: No; Position: 123; Start Offset: 1; End Offset: 234]

AVPlayer Play [Field: TestTable::TextField1[2]; Presentation: Full Screen Only; Disable Interaction: No; Hide Controls: No; Position: 123; Start Offset: 1; End Offset: 234]

AVPlayer Play [URL: "http://www.fmworkmate.de"; Presentation: Full Screen Only; Disable Interaction: No; Hide Controls: No; Position: 123; Start Offset: 1; End Offset: 234]

AVPlayer Play [URL: "http://www.fmworkmate.de"; Disable Interaction: No; Hide Controls: No; Position: 123; Start Offset: 1; End Offset: 234]

AVPlayer Play [URL: "http://www.fmworkmate.de"; Disable Interaction: Yes; Hide Controls: No; Position: 123; Start Offset: 1; End Offset: 234]

AVPlayer Play [URL: "http://www.fmworkmate.de"; Disable Interaction: Yes; Hide Controls: Yes; Position: $abc; Start Offset: 1; End Offset: 234]

AVPlayer Play [URL: "http://www.fmworkmate.de"; Hide Controls: No; Position: $abc; Start Offset: 1; End Offset: 234]

AVPlayer Play [URL: "http://www.fmworkmate.de"; Position: $abc; Start Offset: 1; End Offset: 234]

AVPlayer Play [URL: "http://www.fmworkmate.de"; Start Offset: 1; End Offset: 234]

AVPlayer Play [URL: "http://www.fmworkmate.de"; End Offset: 234]

AVPlayer Play [URL: "http://www.fmworkmate.de"]

AVPlayer Set Options [Presentation: Start Full Screen; Disable Interaction: No; Hide Controls: No; Disable External Controls: No; Pause in Background: No; Position: 123; Start Offset: 123; End Offset: 123; Sequence: Next]

AVPlayer Set Options [Presentation: Start Full Screen]

AVPlayer Set Options [Presentation: Full Screen Only]

AVPlayer Set Options [Presentation: Start Embedded]

AVPlayer Set Options [Presentation: Audio Only]

AVPlayer Set Options [Presentation: Audio Only; Disable Interaction: No]

AVPlayer Set Options [Presentation: Audio Only; Disable Interaction: Yes]

AVPlayer Set Options [Presentation: Audio Only; Disable Interaction: Yes; Hide Controls: No]

AVPlayer Set Options [Presentation: Audio Only; Disable Interaction: Yes; Hide Controls: Yes]

AVPlayer Set Options [Presentation: Audio Only; Disable Interaction: Yes; Hide Controls: Yes; Disable External Controls: No]

AVPlayer Set Options [Presentation: Audio Only; Disable Interaction: Yes; Hide Controls: Yes; Disable External Controls: Yes; Pause in Background: No]

AVPlayer Set Options [Presentation: Audio Only; Disable Interaction: Yes; Hide Controls: Yes; Disable External Controls: Yes; Pause in Background: Yes]

AVPlayer Set Options [Presentation: Audio Only; Disable Interaction: Yes; Hide Controls: Yes; Disable External Controls: Yes; Pause in Background: Yes; Position: 123]

AVPlayer Set Options [Presentation: Audio Only; Disable Interaction: Yes; Hide Controls: Yes; Disable External Controls: Yes; Pause in Background: Yes; Position: 123; Start Offset: 1]

AVPlayer Set Options [Presentation: Audio Only; Disable Interaction: Yes; Hide Controls: Yes; Disable External Controls: Yes; Pause in Background: Yes; Position: 123; Start Offset: 1; End Offset: 456]

AVPlayer Set Options [Presentation: Audio Only; Disable Interaction: Yes; Hide Controls: Yes; Disable External Controls: Yes; Pause in Background: Yes; Position: 123; Start Offset: 1; End Offset: 456; Sequence: None]

AVPlayer Set Options [Presentation: Audio Only; Disable Interaction: Yes; Hide Controls: Yes; Disable External Controls: Yes; Pause in Background: Yes; Position: 123; Start Offset: 1; End Offset: 456; Sequence: Next]

AVPlayer Set Options [Sequence: None]
AVPlayer Set Options [Sequence: Next]
AVPlayer Set Options [Sequence: Previous]

AVPlayer Set Options [Volume: 1000]
AVPlayer Set Options [Zoom: Fit]
AVPlayer Set Options [Zoom: Fill]
AVPlayer Set Options [Zoom: Stretch]
AVPlayer Set Options [Zoom: Fit Only]
AVPlayer Set Options [Zoom: Fill Only]
AVPlayer Set Options [Zoom: Stretch Only]

AVPlayer Set Options [Presentation: Audio Only; Disable Interaction: Yes; Hide Controls: Yes; Disable External Controls: Yes; Pause in Background: Yes; Position: 123; Start Offset: 1; End Offset: 456; Volume: $Volume; Zoom: Stretch; Sequence: Previous]

AVPlayer Set Playback State [Stopped]
AVPlayer Set Playback State [Paused]
AVPlayer Set Playback State [Playing]

Beep

Dial Phone [Phone Number: 12345678; Use Dialing Preferences]
Dial Phone [Phone Number: 12345678; Use Dialing Preferences]
[No dialog]

Enable Touch Keyboard
[Off]
Enable Touch Keyboard
[Toggle]
Enable Touch Keyboard
[On]

Execute FileMaker Data API [ ]
[Select]
Execute FileMaker Data API [ ]
Execute FileMaker Data API [TestTable::TextField1]
Execute FileMaker Data API [TestTable::TextField1; JSONSetElement ("{}" ; "foo" ; "bar" ; JSONString)]
Execute FileMaker Data API [TestTable::TextField1; JSONSetElement ("{}" ; "foo" ; "bar" ; JSONString)]
[Select]

Execute SQL [ ]
[No dialog]
Execute SQL [SQL Text: SELECT * FROM orders]
[No dialog]
Execute SQL [SQL Text: SELECT * FROM orders]

Exit Application

Flush Cache to Disk

Get Folder Path [ ]
Get Folder Path [Allow Folder Creation]
Get Folder Path [Allow Folder Creation; $FolderPath; Default Location: $DefaultLocation]

Get Folder Path [$FolderPath; Dialog Title: $Title; Default Location: $DefaultLocation]

Install Menu Set [“[File Default]”]

Install Menu Set [“[Standard FileMaker Menus]”]

Install Menu Set [“[Standard FileMaker Menus]”]
[Use as file default]

Install Menu Set [“USER Menuset”]
[Use as file default]

Install Menu Set [“ADMIN Menuset”]
[Use as file default]

Install Plug-In File [ ]

Install Plug-In File [TestTable::TextField1]

Open URL [ ]
[No dialog]

Open URL ["http://db.de"]

Open URL ["http://www.mrwatson.de"]
[No dialog]

Open URL ["http://www.mrwatson.de"]
[No dialog]

Open URL ["http://www.mrwatson.de"]
[In external browser; No dialog]

Open URL [ ]
[In external browser; No dialog]

Perform AppleScript [ ]

Perform AppleScript [Native AppleScript: tell application "Finder" to activate]

Perform AppleScript [Native AppleScript: display dialog "Hello world!"]

Perform AppleScript [Calculated AppleScript: "display dialog \"Hello world!\""]

Perform JavaScript in Web Viewer [Object Name: <Active Object>]

Perform JavaScript in Web Viewer [Object Name: "abc"; Function Name: "def";
Parameter 1: $p1 & List(1;2;3;4);
Parameter 2: $p2]

Refresh Object [Object Name: "Obj"; Repetition: 2]

Refresh Portal [Object Name: "Portal1"]

Refresh Portal [Object Name: $MoreComplexName]

Save a Copy as Add-on Package [Window name: ; Replace UUIDs: Off]

Save a Copy as Add-on Package [Window name: ; Replace UUIDs: On]

Save a Copy as Add-on Package [Window name: $window ; Replace UUIDs: Off]

Save a Copy as Add-on Package [Window name: $window ; Replace UUIDs: On]

Save a Copy as Add-on Package [Window name: $window ; Replace UUIDs: On]

#FIXME - edit on windows

Send DDE Execute [ ]

Send Event [Event Class: “”; Event ID: “”]

Send Event [do script; Application Name: “<unknown>”]
[Wait for completion; Bring application to foreground]

Send Event [do script; Application Name: “<unknown>”]
[Bring application to foreground]

Send Event [open application; Application Name: “iCal.app”]

[Wait for completion]

Send Event [do script; Application Name: “Calendar.app”]
[Wait for completion]

Send Event [open document; File Name: “file:../../SnipMaker/fmxmlsnippet.xml”; Application Name: “TextMate.app”]
[Wait for completion]

Send Event [do script; File Name: “file:../../../Library/Scripts/> Applications/FileMaker Pro Advanced/ FMClipboard_Save.scpt”; Application Name: “AppleScript-Editor.app”]
[Wait for completion]

Send Event [do script; Text: “get name of every field of current layout”; Application Name: “AppleScript-Editor.app”]
[Wait for completion; Copy result to clipboard]

Send Mail [Send via E-mail Client; To: $To; CC: $CC; BCC: $BCC; Subject: $Subject; Message: $Message; Attachments: “$FilePath”]

Send Mail [Send via E-mail Client; To: $To; CC: $CC; BCC: $BCC; Subject: $Subject; Message: $Message; Attachments: “$FilePath”]
[No dialog]

Send Mail [Send via SMTP Server; To: $To; CC: $CC; BCC: $BCC; Subject: $Subject; Message: $Message; Attachments: “$FilePath”; Name: $User; Email Address: $UserMail; SMTP Server: $SMTPServer; Port: 25; Use SSL; Authentication Type: Plain Password; User Name: $User; Password: $Password]
[No dialog]

Send Mail [Send via OAuth 2.0; OAuth 2.0 Provider: Google]
[No dialog]

Send Mail [Send via OAuth 2.0; To: "to"; CC: "cc"; BCC: "bcc"; Subject: "Subject"; Message: "Message"; OAuth 2.0 Provider: Google; Name: "example"; Email Address: "example@gmail.com"; Reply-To Address: "reply-to@gmail.com"; Service Account Email: "service@gmail.com"; Admin User Email: "admin@gmail.com"; Private Key: "private"]
[No dialog]

Send Mail [Send via OAuth 2.0; To: "to"; CC: "cc"; BCC: "bcc"; Subject: "Subject"; Message: "Message"; Attachments: “file:one” AND “file:two”; OAuth 2.0 Provider: Google; Name: "example"; Email Address: "example@gmail.com"; Reply-To Address: "reply-to@gmail.com"; Service Account Email: "service@gmail.com"; Admin User Email: "admin@gmail.com"; Private Key: "private"]
[No dialog]

Set Session Identifier [ ]

Set Session Identifier ["It's me, Mario!"]

Set Web Viewer [Object Name: "wv"; Action: Reset]

// Set Web Viewer [Object Name: "wv"; Action: Reload]

// Set Web Viewer [Object Name: "wv"; Action: Go Forward]

Set Web Viewer [Object Name: "wv"; Action: Go Back]

Set Web Viewer [Object Name: "wv"; URL: "http://www.mapquest.com/maps/map.adp?" & "formtype=address&" & "searchtype=address&" & "cid=filemkr&" & "address=" & "" & "&country=" & ""]

Show Custom Dialog [Title: $DlgTitle; Message: $DlgMessage; Default Button: “OK”, Commit: “Yes”; Button 2: “Cancel”, Commit: “No”; Button 3: “Alternative”, Commit: “No”; Input #1: TestTable::TextField1, "Egal"; Input #2: TestTable::TextField_lotsTurnedOn, "Karl"; Input #3: TestTable_Contacts::Name, Password, "PW"]

Show Custom Dialog [Title: $DlgTitle; Message: "Only Button 1 and 3¶" &
"and input 2"; Default Button: “OK”, Commit: “Yes”; Button 3: “Alternative”, Commit: “No”; Input #2: TestTable::NumberField1, Password, "PW" &
TestTable::ID]

Show Custom Dialog [Title: $DlgTitle; Message: $DlgMessage; Default Button: “OK”, Commit: “Yes”; Button 2: “Cancel”, Commit: “No”; Button 3: “Alternative”, Commit: “No”]

Speak [Text: "Standard voice"]
[Wait for completion]

Speak [Text: "Agnes says.."; Voice: “Agnes”]
[Wait for completion]

Speak [Text: "Albert"]
[Wait for completion]

End If

External Plugin steps

If [1]

MBS [Select: On; Destination: TestTable::ContainerField1; Function: $Command; P1: $P1; P2: $P2; P3: $P3; P4: $P4; P5: $P5; P6: $P6; P7: $P7; P8: $P8; P9: $P9]

End If

Errors: Steps whose fmxmlsnippet does not contain 100% of the display information

If [1]

#2 Extra Labels:

Configure NFC Reading [Action: Read; Script: “Hello world”; Format Result as JSON: $format]

#Note: The option to specify the target result or not is NOT part of the clipboard, rather is implied by the existence of a calculation -> copying and pasting the following step ADDS a target calculation

Set Field By Name ["Value"]

Set Field By Name [ ]

End If