

Paul Cowan

Nomadic cattle rustler and inventor of the electric lasso

- [RSS](#)
- [Email](#)

Search
Navigate... 


- [Blog](#)
- [Archives](#)

Clojurescript - Om - Dynamic Components and Unique Keys

Nov 6th, 2014 6:51 am


As I get older my tolerance for javascript seems to be getting worse so I've been employing clojurescript as a shield from the true horrors of javascript. I've been playing around with [om](#) which acts as an interface to [facebook's react](#).

While developing with om, I kept getting the same javascript error after rendering a dynamic list like below:



If you have done any developing with om, then I am confident in saying that you will have come across this warning after rendering such a list:

Each child in an array should have a unique "key" prop. Check the renderComponent call using <tbody>. See <http://fb.me/react-warning-keys> for more information.



Here is the code I was using to render such a list:

old.cljs

```
1 (defn clips-view [{:keys [clips]} owner]
2   (reify
3     om/IRender
4     (render [this]
5       (html/html
6         [:div.well
7           [:table.table.table-bordered.table-hover.table-striped
8             [:tbody
9               (if (empty? clips)
10                [:tr
11                  [:td.text-center {:colSpan "2"} "No Clips!"]]]
12               (om/build-all clip-view clips)))))))
```

Line 12 in the above is the villain of this piece as there is no way that I could find of passing a func that will set the [key](#) property that react uses to identify each dynamic child.

I have been trying to ignore this warning as it did not cause any code to stop executing but I kept seeing this question pop up on the irc channel and I could not find a good answer on the google.

It also turns out that not supplying a react key for each dynamic item could lead to some very [unexpected behaviour](#).

After consulting the [om docs](#) I discovered that [om/build](#) can take a third `:opts` argument and one of the allowed keys is a `:react-key` which is one of the solutions to the problem.

Armed with this information, I refactored the above code to the following:

refactor.cljs

```
1 (defn clips-view [{:keys [clips]} owner]
2   (reify
3     om/IRender
4     (render [this]
5       (html/html
6         [:div.well
7           [:table.table.table-bordered.table-hover.table-striped
8             [:tbody
9               (if (empty? clips)
10                [:tr
11                  [:td.text-center {:colSpan "2"} "No Clips!"]]
12                (map-indexed #(om/build clip-view %2 {:react-key %1}) clips))))))))
```

The only change is on line 12:

```
1 (map-indexed #(om/build clip-view %2 {:react-key %1}) clips))
```

I have used the simplest case of an index for the `:react-key` but if I was rendering from a list where each item had a unique identifier then I would use the `:key` option to specify an element property that would be bound as the react key and would look something like this:

b.clj

```
1 (map #(om/build clip-view % {:key :id}) clips))
```

(thanks to Anna Pawlicka) for mentioning this in the comments below.

Or probably the best option of is to pass an `:opts` map containing a `:key` option to `om/build-all`:

a.clj

```
1 (om/build-all clip-view clips {:key :id})
```

Thanks to [Daniel Szmulewicz](#) for mentioning this on twitter.

I can now paste a link to this post when somebody asks how to get rid of this warning on the clojurescript irc channel.

Posted by Paul Cowan Nov 6th, 2014 6:51 am [clojurescript](#), [om](#)


Tweet Be the first of your friends to like this.

[« Clojure - lazy Sequences for the Masses](#) [Ember.js - Rendering Dynamic Content »](#)

Comments

3 Comments The Software Simpleton

1 Login ▾

 Recommend 1  Share

Sort by Best ▾



Join the discussion...

**mattiasw** • 2 years ago

By adding id + :key, I solved this error:

Uncaught Error: No protocol method IDeref.-deref defined for type cljs.core/PersistentArrayMap:

Thanks!

^ | ▾ • Reply • Share ›

**Anna Pawlicka** • 3 years ago

Lack of unique keys may actually cause a problem - this post explains the importance of having keys in React:

<https://coderwall.com/p/jdy...>

It's worth mentioning that you can also use :key in opt. If you're building components out of a sequence, and each item in this sequence has some unique value, e.g. [{ :id 56 :foo "bar" } { :id 67 :foo "bar" } ...], you can use :id as a unique key.

Option { :key :id } will be used to lookup :id in your data and use it as a React key.

^ | ▾ • Reply • Share ›

**dagda1** Mod → Anna Pawlicka • 3 years ago

cheers, I've updated the post

^ | ▾ • Reply • Share ›

ALSO ON THE SOFTWARE SIMPLETON

Computed Properties and Promises.....don't

1 comment • 2 years ago •

Devin — Misinformation: "data up and actions down".
Ember uses "data DOWN; actions UP" Doing things the other way around would make a simple ...

The Software Simpleton

5 comments • 2 years ago •

thefluxlife — I know this post is kind of old, but I've watched 2 videos, read 1 other blog post, and still felt like I didn't quite get it. I understood the concept but ...

My Failures With Fast Prime Number Generation




1 comment • 2 years ago •

Shannon Severance — If I understand the problem you don't have to look for a prime beyond the 104th. And you can have multiple Ns in a file. It looks like you ...

ember.js - Data Down, Actions up...The End of Two Way Data Binding Hell.

1 comment • 2 years ago •

tommyjr — When I first learned Ember, I also

 Subscribe  Add Disqus to your siteAdd DisqusAdd  Privacy
Paul Cowan

I am a.NET/(J)Ruby/JavaScript etc. polyglot programmer and gun for hire. I am currently based in Glasgow (UK).

[Contact Me](#)



Recent Posts

- [Instance Reducers](#)
- [Streams and Async Await in Nodejs](#)
- [Animated 3D Pyramid With CSS3 and SASS](#)
- [Animating Paths and Arcs With d3.js](#)
- [Animating a Sine Wave With d3.js and MathJax](#)

Latest Tweets

- Twitter's busted

Follow @dagda1

Copyright © 2017 - Paul Cowan - Powered by [Octopress](#)