

# **Embedding Programming Languages: PROLOG in HASKELL**

by

**Mehul Chandrakant Solanki**

*Bachelor of Engineering in Computer Science and Engineering Mumbai University 2012*

THESIS SUBMITTED IN PARTIAL FULFILLMENT OF  
THE REQUIREMENTS FOR THE DEGREE OF  
MASTER OF SCIENCE  
IN  
COMPUTER SCIENCE

UNIVERSITY OF NORTHERN BRITISH COLUMBIA

November 2015

© Mehul Chandrakant Solanki, 2015

# Abstract

This document looks at the problem of combining programming languages with contrasting and conflicting characteristics which mostly belong to different programming paradigms. The purpose to be fulfilled here is that rather than moulding a problem to fit in the chosen language it must be the other way around that the language adapts to the problem at hand. Moreover, it reduces the need for jumping between different languages. The aim is achieved either by embedding a target language whose features are desirable or to be captured into the host language which is the base on to which the mapping takes place which can be carried out by creating a module or library as an extension to the host language or developing a hybrid programming language that accommodates the best of both worlds.

This research focuses on combining the two most important and wide spread declarative programming paradigms, functional and logical programming. This will include playing with languages from each paradigm, HASKELL from the functional side and PROLOG from the logical side. The proposed approach aims at adding logic programming features which are native to PROLOG onto HASKELL by developing an extension which replicates the target language and utilises the advanced features of the host for an efficient implementation.

## 0.1 Thesis Statement

The thesis aims to provide insights into merging two declarative languages namely, HASKELL and PROLOG by embedding the latter into the former and analysing the result of doing so as they have conflicting characteristics. The finished product will be something like a *haskel-lised* PROLOG which has logical programming like capabilities.

We explore embedding domain specific languages in HASKELL

## TABLE OF CONTENTS

|  |            |
|--|------------|
| <b>Abstract</b>  | <b>ii</b>  |
| 0.1 Thesis Statement . . . . .   | ii         |
| <b>Table of Contents</b>   | <b>iii</b> |
| <b>1 Introduction</b>  | <b>1</b>   |
| 1.1 Beginnings . . . . .   | 1          |
| 1.2 Thesis Statement . . . . .   | 2          |
| 1.3 Problem Statement . . . . .  | 2          |
| 1.4 Thesis Organization . . . . .  | 4          |
| <b>2 Background</b>  | <b>5</b>   |
| <b>3 Accomplished Work</b>   | <b>10</b>  |
| 3.1 Current Work . . . . .   | 10         |
| 3.2 Contributions . . . . .  | 11         |
| 3.3 Improved Contributions . . . . .   | 12         |
| 3.4 Thesis Contributions . . . . .   | 13         |
| <b>4 Embedding a Programming Language into another Programming Language</b>    | <b>14</b>  |
| 4.1 The Informal Content from Blogs, Articles and Internet Discussions . . . . | 14         |
| 4.2 Related Books . . . . .  | 15         |
| 4.3 Related Papers . . . . .   | 16         |
| 4.4 Related Libraries in Haskell . . . . .                                     | 17         |
| 4.5 <b>From chap 7</b> . . . . .   | 18         |
| 4.6 Theory . . . . .   | 20         |
| 4.7 Implementations . . . . .  | 21         |
| 4.8 Important People . . . . .   | 21         |
| 4.9 Miscellaneous / Possibly Related Content . . . . .                         | 21         |
| <b>5 Multi Paradigm Languages (Functional Logic Languages)</b>                 | <b>22</b>  |
| 5.1 The Informal Content from Blogs, Articles and Internet Discussions . . . . | 23         |
| 5.2 Literature and Publications . . . . .                                      | 24         |
| 5.3 Some Multi Paradigm Languages . . . . .                                    | 25         |
| 5.4 Functional Logic Programming Languages . . . . .                           | 25         |

|           |  |           |
|-----------|--|-----------|
| 5.5       | From chap 9 . . . . .                              | 26        |
| 5.6       | Theory . . . . .                                   | 27        |
| 5.7       | Implementations . . . . .                          | 27        |
| 5.8       | Miscellaneous / Possibly Related Content . . . . . | 28        |
| <b>6</b>  | <b>Related Work</b>                                | <b>29</b> |
| <b>7</b>  | <b>Prolog in ----</b>                              | <b>31</b> |
| 7.1       | Theory . . . . .                                   | 31        |
| 7.2       | Implementations . . . . .                          | 32        |
| 7.3       | Important People . . . . .                         | 32        |
| 7.4       | Miscellaneous / Possibly Related Content . . . . . | 32        |
| <b>8</b>  | <b>Prolog in Haskell</b>                           | <b>33</b> |
| 8.1       | Theory . . . . .                                   | 33        |
| 8.2       | Implementations . . . . .                          | 34        |
| 8.3       | Important People . . . . .                         | 35        |
| 8.4       | Miscellaneous / Possibly Related Content . . . . . | 35        |
| <b>9</b>  | <b>Quasiquotation</b>                              | <b>37</b> |
| 9.1       | Theory . . . . .                                   | 37        |
| 9.2       | Implementations . . . . .                          | 37        |
| 9.3       | Miscellaneous / Possibly Related Content . . . . . | 38        |
| <b>10</b> | <b>Meta Syntactic Variables</b>                    | <b>39</b> |
| <b>11</b> | <b>Haskell or Why Haskell ?</b>                    | <b>41</b> |
| <b>12</b> | <b>Prolog or Why Prolog ?</b>                      | <b>44</b> |
| <b>13</b> | <b>Prototype 1</b>                                 | <b>45</b> |
| 13.1      | About this chapter . . . . .                       | 45        |
| 13.2      | How Prolog works ? . . . . .                       | 45        |
| 13.3      | What we do in this Prototype . . . . .             | 47        |
| 13.4      | Creating a data type . . . . .                     | 48        |
| 13.5      | Working with the language . . . . .                | 50        |
| 13.6      | Black box . . . . .                                | 51        |
| <b>14</b> | <b>Prototype 2.1</b>                               | <b>52</b> |
| 14.1      | About this chapter . . . . .                       | 52        |
| 14.2      | How prolog-0.2.0.1 works . . . . .                 | 52        |
| 14.3      | What we do in this prototype? . . . . .            | 53        |
| 14.4      | Current implementation (prolog-0.2.0.1) . . . . .  | 53        |
| 14.5      | Modifications . . . . .                            | 54        |
| 14.6      | Results . . . . .                                  | 57        |

|           |  |           |
|-----------|--|-----------|
| <b>15</b> | <b>Prototype 3</b>                       | <b>58</b> |
| 15.1      | Unification . . . . .                    | 58        |
| 15.2      | Resolution . . . . .                     | 58        |
| 15.3      | Search strategies . . . . .              | 59        |
| 15.4      | Stack Engine . . . . .                   | 59        |
| 15.5      | Pure Engine . . . . .                    | 60        |
| 15.6      | Andorra Engine . . . . .                 | 63        |
| 15.7      | Current Unification . . . . .            | 65        |
| 15.8      | Syntax Modification . . . . .            | 68        |
| 15.9      | Monadic Unification . . . . .            | 77        |
| <b>16</b> | <b>Prototype 4</b>                       | <b>79</b> |
| <b>17</b> | <b>Work Completed</b>                    | <b>87</b> |
| 17.1      | What we are doing . . . . .              | 87        |
| 17.2      | Unifiable Data Structures . . . . .      | 87        |
| 17.3      | Why Fix is necessary? . . . . .          | 87        |
| 17.4      | Dr. Casperson's Explanation . . . . .    | 89        |
| 17.5      | The other fix . . . . .                  | 89        |
| 17.6      | The Fix we use . . . . .                 | 90        |
| <b>18</b> | <b>Results</b>                           | <b>92</b> |
| 18.1      | Types . . . . .                          | 92        |
| 18.2      | Lazy Evaluation . . . . .                | 93        |
| 18.3      | Opening up the Language . . . . .        | 93        |
| 18.4      | Quasi Quotation . . . . .                | 93        |
| 18.5      | Template Haskell . . . . .               | 93        |
| 18.6      | Higher Order Functions . . . . .         | 93        |
| 18.7      | I/O . . . . .                            | 94        |
| 18.8      | Mutability . . . . .                     | 94        |
| 18.9      | Unification . . . . .                    | 94        |
| 18.10     | Monads . . . . .                         | 94        |
| <b>19</b> | <b>Conclusion / Expected Outcomes</b>    | <b>95</b> |
| <b>20</b> | <b>Editing to do</b>                     | <b>96</b> |
| 20.1      | Editing suggestions from David . . . . . | 98        |
|           | Bibliography . . . . .                   | 100       |

# List of Tables

# List of Figures

|      |                         |    |
|------|-------------------------|----|
| 13.1 | Trace for append [118]  | 47 |
| 17.1 | Functor Hierarchy [138] | 88 |

# **Chapter 1**

## **Introduction**

### **1.1 Beginnings**

Programming has become an integral part of working and interacting with computers and day by day more and more complex problems are being tackled using the power of programming technologies. It is possibly the only way to talk to computers and hence the need for a robust and multi purpose programming language has never been more urgent. The desirability of a programming language depends on a lot of factors such as the ease of use, the features and functionalities that it provides, adaptability and what sort of problems can it solve. One is spoilt for choice with a number of options for a wide variety of programming paradigms, for example Object Oriented Languages. Over the last decade the declarative style of programming has gained popularity. The methodologies that have stood out are the Functional and Logical Approaches. The former is based on Functions and Lambda Calculus, while the latter is based on Horn Clause Logic. Each of them has its own advantages and downsides. How does one choose which approach to adopt? Perhaps one does not need to choose! This document looks at the attempts, improvements and future possibilities of uniting HASKELL, a Purely Functional Programming Language and PROLOG, a Logical Programming Language so that one is not forced to choose.



## 19 1.2 Thesis Statement

20 The thesis aims to provide insights into merging two declarative languages namely, HASKELL  
21 and PROLOG by embedding the latter into the former and analysing the result of doing so as  
22 they have conflicting characteristics. The finished product will be something like a *haskel-*  
23 *lised* PROLOG which has logical programming like capabilities.

## 24 1.3 Problem Statement

25 Over the years the development of programming languages has become more and more  
26 rapid. Today the number of is in the thousands and counting. The successors attempt to  
27 introduce new concepts and features to simplify the process of coding a solution and assist  
28 the programmer by lessening the burden of carrying out standard tasks and procedures. A  
29 new one tries to capture the best of the old; learn from the mistakes, add new concepts  
30 and move on; which seems to be good enough from an evolutionary perspective. But all  
31 is not that straight forward when shifting from one language to another. There are costs  
32 and incompatibilities to look at. A language might be simple to use and provide better  
33 performance than its predecessor but not always be worth the switch.

34 PROLOG is a language that has a hard time being adopted. Born in an era where proce-  
35 dural languages were receiving a lot of attention, it suered from competing against another  
36 new kid on the block: C. Some of the problems were of its own making. Basic features  
37 like modules were not provided by all compilers. Practical features for real world problems  
38 were added in an ad hoc way resulting in the loss of its purely declarative charm. Some  
39 say that PROLOG is fading away, [85, 131, 130]. It is apparently not used for building large  
40 programs [144, 111, 63]. However there are a lot of good things about Prolog: it is ideal  
41 for search problems; it has a simple syntax, and a strong underlying theory. It is a language  
42 that should not die away.

43 So the question is how to have all the good qualities of PROLOG without actually using

44 PROLOG?

45 Well one idea is to make PROLOG an add-on to another language which is widely used  
46 and in demand. Here the choice is HASKELL; as both the languages are declarative they  
47 share a common background which can help to blend the two.

48 Generally speaking, programming languages with a wide scope over problem domains  
49 do not provide bespoke support for accomplishing even mundane tasks. Approaching to-  
50 wards the solution can be complicated and tiresome, but the programming language in  
51 question acts as the master key.

52 Flipping the coin to the other side we see, the more specific the language is to the  
53 problem domain the easier it is to solve the problem. The simple reason being that, the  
54 problem need not be moulded according to the capability of the language. For example a  
55 problem with a naturally recursive solution cannot take advantage of tail recursion in many  
56 imperative languages. Many problems require the system to be mutation free, but have to  
57 deal with uncontrolled side-effects and so on.

58 Putting all of the above together, Domain Specific Languages are pretty good in doing  
59 what they are designed to do, but nothing else, resulting in choosing a different language  
60 every time. On the other hand, a general purpose language can be used for solving a wide  
61 variety of problems but many a times, the programmer ends up writing some code dictated  
62 by the language rather than the problem.

63 The solution, a programming language with a split personality, in our case, sometimes  
64 functional, sometimes logical and sometimes both. Depending upon the problem, the lan-  
65 guage shapes itself accordingly and exhibits the desired characteristics. The ideal situation  
66 is a language with a rich feature set and the ability to mould itself according to the problem.  
67 A language with ability to take the appropriate skill set and present it to the programmer,  
68 which will reduce the hassle of jumping between languages or forcibly trying to solve a  
69 problem according to a paradigm.

70 The subject in question here is HASKELL and the split personality being PROLOG. How

71 far can HASKELL be pushed to dawn the avatar of PROLOG ? is the million dollar question.

72 The above will result in a set of characteristics which are from both the declarative  
73 paradigms.

74 This can be achieved in two ways,

75 **Embedding ([Chapter 4](#)):** This approach involves, translating a complete language into  
76 the host language as an extension such as a library and/ or module . The result is  
77 very shallow as all the positives as well as the negatives are brought into the host  
78 language. The negatives mentioned being, that languages from different paradigms  
79 usually have conflicting characteristics and result in inconsistent properties of the  
80 resulting embedding. Examples and further discussion on the same is provided in the  
81 chapters to come.

82 **Paradigm Integration ([Chapter 5](#)):** This approach goes much deeper as it does not in-  
83 volve a direct translation. An attempt is made by taking a particular characteristic  
84 of a language and merging it with the characteristic of the host language in order to  
85 eliminate conflicts resulting in a multi paradigm language. It is more of weaving the  
86 two languages into one tight package with the best of both and maybe even the worst  
87 of both.

## 88 1.4 Thesis Organization

89 The next chapter, [Chapter 2](#) provides details about the short comings of the previous works  
90 and the road to a better future. [Chapter 3](#), the background talks about the programming  
91 paradigms and languages in general and the ones in question. Then we look at the ques-  
92 tion from different angles namely, [Chapter 4](#), Embedding a Programming Language into  
93 another Programming Language and [Chapter 5](#), Multi Paradigm Languages ( Functional  
94 Logic Languages). Some of the indirectly related content [Chapter 6](#) and finishing off with  
95 the [Chapter 7](#), the expected outcomes.

## 96 Chapter 2

## 97 Background

98 Programming Languages fall into different categories also known as "paradigms". They  
99 exhibit different characteristics according to the paradigm they fall into. It has been argued  
100 [68] that rather than classifying a language into a particular paradigm, it is more accurate  
101 that a language exhibits a set of characteristics from a number of paradigms. Either way,  
102 the broader the scope of a language the more the expressibility or use it has.

103 Programming Languages that fall into the same family, in our case declarative program-  
104 ming languages, can be of different paradigms and can have very contrasting, conflicting  
105 characteristics and behaviours. The two most important ones in the family of declarative  
106 languages are the Functional and Logical style of programming.

107 Functional Programming, [55] gets its name as the fundamental concept is to apply  
108 mathematical functions to arguments to get results. A program itself consists of functions  
109 and functions only which when applied to arguments produce results without changing the  
110 state that is values on variables and so on. Higher order functions allow functions to be  
111 passed as arguments to other functions. The roots lie in  $\lambda$ -calculus [156], a formal system  
112 in mathematical logic and computer science for expressing computation based on function  
113 abstraction and application using variable binding and substitution. It can be thought as the  
114 smallest programming language [101], a single rule and a single function definition scheme.

115 In particular there are typed and untyped  $\lambda$  calculi. In the untyped  $\lambda$  calculus functions have  
116 no predetermined type whereas typed lambda calculus puts restriction on what sort(type)  
117 of data can a function work with. SCHEME is based on the untyped variant while ML  
118 and HASKELL are based on typed  $\lambda$  calculus. Most typed  $\lambda$  calculus languages are based  
119 on Hindley-Milner or Damas-Milner or Damas- Hindley-Milner [154] type system. The  
120 ability of the type system to give the most general type of a program without any help  
121 (annotation). The algorithm [20] works by initially assigning undefined types to all inputs,  
122 next check the body of the function for operations that impose type constraints and go on  
123 mapping the types of each of the variables, lastly unifying all of the constraints giving the  
124 type of the result.

125 Logical Programming, [113] on the other hand is based on formal logic. A program is  
126 a set of rules and formulæ in symbolic logic that are used to derive new formulas from the  
127 old ones. This is done until the one which gives the solution is not derived.

128 The languages to be worked with being HASKELL and PROLOG respectively. Some  
129 differences include things like, HASKELL uses Pattern Matching while PROLOG uses Uni-  
130 fication, HASKELL is all about functions while PROLOG is on Horn Clause Logic and so  
131 on.

132 PROLOG [144] being one of the most dominant Logic Programming Languages has  
133 spawned a number of distributions and is present from academia to industry.

134 HASKELL is one the most popular [73] functional languages around and is the first  
135 language to incorporate Monads [133] for safe *IO*. Monads can be described as composable  
136 computation descriptions [142] . Each monad consists of a description of what has action  
137 has to be executed, how the action has to be run and how to combine such computations.  
138 An action can describe an impure or side-effecting computation, for example, *IO* can be  
139 performed outside the language but can be brought together with pure functions inside in  
140 a program resulting in a separation and maintaining safety with practicality. HASKELL  
141 computes results lazily and is strongly typed.

142       The languages taken up are contrasting in nature and bringing them onto the same plate  
143 is tricky. The differences in typing, execution, working among others lead to an altogether  
144 mixed bag of properties.

145       The selection of languages is not uncommon and this not only the case with HASKELL,  
146 PROLOG seems to be the all time favourite for "let's implement PROLOG in the language  
147 X for proving it's power and expressibility". The PROLOG language has been partially  
148 implemented [31] in other languages like SCHEME [110], LISP [66, 99, 100], JAVA [144,  
149 58], JAVASCRIPT [59] and the list [93] goes on and on.

150       The technique of embedding is a shallow one, it is as if the embedded language floats  
151 over the host. Over time there has been an approach that branches out, which is Paradigm  
152 Integration. A lot of work has been done on Unifying the Theories of Programming [33,  
153 12, 94, 165, 52, 43]. All sorts of hybrid languages which have characteristics from more  
154 than one paradigm are coming into the mainstream.

155       Before moving on, let us take a look at some terms related to the content above. To  
156 begin with Foreign Function Interfaces (FFI) [155], a mechanism by which a program  
157 written in one programming language can make use of services written in another. For  
158 example, a function written in C can be called within a program written in HASKELL and  
159 vice versa through the FFI mechanism. Currently the HASKELL foreign function interface  
160 works only for one language. Another notable example is the Common Foreign Function  
161 Interface (CFFI) [11] for LISP which provides fairly complete support for C functions and  
162 data. JAVA provides the Java Native Interface(JNI) for the working with other languages.  
163 Moreover there are services that provide a common platform for multiple languages to  
164 work with each other and run their programs. They can be termed as multi lingual run  
165 times which lay down a common layer for languages to use each others functions. An  
166 example for this is the Microsoft Common Language Runtime (CLR) [151] which is an  
167 implementation of the Common Language Infrastructure (CLI) standard [150].

168       Another important concept is meta programming [158], which involves writing com-

puter programs that write or manipulate other programs. The language used to write meta programs is known as the meta language while the the language in which the program to be modified is written is the object language. If both of them are the same then the language is said to be reflective. HASKELL programs can be modified using Template HASKELL [49] an extension to the language which provides services to jump between the two types of programs. The abstract syntax trees in the form of HASKELL data types can be modified at compile time which playing with the code and going back and forth.

A specific tool used in meta programming is quasi quotation [76, 136, 149], permits HASKELL expressions and patterns to be constructed using domain specific, programmer-defined concrete syntax. For example, consider a particular application that requires a complex data type. To accommodate the same it has to be represented using HASKELL syntax and performing pattern matching may turn into a tedious task. So having the option of using specific syntax reduces the programmer from this burden and this is where a quasi-quoter comes into the picture. Template HASKELL provides the facilities mentioned above. For example, consider the following code in PROLOG to append two lists, going through the

```

1  append([], X, X).
2  append([X|Xs], Ys, [X|Zs]) :- append(Xs, Ys, Zs).

```

code, the first rule says that an empty list appended with any list results in the list itself. The second predicate matches the head of the first and the resulting lists and then recurs on the tails. The same in HASKELL,

```

1  append(Ps, Qs, Rs) = (Ps = [] & Qs = Rs) ||
2      | X, Xs, Ys -> Ps = [X|Xs] &
3      Rs = [X|Ys] &
4      append(Xs, Qs, Ys)

```

Consider the Object Functional Programming Language, SCALA [168], it is purely functional but with objects and classes. With the above in mind, coming back to the prob-

189 lem of implementing PROLOG in HASKELL. There have been quite a few attempts to  
190 "merge" the two programming languages from different programming paradigms. The at-  
191 tempts fall into two categories as follows,

192 1. Embedding, where PROLOG is merely translated to the host language HASKELL or  
193 a Foreign Function Interface.

194 2. Paradigm Integration, developing a hybrid programming language that is a Func-  
195 tional Logic Programming Language with a set of characteristics derived from both  
196 the participating languages.

197 The approaches listed above are next in line for discussions.



## 198 Chapter 3

## 199 Accomplished Work

### 200 3.1 Current Work

201 There have been several attempts at embedding PROLOG into HASKELL which are dis-  
202 cussed below along with the shortcomings.

203 1. Very few embedded implementations exist which offer a perspective into the job  
204 at hand. One of the earliest implementations [61] is for an older specification of  
205 HASKELL called HASKELL 98 hugs. It is more of a proof of concept providing a  
206 mechanism to include variable search strategies in order to produce a result. Another  
207 implementation [166] based of it simplifies the notation to a list format. Nonetheless,  
208 both implementations lack simplicity and support for basic PROLOG features such as  
209 *cuts, fails, assert* among others.

210 2. The papers that try to take the above further are also few in number and do not  
211 have any implementations with the proposed concepts. Moreover, none of them are  
212 complete and most lack many practical parts of PROLOG.

213 3. In the case of libraries, a few exist, most are old and are not currently maintained or  
214 updated. Many provide only a shell through which one has to do all the work, which

215 is synonymous with the embeddings mentioned above. Some are far more feature  
216 rich than others that is with some practical PROLOG concepts, but are not complete.

217 4. Moreover, none of the above have full list support that exist in PROLOG.

218 And as far as the idea of merging paradigms goes, it is not the main focus of this  
219 thesis and can be more of an "add-on". A handful of crossover hybrid languages based  
220 on HASKELL exist, CURRY [129] being the prominent one. Moving away from HASKELL  
221 and exploring other languages from different paradigms, a respectable number of crossover  
222 implementations exist but again most of them have faded out.

223 As discussed in the sections above, either an embedding or an integration approach is  
224 taken up for programming languages to work together. So, there is either a very shallow  
225 approach that does not utilize the constructs available in the host language and results in a  
226 mere translation of the characteristics, or the other is a fairly complex process which results  
227 in tackling the conflicting nature of different programming paradigms and languages, re-  
228 sulting in a toned-down compromised language that takes advantages of neither paradigms.  
229 Mostly the trend is to build a library for extension to replicate the features as an add on.

## 230 3.2 Contributions

231 Taking into consideration above, there is quite some room for improvement and additions.  
232 Moving onto what this thesis shall explore, first thing's first a complete, fully functional  
233 library which comes close to a PROLOG like language and has practical abilities to carry  
234 out real-world tasks. They include predicates like *cut*, *assert*, *fail*, *setOf*, *bagOf* among  
235 others. This would form the first stage of the implementation. Secondly, exploring aspects  
236 such as *assert* and database capabilities. A third question to address is the accommodation  
237 of input and output, specifically dealing with the *IO Monad* in HASKELL with PROLOG *IO*.  
238 Moreover, PROLOG is an untyped language which allows lists with elements of different  
239 types to be created. Something like this is not by default in HASKELL. Hence syntactic

240 support for the same is the next question to address. Furthermore, experimenting with how  
241 programs expressed with same declarative meaning differ operationally. Lastly, how would  
242 characteristics of hybrid languages fit into and play a role in an embedded setting.

### 243 3.3 Improved Contributions

244 1. Most languages have a recursive abstract syntax which restricts the eDSL in terms of  
245 its capability to *open up* the language i.e. to include meta syntactic variables, adding  
246 custom quantifiers and logic. ([Prototype 1](#)) provides a methodology to convert a  
247 language whose recursive abstract syntax is represented by a tree into a non-recursive  
248 version whose fixed point is isomorphically equivalent to the original type. One of  
249 the outcomes is a polymorphically typed embedded language within HASKELL

250 To test it out we adopt the closed PROLOG like language defined in [103] and open  
251 it up. And for the unification part we use [123], which provides a generic unification  
252 algorithm implementation encapsulated into a monad.

253 2. ([Prototype 2](#)) does the what a PROLOG query resolver would do given a query and a  
254 knowledge base. The mechanism for the same is adopted from [103]. The embedded  
255 language is modified as per the procedure in ([Prototype 1](#)) and the monadic unifica-  
256 tion part is plugged into the existing architecture to demonstrate that it is independent  
257 of the other components. Lastly the result is converted into the original language via  
258 a translate function.

259 3. ([Prototype 3](#)) demonstrates the modularity of the unification process of the query  
260 resolver with multiple search strategies.

261 4. ([Prototype 4](#)) throws light on how IO operations can be embedded into the abstract  
262 syntax of a DSL which when interpreted would produce output consisting of a pure  
263 set of instructions irrespective of the nature of the construct. The effects are only

264        produced only when the actions are executed.

## 265    **3.4    Thesis Contributions**

266        1. Prototype 1 does flattening language opening up the language (binding monad) adding  
267            custom variables monadic unification (stuff happens in a bubble)  $\text{rec type} \rightarrow \text{non rec}$   
268             $\text{type} \rightarrow \text{fix non rec type isomorphically} == \text{rec type}$

269            You can make an Flatterm int

270            but you cannot make term int

271            adding quantifiers

272        2. Prototype 2 does extends current prolog-0.2.0.1 this is to show that we can plug out  
273            approach into existing implementation and things work

274        3. Prototype 3 does variable search strategy what ever method you do for searching at  
275            the point of unification you can do it with our approach

276        4. Prototype 4 does how can io be squeezed into this model where whenever the resolver  
277            encounters an io operation it generates a thunk (sort of unsolved statement) which  
278            when executed would result in a side effect but till that point every thing is pure

## Chapter 4

# Embedding a Programming Language into another Programming Language

The art of embedding a programming language into another one has been explored a number of times in the form of building libraries or developing Foreign Function Interfaces and so on. This area mainly aims at an environment and setting where two or more languages can work with each other harmoniously with each one able to play a part in solving the problem at hand. This chapter mainly reviews the content related to embedding PROLOG in HASKELL but also includes information on some other implementations and embedding languages in general.

### 4.1 The Informal Content from Blogs, Articles and Internet Discussions

Before moving on to the formal content such as publications, modules and libraries let's take a look at some of the unofficially published content. This subsection takes a look at the information, thoughts and discussions that are currently taking place from time to time on the internet. A lot of interesting content is generated which has often led to some formal

295 content.

296 A lot has been talked about embedding languages and also the techniques and methods  
297 to do so. It might not seem such a hot topic as such but it has always been a part of any pro-  
298 gramming language to work and integrate their code with other programming languages.  
299 One of the top discussions are in, Lambda the Ultimate, The Programming Languages  
300 Weblog [69], which lists a number of PROLOG implementations in a variety of languages  
301 like LISP, SCHEME, SCALA, JAVA, JAVASCRIPT, RACKET [110] and so on. Moreover the  
302 discussion focusses on a lot of critical points that should be considered in a translation of  
303 PROLOG to the host language regarding types and modules among others.

304 One of the implementations discussed redirects us to one of the most earliest imple-  
305 mentations of PROLOG in HASKELL for Hugs 98, called Mini PROLOG [61]. Although this  
306 implementation takes as reference the working of the PROLOG Engine and other details,  
307 it still is an unofficial implementation with almost no documentation, support or ongoing  
308 development. Moreover, it comes with an option of three engines to play with but still lacks  
309 complete list support and a lot of practical features that PROLOG has and this seems to be  
310 a common problem with the only other implementation that exists, [166].

311 Adding fuel to fire, is the question on PROLOG's existence and survival [130, 85, 131,  
312 111] since its use in industry is far scarce than the leading languages of other paradigms.  
313 The purely declarative nature lacks basic requirements such as support for modules. And  
314 then there is the ongoing comparison between the siblings [167] of the same family, the  
315 family of Declarative Languages. Not to forget HASKELL also has some tricks [134] up its  
316 sleeve which enables encoding of search problems.

## 317 **4.2 Related Books**

318 As HASKELL is relatively new in terms of being popular, its predecessors like SCHEME  
319 have explored the territory of embedding quite profoundly [25], which aims at adding a

320 few constructs to the language to bring together both styles of Declarative Programming  
321 and capture the essence of PROLOG. Moreover, HASKELL also claims for it to be suitable  
322 for basic Logic Programming naturally using the List Monad [135]. A general out look  
323 towards implementing PROLOG has also been discussed by [67] to push the ideas forward.

## 324 4.3 Related Papers

325 There is quite some literature that can be found and which consist of embedding detailed  
326 parts of Prolog features like basic constructs, search strategies and data types. One of  
327 the major works is covered by the subsection below consisting of a series of papers from  
328 Mike Spivey and Silvija Seres aimed at bring Haskell and Prolog closer to each other. The  
329 next subsection covers the literature based on the above with improvements and further  
330 additions.

### 331 • Papers from Mike Spivey and Silvija Seres

332 The work presented in the series [115, 107, 108, 114, 105] attempts to encapsulate  
333 various aspects of an embedding of PROLOG in HASKELL. Being the very first doc-  
334 umented formal attempt, the work is influenced by similar embeddings of PROLOG  
335 in other languages like SCHEME and LISP. Although the host language has distinct  
336 characteristics such as lazy evaluation and strong type system the proposed scheme  
337 tends to be general as the aim here is to achieve PROLOG like working not a multi  
338 paradigm declarative language. PROLOG predicates are translated to HASKELL func-  
339 tions which produce a stream of results lazily depicting depth first search with sup-  
340 port for different strategies and practical operators such as *cut* and *fail* with higher  
341 order functions. The papers provide a minimalistic extension to HASKELL with only  
342 four new constructs. Though no implementation exists, the synthesis and transforma-  
343 tion techniques for functional programs have been *logicalised* and applied to PRO-  
344 LOG programs. Another related work [116] looks through conventional data types so

345 as to adapt to the problems at hand so as to accommodate and jump between search  
346 strategies.

347 • Other works related or based on the above

348 Continuing from above, [19] taps into the advantages of the host language to em-  
349 bed a typed functional logic programming language. This results in typed logical  
350 predicates and a backtracking monad with support for various data types and search  
351 strategies. Though not very efficient nor practical the method aims at a more ele-  
352 gant translation of programs from one language to the other. While other papers [36]  
353 attempt at exercising HASKELL features without adding anything new rather doing  
354 something new with what is available. Specifically speaking, using HASKELL type  
355 classes to express general structure of a problem while the solutions are instances.  
356 [51] replicates PROLOG's control operations in HASKELL suggesting the use of the  
357 HASKELL *State Monad* to capture and maintain a global state. The main contribu-  
358 tions are a Backtracking Monad Transformer that can enrich any monad with back-  
359 tracking abilities and a monadic encapsulation to turn a PROLOG predicate into a  
360 HASKELL function.

## 361 4.4 Related Libraries in Haskell

362 • Prolog Libraries

363 To replicate Prolog like capabilities Haskell seems to be already in the race with a  
364 host of related libraries. First we begin with the libraries about Prolog itself, a few  
365 exist [120] being a preliminary or "mini Prolog" as such with not much in it to be able  
366 to be useful, [121] is all powerful but is an Foreign Function Interface so it is "Prolog  
367 in Haskell" but we need Prolog for it, [103] which is the only implementation that  
368 comes the closest to something like an actual practical Prolog. But all they give is a  
369 small interpreter, none or a few practical features, incomplete support for lists, minor



370 or no monadic support and an REPL without the ability to "write a Prolog Program  
371 File".

#### 372 • Logic Libraries

373 The next category is about the logical aspects of Prolog, again a handful of libraries  
374 do exist and provide a part of the functionality which is related propositional logic  
375 and backtracking. [23] is a continuation-based, backtracking, logic programming  
376 monad which sort of depicts Prolog's backtracking behaviour. Prolog is heavily  
377 based on formal logic, [41] provides a powerful system for Propositional Logic.  
378 Others include small hybrid languages [37] and Parallelising Logic Programming  
379 and Tree Exploration [22].

#### 380 • Unification Libraries

381 The more specific the feature the lesser the support in Haskell. Moving on to the other  
382 distinct feature of Prolog is Unification, two libraries exist [123], [95] that unify two  
383 Prolog Terms and return the resulting substitution.

#### 384 • Backtracking

385 Another important aspect of PROLOG is backtracking. To simulate it in HASKELL,  
386 the libraries [38, 112] use monads. Moreover, there is a package for the EGISON  
387 programming language [53] which supports non-linear pattern-matching with back-  
388 tracking.

## 389 **4.5 From chap 7**

390 Embedding a language into another language has been explored with a variety of languages.  
391 Attempts have been made to build Domain Specific Languages from the host languages  
392 [54], Foreign Function Interfaces [8]

393       Creating a programming language from scratch is a tedious task requiring ample amount  
394 of programming, not to mention the effort required in designing. A typical procedure would  
395 consist of formulating characteristics and properties based on the following points,

- 396       1. Syntax
- 397       2. Semantics
- 398       3. Standard Library
- 399       4. Runtime System
- 400       5. Parsers
- 401       6. Code Generators
- 402       7. Interpreters
- 403       8. Debuggers

404       A lot of the above can be skipped or taken from the base language if an embedding  
405 approach is chosen. For an embedded domain specific language the functionality is trans-  
406 lated and written as an add on. The result can be thought of as a library. But the difference  
407 between an ordinary library and an eDSL is the feature set provided and the degree of em-  
408 bedding [140]. For example, reading a file and parsing its contents to perform certain  
409 operations to return *string* results is a shallow form of embedding as the generation of  
410 code, results is not native nor are the functions processing them dealing with embedded  
411 data types as such. On the other hand, building data structures in the base language which  
412 represent the target language expression would be called a deep embedding approach.

413       The snippet of HASKELL code below describes PROLOG entities,

```
1  data Term = Struct Atom [Term]
2           | Var VariableName
3           | Wildcard
```

```

4         | PString   !String
5         | PInteger  !Integer
6         | PFloat    !Double
7         | Flat [FlatItem]
8         | Cut Int
9     deriving (Eq, Data, Typeable)

```

414 The above can be described as concrete syntax for the "new" language and can be used  
 415 to write a program.

416 As discussed in the

## 417 4.6 Theory

### 418 1. Papers

- 419 (a) Embedding an interpreted language using higher-order functions, [96]
- 420 (b) Building domain-specific embedded languages, [54]
- 421 (c) Embedded interpreters, [9]
- 422 (d) Cayenne – a Language With Dependent Types, [5]
- 423 (e) Foreign interface for PLT Scheme, [8]
- 424 (f) Dot-Scheme: A PLT Scheme FFI for the .NET framework, [91]
- 425 (g) Application-specific foreign-interface generation, [97]
- 426 (h) Embedding S in other languages and environments, [72]

### 427 2. Books

- 428 (a) ?????????

### 429 3. Articles / Blogs / Discussions

- 430 (a) Embedding one language into another, [70]

431 (b) Application-specific foreign-interface generation, [71]

432 (c) Linguistic Abstraction, [88]

433 (d) LISP, Unification and Embedded Languages, [89]

434 4. Websites

435 (a) Embedding SWI-Prolog in other applications, [31]

## 436 **4.7 Implementations**

437 1. Lots of them I guess

## 438 **4.8 Important People**

439 1. ????

## 440 **4.9 Miscellaneous / Possibly Related Content**

441 1. ????

## 442 Chapter 5

# 443 Multi Paradigm Languages (Functional 444 Logic Languages)

445 Over the years another approach has branched off from embedding languages, to merge  
446 and/or integrate programming languages from different paradigms. Let us take an example  
447 of the SCALA Programming Language [168], a hybrid Object-Functional Programming  
448 Language which takes a leaf from each of the two books. In this thesis, the languages in  
449 question are HASKELL and PROLOG. This section takes a look at the literature on Multi  
450 Paradigm Languages, mainly Functional Logic Programming Languages that combine two  
451 of the most widespread Declarative Programming Styles.

452 A peak into language classification reveals that it is not always a straight forward task to  
453 segregate languages according to their features and/or characteristics. Turns out that there  
454 are a number of notions which play a role in deciding where the language belongs. Many  
455 a times a language ends up being a part of almost all paradigms due extensive libraries.  
456 Simply speaking, a multi-paradigm programming language is a programming language  
457 that supports more than one programming paradigm [68], more over as Timothy Budd  
458 puts it [160] ”The idea of a multi paradigm language is to provide a framework in which  
459 programmers can work in a variety of styles, freely intermixing constructs from different

460 paradigms.”

## 461 **5.1 The Informal Content from Blogs, Articles and Inter-** 462 **net Discussions**

### 463 • Multi Paradigm Languages

464 A lot has been talked and discussed on coming to clear grounds about the classifica-  
465 tion of programming languages. If the conventional ideology is considered then the  
466 scope of each language is pretty much infinite as small extension modules replicate  
467 different feature sets which are not naturally native to the language itself. The defini-  
468 tions of multi paradigm languages across the web [160, 86, 13] converge to roughly  
469 the same thing that of providing a framework to work with different styles with a list  
470 of languages [157, 30] that ticks the boxes. Generally speaking, it does not feel all  
471 that hot or popular in programming circles; one reason could be that it is a very broad  
472 topic and specifying details can clear the fog.

### 473 • Functional Logic Programming Languages

474 Continuing from the previous section, narrowing down the search by considering  
475 only multi paradigm declarative languages namely, Functional Logical programming  
476 languages. By doing so a large amount of information pops up, from articles that  
477 give brief description and mentions [148, 145] to the implementing techniques [2]  
478 which give a brief overview of the aim and also the backdrop of publications.

479 The jackpot however is the fact that there is a dedicated website [47] for the history,  
480 research and development, existing languages, the literature, the contacts and every-  
481 thing else that one can think of for functional logic languages. As a matter of fact the  
482 holy grail of information is maintained by two of the most important people in the  
483 field Michael Hanus [45] and Sergio Antoy [3].

## 484 5.2 Literature and Publications

### 485 • Multi Paradigm Languages

486 Possibly one of the most important works towards bringing programming styles to-  
487 gether is the book by C.A.R. Hoare [52] which points out that among the large num-  
488 ber of programming paradigms and/or theories the unification theory serves as a com-  
489plementary rather than a replacement to relate the universe. As as always since we  
490are talking about HASKELL we have to include monads and unifying theories using  
491monads [43].

### 492 • Functional Logic Programming Languages

493 A recent survey [46] throws light on these hybrid languages.

494 One of the most prominent multi paradigm languages in HASKELL is CURRY [4].  
495 Th syntax is borrowed from the parent language and so are a lot of the features.  
496 Taking a recap, a functional programming language works on the notion of mathe-  
497matical functions while a logic programming language is based on predicate logic.  
498 The strong points of CURRY are that the features or basis of the language are general  
499and are visible in a number of languages like [27]. The language can play with prob-  
500lems from both worlds. In a problem where there are no unknowns and/or variables  
501the language behaves like a functional language which is pattern matching the rules  
502and execute the respective bodies. In the case of missing information, it behaves  
503like PROLOG; a sub-expression  $e$  is evaluated on the conditions that it should satisfy  
504which constraint the possible values of  $e$ . This brings us to the first important fea-  
505ture of functional logic languages *narrowing*. The expressions contain *free variables*;  
506simply speaking incomplete information that needs to be *unified* to a value depending  
507on the constraints of the problem. The language introduces only a few new constructs  
508to support non determinism and choice. Firstly, *narrowing* ( $==$ ), which deals with  
509the expressions and unknown values and binds them with appropriate values. The

510 next one is the *choice* operator (?) for non-deterministic operations. Lastly, for uni-  
511 fying variables and values under some conditions, (&) operator has been provided to  
512 add constraints to the equation. Putting it all together, it gives us the feel of a logic  
513 language for something that looks very much like HASKELL. Unification is like two  
514 way pattern matching and with a similar analogy CURRY is a HASKELL that works  
515 both ways and hence variables can be on either sides. Although the language can do  
516 a lot but gaps do exist such as the improvement of narrowing techniques.

## 517 **5.3 Some Multi Paradigm Languages**

518 The list of multi paradigm languages is huge, but in this thesis we will mostly stick to Func-  
519 tional Logical programming languages. Beginning with functional hybrids, a small project  
520 language called VIRGIL [128], combining objects to work with functions and procedures.  
521 On similar lines is COMMON OBJECT LISP SYSTEM (CLOS) [146]. This can be justified  
522 as object oriented programming has been one of the most dominant styles of programming  
523 and hence even HASKELL has one called O'HASKELL [87] though it last saw a release  
524 back in 2001. Another prominent implementation is OCAML [159, 90] which adds object  
525 oriented capabilities with a powerful type system and module support. This is the case with  
526 most of the languages in this section hardly a few have survived as the new ones incorpo-  
527 rated the positives of the old. As mentioned before one of the most popular [73] and widely  
528 usage both in academia and industry is the SCALA [168] programming language stands  
529 out.

## 530 **5.4 Functional Logic Programming Languages**

531 Knowing that there is quite some amount of literature out there on these type of languages,  
532 it is fairly easy to say that there have been numerous attempts at specifications and/or imple-  
533 mentations. Sadly though not many have survived leave alone being successful as a result of



the competition. Only the ones that are easily available or have an implementation or have been cited or referred by other attempts have been included as the list is long and does not reflect the main intention of the document. Beginning with the ones from Australia, which seems to be a popular destination for fiddling with PROLOG and merging paradigms. As of now there have been three popular ones, beginning with NEU PROLOG, [74], OZ (MOZART PROGRAMMING SYSTEM) [21] and MERCURY [28]. Delving deeper the languages feel more like extensions of PROLOG rather than hybrids. Starting with MERCURY which a boundary between deterministic and non-deterministic programs, similarly NUE PROLOG has special support for functions while OZ gives concurrent constraint programming plus distributed support, with different function types for goal solving and expression rewriting. ESCHER [75] comes very close to HASKELL with monads, higher order functions and lazy evaluation. Taking a look at PROLOG variants, CIAO [18]; a preprocessor to PROLOG for functional syntax support,  $\lambda$  PROLOG [84] aims at modular higher order programming with abstract data types in a logical setting, BABEL [50, 81, 80] combines pure PROLOG with a first order functional notation, LIFE [127] is for Logic, Inheritance, Functions and Equations in PROLOG syntax with currying and other features like functional languages and others [10, 77].

The functional language SCHEME is a very popular choice for this sort of a thing. With a book [25] and an implementation to accompany [26, 122] which seems to have translated into HASKELL, [57, 39, 132].

Finally talking about CURRY, one of the most popular HASKELL based multi paradigm languages with support for deterministic and non-deterministic computations. Contributing to the same there have been some predecessors [125, 27].

## 5.5 From chap 9

Unifying / Marrying / Merging / Combining Programming Paradigms / Theories

## 559 **5.6 Theory**

### 560 • Papers

- 561 1. Unifying Theories of Programming with Monads, [43]
- 562 2. Symposium on Unifying Theories of Programming, 2006, [33].
- 563 3. Symposium on Unifying Theories of Programming, 2008, [12].
- 564 4. Symposium on Unifying Theories of Programming, 2010, [94].
- 565 5. Symposium on Unifying Theories of Programming, 2012, [165].

### 566 • Books

- 567 1. Unifying Theories of Programming, [52]

### 568 • Articles / Blogs / Discussions

- 569 1. ???

### 570 • Websites

- 571 1. ???

## 572 **5.7 Implementations**

- 573 1. Scala
- 574 2. Virgil
- 575 3. CLOS, Common Lisp Object System
- 576 4. Visual Prolog
- 577 5. ????

578 **5.8 Miscellaneous / Possibly Related Content**

579 1. ???

## Chapter 6

### Related Work

There are some technicalities which are indirectly related to the problem but do not bare a point of contact. The underpinnings of the languages throw some more light on the how different languages work to solve a problem. Different programming paradigms incorporate different operational mechanisms. For example, PROLOG programs execute on the Warren Abstract Machine [1] which has three different storage usages; a global stack for compound terms, for environment frames and choice points and lastly the trail to record which variables bindings ought to be undone on backtracking.

Constraint programming [153] is closely related to the declarative programming paradigm in the sense that the relations between variables is specified in the form of constraints. For example, consider a program to solve a simultaneous equation, now adding on to that restricting the range of the values that the variables can possible take, thus adding constraints to the possible solutions. Related to the same are Constraint Handling Rules [152], which are extensions to a language, simply speaking adding constraints to a language like PROLOG.

Lastly some details on the working of functional logic programming languages, residuation and narrowing [48, 147]. Residuation involves delaying of functions calls until they are deterministic, that is, deterministic reduction of functions with partial data. This princi-

599 ple is used in languages like ESCHER [75], LIFE [127], NUE-PROLOG [74] and Oz [21].  
600 Narrowing on the other hand is a mixture of reduction in functional languages and unifi-  
601 cation in logic languages. In narrowing, a variable is bound a value within the specified  
602 constraints and try to find a solution, values are generated while searching rather than just  
603 for testing. The languages based on this approach are ALF [125], BABEL [50], LPG [10]  
604 and CURRY [129].

## 605 **Chapter 7**

## 606 **Prolog in \_\_\_\_\_**

607 Prolog in \_\_\_\_\_

### 608 **7.1 Theory**

#### 609 • Papers

610 1. QLog, [66]

611 2. LogLisp Motivation, design, and implementation, [99]

#### 612 • Books

613 1. Warrens Abstract Machine A TUTORIAL RECONSTRUCTION, [1]

614 2. LOGLISP: an alternative to PROLOG, [100]

#### 615 • Articles / Blogs / Discussions

616 1. Hello

#### 617 • Websites

618 1. Hello

## 619 **7.2 Implementations**

- 620 1. Castor : Logic paradigm for C++, [83]
- 621 2. GNU Prolog for Java, [44]
- 622 3. JLog - Prolog in Java, [58]
- 623 4. JScriptLog - Prolog in Java, [59]
- 624 5. Quintus Prolog, [92]
- 625 6. Yield Prolog, [93]
- 626 7. Racklog, [110]

## 627 **7.3 Important People**

- 628 1. ???

## 629 **7.4 Miscellaneous / Possibly Related Content**

- 630 1. ???

## 631 **Chapter 8**

## 632 **Prolog in Haskell**

633 Prolog in Haskell

### 634 **8.1 Theory**

635 • Papers

- 636 1. Embedding Prolog in Haskell / Functional Reading of Logic Programs, [115]
- 637 2. Algebra of Logic Programming, [107]
- 638 3. The Algebra of Logic Programming, [105]
- 639 4. Optimisation Problems in Logic Programming : An Algebraic Approach, [106]
- 640 5. Higher Order Transformation of Logic Programs, [108]
- 641 6. The Algebra of Searching, [114]
- 642 7. FUNCTIONAL PEARL Combinators for breadth-first search, [116]
- 643 8. Type Logic Variables, K Classen, [19]
- 644 9. A Type-Safe Embedding of Constraint Handling Rules into Haskell Wei-Ngan
- 645 Chin, Mar-tin Sulzmann and Meng Wang, [17]



646 10. Prological Features in a Functional Setting Axioms and Implementation, R  
647 Hinze, [51]

648 11. Escape from Zurg: An Exercise in Logic Programming, [36]

649 • Books

650 1. The Reasoned Schemer, Daniel P. Friedman, William E. Byrd, Oleg Kiselyov,  
651 [25]

652 2. Programming Languages: Application and Interpretation, Shriram Krishna-  
653 murthi, Chapters 33-34 of PLAI discuss Prolog and implementing Prolog, [67]

654 • Articles / Blogs / Discussions

655 1. Lambda the Ultimate, Programming Languages, [69]

656 2. Takashi's Workplace (Implementation), [166]

657 3. Haskell vs. Prolog Comparison, [117]

658 • Websites

659 1. Logic Programming in Haskell, [134]

## 660 **8.2 Implementations**

661 1. A Prolog in Haskell, Takashi's Workplace, [166]

662 2. Mini Prolog for Hugs 98, [61]

663 3. Nano Prolog, [120]

664 4. Prolog, [103]

665 5. cspm-To-Prolog, [40]

- 666 6. prolog-graph, [7]
- 667 7. prolog-graph-lib, [102]
- 668 8. hswip, [121]

## 669 **8.3 Important People**

- 670 1. Mike Spivey
- 671 2. Silvija Seres

## 672 **8.4 Miscellaneous / Possibly Related Content**

- 673 1. Unification Libraries
  - 674 (a) unification-fd, [123]
  - 675 (b) cmu, [95]
- 676 2. Logic Libraries
  - 677 (a) logicct, [23], [24]
  - 678 (b) logic-classes, [?]
  - 679 (c) proplogic, [41]
  - 680 (d) cflp, [37]
  - 681 (e) logic-grows-on-trees, [22]
- 682 3. Concatenative Programming
  - 683 (a) peg, [29]
- 684 4. Constraint Programming and Constraint Handling Rules

- 685       (a) monadiccp, [98]
- 686       (b) monadiccp-gecode, [124]
- 687       (c) csp, [6]
- 688       (d) liquid fix point, [104]

## 689 **Chapter 9**

# 690 **Quasiquotation**

## 691 **9.1 Theory**

### 692 1. Papers

693 (a)

### 694 2. Books

695 (a)

### 696 3. Articles / Blogs / Discussions

697 (a)

### 698 4. Websites

699 (a) Quasiquotation Wikipedia, [149]

700 (b) Quasiquotation in Haskell, [136]

## 701 **9.2 Implementations**

702 1.

703 **9.3 Miscellaneous / Possibly Related Content**

704 1.

## 705 Chapter 10

### 706 Meta Syntactic Variables

707 Some sources for the topic

708 [164] A metasyntactic variable is a placeholder name used in computer science, a word  
709 without meaning intended to be substituted by some objects pertaining to the context where  
710 it is used. The word foo as used in IETF Requests for Comments is a good example. By  
711 mathematical analogy, a metasyntactic variable is a word that is a variable for other words,  
712 just as in algebra letters are used as variables for numbers. Any symbol or word which does  
713 not violate the syntactic rules of the language can be used as a metasyntactic variable.

714 [15] A name used in examples and understood to stand for whatever thing is under  
715 discussion, or any random member of a class of things under discussion. The word foo is  
716 the canonical example. To avoid confusion, hackers never (well, hardly ever) use foo or  
717 other words like it as permanent names for anything. In filenames, a common convention  
718 is that any filename beginning with a metasyntactic-variable name is a scratch file that may  
719 be deleted at any time.

720 Metasyntactic variables are so called because they are variables in the metalanguage  
721 used to talk about programs etc; they are variables whose values are often variables (as in  
722 usages like the value of  $f(\text{foo}, \text{bar})$  is the sum of foo and bar). However, it has been plausibly  
723 suggested that the real reason for the term metasyntactic variable is that it sounds good. To

724 some extent, the list of one's preferred metasyntactic variables is a cultural signature. They  
725 occur both in series (used for related groups of variables or objects) and as singletons. Here  
726 are a few common signatures:

727 [56] In programming, a metasyntactic (which derives from meta and syntax ) variable is  
728 a variable (a changeable value) that is used to temporarily represent a function . Examples  
729 of metasyntactic variables include (but are by no means limited to) ack, bar , baz, blarg,  
730 wibble, foo , fum, and qux. Metasyntactic variables are sometimes used in developing a  
731 conceptual version of a program or examples of programming code written for illustrative  
732 purposes.

733 Any filename beginning with a metasyntactic variable denotes a scratch file. This means  
734 the file can be deleted at any time without affecting the program.

735 [14]

736 A word, used in conversation or text that is meant as a variable. There is a fairly  
737 standard set in the ComputerScience culture. People tend to create their own if they are not  
738 exposed to others, which can be confusing. Of course, if you haven't seen them before they  
739 can be quite confusing. They are, however, useful enough that this is not enough reason to  
740 give them up. Standard set: foo, bar, baz, foobar/quux, quuux, quuuux, ....

741 example: "Suppose I have a list, foo, with a node, bar, ..."

## Chapter 11

### Haskell or Why Haskell ?

In this chapter we discuss the properties of HASKELL

This chapter discusses the properties of the host language HASKELL and mainly the feature set it provides for embedding domain specific languages(EDSLs).

1. HASKELL as a functional programming language Haskell is an advanced purely-functional programming language. In particular, it is a polymorphically statically typed, lazy, purely functional language [139]. It is one of the popular functional programming languages [73]. HASKELL is widely used in the industry [143].

Shifting a bit to Embedded Domain Specific Languages (EDSLs) such as Emacs LISP. Opting for embedding provides a "shortcut" to create a language which may be designed to provide specific functionality. Designing a language from scratch would require writing a parser, code generator / interpreter and possibly a debugger, not to mention all the routine stuff that every language needs like variables, control structures and arithmetic types. All of the aforementioned are provided by the host language; in this case HASKELL. Examples for the same can be found here [62, 79] which talk about introducing combinator libraries for custom functionality.

The flip side of the coin is that the host language enforces certain aspects and properties of the eDSL and hence might not be exact to specification, all required constructs



761 cannot be implemented due to constraints, programs could be difficult to debug since  
762 it happens at the host level and so on.

## 763 2. Looking at HASKELL as a tool for embedding domain specific languages[60]

### 764 (a) Monads

765 Control flow defines the order/ manner of execution of statements in a program[162].

766 The specification is set by the programming language. Generally, in the case  
767 of imperative languages the control flow is sequential while for a functional  
768 language is recursion [126]. For example, JAVA has a top down sequential  
769 execution approach. The declarative style consists of defining components of  
770 programs i.e. computations not a control flow[163].

771 This is where HASKELL shines by providing something called a *monad*. Func-  
772 tional Programming Languages define computations which then need to be or-  
773 dered in some way to form a combination[137]. A monad gives a bubble within  
774 the language to allow modification of control flow without affecting the rest of  
775 the universe. This is especially useful while handling side effects.

776 A related topic would be of persistence languages, architectures and data struc-  
777 tures. Persistent programming is concerned with creating and manipulating  
778 data in a manner that is independent of its lifetime [82]. A persistent data struc-  
779 ture supports access to multiple versions which may arise after modifications  
780 [32, 64]. A structure is partially persistent if all versions can be accessed but  
781 only the current can be modified and fully persistent if all of them can be mod-  
782 ified.

783 Coming back to control flow; for example, implementing backtracking in an  
784 imperative language would mean undoing side effects which even PROLOG is  
785 not able to do since the asserts and retracts cannot be undone. In HASKELL, a  
786 monad defines a model for control flow and how side effects would propagate

787 through a computation from step to step or modification to modification. And  
788 HASKELL allows creation of custom monads relieving the burden of dealing  
789 with a fixed model of the host language.

790 (b) Lazy Evaluation

791 Another property of HASKELL is laziness or lazy evaluation which means that  
792 nothing is evaluated until it is necessary. This results in the ability to define  
793 infinite data structures because at execution only a fragment is used [141].

## 794 Chapter 12

### 795 Prolog or Why Prolog ?

796 This chapter discusses the properties of the target language PROLOG and the feature set  
797 that will be translated to the host language to extend its capabilities.

798 1. PROLOG as a logic programming language.

799 PROLOG is a general purpose logic programming language mainly used in artificial  
800 intelligence and computational linguistics. It is a Declarative language i.e. a pro-  
801 gram is a set of facts and rules running a query on which will return a result. The  
802 relation between them is defined by clauses using *Horn Clauses*[144]. PROLOG is  
803 very popular and has a number of implementations [161] for different purposes.

804 2. Why embed PROLOG ?

# Chapter 13

## Prototype 1

### 13.1 About this chapter

This chapter throws light on what PROLOG does to resolve a given query via *unification* and this can be replicated in the host language along with the challenges.

This chapter discusses the aspects of opening a language while preserving the original structure of a closed recursive structure in HASKELL. Also discussed are the issues related to customizing certain aspects such as meta-syntactic variables.

### 13.2 How Prolog works ?

Looking at how PROLOG works [119].

Most PROLOG distributions have three types of terms:

1. Constants.

2. Variables.

3. Complex terms.

Two terms can be unified if they are the same or the variables can be assigned to terms such that the resulting terms are equal.

821 The possibilities could be,

- 822 1. If term1 and term2 are constants, then term1 and term2 unify if and only if they are  
823 the same atom, or the same number.

```
1  ?- =(mia,mia).  
2  yes
```

- 824 2. If term1 is a variable and term2 is any type of term, then term1 and term2 unify, and  
825 term1 is instantiated to term2 . Similarly, if term2 is a variable and term1 is any type  
826 of term, then term1 and term2 unify, and term2 is instantiated to term1 . (So if they  
827 are both variables, theyre both instantiated to each other, and we say that they share  
828 values.)

```
1  ?- mia = X.  
2  X = mia  
3  yes
```

```
1  ?- X = Y.  
2  yes
```

- 829 3. If term1 and term2 are complex terms, then they unify if and only if:

830 (a) They have the same functor and arity, and

831 (b) all their corresponding arguments unify, and

832 (c) the variable instantiations are compatible.

```
1  ?- k(s(g),Y) = k(X,t(k)).  
2  X = s(g)  
3  Y = t(k)  
4  yes
```

- 833 4. Two terms unify if and only if it follows from the previous three clauses that they  
834 unify.

835 For example, consider the append function

```
1 append([],L,L).  
2 append([H|T],L2,[H|L3]) :- append(T,L2,L3).
```




Figure 13.1: Trace for append [118]

### 836 13.3 What we do in this Prototype

837 This prototype throws light on the process of tackling the issues involved in creating a data  
838 type to replicate the target language type system while conforming to the host language  
839 restrictions and also utilizing the benefits.

840 We have a PROLOG like language in HASKELL defined via *data*.

841 The language defined is recursive in nature.

842 We convert it into a non recursive data type.

843 Basically we do Unification monadically.

## 844 **13.4 Creating a data type**

845 A type system consists of a set of rules to define a "type" to different constructs in a pro-  
846 gramming language such as variables, functions and so on. A static type system requires  
847 types to be attached to the programming constructs before hand which results in finding  
848 errors at compile time and thus increase the reliability of the program. The other end is the  
849 dynamic type system which passes through code which would not have worked in former  
850 environment, it comes of as less rigid.

851 The advantages of static typing [78]

- 852 1. Earlier detection of errors
- 853 2. Better documentation in terms of type signatures
- 854 3. More opportunities for compiler optimizations
- 855 4. Increased run-time efficiency
- 856 5. Better developer tools

857 For dynamic typing

- 858 1. Less rigid
- 859 2. Ideal for prototyping / unknown / changing requirements or unpredictable behaviour
- 860 3. Re-usability

861 **Transitional paragraph** An ideal case would would be something that is ..... dont  
862 know what to write

863 To start with, replicating the single type "term" in PROLOG one must consider the dis-  
 864 tinct constructs it can be associated to such as complex structures (for example predicates,  
 865 clauses etc.), don't cares, cuts, variables and so on.

866 Consider the language below,

```

1  data VariableName = VariableName Int String
2      deriving (Eq, Data, Typeable, Ord)
3  data Atom          = Atom          !String
4                      | Operator    !String
5      deriving (Eq, Ord, Data, Typeable)
6  data Term = Struct Atom [Term]
7              | Var VariableName
8              | Wildcard
9              | PString    !String
10             | PInteger   !Integer
11             | PFloat     !Double
12             | Flat [FlatItem]
13             | Cut Int
14      deriving (Eq, Data, Typeable)
15  data Clause = Clause { lhs :: Term, rhs_ :: [Goal] }
16              | ClauseFn { lhs :: Term, fn :: [Term] -> [Goal] }
17      deriving (Data, Typeable)
18  type Program = [Sentence]
19  type Body     = [Goal]
20  data Sentence = Query    Body
21                | Command Body
22                | C Clause
23      deriving (Data, Typeable)

```

867 Even though *Term* has a number of constructors the resulting construct has a single  
 868 type. Hence, a function would still be untyped / singly typed,

```
append :: [Term] -> [Term] -> [Term]
```

869 The above data type is recursive as seen in the constructor,

```
Struct Atom [Term]
```

870 One of the issues with the above is that it is not possible to distinguish the structure of  
 871 the data from the data type itself [109]. Consider the following, a reduced version of the  
 872 above data type,



```

1  type Atom          = String
2  data VariableName = VariableName Int String
3      deriving (Eq, Data, Typeable, Ord)
4  data Term = Struct Atom [Term]
5      | Var VariableName
6      | Wildcard -- Don't cares
7      | Cut Int
8      deriving (Eq, Data, Typeable)

```

873 Also one cannot create Quantifiers plus logic

874 To split a data type into two levels, a single recursive data type is replaced by two related  
875 data types. Consider the following,

```

1  data FlatTerm a =
2      Struct Atom [a]
3      | Var VariableName
4      | Wildcard
5      | Cut Int deriving (Show, Eq, Ord)

```

876 One result of the approach is that the non-recursive type *FlatTerm* is modular and  
877 generic as the structure "FlatTerm" is separate from it's type which is "a". Simply speaking  
878 we can have something like

```
FlatTerm Bool
```

879 and a generic fuinction like,

```
map :: (a -> b) -> FlatTerm a -> FlatTerm b
```

## 880 13.5 Working with the language

881 Creating instances,

```

1  instance Functor (FlatTerm) where
2      fmap = T.fmapDefault
3  instance Foldable (FlatTerm) where
4      foldMap = T.foldMapDefault
5  instance Traversable (FlatTerm) where
6      traverse f (Struct atom x) = Struct atom <$>
7      sequenceA (Prelude.map f x)

```

```

8         traverse _ (Var v)           = pure (Var v)
9         traverse _ Wildcard          = pure (Wildcard)
10        traverse _ (Cut i)            = pure (Cut i)
11    instance Unifiable (FlatTerm) where
12        zipMatch (Struct al ls) (Struct ar rs) =
13            if (al == ar) && (length ls == length rs)
14                then Struct al <$>
15                    pairWith (\l r -> Right (l,r)) ls rs
16                else Nothing
17        zipMatch Wildcard _ = Just Wildcard
18        zipMatch _ Wildcard = Just Wildcard
19        zipMatch (Cut i1) (Cut i2) = if (i1 == i2)
20            then Just (Cut i1)
21            else Nothing
22    instance Applicative (FlatTerm) where
23        pure x = Struct "" [x]
24        _ <*> Wildcard          = Wildcard
25        _ <*> (Cut i)            = Cut i
26        _ <*> (Var v)            = (Var v)
27        (Struct a fs) <*> (Struct b xs) = Struct (a ++ b) [f x | f <- fs, x <- xs]

```

882 After flattening do fixing,

883 Opening up the language somehow so as to accommodate your own variables.

## 884 13.6 Black box

# Chapter 14

## Prototype 2.1

### 14.1 About this chapter

This chapter attempts to infuse the generic methodology from 13 in a current PROLOG implementation [103] and make the unification "monadic".

### 14.2 How prolog-0.2.0.1 works

The original syntax used by the library,

```
1 data Term = Struct Atom [Term]
2           | Var VariableName
3           | Wildcard -- Don't cares
4           | Cut Int
5           deriving (Eq, Data, Typeable)
6
7 data Clause = Clause { lhs :: Term, rhs_ :: [Goal] }
8               | ClauseFn { lhs :: Term, fn :: [Term] -> [Goal] }
9               deriving (Data, Typeable)
10
11 rhs :: Clause -> [Term] -> [Goal]
12 rhs (Clause _ rhs) = const rhs
13 rhs (ClauseFn _ fn) = fn
14
15 data VariableName = VariableName Int String
```

```

16     deriving (Eq, Data, Typeable, Ord)
17
18     type Atom          = String
19     type Goal          = Term
20     type Program       = [Clause]

```

892 The above language suffers from most of the problems discussed in the previous chap-  
893 ter.

894 The above is used to construct PROLOG "terms" which are of a "single type".

895 A database is used to store the terms which can then be used to resolve a query.

896 An interpreter to solve a query and lastly the unifier,

897 There are a few other components such as the REPL, Parser.

## 898 14.3 What we do in this prototype?

899 In the first prototype we just did unification of two terms not query resolution.

900 We do complete PROLOG query resolution like stuff.

901 13 provides a generic procedure / methodology to convert a language into monadic  
902 unifiable form

## 903 14.4 Current implementation (prolog-0.2.0.1)

904 The current unification uses basic pattern matching to unify the terms

```

1  unify, unify_with_occurs_check :: MonadPlus m => Term -> Term
2  -> m Unifier
3
4  unify = fix unify'
5
6  unify_with_occurs_check =
7      fix $ \self t1 t2 -> if (t1 'occursIn' t2 || t2 'occursIn' t1)
8                          then fail "occurs check"
9                          else unify' self t1 t2
10  where

```

```

11     occursIn t = everything (||) (mkQ False (==t))
12
13 unify' :: MonadPlus m => (Term -> Term -> m Unifier) -> Term ->
14 Term -> m [(VariableName, Term)]
15
16 -- If either of the terms are don't cares then no unifiers exist
17 unify' _ Wildcard _ = return []
18 unify' _ _ Wildcard = return []
19
20 -- If one is a variable then equate the term to its value which
21 -- forms the unifier
22 unify' _ (Var v) t = return [(v,t)]
23 unify' _ t (Var v) = return [(v,t)]
24
25 -- Match the names and the length of their parameter list and
26 -- then match the elements of list one by one.
27 unify' self (Struct a1 ts1) (Struct a2 ts2)
28     | a1 == a2 && same length ts1 ts2 =
29     unifyList self (zip ts1 ts2)
30
31 unify' _ _ _ = mzero
32
33 same :: Eq b => (a -> b) -> a -> a -> Bool
34 same f x y = f x == f y
35
36 -- Match the elements of each of the tuples in the list.
37 unifyList :: Monad m => (Term -> Term -> m Unifier) ->
38 [(Term, Term)] -> m Unifier
39 unifyList _ [] = return []
40 unifyList unify ((x,y):xys) = do
41     u <- unify x y
42     u' <- unifyList unify (Prelude.map (both (apply u)) xys)
43     return (u++u')

```

## 14.5 Modifications

The first modification to the language is to make it compatible with the library which provides this nice generic mechanism to perform unification in a monadic manner. Fixing, flattening, creating necessary instances

```

1 data FTS a = FS Atom [a] | FV VariableName | FW | FC Int
2             deriving (Show, Eq, Typeable, Ord)

```

```

3
4 newtype Prolog = P (Fix FTS) deriving (Eq, Show, Ord, Typeable)
5
6 unP :: Prolog -> Fix FTS
7 unP (P x) = x
8
9 instance Functor (FTS) where
10     fmap                = T.fmapDefault
11
12 instance Foldable (FTS) where
13     foldMap              = T.foldMapDefault
14
15 instance Traversable (FTS) where
16     traverse f (FS atom xs)      = FS atom <$>
17     sequenceA (Prelude.map f xs)
18     traverse _ (FV v)            = pure (FV v)
19     traverse _ FW                = pure (FW)
20     traverse _ (FC i)            = pure (FC i)
21
22 instance Unifiable (FTS) where
23     zipMatch (FS al ls) (FS ar rs) =
24         if (al == ar) && (length ls == length rs)
25         then FS al <$> pairWith (\l r -> Right (l,r)) ls rs
26         else Nothing
27     zipMatch FW _ = Just FW
28     zipMatch _ FW = Just FW
29     zipMatch (FC i1) (FC i2) = if (i1 == i2)
30     then Just (FC i1)
31     else Nothing
32
33 instance Applicative (FTS) where
34     pure x                = FS "" [x]
35     _ <*> FW              = FW
36     _ <*> (FC i)           = FC i
37     _ <*> (FV v)           = (FV v)
38     (FS a fs) <*> (FS b xs) = FS (a ++ b) [f x | f <- fs, x <- xs]

```

909 some translation and helper functions .....

910 and finally the unification

```

1 monadicUnification :: (BindingMonad FTS (STVar s FTS)
2   (ST.STBinding s))
3 => (forall s. ((Fix FTS) -> (Fix FTS) ->
4   ErrorT (UT.UFailure (FTS) (ST.STVar s (FTS))))

```

```

5         (ST.STBinding s) (UT.UTerm (FTS) (ST.STVar s (FTS)),
6         Map VariableName (ST.STVar s (FTS))))))
7 monadicUnification t1 t2 = do
8   -- let
9   --   t1f = termFlattener t1
10  --   t2f = termFlattener t2
11  (x1,d1) <- lift . translateToUTerm $ t1
12  (x2,d2) <- lift . translateToUTerm $ t2
13  x3 <- U.unify x1 x2
14  --get state from somewhere, state -> dict
15  return $! (x3, d1 'Map.union' d2)
16
17
18 goUnify ::
19   (forall s. (BindingMonad FTS (STVar s FTS) (ST.STBinding s))
20   =>
21     (ErrorT
22       (UT.UFailure FTS (ST.STVar s FTS))
23       (ST.STBinding s)
24       (UT.UTerm FTS (ST.STVar s FTS),
25        Map VariableName (ST.STVar s FTS)))
26     )
27   -> [(VariableName, Prolog)]
28 goUnify test = ST.runSTBinding $ do
29   answer <- runErrorT $ test --ERROR
30   case answer of
31     (Left _)          -> return []
32     (Right (_, dict)) -> f1 dict
33
34
35 f1 ::
36   (BindingMonad FTS (STVar s FTS) (ST.STBinding s))
37   => (forall s. Map VariableName (STVar s FTS)
38     -> (ST.STBinding s [(VariableName, Prolog)]))
39     )
40 f1 dict = do
41   let ld1 = Map.toList dict
42   ld2 <- Control.Monad.Error.sequence
43   [ v1 | (k,v) <- ld1, let v1 = UT.lookupVar v ]
44   let ld3 = [ (k,v) | ((k,_),Just v) <- ld1 'zip' ld2 ]
45   ld4 = [ (k,v) | (k,v2) <- ld3,
46     let v = translateFromUTerm dict v2 ]
47   return ld4

```

## 911 **14.6 Results**

912 It works,



## 913 **Chapter 15**

## 914 **Prototype 3**

915 When two terms are to be unified we can use 13 ,  
916 term1 and term2 are matched and an assignment is the result  
917 now this may be a part of a query resolution procedure  
918 to reach the point where two terms need to unified will happen through some sort of  
919 search strategy  
920 and our approach is independent of that, and this prototype is a proof of concept to  
921 implementing query resolution using unification with variable search strategy

### 922 **15.1 Unification**

923 The first, "unification," regards how terms are matched and variables assigned to make  
924 terms match. [35]

### 925 **15.2 Resolution**

926 this where the complete procedure takes place after the query is passed along with the  
927 knowledge  
928 the resolver searches to create and a list of goals and then tries to achieve each one.

929 [34]

## 930 15.3 Search strategies

931 The base implementation used for this prototype is [61] and below are the search strategies

## 932 15.4 Stack Engine

```
1  -- Stack based Prolog inference engine
2  -- Mark P. Jones November 1990, modified for Gofer 20th July 1991,
3  -- and for Hugs 1.3 June 1996.
4  --
5  -- Suitable for use with Hugs 98.
6  --
7
8  module StackEngine( version, prove ) where
9
10 import Prolog
11 import st
12 import Interact
13
14 version = "stack based"
15
16 --- Calculation of solutions:
17
18 -- the stack based engine maintains a stack of triples (s,goal,alts)
19 -- corresponding to backtrack points, where s is the stitution at that
20 -- point, goal is the outstanding goal and alts is a list of possible ways
21 -- of extending the current proof to find a solution. Each member of alts
22 -- is a pair (tp,u) where tp is a new goal that must be proved and u is
23 -- a unifying stitution that must be combined with the stitution s.
24 --
25 -- the list of relevant clauses at each step in the execution is produced
26 -- by attempting to unify the head of the current goal with a suitably
27 -- renamed clause from the database.
28
29 type Stack = [ (st, [Term], [Alt]) ]
30 type Alt   = ([Term], st)
31
32 alts      :: Database -> Int -> Term -> [Alt]
```

```

33  alts db n g = [ (tp,u) | (tm:-tp) <- renClauses db n g, u <- unify g tm ]
34
35  -- The use of a stack enables backtracking to be described explicitly,
36  -- in the following 'state-based' definition of prove:
37
38  prove      :: Database -> [Term] -> [st]
39  prove db gl = solve 1 nullst gl []
40  where
41    solve :: Int -> st -> [Term] -> Stack -> [st]
42    solve n s []      ow      = s : backtrack n ow
43    solve n s (g:gs) ow
44        | g==theCut = solve n s gs (cut ow)
45        | otherwise = choose n s gs (alts db n (app s g)) ow
46
47    choose :: Int -> st -> [Term] -> [Alt] -> Stack -> [st]
48    choose n s gs []      ow = backtrack n ow
49    choose n s gs ((tp,u):rs) ow = solve (n+1) (u@@s) (tp++gs) ((s,gs,rs):ow)
50
51    backtrack      :: Int -> Stack -> [st]
52    backtrack n []      = []
53    backtrack n ((s,gs,rs):ow) = choose (n-1) s gs rs ow
54
55
56  --- Special definitions for the cut predicate:
57
58  theCut      :: Term
59  theCut      = Struct "!" []
60
61  cut          :: Stack -> Stack
62  cut ss      = []
63
64  --- End of Engine.hs

```

## 933 15.5 Pure Engine

```

1  -- The Pure Prolog inference engine (using explicit prooftrees)
2  -- Mark P. Jones November 1990, modified for Gofer 20th July 1991,
3  -- and for Hugs 1.3 June 1996.
4  --
5  -- Suitable for use with Hugs 98.
6  --
7

```

```

8  module PureEngine( version, prove ) where
9
10 import Prolog
11 import st
12 import Interact
13 import Data.List(nub)
14
15 version = "tree based"
16
17 --- Calculation of solutions:
18
19 -- Each node in a proof tree corresponds to:
20 -- either: a solution to the current goal, represented by Done s, where s
21 --          is the required stitution
22 -- or:      a choice between a number of trees ts, each corresponding to a
23 --          proof of a goal of the current goal, represented by Choice ts.
24 --          The proof tree corresponding to an unsolvable goal is Choice []
25
26 data ProofTree = Done st | Choice [ProofTree]
27
28 -- proof tree uses the rules of Prolog to construct a suitable proof tree for
29 -- a specified goal
30 proofTree :: Database -> Int -> st -> [Term] -> ProofTree
31 proofTree db = pt
32   where pt :: Int -> st -> [Term] -> ProofTree
33         pt n s [] = Done s
34         pt n s (g:gs) = Choice [ pt (n+1) (u@@s) (map (app u) (tp++gs))
35                                   | (tm:-tp)<-renClauses db n g, u<-unify g tm ]
36   {--
37   pt 1 nullst [] = Done (nullst)
38
39   pt n s (g:gs)
40
41   renClauses :- Rename variables in a clause, the parameters are the database, an
42                 (head of list) resulting in a clause.
43
44   unify :- take the head of the list and and match with head of clause from renCla
45
46   app :- function for applying (st) to (Terms)
47   the new list is formed by replacing the cluase head with its body and applying t
48
49   so the new parameters for pt are
50
51   (n+1) (the old stitution + the new one from unify) (the list formed after applyi
52

```

```

53
54 Working of a small example
55
56 The database,
57 (foldl addClause emptyDb [((:-) (Struct "hello" []) []), ((:-) (Struct "hello" [
58 hello.
59 hello(world).
60 hello:-world.
61 hello(X_1).
62
63 The other parameters are 1 nullst(as mentioned in the prove function).
64
65 For the list of goals, [(Struct "hello" []), (Struct "hello" [(Struct "world" [
66
67 1. [Struct "hello" []] :: [Term]
68
69 * Rule 1 does not apply
70
71 * Rule 2 does apply,
72
73 (tm:- tp) <- renClauses db 1 (Struct "hello" [])
74
75 tm ==> "hello , hello(world) , hello , hello(X_1) , "
76 tp ==> "[] , [] , [world] , [] , "
77
78
79
80
81
82
83
84
85
86 --}
87
88
89
90 -- DFS Function
91 -- search performs a depth-first search of a proof tree, producing the list
92 -- of solution stitutions as they are encountered.
93 search :: ProofTree -> [st]
94 search (Done s) = [s]
95 search (Choice pts) = [ s | pt <- pts, s <- search pt ]
96
97

```

```

98 prove    :: Database -> [Term] -> [st]
99 prove db = search . prooftree db 1 nullst
100
101 --- End of PureEngine.hs

```

## 934 15.6 Andorra Engine

```

1  {-
2  By Donald A. Smith, December 22, 1994, based on Mark Jones' PureEngine.
3
4  This inference engine implements a variation of the Andorra Principle for
5  logic programming. (See references at the end of this file.) The basic
6  idea is that instead of always selecting the first goal in the current
7  list of goals, select a relatively deterministic goal.
8
9  For each goal g in the list of goals, calculate the resolvents that would
10 result from selecting g. Then choose a g which results in the lowest
11 number of resolvents. If some g results in 0 resolvents then fail.
12 (This would occur for a goal like: ?- append(A,B,[1,2,3]),equals(1,2).)
13 Prolog would not perform this optimization and would instead search
14 and backtrack wastefully. If some g results in a single resolvent
15 (i.e., only a single clause matches) then that g will get selected;
16 by selecting and resolving g, bindings are propagated sooner, and useless
17 search can be avoided, since these bindings may prune away choices for
18 other clauses. For example: ?- append(A,B,[1,2,3]),B=[].
19 -}
20
21 module AndorraEngine( version, prove ) where
22
23 import Prolog
24 import st
25 import Interact
26
27 version = "Andorra Principle Interpreter (select deterministic goals first)"
28
29 solve    :: Database -> Int -> st -> [Term] -> [st]
30 solve db = slv where
31     slv    :: Int -> st -> [Term] -> [st]
32     slv n s [] = [s]
33     slv n s goals =
34         let allResolvents = resolve_selecting_each_goal goals db n in
35         let (gs,gres) = findMostDeterministic allResolvents in

```

```

36         concat [slv (n+1) (u@@s) (map (app u) (tp++gs)) | (u,tp) <- gres]
37
38 resolve_selecting_each_goal::
39     [Term] -> Database -> Int -> [[Term],[[st,[Term]]]]
40 -- For each pair in the list that we return, the first element of the
41 -- pair is the list of unresolved goals; the second element is the list
42 -- of resolvents of the selected goal, where a resolvent is a pair
43 -- consisting of a stitution and a list of new goals.
44 resolve_selecting_each_goal goals db n = [(gs, gResolvents) |
45     (g,gs) <- delete goals, let gResolvents = resolve db g n]
46
47 -- The unselected goals from above are not passed in.
48 resolve :: Database -> Term -> Int -> [(st,[Term])]
49 resolve db g n = [(u,tp) | (tm:-tp)<-renClauses db n g, u<-unify g tm]
50 -- u is not yet applied to tp, since it is possible that g won't be selected.
51 -- Note that unify could be nondeterministic.
52
53 findMostDeterministic:: [[Term],[[st,[Term]]]] -> ([Term],[[st,[Term]]])
54 findMostDeterministic allResolvents = minF comp allResolvents where
55     comp:: (a,[b]) -> (a,[b]) -> Bool
56     comp (_,gs1) (_,gs2) = (length gs1) < (length gs2)
57 -- It seems to me that there is an opportunity for a clever compiler to
58 -- optimize this code a lot. In particular, there should be no need to
59 -- determine the total length of a goal list if it is known that
60 -- there is a shorter goal list in allResolvents ... ?
61
62 delete :: [a] -> [(a,[a])]
63 delete l = d l [] where
64     d :: [a] -> [a] -> [(a,[a])]
65     d [g]sofar = [ (g,sofar) ]
66     d (g:gs)sofar = (g,sofar++gs) : (d gs (g:sofar))
67
68 minF :: (a -> a -> Bool) -> [a] -> a
69 minF f (h:t) = m h t where
70 -- m :: a -> [a] -> a
71     m sofar [] = sofar
72     m sofar (h:t) = if (f h sofar) then m h t else m sofar t
73
74 prove :: Database -> [Term] -> [st]
75 prove db = solve db 1 nullst
76
77 {- An optimized, incremental version of the above interpreter would use
78    a data representation in which for each goal in "goals" we carry around
79    the list of resolvents. After each resolution step we update the lists.
80 -}

```

```

81
82 {- References
83
84   Seif Haridi & Per Brand, "Andorra Prolog, an integration of Prolog
85   and committed choice languages" in Proceedings of FGCS 1988, ICOT,
86   Tokyo, 1988.
87
88   Vitor Santos Costa, David H. D. Warren, and Rong Yang, "Two papers on
89   the Andorra-I engine and preprocessor", in Proceedings of the 8th
90   ICLP. MIT Press, 1991.
91
92   Steve Gregory and Rong Yang, "Parallel Constraint Solving in
93   Andorra-I", in Proceedings of FGCS'92. ICOT, Tokyo, 1992.
94
95   Sverker Janson and Seif Haridi, "Programming Paradigms of the Andorra
96   Kernel Language", in Proceedings of ILPS'91. MIT Press, 1991.
97
98   Torkel Franzen, Seif Haridi, and Sverker Janson, "An Overview of the
99   Andorra Kernel Language", In LNAI (LNCS) 596, Springer-Verlag, 1992.
100 -}

```

## 935 15.7 Current Unification

```

1  {-# LANGUAGE DeriveDataTypeable,
2      ViewPatterns,
3      ScopedTypeVariables,
4      DefaultSignatures,
5      TypeOperators,
6      TypeFamilies,
7      DataKinds,
8      DataKinds,
9      PolyKinds,
10     OverlappingInstances,
11     TypeOperators,
12     LiberalTypeSynonyms,
13     TemplateHaskell,
14     AllowAmbiguousTypes,
15     ConstraintKinds,
16     Rank2Types,
17     MultiParamTypeClasses,
18     FunctionalDependencies,
19     FlexibleContexts,

```



```

20         FlexibleInstances,
21         UndecidableInstances
22     #-}
23
24 --stitutions and Unification of Prolog Terms
25 -- Mark P. Jones November 1990, modified for Gofer 20th July 1991,
26 -- and for Hugs 1.3 June 1996.
27 --
28 -- Suitable for use with Hugs 98.
29 --
30
31 module st where
32
33 import Prolog
34 import CustomSyntax
35 import Data.Map as Map
36 import Data.Maybe
37 import Data.Either
38
39 --Unification
40 import Control.Unification.IntVar
41 import Control.Unification.STVar as ST
42
43 import Control.Unification.Ranked.IntVar
44 import Control.Unification.Ranked.STVar
45
46 import Control.Unification.Types as UT
47
48 import Control.Monad.State.UnificationExtras
49 import Control.Unification as U
50
51 -- Monads
52 import Control.Monad.Error
53 import Control.Monad.Trans.Except
54
55 import Data.Functor.Fixedpoint as DFF
56
57 --State
58 import Control.Monad.State.Lazy
59 import Control.Monad.ST
60 import Control.Monad.Trans.State as Trans
61
62 infixr 3 @@
63 infix 4 ->-
64

```

```

65  --- substitutions:
66
67  type st = Id -> Term
68
69  newtype stP = stP { unstP :: st }
70
71  -- instance Show stP where
72  --   show (i) = show £ Var i
73  -- substitutions are represented by functions mapping identifiers to terms.
74  --
75  -- app s      extends the stitution s to a function mapping terms to terms
76  {--
77  Looks like an apply function that applies a stitution function tho the variables
78  --}
79
80
81  -- nullst is the empty stitution which maps every identifier to the same identifi
82
83
84
85  -- i ->- t    is the stitution which maps the identifier i to the term t, but oth
86
87
88  -- s1@@ s2    is the composition of stitutions s1 and s2
89  --           N.B. app is a monoid homomorphism from (st,nullst,(@@))
90  --           to (Term -> Term, id, (.) ) in the sense that:
91  --           app (s1 @@ s2) = app s1 . app s2
92  --           s @@ nullst = s = nullst @@ s
93
94  app                :: st -> Term -> Term
95  app s (Var i)      = s i
96  app s (Struct a ts) = Struct a (Prelude.map (app s) ts)
97  {--
98  app (stFunction) (Struct "hello" [Var (0, "Var")])
99  hello(Var_2) :: Term
100
101  --}
102
103
104  nullst              :: st
105  nullst i            = Var i
106  {--
107  nullst (0, "Var")
108  Var :: Term
109  --}

```

```

110
111
112  --
113  (->-) :: Id -> Term -> st
114  (i ->- t) j | j==i      = t
115              | otherwise = Var j
116  {--
117  :t (->-) (1,"X") (Struct "hello" [])
118  (1,"X") ->- Struct "hello" [] :: (Int,[Char]) -> Term
119  --}
120
121
122  -- Function composition for applying two stitution functions.
123  (@@) :: st -> st -> st
124  s1 @@ s2      = app s1 . s2

```

## 936 15.8 Syntax Modification

```

1  {-# LANGUAGE DeriveDataTypeable,
2      ViewPatterns,
3      ScopedTypeVariables,
4      FlexibleInstances,
5      DefaultSignatures,
6      TypeOperators,
7      FlexibleContexts,
8      TypeFamilies,
9      DataKinds,
10     OverlappingInstances,
11     DataKinds,
12     PolyKinds,
13     TypeOperators,
14     LiberalTypeSynonyms,
15     TemplateHaskell,
16     RankNTypes,
17     AllowAmbiguousTypes,
18     MultiParamTypeClasses,
19     FunctionalDependencies,
20     ConstraintKinds,
21     ExistentialQuantification
22     #-}
23
24  module CustomSyntax where

```

```

25
26 import Data.Generics (Data(..), Typeable(..))
27 import Data.List (intercalate)
28 import Data.Char (isLetter)
29
30 import Control.Monad.State.UnificationExtras
31 import Control.Unification as U
32
33
34 import Data.Functor.Fixedpoint as DFF
35
36
37 import Control.Unification.IntVar
38 import Control.Unification.STVar as ST
39
40 import Control.Unification.Ranked.IntVar
41 import Control.Unification.Ranked.STVar
42
43 import Control.Unification.Types as UT
44
45
46
47 import Data.Traversable as T
48 import Data.Functor
49 import Data.Foldable
50 import Control.Applicative
51
52
53 import Data.List.Extras.Pair
54 import Data.Map as Map
55 import Data.Set as S
56
57
58 import Control.Monad.Error
59 import Control.Monad.Trans.Except
60
61
62 import Prolog
63
64 data FTS a = forall a . FV Id | FS Atom [a] deriving (Eq, Show, Ord, Typeable)
65
66 newtype Prolog = P (Fix FTS) deriving (Eq, Show, Ord, Typeable)
67
68 unP :: Prolog -> Fix FTS
69 unP (P x) = x

```

```

70
71 instance Functor FTS where
72     fmap = T.fmapDefault
73
74 instance Foldable FTS where
75     foldMap = T.foldMapDefault
76
77 instance Traversable FTS where
78     traverse f (FS atom xs) = FS atom <$> sequenceA (Prelude.map f xs)
79     traverse _ (FV v) = pure (FV v)
80
81 instance Unifiable FTS where
82     zipMatch (FS al ls) (FS ar rs) = if (al == ar) && (length ls == length rs)
83                                     then FS al <$> pairWith (\l r -> Right (l,r))
84                                     else Nothing
85     zipMatch (FV v1) (FV v2) = if (v1 == v2) then Just (FV v1)
86                               else Nothing
87     zipMatch _ _ = Nothing
88
89 instance Applicative FTS where
90     pure x = FS "" [x]
91     (FS a fs) <*> (FS b xs) = FS (a ++ b) [f x | f <- fs, x <- xs]
92     --other cases
93     {--
94     instance Monad FTS where
95         func =
96     instance Variable FTS where
97         func =
98
99     instance BindingMonad FTS where
100         func =
101     --}
102
103 data VariableName = VariableName Int String
104
105 idToVariableName :: Id -> VariableName
106 idToVariableName (i, s) = VariableName i s
107
108 variablenameToId :: VariableName -> Id
109 variablenameToId (VariableName i s) = (i,s)
110
111 termFlattener :: Term -> Fix FTS
112 termFlattener (Var v) = DFF.Fix $ FV v
113 termFlattener (Struct a xs) = DFF.Fix $ FS a (Prelude.map termFlattener xs)
114

```

```

115 unFlatten :: Fix FTS -> Term
116 unFlatten (DFF.Fix (FV v))      = Var v
117 unFlatten (DFF.Fix (FS a xs))   = Struct a (Prelude.map unFlatten xs)
118
119
120 variableExtractor :: Fix FTS -> [Fix FTS]
121 variableExtractor (Fix x) = case x of
122   (FS _ xs)   -> Prelude.concat $ Prelude.map variableExtractor xs
123   (FV v)      -> [Fix $ FV v]
124   -- _        -> []
125
126 variableIdExtractor :: Fix FTS -> [Id]
127 variableIdExtractor (Fix x) = case x of
128   (FS _ xs) -> Prelude.concat $ Prelude.map variableIdExtractor xs
129   (FV v)    -> [v]
130
131 {--
132   variableNameExtractor :: Fix FTS -> [VariableName]
133   variableNameExtractor (Fix x) = case x of
134     (FS _ xs) -> Prelude.concat & Prelude.map variableNameExtractor xs
135     (FV v)    -> [v]
136     _        -> []
137   --}
138
139 variableSet :: [Fix FTS] -> S.Set (Fix FTS)
140 variableSet a = S.fromList a
141
142 variableNameSet :: [Id] -> S.Set (Id)
143 variableNameSet a = S.fromList a
144
145
146 varsToDictM :: (Ord a, Unifiable t) =>
147   S.Set a -> ST.STBinding s (Map a (ST.STVar s t))
148 varsToDictM set = foldrM addElt Map.empty set where
149   addElt sv dict = do
150     iv <- freeVar
151     return $! Map.insert sv iv dict
152
153
154 uTermify
155   :: Map Id (ST.STVar s (FTS))
156   -> UTerm FTS (ST.STVar s (FTS))
157   -> UTerm FTS (ST.STVar s (FTS))
158 uTermify varMap ux = case ux of
159   UT.UVar _      -> ux

```

```

160   UT.UTerm (FV v)          -> maybe (error "bad map") UT.UVar $ Map.lookup v varMap
161   -- UT.UTerm t            -> UT.UTerm £! fmap (uTermify varMap) t
162   UT.UTerm (FS a xs)      -> UT.UTerm $ FS a $! fmap (uTermify varMap) xs
163
164
165   translateToUTerm ::
166       Fix FTS -> ST.STBinding s
167       (UT.UTerm (FTS) (ST.STVar s (FTS))),
168       Map Id (ST.STVar s (FTS)))
169   translateToUTerm e1Term = do
170       let vs = variableNameSet $ variableIdExtractor e1Term
171       varMap <- varsToDictM vs
172       let t2 = uTermify varMap . unfreeze $ e1Term
173       return (t2,varMap)
174
175
176   -- / uTermify recursively converts @UVar x@ into @UTerm (VarA x).
177   -- This is a routine of @ translateFromUTerm @. The resulting
178   -- term has no (UVar x) terms.
179
180   vTermify :: Map Int Id ->
181       UT.UTerm (FTS) (ST.STVar s (FTS)) ->
182       UT.UTerm (FTS) (ST.STVar s (FTS))
183   vTermify dict t1 = case t1 of
184       UT.UVar x -> maybe (error "logic") (UT.UTerm . FV) $ Map.lookup (UT.getVarID x)
185       UT.UTerm r ->
186           case r of
187               FV iv -> t1
188               _ -> UT.UTerm . fmap (vTermify dict) $ r
189
190   translateFromUTerm ::
191       Map Id (ST.STVar s (FTS)) ->
192       UT.UTerm (FTS) (ST.STVar s (FTS)) -> Prolog
193   translateFromUTerm dict uTerm =
194       P . maybe (error "Logic") id . freeze . vTermify varIdDict $ uTerm where
195       forKV dict initial fn = Map.foldlWithKey' (\a k v -> fn k v a) initial dict
196       varIdDict = forKV dict Map.empty $ \ k v -> Map.insert (UT.getVarID v) k
197
198
199   -- / Unify two (E1 a) terms resulting in maybe a dictionary
200   -- of variable bindings (to terms).
201   --
202   -- NB !!!!
203   -- The current interface assumes that the variables in t1 and t2 are
204   -- disjoint. This is likely a mistake that needs fixing

```

```

205
206 unifyTerms :: Fix FTS -> Fix FTS -> Maybe (Map Id (Prolog))
207 unifyTerms t1 t2 = ST.runSTBinding $ do
208     answer <- runExceptT $ unifyTermsX t1 t2
209     return $! either (const Nothing) Just answer
210
211 -- / Unify two (E1 a) terms resulting in maybe a dictionary
212 -- of variable bindings (to terms).
213 --
214 -- This routine works in the unification monad
215
216 unifyTermsX ::
217     Fix FTS -> Fix FTS ->
218     ExceptT (UT.UFailure (FTS) (ST.STVar s (FTS)))
219     (ST.STBinding s)
220     (Map Id (Prolog))
221 unifyTermsX t1 t2 = do
222     (x1,d1) <- lift . translateToUTerm $ t1
223     (x2,d2) <- lift . translateToUTerm $ t2
224     _ <- unify x1 x2
225     makeDicts $ (d1,d2)
226
227
228
229 mapWithKeyM :: (Ord k,Applicative m,Monad m)
230              => (k -> a -> m b) -> Map k a -> m (Map k b)
231 mapWithKeyM = Map.traverseWithKey
232
233
234 makeDict ::
235     Map Id (ST.STVar s (FTS)) -> ST.STBinding s (Map Id (Prolog))
236 makeDict sVarDict =
237     flip mapWithKeyM sVarDict $ \ _ -> \ iKey -> do
238         Just xx <- UT.lookupVar $ iKey
239         return $! (translateFromUTerm sVarDict) xx
240
241
242 -- / recover the bindings for the variables of the two terms
243 -- unified from the monad.
244
245 makeDicts ::
246     (Map Id (ST.STVar s (FTS)), Map Id (ST.STVar s (FTS))) ->
247     ExceptT (UT.UFailure (FTS) (ST.STVar s (FTS)))
248     (ST.STBinding s) (Map Id (Prolog))
249 makeDicts (svDict1, svDict2) = do

```



```

250   let svDict3 = (svDict1 'Map.union' svDict2)
251   let ivs = Prelude.map UT.UVar . Map.elems $ svDict3
252   applyBindingsAll ivs
253   -- the interface below is dangerous because Map.union is left-biased.
254   -- variables that are duplicated across terms may have different
255   -- bindings because 'translateToUTerm' is run separately on each
256   -- term.
257   lift . makeDict $ svDict3
258
259   instance (UT.Variable v, Functor t) => Error (UT.UFailure t v) where {}
260
261   test1 ::
262     ErrorT (UT.UFailure (FTS) (ST.STVar s (FTS)))
263       (ST.STBinding s)
264       (UT.UTerm (FTS) (ST.STVar s (FTS)),
265        Map Id (ST.STVar s (FTS)))
266   test1 = do
267     let
268       t1a = (Fix $ FV $ (0, "x"))
269       t2a = (Fix $ FV $ (1, "y"))
270       (x1,d1) <- lift . translateToUTerm $ t1a --error
271       (x2,d2) <- lift . translateToUTerm $ t2a
272       x3 <- U.unify x1 x2
273       return (x3, d1 'Map.union' d2)
274
275
276   test2 ::
277     ErrorT (UT.UFailure (FTS) (ST.STVar s (FTS)))
278       (ST.STBinding s)
279       (UT.UTerm (FTS) (ST.STVar s (FTS)),
280        Map Id (ST.STVar s (FTS)))
281   test2 = do
282     let
283       t1a = (Fix $ FS "a" [Fix $ FV $ (0, "x")])
284       t2a = (Fix $ FV $ (1, "y"))
285       (x1,d1) <- lift . translateToUTerm $ t1a --error
286       (x2,d2) <- lift . translateToUTerm $ t2a
287       x3 <- U.unify x1 x2
288       return (x3, d1 'Map.union' d2)
289
290
291   test3 ::
292     ErrorT (UT.UFailure (FTS) (ST.STVar s (FTS)))
293       (ST.STBinding s)
294       (UT.UTerm (FTS) (ST.STVar s (FTS)),

```

```

295         Map Id (ST.STVar s (FTS)))
296 test3 = do
297     let
298         t1a = (Fix $ FS "a" [Fix $ FV $ (0, "x")])
299         t2a = (Fix $ FV $ (0, "x"))
300         (x1,d1) <- lift . translateToUTerm $ t1a --error
301         (x2,d2) <- lift . translateToUTerm $ t2a
302         x3 <- U.unify x1 x2
303         return (x3, d1 'Map.union' d2)
304     {--
305     goTest test3
306     "ok:      STVar -9223372036854775807
307     [(VariableName 0 \"x\",STVar -9223372036854775808)]"
308     --}
309
310 test4 ::
311     ErrorT (UT.UFailure (FTS) (ST.STVar s (FTS)))
312         (ST.STBinding s)
313         (UT.UTerm (FTS) (ST.STVar s (FTS))),
314         Map Id (ST.STVar s (FTS)))
315 test4 = do
316     let
317         t1a = (Fix $ FS "a" [Fix $ FV $ (0, "x")])
318         t2a = (Fix $ FV $ (0, "x"))
319         (x1,d1) <- lift . translateToUTerm $ t1a --error
320         (x2,d2) <- lift . translateToUTerm $ t2a
321         x3 <- U.unifyOccurs x1 x2
322         return (x3, d1 'Map.union' d2)
323     {--
324     goTest test4
325     "ok:      STVar -9223372036854775807
326     [(VariableName 0 \"x\",STVar -9223372036854775808)]"
327     --}
328
329 test5 ::
330     ErrorT (UT.UFailure (FTS) (ST.STVar s (FTS)))
331         (ST.STBinding s)
332         (UT.UTerm (FTS) (ST.STVar s (FTS))),
333         Map Id (ST.STVar s (FTS)))
334 test5 = do
335     let
336         t1a = (Fix $ FS "a" [Fix $ FV $ (0, "x")])
337         t2a = (Fix $ FS "b" [Fix $ FV $ (0, "y")])
338         (x1,d1) <- lift . translateToUTerm $ t1a --error
339         (x2,d2) <- lift . translateToUTerm $ t2a

```

```

340     x3 <- U.unify x1 x2
341     return (x3, d1 'Map.union' d2)
342
343 goTest :: (Show b) => (forall s .
344     (ErrorT (UT.UFailure (FTS) (ST.STVar s (FTS)))
345         (ST.STBinding s)
346         (UT.UTerm (FTS) (ST.STVar s (FTS)),
347             Map Id (ST.STVar s (FTS)))))) -> String
348 goTest test = ST.runSTBinding $ do
349     answer <- runErrorT $ test
350     return $! case answer of
351         (Left x)  -> "error: " ++ show x
352         (Right y) -> "ok:    " ++ show y
353
354
355 -----
356 -----
357 -----GLUE-CODE-----
358 {--
359 monadicUnify :: Term -> Term -> ErrorT (UT.UFailure (FTS) (ST.STVar s (FTS)))
360             (ST.STBinding s)
361             (UT.UTerm (FTS) (ST.STVar s (FTS)),
362             Map Id (ST.STVar s (FTS)))
363 monadicUnify t1 t2 = do
364     let
365         t1f = termFlattener t1
366         t2f = termFlattener t2
367         (x1,d1) <- lift . translateToUTerm £ t1f
368         (x2,d2) <- lift . translateToUTerm £ t2f
369         x3 <- U.unify x1 x2
370         return (x3, d1 'Map.union' d2)
371
372 --}
373
374 -- type st = Id -> Term
375
376 -- Convert result from monadicUnify to [st]
377 {--
378 goMonadicTest :: (Show b) => (forall s .
379     (ErrorT (UT.UFailure (FTS) (ST.STVar s (FTS)))
380         (ST.STBinding s)
381         (UT.UTerm (FTS) (ST.STVar s (FTS)),
382             Map Id (ST.STVar s (FTS)))))) -> [st]
383 goMonadicTest test = ST.runSTBinding £ do
384     answer <- runErrorT £ test

```

```

385     return £! case answer of
386       (Left x)  -> [nullst]
387       (Right y) -> convertTost y
388   --}
389
390   --(Id, STVar s FTS)
391   --convertTost :: Map Id (ST.STVar s FTS) -> [(Id, ST.STVar s FTS)]
392   {--
393   convertTost m = convertTost1 Map.toAscList m
394
395   convertTost1 (id, ST.STVar _ fts):xs = (id, (unFlatten fts)) : convertTost1 xs
396   --}

```

## 937 15.9 Monadic Unification

```

1  monadicUnification :: (BindingMonad FTS (STVar s FTS) (ST.STBinding s)) => (forall
2      (ST.STBinding s) (UT.UTerm (FTS) (ST.STVar s (FTS))),
3      Map Id (ST.STVar s (FTS))))
4  monadicUnification t1 t2 = do
5      let
6          t1f = termFlattener t1
7          t2f = termFlattener t2
8          (x1,d1) <- lift . translateToUTerm $ t1f
9          (x2,d2) <- lift . translateToUTerm $ t2f
10         x3 <- U.unify x1 x2
11         --get state from somewhere, state -> dict
12         return $! (x3, d1 'Map.union' d2)
13
14
15  goUnify ::
16      (forall s. (BindingMonad FTS (STVar s FTS) (ST.STBinding s))
17      =>
18          (ErrorT
19              (UT.UFailure FTS (ST.STVar s FTS))
20              (ST.STBinding s)
21              (UT.UTerm FTS (ST.STVar s FTS),
22              Map Id (ST.STVar s FTS)))
23          )
24      -> [(Id, Prolog)]
25  goUnify test = ST.runSTBinding $ do
26      answer <- runErrorT $ test --ERROR
27      case answer of

```

```

28     (Left _)          -> return []
29     (Right (_, dict)) -> f1 dict
30
31
32 f1 ::
33   (BindingMonad FTS (STVar s FTS) (ST.STBinding s))
34   => (forall s. Map Id (STVar s FTS)
35       -> (ST.STBinding s [(Id, Prolog)]))
36       )
37 f1 dict = do
38   let ld1 = Map.toList dict
39   ld2 <- sequence [ v1 | (k,v) <- ld1, let v1 = UT.lookupVar v]
40   let ld3 = [ (k,v) | ((k,_),Just v) <- ld1 'zip' ld2]
41   ld4 = [ (k,v) | (k,v2) <- ld3, let v = translateFromUTerm dict v2 ]
42   return ld4
43
44
45 --unify :: Term -> Term -> [st]
46 unify t1 t2 = stConvertor (goUnify (monadicUnification t1 t2))
47
48
49 varX :: Term
50 varX = Var (0,"x")
51
52 varY :: Term
53 varY = Var (1,"y")
54
55
56 stConvertor :: [(Id, Prolog)] -> [st]
57 stConvertor xs = Prelude.map \(varId, p) -> (->-) varId (unFlatten $ unP $ p) xs

```

## 938 Chapter 16

## 939 Prototype 4

940 Our aim to embedd IO into the DSL

941 So something like a "data" declaration for IO operations

```
1  -- http://chris-taylor.github.io/blog/2013/02/09/io-is-not-a-side-effect/
2
3  data IOAction a =
4    -- A container for a value of type a.
5      Return a
6    -- A container holding a String to be printed to stdout, followed by another IOAction
7      | Put String (IOAction a)
8    -- A container holding a function from String -> IOAction a, which can be applied
9      | Get (String -> IOAction a)
10  {--
11
12  Return 1
13
14  Put "hello" (Return ())
15  Put "hello" (
16    Return ()
17  )
18
19  Put "hello" (Return 1)
20  Put "hello" (
21    Return 1
22  )
23
24  Put "hello" (get)
25  Put "hello" (
```

```

26     Get (f0 ->
27         Return "f0"
28     )
29 )
30
31 Get put
32 Get (f0 ->
33     Put "f0" (
34         Return ()
35     )
36 )
37
38 --}
39
40 -- Read and return
41 get :: IOAction String
42 get  = Get Return
43 {--
44
45     Get (f0 ->
46         Return "f0"
47     )
48
49 --}
50
51 -- Print and return.
52 put :: String -> IOAction ()
53 put s = Put s (Return ())
54 {--
55
56     put "hello"
57     Put "hello" (
58         Return ()
59     )
60
61 --}
62
63 -- (>=) Action sequencer and combiner :- read -> write -> read -> write -> ....
64 seqio :: IOAction a -> (a -> IOAction b) -> IOAction b
65 --     (First action    (Take and perform
66 --     which generates  next action)
67 --     value a)
68 seqio (Return a) f = f a
69 seqio (Put s io) f = Put s (seqio io f)
70 seqio (Get g)     f = Get (\s -> seqio (g s) f)

```

```

71
72  --Take input and print.
73  echo :: IOAction ()
74  echo = get 'seqio' put
75  {--
76
77  Get (£0 ->
78      Put "£0" (
79          Return ()
80      )
81  )
82
83  --}
84
85  hello :: IOAction ()
86  hello = put "What is your name?"      'seqio' \_ ->
87          get                          'seqio' \name ->
88          put "What is your age?"      'seqio' \_ ->
89          get                          'seqio' \age ->
90          put ("Hello " ++ name ++ "!") 'seqio' \_ ->
91          put ("You are " ++ age ++ " years old")
92  {--
93
94  Put "What is your name?" (
95      Get (£0 ->
96          Put "What is your age?" (
97              Get (£1 ->
98                  Put "Hello £0!" (
99                      Put "You are £1 years old" (
100                          Return ()
101                      )
102                  )
103              )
104          )
105      )
106  )
107
108  run hello
109  What is your name?
110  Mehul
111  What is your age?
112  25
113  Hello Mehul!
114  You are 25 years old
115

```



```

116 --}
117
118 -- hello in "do" block since IOAction is a Monad
119 hello2 :: IOAction ()
120 hello2 = do put "What is your name?"
121             name <- get
122             put "What is your age?"
123             age <- get
124             put ("Hello, " ++ name ++ "!")
125             put ("You are " ++ age ++ " years old!")
126 {--
127
128 Put "What is your name?" (
129   Get (£0 ->
130     Put "What is your age?" (
131       Get (£1 ->
132         Put "Hello, £0!" (
133           Put "You are £1 years old!" (
134             Return ()
135           )
136         )
137       )
138     )
139   )
140 )
141
142 run hello2
143 What is your name?
144 Mehul
145 What is your age?
146 25
147 Hello, Mehul!
148 You are 25 years old!
149
150 --}
151
152 -- where the effects happen.
153 -- "Real" IO functions like return, putStrLn, getLine.
154 run :: IOAction a -> IO a
155 run (Return a) = return a
156 run (Put s io) = putStrLn s >> run io
157 run (Get f)    = getLine >>= run . f
158 {--
159
160 run (Return 1)

```

```

161 1
162
163 run (Put "hello" get)
164 hello
165 1
166 "1"
167
168 run (Get put)
169 1
170 1
171
172 --}
173
174
175 -- Glue code that makes everything play nice --
176
177 instance Monad IOAction where
178     return = Return
179     (>=) = seqio
180
181 instance Show a => Show (IOAction a) where
182     show io = go 0 0 io
183     where
184         go m n (Return a) = ind m "Return " ++ show a
185         go m n (Put s io) = ind m "Put " ++ show s ++ " (\n" ++ go (m+2) n io ++ "\n"
186         go m n (Get g)     = let i = "$" ++ show n
187                               in ind m "Get (" ++ i ++ " -> \n" ++ go (m+2) (n+1) (g i)
188
189         ind m s = replicate m ' ' ++ s
190
191 -- IOAction is also a Functor --
192
193 mapio :: (a -> b) -> IOAction a -> IOAction b
194 mapio f (Return a) = Return (f a)
195 mapio f (Put s io) = Put s (mapio f io)
196 mapio f (Get g)     = Get (\s -> mapio f (g s))
197 {--
198
199 mapio (+1) (Return 1)
200 Return 2
201
202 mapio (id) (Put "hello" get)
203 Put "hello" (
204     Get (£0 ->
205         Return "£0"

```

```

206     )
207   )
208
209   mapio (id) (Get put)
210   Get (£0 ->
211     Put "£0" (
212       Return ()
213     )
214   )
215
216 --}
217
218 instance Functor IOAction where
219     fmap = mapio

```

942       So when the program is getting interpreted the interpreter encounters an IO operation  
943       which then gets "interpreted" to the above and it continues normally.

944       The interpreted program is still pure since the IO actions have not been executed  
945       if the running is done inside a monad then the IO still is pure.

```

1  -- Prolog IO
2
3  {--
4  FREE MONADS
5  In general, a structure is called free when it is left-adjoint to a forgetful fu
6  In this specific instance, the Term data type is a higher-order functor that map
7  a functor f to the monad Term f ; this is illustrated by the above two instance
8  definitions. This Term functor is left-adjoint to the forgetful functor from mon
9  to their underlying functors.
10 --}
11
12 data Term f a = Pure a
13               | Impure (f (Term f a))
14
15 main                                     = undefined
16
17 instance Functor f => Functor (Term f) where
18     fmap f (Pure x )                = Pure (f x )
19     fmap f (Impure t)                = Impure (fmap (fmap f ) t)
20
21 instance Functor f => Monad (Term f) where
22     return x                         = Pure x

```

```

23         (Pure x )           >>=           f           = f x
24         (Impure t)          >>=           f           = Impure (fmap (>>= f ) t)

1  import Data.Traversable
2  import Control.Monad
3  import Data.Functor
4  import Control.Applicative
5  import System.IO
6
7  data PrologResult
8      = NoResult
9      | Cons OneBinding PrologResult
10     | IOIn (IO String) (String -> PrologResult)
11     | IOOut (IO ()) PrologResult
12
13
14
15  data OneBinding = Pair VariableName VariableName
16
17
18  --data MiniLang a = MyData a | Empty | Input
19
20  --runInIO :: PrologResult -> IO [OneBinding]
21
22
23  data PrologIO a = Input (IO a) | Output (a -> IO ()) | PrologData a | Empty
24                  deriving (Show, Eq, Ord)
25  {--
26  instance Functor (PrologIO) where
27      fmap f Empty                                = Empty
28      fmap f (Input (IO a))                        = Input (IO (f a))
29      --      fmap f (Output (a -> IO ()))          = Output (a -> IO ())
30      --      fmap f (PrologData a)                  = PrologData (f a)
31  --}
32
33  instance Monad PrologIO where
34      return a = PrologData a
35      --      (Input i) >>= (Output o) = i >>= (\a -> (o a))
36
37  instance (Show a) => Show (PrologIO a) where
38      show (Empty)                                = show "No result"
39      show (PrologData a) = show a
40      --      show (Input f)                        = show (f ++ "")
41      --      show (Output )

```

```

42
43
44 -- (>=) Action sequencer and combiner :- read -> write -> read -> write -> ....
45 seqio :: PrologIO a -> (a -> PrologIO b) -> PrologIO b
46 --      (First action      (Take and perform
47 --      which generates next action)
48 --      value a)
49 seqio (PrologData a)          f          = f a
50 --seqio (Output o)              f          = \a -> o a
51 --seqio (Input i)              f          = \s -> (seqio (i s) f) --
52
53
54
55 {--
56 instance Applicative PrologIO where
57     func =
58
59 instance Traversable PrologIO where
60     traverse f Empty                      = Empty
61     traverse f (Input (IO a))              = Input (IO (f a))
62     traverse f (Output (a -> IO ()))        = Output ((a) -> IO (f))
63     traverse f (PrologData a)              = PrologData (f a)
64 --}
65
66
67 concat :: PrologIO t -> PrologIO t -> IO ()
68 concat (Input f1) (Output f2) = do
69     x <- f1
70     f2 x
71 {--
72 concat (Input getLine) (Output putStrLn)
73 Loading package list-extras-0.4.1.4 ... linking ... done.
74 Loading package syb-0.5.1 ... linking ... done.
75 Loading package array-0.5.0.0 ... linking ... done.
76 Loading package deepseq-1.3.0.2 ... linking ... done.
77 Loading package containers-0.5.5.1 ... linking ... done.
78 Loading package transformers-0.4.3.0 ... linking ... done.
79 Loading package mtl-2.2.1 ... linking ... done.
80 Loading package logict-0.6.0.2 ... linking ... done.
81 Loading package unification-fd-0.10.0.1 ... linking ... done.
82 1
83 1
84 --}

```

## 946 **Chapter 17**

## 947 **Work Completed**

### 948 **17.1 What we are doing**

949 A partial implementation of the logic programming language PROLOG is provided by the  
950 library `prolog-0.2.0.1`. One of the objectives is to implement monadic unification using  
951 the library [123].

### 952 **17.2 Unifiable Data Structures**

953 For a data type to be Unifiable, it must have instances of Functor, Foldable and Traversable.  
954 The interaction between different classes is depicted in figure 17.1.

955 The Functor class provides the `fmap` function which applies a particular operation to  
956 each element in the given data structure. The Foldable class *folds* the data structure by  
957 recursively applying the operation to each element and

### 958 **17.3 Why Fix is necessary?**

959 Since HASKELL is a lazy language it can work with infinite data structures. *Type Synonyms*  
960 in HASKELL cannot be self referential.




Figure 17.1: Functor Hierarchy [138]

961 In our case consider the following example,

```

-- The Prolog Syntax
type Atom = String
data VariableName = VariableName Int String deriving (Show,Eq,Ord)
data FlatTerm a =
    Struct Atom [a]
    | Var VariableName
    | Wildcard
    | Cut Int deriving (Show,Eq,Ord)
  
```

962 A FlatTerm can be of infinite depth which due to the reason stated above cannot be  
 963 accounted for during application function. The resulting type signature would be of the  
 964 form,

```
FlatTerm (FlatTerm (FlatTerm (FlatTerm (.....))))
```

965 Enter the Fix same as the function as a data type. The above would be simply reduced  
 966 to,

```
Fix FlatTerm
```

967 resulting in the PROLOG Data Type

```
data Prolog = P (Fix FlatTerm) deriving (Show,Eq,Ord)
```

## 968 17.4 Dr. Casperson's Explanation

969 A recursive data type in HASKELL is where one value of some type contains values of that  
970 type, which in turn contain more values of the same type and so on. Consider the following  
971 example.

```
data Tree = Leaf Int | Node Int (Tree) (Tree)
```

972 A sample Tree would be,

```
(Node 0 (Leaf 1) (Node 2 (Leaf 3) (Leaf 4)))
```

973 The above structure can be infinitely deep since HASKELL is a *lazy* programming lan-  
974 guage. But working with an infinitely deep / nested structure is not possible and will result  
975 in a *occurs check* error. This is because writing a type signature for a function to deal  
976 with such a parameter is not possible. One option would be to *flatten* the data type by the  
977 introduction of a type variable. Consider the following,

```
data FlatTree a = Leaf Int | Node Int a a
```

978 A sample FlatTerm would be similar to Tree.

979 The FlatTree is recursive but does not reference itself. But it too can be infinitely deep  
980 and hence writing a function to work on the structure is not possible.

## 981 17.5 The other fix

982 The `fix` function in the `Control.Monad.Fix` module allows for the definition of recursive  
983 functions in HASKELL. Consider the following scenario,



```
fix :: (a -> a) -> a
```

984 The above function results in an infinite application stream,

```
f s : f (f (f (...)))
```

985 A fixed point of a function `f` is a value `a` such that `f a == a`. This is where the name of  
986 `fix` comes from: it finds the least-defined fixed point of a function.

## 987 17.6 The Fix we use

988 Fix-point type allows to define generic recursion schemes [65].

```
1  Fix f = f (Fix f)
```

989 The Essence of Algebra There are two really essential aspects of an algebra:

990 The ability to form expressions and The ability to evaluate these expressions The Essence  
991 of Expression

992 The standard way of generating expressions is to use grammars. Here's an example of  
993 a grammar in Haskell:

```
1  data Expr = Const Int
2             | Add Expr Expr
3             | Mul Expr Expr
```

994 Like most non-trivial grammars, this one is defined recursively. You may think of `Expr`  
995 as a self-similar fractal. An `Expr`, as a type, contains not only `Const Int`, but also `Add` and  
996 `Mult`, which inside contain `Exprs`, and so on. It's trees all the way down.

997 But recursion can be abstracted away to uncover the real primitives behind expressions.  
998 The trick is to define a non-recursive function and then find its fixed point.

999 Since here we are dealing with types, we have to define a type function, otherwise  
1000 known as type constructor. Here's the non-recursive precursor of our grammar (later you'll  
1001 see that the `F` in `ExprF` stands for functor):

```
1 ExprF a = Const Int
2         | Add a a
3         | Mul a a
```

1002     The fractally recursive structure of Expr can be generated by repeatedly applying ExprF  
1003 to itself, as in ExprF (ExprF (ExprF a))), etc. The more times we apply it, the deeper trees  
1004 we can generate. After infinitely many iterations we should get to a fix point where further  
1005 iterations make no difference. It means that applying one more ExprF wouldn't change  
1006 anything – a fix point doesn't move under ExprF. It's like adding one to infinity: you get  
1007 back infinity.

1008     In Haskell, we can express the fix point of a type constructor f as a type:

1009     More stuff that I did not understand well can be found here,

1010     <https://www.fpcomplete.com/user/bartosz/understanding-algebras>

# Chapter 18

## Results

### 18.1 Types

One of the major differences between PROLOG and HASKELL is how each language handles types. PROLOG is an untyped language meaning any operation can be performed on the data irrespective of its type. HASKELL on the other hand is strongly typed i.e. each operation requires a signature stating what types of data it can work with. Moreover, the HASKELL type system is static.

PROLOG like any other language can work with some basic data types like numbers, characters, strings among others. Using these one can make terms like *Atoms*, *Clauses*, *Constants*, *Strings*, *Characters*, *Predicates*, *Structures*, *Special Characters* and so on. These need to be incorporated into the implementation so as to give a palette for writing programs.

Our preliminary implementation is as follows,

```
type Atom = String

data VariableName = VariableName Int String deriving (Show,Eq,Ord)

data FlatTerm a =
    Struct Atom [a]
    | Var VariableName
    | Wildcard
    | Cut Int deriving (Show,Eq,Ord)
```

```

{--
Output :-

Struct "a" [Var (VariableName 0 "x"),Cut 0,Wildcard,Struct "b" []]

--}

```

1024        which in PROLOG would look like,

```
a(X, !, b).
```

## 1025    **18.2    Lazy Evaluation**

## 1026    **18.3    Opening up the Language**

1027        **Flattening**

1028        **Fixing**

1029        **MetaSyntactic Variables**

## 1030    **18.4    Quasi Quotation**

## 1031    **18.5    Template Haskell**

## 1032    **18.6    Higher Order Functions**

```
% Mehul Solanki.
```

```
% Higher Order Functions.
```

```
% The following library contains the maplist function.
```

```

:- use_module(library(apply)).

% The maplist function takes a function and a list to apply the
% function.
% The function write is passes which will print out the elements
% of the list.
higherOrder(X) :- maplist(write,X).

/*
higherOrder([1,2,3,4]).
1234
true
*/

```

## 1033 18.7 I/O

```

data Result = Ordinary ----- --No I/O required
| SideEffect (IO -----)      -- Requiring Output
| ReadEffect (IO ----- -> Result) -- Requiring Input

```

## 1034 18.8 Mutability

## 1035 18.9 Unification

## 1036 18.10 Monads

## 1037 **Chapter 19**

### 1038 **Conclusion / Expected Outcomes**

1039 The aim of this study is to experiment with two different languages working together and/or  
1040 contributing in providing a solution. Mixing and matching conflicting characteristics may  
1041 lead to a behaviour similar to that of a multi paradigm language. The points to be looked at  
1042 are efficiency of the emulation, semantics of the resulting embedding.

1043 Moreover, this will be an attempt to answer the question how practical PROLOG fits  
1044 into HASKELL.

# Chapter 20

## Editing to do

*This Chapter needs to be removed from the final work.*

**2015-10-29**

1. Abstract is too long and incorrect.
2. Remove first ¶ from intro.
3. Thesis statement is close to being an abstract.

**Mehul**

4. **Rewrite (Section) Chapter 3.2**. You are now in a position to state what your contributions are. In some sense everything else flows around this.
5. Fix the reference at the bottom of page 2:  
`citewikipro- log,somogyi1995logic,website:prolog1000db`. **SOLVED**
6. Write enough of Chapters 13–16 that we can decide what material is needed in Chapters ??, ??, and ??.
7. [T<sub>E</sub>Xnical] Remove the `\paragraph{}`s from the running text. L<sup>A</sup>T<sub>E</sub>X ends a paragraph every time that it encounters two end-of-lines with only whitespace between them. `\par` does the same thing.

The `\paragraph` command is in the same family as `chapter`, `\section`, and so on. For its correct use, see later in this file.

If you don't like the shape of the paragraphs that you get without `paragraph`, use something like

```
\setlength{\parindent}{3em}
\setlength{\parskip}{2\baselineskip}
```

to adjust either the initial paragraph indent, or the inter-paragraph space.

8. Rewrite (Section) Chapter 3 in formal English.
9. Bump the sectioning levels up by one. That is, what is currently a section should become a chapter, what is currently a subsection should become a section, and so on. It may not make sense to do this until you have switch to `thesis.sty`.
10. “re-curses” means to swear again (*p* 9). **Changed to recurs**
11. I am not sure that I agree with the use of “reflective” on *p* 8 (*l* 25). Reflection often means run-time introspection (for instance the Java `.getClass()` method). In computer science, reflection is the ability of a computer program to examine (see type introspection) and modify its own structure and behavior (specifically the values, meta-data, properties and functions) at runtime.
12. Supply your credentials in the front material (what degrees do you have?). (Search for `%% Supply your credentials in proposal1.tex`.)
13. The abstract is too long. UNBC guidelines limit Masters’ theses abstracts to 150 words.

## David

14. Clean up the non-exclusive license page in `unbcthesis.cls`



15. Incorporate unbethesis.cls into Mehul's work.
16. Review Chapter 2
17. Review Chapter 3
18. Review Chapter 4
19. Review Chapter 5
20. Review Chapter 6
21. Review Chapter 7
22. Review Chapter 8
23. Review Chapter 18

## 20.1 Editing suggestions from David

**Thoughts on 1.1** We need to firmly fix in mind who the target audience is. Some possibilities

1. Undergraduate Physics students
2. Undergraduate Computer Science students
3. Future graduate students of Casperson who have just begun their thesis work.
4. Simon Peyton-Jones.

If we assume (3), then the material in the first paragraph and part of the second are unnecessary.

**Thoughts on 1.3** I am unsure that I can summarize this subsection in two sentences. I don't know what the problem statement is at the end of it.

**Thoughts on 1.4** Rename to “Thesis Organization”.

**Thoughts on Chapter 2** Here are some potential keywords from Chapter 2: • Hindley-Milner type systems • Horn clauses •  $\lambda$ -calculi • HASKELL • SCALA • declarative programming languages • foreign function interfaces • functional programming • implementing Prolog in other languages • language embedding • language families • language paradigms • logic programming • meta-programming • monads • paradigm integration • quasi-quotation • the typed  $\lambda$ -calculus • the untyped  $\lambda$ -calculus .

What is the overall message?

# Bibliography

- [1] Hassan Aït-Kaci and Forêt Des Flambertins, *Warrens abstract machine a tutorial reconstruction*, (1999).
- [2] Sergio Antoy, *Implementing functional logic programming languages*.
- [3] ———, *Sergio antoy home page*.
- [4] Sergio Antoy and Michael Hanus, *Functional logic programming*, Communications of the ACM **53** (2010), no. 4, 74–85.
- [5] Lennart Augustsson, *Cayenne – a language with dependent types*, IN INTERNATIONAL CONFERENCE ON FUNCTIONAL PROGRAMMING, ACM Press, 1998, pp. 239–250.
- [6] Andrei Barbu, *The csp package*, August 2013, <http://hackage.haskell.org/package/csp>.
- [7] Matthias Bartsch, *The prolog-graph package*, September 2011, <http://hackage.haskell.org/package/prolog-graph>.
- [8] Eli Barzilay and Dmitry Orlovsky, *Foreign interface for plt scheme*, on Scheme and Functional Programming (2004), 63.
- [9] Nick Benton, *Embedded interpreters*, Journal of Functional Programming **15** (2005), no. 4, 503–542.
- [10] Didier Bert, Pascal Drabik, and Rachid Echahed, *Lpg: A generic, logic and functional programming language*, STACS 87, Springer, 1987, pp. 468–469.
- [11] James Bielman and Lus Oliveira, *Common lisp foreign function interface*, March 2014.
- [12] Andrew Butterfield (ed.), *Unifying theories of programming, second international symposium, utp 2008, dublin, ireland, september 8-10, 2008, revised selected papers*, Lecture Notes in Computer Science, vol. 5713, Springer, 2010.
- [13] C2, *Multi paradigm programming language*, September 2012.
- [14] c2 wiki, *Metasyntactic variables*, September 2011.

- 1072 [15] Catb, *Metasynatactic variables*.
- 1073 [16] Prolog Development Center, *Visual prolog*, June 2013.
- 1074 [17] Wei-Ngan Chin, Martin Sulzmann, and Meng Wang, *A type-safe embedding of con-*  
 1075 *straint handling rules into haskell*, Technical report School of Computing, National  
 1076 University of Singapore, Boston, MA, USA (2003).
- 1077 [18] Ciao, *Ciao programming language*, August 2011.
- 1078 [19] Koen Claessen and Peter Ljunglöf, *Typed logical variables in haskell.*, Electr. Notes  
 1079 Theor. Comput. Sci. **41** (2000), no. 1, 37.
- 1080 [20] Code Commit, *Hindley milner type system*, December 2008.
- 1081 [21] Mozart Consortium, *Oz / mozart*, March 2013.
- 1082 [22] Gregory Crosswhite, *The logicgrowsontrees package*, September 2013, [http://](http://hackage.haskell.org/package/LogicGrowsOnTrees)  
 1083 [hackage.haskell.org/package/LogicGrowsOnTrees](http://hackage.haskell.org/package/LogicGrowsOnTrees).
- 1084 [23] DanDoel, *The logict package*, August 2013, [http://hackage.haskell.org/](http://hackage.haskell.org/package/logict)  
 1085 [package/logict](http://hackage.haskell.org/package/logict).
- 1086 [24] ———, *The logict package example*, August 2013, [http://okmij.org/ftp/](http://okmij.org/ftp/Computation/monads.html)  
 1087 [Computation/monads.html](http://okmij.org/ftp/Computation/monads.html).
- 1088 [25] Oleg Kiselyov Daniel P. Friedman, William E. Byrd, *The reasoned schemer*, The  
 1089 MIT Press, Cambridge Massachusetts, London England, 2005.
- 1090 [26] William E. Byrd Daniel P. Friedman and Oleg Kiselyov, *Kanren*, March 2009.
- 1091 [27] Universidad Complutense de Madrid, *Toy*, Decmeber 2006.
- 1092 [28] University Of Melbourne Computer Science department, *Mercury programming lan-*  
 1093 *guage*, February 2014.
- 1094 [29] Dustin DeWeese, *The peg package*, April 2012, [http://hackage.haskell.org/](http://hackage.haskell.org/package/peg)  
 1095 [package/peg](http://hackage.haskell.org/package/peg).
- 1096 [30] Open Directory Project dmoz, *Multi paradigm*, November 2013.
- 1097 [31] SWI Prolog Documentation, *Embedding swi-prolog in other applications*, June  
 1098 2013, <http://www.swi-prolog.org/pldoc/man?section=embedded>.
- 1099 [32] James R Driscoll, Neil Sarnak, Daniel Dominic Sleator, and Robert Endre Tarjan,  
 1100 *Making data structures persistent*, Proceedings of the eighteenth annual ACM sym-  
 1101 *posium on Theory of computing*, ACM, 1986, pp. 109–121.
- 1102 [33] Steve Dunne and Bill Stoddart (eds.), *Unifying theories of programming, first in-*  
 1103 *ternational symposium, utp 2006, walworth castle, county durham, uk, february 5-*  
 1104 *7, 2006, revised selected papers*, Lecture Notes in Computer Science, vol. 4010,  
 1105 Springer, 2006.

- 1106 [34] Joshua Eckroth, *Prolog resolution*, April 2014.
- 1107 [35] ———, *Prolog unification*, April 2014.
- 1108 [36] Martin Erwig, *Escape from zurg: an exercise in logic programming*, Journal of Func-  
1109 tional Programming **14** (2004), no. 03, 253–261.
- 1110 [37] Sebastian Fischer, *The cflp package*, June 2009, [http://hackage.haskell.org/](http://hackage.haskell.org/package/cflp)  
1111 [package/cflp](http://hackage.haskell.org/package/cflp).
- 1112 [38] ———, *stream-monad*, September 2012.
- 1113 [39] Adam C. Foltzer, *Molog*, March 2013.
- 1114 [40] Marc Fontaine, *The cspm-toprolog package*, August 2013, <http://hackage.haskell.org/package/CSPM-ToProlog>.  
1115
- 1116 [41] David Fox, *The proplogic package*, April 2012, [http://hackage.haskell.org/](http://hackage.haskell.org/package/PropLogic)  
1117 [package/PropLogic](http://hackage.haskell.org/package/PropLogic).
- 1118 [42] ———, *The logic-classes package*, October 2013, <http://hackage.haskell.org/package/logic-classes>.  
1119
- 1120 [43] Jeremy Gibbons, *Unifying theories of programming with monads*, Unifying Theories  
1121 of Programming, Springer, 2013, pp. 23–67.
- 1122 [44] GNU, *Gnu prolog for java*, August 2010, [http://www.gnu.org/software/](http://www.gnu.org/software/gnuprologjava/)  
1123 [gnuprologjava/](http://www.gnu.org/software/gnuprologjava/).
- 1124 [45] Michael Hanus, *Michael hanus home page*.
- 1125 [46] Michael Hanus, *Multi-paradigm declarative languages*, Logic Programming,  
1126 Springer, 2007, pp. 45–75.
- 1127 [47] Michael Hanus, *Functional logic programming*, February 2009.
- 1128 [48] Michael Hanus, Herbert Kuchen, and Juan Jose Moreno-Navarro, *Curry: A truly*  
1129 *functional logic language*, Proc. ILPS, vol. 95, 1995, pp. 95–107.
- 1130 [49] Haskellwiki, *Template haskell*, October 2013.
- 1131 [50] Juan Jose Moreno Navarro Herbert Kuchen, *Babel programming language*, January  
1132 1988.
- 1133 [51] Ralf Hinze et al., *Prological features in a functional setting axioms and implemen-*  
1134 *tation.*, Fuji International Symposium on Functional and Logic Programming, Cite-  
1135 seer, 1998, pp. 98–122.
- 1136 [52] Charles Anthony Richard Hoare and Jifeng He, *Unifying theories of programming*,  
1137 vol. 14, Prentice Hall Englewood Cliffs, 1998.

- 1138 [53] Satoshi Egi Ryo Tanaka Takahisa Watanabe Kentaro Honda, *Egison package*, March  
1139 2014.
- 1140 [54] Paul Hudak, *Building domain-specific embedded languages*, ACM Comput. Surv.  
1141 **28** (1996), no. 4es, 196.
- 1142 [55] John Hughes, *Why functional programming matters*, The computer journal **32**  
1143 (1989), no. 2, 98–107.
- 1144 [56] What is Tech Target, *Metasynatactic variables*, September 2005.
- 1145 [57] JaimieMurdock, *Haskell kanren*, March 2012.
- 1146 [58] JLogic, *Jlog - prolog in java*, September 2012, <http://jlogic.sourceforge.net/index.html>.  
1147
- 1148 [59] ———, *Jscriptlog - prolog in javascript*, September 2012, <http://jlogic.sourceforge.net/index.html>.  
1149
- 1150 [60] Paul Johnson, *Why haskell is good for embedded domain specific languages*, January  
1151 2008.
- 1152 [61] Mark P Jones, *Mini-prolog for hugs 98*, June 1996, <http://darcs.haskell.org/hugs98/demos/prolog/>.  
1153
- 1154 [62] Simon L Peyton Jones, Jean-Marc Eber, and Julian Seward, *Composing contracts: An adventure in financial engineering*, FME, vol. 2021, 2001, p. 435.  
1155
- 1156 [63] Mark Kantrowitz, *The prolog 1000 database*, August 2012.
- 1157 [64] David Karger, *Persistent data structures*, September 2005.
- 1158 [65] Anton Kholomiov, *data-fix*, February 2013.
- 1159 [66] H Jan Komorowski, *Qlog: The programming environment for prolog in lisp*, Logic  
1160 Programming (1982), 315–324.
- 1161 [67] Shriram Krishnamurthi, *Programming languages: Application and interpretation*,  
1162 ch. 33-34, pp. 295–305, 307–311, Brown Univ., 2007.
- 1163 [68] ———, *Teaching programming languages in a post-linnaean age*, SIGPLAN Not.  
1164 **43** (2008), no. 11, 81–83.
- 1165 [69] The Programming Languages Weblog Lambda The Ultimate, *Embedding prolog in  
1166 haskell*, July 2004, <http://lambda-the-ultimate.org/node/112>.
- 1167 [70] ———, *Embedding one language into another*, March 2005, <http://lambda-the-ultimate.org/node/578>.  
1168
- 1169 [71] ———, *Application-specific foreign-interface generation*, October 2006, <http://lambda-the-ultimate.org/node/2304>.  
1170

- 1171 [72] Duncan Temple Lang, *Embedding s in other languages and environments*, Proceed-  
1172 ings of DSC, vol. 2, 2001, p. 1.
- 1173 [73] LangPop.com, *Programming language popularity*, October 2013.
- 1174 [74] University of Melbourne Lee Naish, *Neu prolog*, February 1991.
- 1175 [75] John W Lloyd, *Programming in an integrated functional and logic language*, Journal  
1176 of Functional and Logic Programming **3** (1999), no. 1-49, 68–69.
- 1177 [76] Geoffrey Mainland, *Why it's nice to be quoted: quasiquoting for haskell*, Proceed-  
1178 ings of the ACM SIGPLAN workshop on Haskell workshop, ACM, 2007, pp. 73–82.
- 1179 [77] Yonathan Malachi, Zohar Manna, and Richard Waldinger, *Tablog: The deductive-  
1180 tableau programming language*, Proceedings of the 1984 ACM Symposium on LISP  
1181 and functional programming, ACM, 1984, pp. 323–330.
- 1182 [78] Erik Meijer and Peter Drayton, *Static typing where possible, dynamic typing when  
1183 needed: The end of the cold war between programming languages*, Citeseer, 2004.
- 1184 [79] Bertrand Meyer, *Eiffel as a framework for verification*, Verified Software: Theories,  
1185 Tools, Experiments, Springer, 2008, pp. 301–307.
- 1186 [80] Juan José Moreno-Navarro and Mario Rodriguez-Artalejo, *Babel: A functional and  
1187 logic programming language based on constructor discipline and narrowing*, Alge-  
1188 braic and Logic Programming, Springer, 1988, pp. 223–232.
- 1189 [81] Juan Jose Moreno-Navarro and Mario Rodriguez-Artalejo, *Logic programming with  
1190 functions and predicates: The language babel*, The Journal of Logic Programming  
1191 **12** (1992), no. 3, 191–223.
- 1192 [82] R Morrison and MP Atkinson, *Persistent languages and architectures*, Security and  
1193 Persistence, Springer, 1990, pp. 9–28.
- 1194 [83] MPprogramming.com, *Castor : Logic paradigm for c++*, August 2010, [http://  
1195 www.mpprogramming.com/cpp/](http://www.mpprogramming.com/cpp/).
- 1196 [84] Gopalan Nadathur, *λ prolog*, September 2013.
- 1197 [85] Mark J Nelson, *Why did prolog lose steam?*, August 2010, [http://www.kmjn.org/  
1198 notes/prolog\\_lost\\_steam.html](http://www.kmjn.org/notes/prolog_lost_steam.html).
- 1199 [86] Mozilla Developer Network, *Multi paradigm language*, February 2014.
- 1200 [87] Johan Nordlander, *O'haskell*, January 2001.
- 1201 [88] Kurt Nrmark Department of Computer Science Aalborg University Denmark,  
1202 *Linguistic abstraction*, July 2013, [http://people.cs.aau.dk/~normark/  
1203 prog3-03/html/notes/languages\\_themes-intro-sec.html#languages\\_  
1204 intro-sec\\_section-title\\_1](http://people.cs.aau.dk/~normark/prog3-03/html/notes/languages_themes-intro-sec.html#languages-intro-sec_section-title_1).

- 1205 [89] University of Maryland Medical Center, *Lisp, unification and embedded languages*,  
1206 October 2012, <http://www.cs.unm.edu/~luger/ai-final2/LISP/>.
- 1207 [90] Ocaml Org, *Ocaml programming language*, March 2014.
- 1208 [91] Pedro Pinto, *Dot-scheme: A plt scheme ffi for the .net framework*, Workshop on  
1209 Scheme and Functional Programming, Citeseer, 2003.
- 1210 [92] Quintus Prolog, *Embeddability*, December 2003, <http://quintus.sics.se/isl/quintuswww/site/embed.html>.  
1211
- 1212 [93] Yield Prolog, *Yield prolog*, October 2011, <http://yieldprolog.sourceforge.net/>.  
1213
- 1214 [94] Shengchao Qin (ed.), *Unifying theories of programming - third international symposium, utp 2010, shanghai, china, november 15-16, 2010. proceedings*, Lecture Notes  
1215 in Computer Science, vol. 6445, Springer, 2010.  
1216
- 1217 [95] John Ramsdell, *The cmu package*, February 2013, <http://hackage.haskell.org/package/cmu>.  
1218
- 1219 [96] Norman Ramsey, *Embedding an interpreted language using higher-order functions and types*, Proceedings of the 2003 workshop on Interpreters, virtual machines and  
1220 emulators, ACM, 2003, pp. 6–14.  
1221
- 1222 [97] John Reppy and Chunyan Song, *Application-specific foreign-interface generation*, Proceedings of the 5th international conference on Generative programming and  
1223 component engineering, ACM, 2006, pp. 49–58.  
1224
- 1225 [98] Maik Riechert, *The monadiccp package*, July 2013, <http://hackage.haskell.org/package/monadiccp>.  
1226
- 1227 [99] J Alan Robinson and Ernest E Sibert, *Loglisp: Motivation, design, and implementation*, 1982.  
1228
- 1229 [100] John Alan Robinson and EE Silbert, *Loglisp: an alternative to prolog*, School of  
1230 Computer and Information Science, Syracuse University, 1980.
- 1231 [101] Raúl Rojas, *A tutorial introduction to the lambda calculus*, DOI= <http://www.utdallas.edu/~gupta/courses/apl/lambda.pdf> (2004).  
1232
- 1233 [102] Daniel Seidel, *The prolog-graph-lib package*, June 2012, <http://hackage.haskell.org/package/prolog-graph-lib>.  
1234
- 1235 [103] ———, *The prolog package*, June 2012, <http://hackage.haskell.org/package/prolog>.  
1236
- 1237 [104] Eric Seidel, *The liquid-fixpoint package*, September 2013, <http://hackage.haskell.org/package/liquid-fixpoint>.  
1238



- 1239 [105] Silvija Seres, *The algebra of logic programming*, Ph.D. thesis, 2001.
- 1240 [106] Silvija Seres and Shin-Cheng Mu, *Optimisation problems in logic programming: an*  
1241 *algebraic approach*, (2000).
- 1242 [107] Silvija Seres, J Michael Spivey, and CAR Hoare, *Algebra of logic programming.*,  
1243 ICLP, 1999, pp. 184–199.
- 1244 [108] Silvija Seres and Michael Spivey, *Higher-order transformation of logic programs*,  
1245 Logic Based Program Synthesis and Transformation, Springer, 2001, pp. 57–68.
- 1246 [109] Tim Sheard and Emir Pasalic, *Two-level types and parameterized modules*, Journal  
1247 of Functional Programming **14** (2004), no. 05, 547–587.
- 1248 [110] Dorai Sitaram, *Racklog: Prolog-style logic programming*, January 2014.
- 1249 [111] Zoltan Somogyi, Fergus Henderson, Thomas Conway, and Richard OKeefe, *Logic*  
1250 *programming for the real world*, Proceedings of the ILPS, vol. 95, 1995, pp. 83–94.
- 1251 [112] Andy Sonnenburg, *logicst*, April 2013.
- 1252 [113] JM Spivey, *An introduction to logic programming through prolog*, 1995.
- 1253 [114] JM Spivey and Silvija Seres, *The algebra of searching*, Festschrift in honour of  
1254 CAR Hoare (1999).
- 1255 [115] ———, *Embedding prolog in haskell*, Proceedings of Haskell, vol. 99, Citeseer,  
1256 1999, pp. 1999–28.
- 1257 [116] Michael Spivey, *Functional pearls combinators for breadth-first search*, Journal of  
1258 Functional Programming **10** (2000), no. 4, 397–408.
- 1259 [117] Stackoverflow, *Haskell vs. prolog comparison*, December 2009, [http://](http://stackoverflow.com/questions/1932770/haskell-vs-prolog-comparison)  
1260 [stackoverflow.com/questions/1932770/haskell-vs-prolog-comparison](http://stackoverflow.com/questions/1932770/haskell-vs-prolog-comparison).
- 1261 [118] Patrick Blackburn Johan Bos Kristina Striegnitz, *Learn prolog now*, January 2012.
- 1262 [119] ———, *Learn prolog now*, January 2012.
- 1263 [120] Jurrien Stutterheim, *The nanoprolog package*, December 2011, [http://hackage.](http://hackage.haskell.org/package/NanoProlog)  
1264 [haskell.org/package/NanoProlog](http://hackage.haskell.org/package/NanoProlog).
- 1265 [121] Evgeny Tarasov, *The hswip package*, August 2010, [http://hackage.haskell.](http://hackage.haskell.org/package/hswip)  
1266 [org/package/hswip](http://hackage.haskell.org/package/hswip).
- 1267 [122] William E. Byrd The Reasoned Schemer’ (MIT Press, 2005) by Daniel P. Friedman  
1268 and Oleg Kiselyov, *minikanren*.
- 1269 [123] Wren Thornton, *The unification-fd package*, July 2012, [http://hackage.](http://hackage.haskell.org/package/unification-fd)  
1270 [haskellhttp://yieldprolog.sourceforge.net/.org/package/](http://hackage.haskell.org/package/unification-fd)  
1271 [unification-fd](http://yieldprolog.sourceforge.net/.org/package/unification-fd).

- 1272 [124] Jan Tikovsky, *The monadiccp-gecode package*, January 2014, <http://hackage.haskell.org/package/monadiccp-gecode>.  
1273
- 1274 [125] Carnegie Mellon University, *Algebraic logic functional programming language*,  
1275 February 1995.
- 1276 [126] Dalhousie University, *Control flow*, January 2012.
- 1277 [127] Simon Fraiser University, *Life programming language*, March 1998.
- 1278 [128] Los Angeles University of California, *Virgil programming language*, March 2012.
- 1279 [129] Germany University of Kiel, *Curry programming language*, September 2013.
- 1280 [130] Maarten van Emden, *Who killed prolog?*, August 2010, <http://vanemden.wordpress.com/2010/08/21/who-killed-prolog/>.  
1281
- 1282 [131] Andre Vellino, *Prolog's death*, August 2010, <http://synthese.wordpress.com/2010/08/21/prologs-death/>.  
1283
- 1284 [132] Job Vranish, *minikanrent*, March 2013.
- 1285 [133] Philip Wadler, *Comprehending monads*, Mathematical Structures in Computer Science **2** (1992), no. 04, 461–493.  
1286
- 1287 [134] Haskell Website, *Logic programming example*, February 2010, [http://www.haskell.org/haskellwiki/Logic\\_programming\\_example](http://www.haskell.org/haskellwiki/Logic_programming_example).  
1288
- 1289 [135] ———, *Logic programming example in haskell*, February 2010.
- 1290 [136] ———, *Quasiquote in haskell*, January 2014, <http://www.haskell.org/haskellwiki/Quasiquote>.  
1291
- 1292 [137] Haskell Wiki, *Monads as computation*, December 2011.
- 1293 [138] ———, *Foldable and traversable*, January 2013.
- 1294 [139] ———, *The haskell programming language*, October 2013.
- 1295 [140] ———, *Embedded domain specific languages*, September 2014.
- 1296 [141] ———, *Haskell/laziness*, November 2014.
- 1297 [142] ———, *Monads in haskell*, January 2014.
- 1298 [143] ———, *Haskell in industry*, June 2015.
- 1299 [144] Wikipedia, *Prolog wikipedia*, March 2004.
- 1300 [145] ———, *Functional logic programming languages*, February 2005.
- 1301 [146] ———, *Common lisp object system*, December 2013.

- 1302 [147] ———, *Curry programming language*, December 2013.
- 1303 [148] ———, *Functional logic programming*, May 2013.
- 1304 [149] ———, *Quasiquotation*, November 2013, [http://en.wikipedia.org/wiki/](http://en.wikipedia.org/wiki/Quasi-quotation)  
1305 Quasi-quotation.
- 1306 [150] ———, *Common language infrastructure*, February 2014.
- 1307 [151] ———, *Common language runtime*, March 2014.
- 1308 [152] ———, *Constraint handling rules*, March 2014.
- 1309 [153] ———, *Constraint programming*, March 2014.
- 1310 [154] ———, *Damas-hindley-milner type system*, February 2014.
- 1311 [155] ———, *Foreign function interface*, January 2014.
- 1312 [156] ———, *Lambda calculus*, March 2014.
- 1313 [157] ———, *List of multi paradigm languages*, March 2014.
- 1314 [158] ———, *Meta programming*, March 2014.
- 1315 [159] ———, *Ocaml*, March 2014.
- 1316 [160] ———, *Programming paradigm*, March 2014.
- 1317 [161] ———, *Comparison of prolog implementations*, August 2015.
- 1318 [162] ———, *Control flow*, August 2015.
- 1319 [163] ———, *Declarative programming*, September 2015.
- 1320 [164] ———, *Metasyntactic variable*, October 2015.
- 1321 [165] Burkhart Wolff, Marie-Claude Gaudel, and Abderrahmane Feliachi (eds.), *Unifying*  
1322 *theories of programming, 4th international symposium, utp 2012, paris, france, au-*  
1323 *gust 27-28, 2012, revised selected papers*, Lecture Notes in Computer Science, vol.  
1324 7681, Springer, 2013.
- 1325 [166] Takashi’s Workplace, *A prolog in haskell*, April 2009, [http://propella.](http://propella.blogspot.in/2009/04/prolog-in-haskell.html)  
1326 [blogspot.in/2009/04/prolog-in-haskell.html](http://propella.blogspot.in/2009/04/prolog-in-haskell.html).
- 1327 [167] xkcd, *Haskell vs prolog, or giving haskell a choice*, February 2009, [http://](http://echochamber.me/viewtopic.php?f=11&t=35369)  
1328 [echochamber.me/viewtopic.php?f=11&t=35369](http://echochamber.me/viewtopic.php?f=11&t=35369).
- 1329 [168] Switzerland cole Polytechnique Fdrale de Lausanne (EPFL) Lausanne, *Scala pro-*  
1330 *gramming language*, 2002-2014.