Session 1 — Terminal & Git fundamentals

Git, Python Environments & Coding Best Practices

Guillaume Leveque

Session 1 of 4

Master of Data & AI — MSA-DATB07-03

Why this course (5 min)

The folder everybody has

```
analysis.py
analysis_v2.py
analysis_v2_final.py
analysis_v2_final_REAL.py
analysis_v2_final_REAL_bob.py
copy of analysis (1).py
```

What goes wrong:

- Which file is the right one? What changed between two of them, who changed it, and why?
- Two people edit the same file: one silently overwrites the other.
- "It works on my laptop" but not on yours: different Python, different packages.

What this course gives you

Track every change and go back in time. **Work as a team** on the same code without overwriting each other. **Share the same environment** and the same quality rules, so that everyone's code runs everywhere.

Four sessions, one project

#	topic	you leave able to ...
1	Terminal & Git basics	use the terminal; save versions of your work and go back
2	Branches & merges	work on several things in parallel, combine them, fix conflicts
3	GitHub & pull requests	share your work, review teammates' code, contribute
4	Environments & code quality	recreate the same Python setup on any machine; let tools check the code for you

Tools of session 4, in one line each: **black** rewrites the layout of your code automatically; **ruff** spots likely mistakes; **mypy** checks that types are consistent; **CI** (continuous integration) is GitHub running these checks on every change.

One small project, `sales-analysis`, follows you through the four practicals: you build it, branch it, share it, then clean it up.

Today

min	block
5	why this course
8	terminal, shell, OS
15	navigating and handling files
12	redirections, search, environment
18	network and system survival kit

min	block
9	why Git: the problem, the model
13	the core loop: add, commit, log, diff
8	.gitignore and undoing
2	wrap-up
90	**TD1: install, shell treasure hunt, first repository**

Terminal, shell, OS (8 min)

The terminal: talking to the computer in text

- When you double-click an icon, you ask the computer to *run a program*.
- Applications do this all the time behind the scenes: the *Run* button of VS Code runs `python analysis.py` for you; its Git panel runs `git` commands.
- The terminal lets you give these orders yourself, by typing them.

Why bother?

- **precise**: you see exactly what runs
- **repeatable**: copy a command, put it in a script
- **everywhere**: servers and cloud machines have no mouse

```
python analysis.py      # what the Run button does: "python, please run analysis.py"
```

Three words that are not synonyms

Terminal the window that shows text and takes keystrokes (Windows Terminal, Terminal.app, the panel at the bottom of VS Code).

Shell the program running inside it that reads what you type and runs it: `bash`, `zsh`, PowerShell, `cmd`.

OS the operating system the shell talks to: Windows, macOS, Linux.

Tip — why we care

Data science tools (Python, Git, Docker, cloud tools, servers) are documented for a Unix shell such as bash. Learning bash once pays off on every platform, Windows included.

One shell for everyone: bash

Windows comes with two shells, neither of them bash:

- `cmd.exe`: `dir`, `copy`, backslashes
- PowerShell: its commands look like bash (`ls`, `cd`) but many differ (`rm -rf`, `touch`, `export`)

macOS comes with `zsh`, which behaves like bash for everything in this course. Linux comes with `bash`.

Our choice

So that every command in this course exists in one version only, everybody uses a bash shell: **Git Bash** on Windows (it comes with Git for Windows) and **Terminal** on macOS, both usable inside VS Code.

What you will install at the start of the TD

	Windows	**macOS**
Git + a bash shell	*Git for Windows*: gives Git **and** Git Bash	comes with the Apple developer tools
Python 3.10 or newer	python.org, separate install	python.org, separate install
Editor	VS Code + Python extension	VS Code + Python extension

Pitfall — Git does not install Python

Git for Windows gives you Git and Git Bash, nothing else. Python is a separate program with its own installer. On Windows, tick *Add python.exe to PATH* in the Python installer.

Two pitfalls to know from day one

Pitfall — the shell that looks like bash but is not

PowerShell accepts `ls` and `cd`, then fails on `rm -rf`, `touch` or `export`. If a command from the slides fails on Windows, type `echo $0`: Git Bash answers `bash`. Anything else means you are in the wrong shell.

Pitfall — python vs python3

On macOS the command is usually `python3`, not `python`. The slides write `python` to stay short. Session 4 removes the difference with virtual environments.

Navigating and handling files (15 min)

Where am I, what is here, go somewhere

```
pwd             # "print working directory": where am I?
ls              # "list": the files and folders here
ls -l           # -l = long format: size, date, permissions
ls -la          # -a = all, including hidden files (names starting with a dot)
cd data/raw     # "change directory": go into data, then raw
cd ..           # .. = the folder above
cd ~            # ~ = your home folder
cd -            # back to the previous folder
```

Options start with a dash and change what a command does: `ls` lists, `ls -l` lists with details. They can be combined: `-la` = `-l` + `-a`.

Paths: the address of a file

Absolute path: starts from the top of the disk.
`/Users/alice/Documents/cours` (macOS)
`/c/Users/alice/Documents/cours` (Git Bash)

Relative path: starts from where you are.
`data/raw/sales.csv`
`../other_project`

`.`	this folder
`..`	the folder above
`~`	your home folder
`/`	separator, and the top of the disk

Tip — name files and folders without spaces

A space splits a command into two words: `cd my project` looks for a folder called `my`. Use underscores: `my_project`, `sales_2024.csv`, `td1_answers.md`. For a path you cannot rename, put quotes around it: `cd "OneDrive - Company"`.

Two tricks so that you never type a full path

Tab completion

- Type the first letters of a name, press `Tab`: the shell completes it.
- Several candidates? Press `Tab` twice to see them all.
- No completion = the name does not exist here. Check with `ls`.

Drag and drop

- Type `cd` and a space.
- Drag a folder from the file explorer (Windows) or the Finder (macOS) onto the terminal: its full path is typed for you.
- Press `Enter`. Works for files too: `head` + drag a CSV.

Tip — find where a file is

Not sure where a file lives on your disk? Drag it onto the terminal: you get its exact path, ready to copy.

Create, copy, move, delete

```
mkdir outputs              # "make directory": create a folder
mkdir -p data/raw/2024     # -p = create the whole chain of folders at once
touch notes.md             # create an empty file
cp sales.csv backup.csv    # "copy": cp <from> <to>
cp -r data data_backup     # -r = recursive: copy a folder and everything inside
mv notes.md README.md      # "move": also the way to rename
mv README.md docs/         # move into a folder
rm backup.csv              # "remove": delete a file
rm -r data_backup          # delete a folder and everything inside
```

Pitfall — there is no recycle bin

`rm` deletes immediately and for good. Read the path twice before pressing `Enter`. Git will give you a safety net for the files it tracks.

Look inside files

```
cat README.md           # print the whole file
less logs/server.log    # read page by page: space = next page, q = quit, /word = search
head -n 5 sales.csv     # the first 5 lines (-n = number of lines)
tail -n 5 sales.csv     # the last 5 lines
wc -l sales.csv         # "word count", -l = count the lines
```

Tip — first reflex on a new dataset

`head -n 3 file.csv` shows the column names and the format before you write a single line of Python.

Keyboard habits

`Tab`	complete a file, folder or command name
`Up` / `Down`	scroll through the commands you already typed
`Ctrl+R`	search in that history (type a few letters)
`Ctrl+C`	**stop** the running command (it does not copy!)
`Ctrl+L` or `clear`	clean the screen
`Ctrl+Insert` / `Shift+Insert`	copy / paste (Windows: Git Bash and VS Code)
`Cmd+C` / `Cmd+V`	copy / paste (macOS)
`code .`	open the current folder in VS Code

Pitfall — Ctrl+C in a terminal

In a terminal, `Ctrl+C` interrupts the program that is running. To copy, select the text and use `Ctrl+Insert` (Windows) or `Cmd+C` (macOS).

Demo folder: shell-lab

The TD1 repository contains a practice folder. I use it now for the live demo; you will explore it yourself during the TD.

```
shell-lab/
|-- README.txt
|-- data/
|   |-- raw/      sales_2024_q1.csv ... q4.csv, README.txt
|   `-- processed/
|-- docs/
|   |-- notes/    meeting_2024-01-15.md, meeting_2024-02-12.md
|   |-- archive/  2019/old_report.txt, 2020/old_report.txt
|   `-- glossary.md
|-- logs/         server.log (300 lines), app.log
`-- scripts/      clean.py, report.sh
```

Questions for the demo: how many rows in `sales_2024_q1.csv`? Which file mentions `PENGUIN`? Something is hidden in this tree: what?

Redirections, search, environment (12 min)

Send the output to a file, or to another command

A command normally prints its result on the screen. You can send it elsewhere:

```
ls -la > listing.txt           # > : write the output into listing.txt (replaces its content)
echo "one more line" >> notes.md   # >> : add at the end of notes.md (keeps the content)
head -n 3 sales.csv | wc -l    # | : "pipe", the output of head becomes the input of wc
```

- > creates the file if needed and **erases** what was in it. » appends.
- The pipe | is the heart of the shell: small commands that each do one thing, chained together.

Normal output and error messages: 1, 2 and 2>&1

Every command has two output channels, both shown on the screen by default:

- channel **1**: the normal output (*stdout*)
- channel **2**: the error messages (*stderr*)

```
python script.py > out.txt 2>&1
```

piece	meaning
`python script.py`	run the script
`> out.txt`	send channel 1 (normal output) into `out.txt`
`2>&1`	send channel 2 (errors) to the same place as channel 1

Result: everything the script prints, errors included, ends up in `out.txt`. Variant: `python script.py 2> errors.txt` keeps only the errors.

Search inside files: grep

```
grep ERROR logs/server.log          # the lines that contain ERROR
grep -n ERROR logs/server.log       # -n = with their line numbers
grep -i error logs/server.log       # -i = ignore upper/lower case
grep -c ERROR logs/server.log       # -c = only count them
grep -r PENGUIN .                   # -r = in every file of every sub-folder of . (here)
grep -rl PENGUIN .                  # -l = only the names of the files
grep -v INFO logs/server.log        # -v = the lines that do NOT contain INFO
```

Wildcards in file names: `*` = any text, `?` = one character. `grep Widget data/raw/*.csv` searches every CSV of `data/raw`.

Search for files: find

```
find . -name "*.md"            # every file ending in .md, from here (.) downwards
find . -type d                 # -type d = only folders ("directories")
find . -type f -name "*.csv"   # -type f = only files, and named *.csv
find . -size +10k              # bigger than 10 kB
```

`grep` searches *inside* files, `find` searches file *names*. Both start from the folder you give them: `.` means "here".

Chaining: which error is the most frequent?

```
grep ERROR logs/server.log | cut -c27- | sort | uniq -c | sort -nr
```

1. `grep ERROR logs/server.log`: keep the error lines
2. `cut -c27-`: keep characters 27 to the end, i.e. the message without date and time
3. `sort`: identical lines end up next to each other
4. `uniq -c`: merge identical neighbours, `-c` = with a count
5. `sort -nr`: sort again, `-n` = by number, `-r` = reversed: biggest first

Tip — build it one pipe at a time

Run step 1, look at the result, add `| cut -c27-`, look again, and so on. Never write five pipes in one go.

Environment variables and PATH

The shell keeps named values, called *variables*. `$NAME` reads one.

```
echo $HOME                # your home folder
echo $PATH                # the list of folders where the shell looks for programs
which python              # which python will run when I type "python"?
export PROJECT=sales      # create a variable for this terminal window
echo $PROJECT             # sales
```

- When you type `python`, the shell looks in each folder of `PATH`, in order, and runs the *first* `python` it finds. This explains most "wrong Python version" problems (session 4).
- A variable created with `export` disappears when you close the window.

Shell configuration: commands run at every start

A file in your home folder is read each time a terminal opens:

- Git Bash and Linux: `~/.bashrc`; macOS: `~/.zshrc`

```
alias ll='ls -la'          # shortcut: typing ll now runs ls -la
alias gs='git status'
export PROJECT=sales       # a variable available in every new window
```

Apply the changes without reopening the terminal: `source ~/.bashrc`.

Pitfall — never write a secret in your files

A *secret* is anything that gives access: a password, or an *API key*, which is a password that a program uses to access an online service (a weather service, a database, an AI model). A secret written in a file can end up in Git and be shared with everyone. We will see how to prevent it with `.gitignore` later today.

Network and system survival kit (18 min)

Why a survival kit

Network

- "The website does not answer": is it down, or is it my connection?
- "`pip install` hangs": network, name resolution, firewall?
- "Jupyter says the port is already in use."
- "Download the dataset from a URL."

System

- "My notebook is frozen": which program, how to stop it?
- "No space left on device": what fills the disk?
- "Permission denied" on a script you just wrote.
- "Send me the logs": pack a folder into one file.

Network commands are the Windows programs when you are on Windows, so a few names differ between Windows and macOS. All of them are on the cheat-sheet.

Is it reachable? ping

`ping` sends a few small test messages to a machine and measures how long the answer takes. Nothing of yours is sent.

```
ping github.com            # Windows: sends 4 test messages, then stops
ping -c 4 github.com       # macOS: -c 4 = "count", send 4 (otherwise it never stops: Ctrl+C)
```

```
64 bytes from 140.82.121.4: icmp_seq=1 ttl=52 time=18.3 ms
...
4 packets transmitted, 4 received, 0% packet loss
```

- `time`: the round trip in milliseconds. `0% packet loss`: every message came back.
- 100 % loss while the website opens in your browser: the network blocks `ping`, the server is fine.

Where does it stop? tracert / traceroute

```
tracert -d github.com      # Windows   (-d = show numbers, skip name lookups: faster)
traceroute -n github.com   # macOS     (-n = the same option, other name)
```

```
  1     1 ms    192.168.1.1        <- my box / router
  2    12 ms    10.20.0.1          <- my internet provider
  3     *       *       *          <- a step that does not answer (normal)
  9    19 ms    140.82.121.4       <- destination reached
```

- One line per *hop*, each machine your message goes through on its way.
- `* * *`: that machine does not answer this kind of test. It is not a failure as long as later lines appear.
- If everything stops after line 1, the problem is at home or on campus, not on the server.

Names and addresses: nslookup, ipconfig

On the internet, machines are found by a number, the *IP address*. The *DNS* works like a phone book: it turns a name into that number.

```
nslookup github.com          # name -> IP address, and which DNS server answered
ipconfig                     # Windows: my own IP address
ipconfig getifaddr en0       # macOS: my own IP address on Wi-Fi
```

- `nslookup` fails but `ping 140.82.121.4` works: the phone book (DNS) is broken, not the network.
- Your address starts with `192.168.` or `10.`: a private address inside your home or campus network.

Ports: who is using 8888?

One machine runs many services. Each one listens on a numbered *port*: Jupyter uses 8888, websites 443.

```
netstat -ano | findstr 8888    # Windows
lsof -i :8888                  # macOS
```

piece	meaning
`netstat -ano`	list the connections: `-a` all, `-n` numbers, `-o` with the program number (PID)
`| findstr 8888`	keep the lines with 8888 (`findstr` is the Windows `grep`)
`lsof -i :8888`	macOS: "list open files" using network port 8888

"Address already in use": an old Jupyter still holds the port. The last column gives its PID; stop it with `kill` (two slides later).

Talk to a website: curl

`curl` fetches a web address from the terminal, like a browser that shows the raw text.

```
curl -I https://github.com                # -I = only the headers (status, server...)
curl -o sales.csv https://example.com/sales.csv   # -o = save into a file instead of
    printing
curl -L -o data.zip https://example.com/data      # -L = follow redirections
```

The first line of `curl -I` is the *status code*:

200	OK
301 / 302	moved elsewhere (`-L` follows it)
403 / 404	forbidden / not found
500 and above	the server has a problem, not you

Ask a service for data: an API and JSON

An *API* is a web address that answers with data instead of a page. The answer is often *JSON*, a text format that looks like a Python dictionary.

```
curl -s "https://api.open-meteo.com/v1/forecast?latitude=48.85&longitude=2.35&current=
    temperature_2m"
```

- `-s` = silent: no progress bar, only the answer.
- The quotes are needed: the URL contains `&`, which means something else for the shell.
- The answer: `{"latitude":48.86, ..., "current":{"temperature_2m":14.2}}`, the current temperature in Paris.

Read JSON comfortably

```
curl -s "https://api.open-meteo.com/v1/forecast?latitude=48.85&longitude=2.35&current=
    temperature_2m" | python -m json.tool
```

piece	meaning
`curl -s "..."`	fetch the data, silently
`|`	give the answer to the next command
`python -m json.tool`	`-m` = run a module that comes with Python; `json.tool` indents JSON

Looking at an API with `curl` first, then writing the Python code with `requests`, saves a lot of guessing.

Processes: what is running, how to stop it

Every running program is a *process* with a number, its *PID*.

```
ps                          # my processes in this terminal (macOS: ps aux = all of them)
ps aux | grep python        # macOS/Linux: the python processes and their PID
kill 12345                  # ask process 12345 to stop
kill -9 12345               # force it (last resort: it cannot save anything)
```

- A command still running in your terminal: `Ctrl+C`.
- On Windows, the Task Manager (`Ctrl+Shift+Esc`) shows every process with its PID.

Disk: what takes the space?

```
df -h                    # "disk free": space left on each disk, -h = readable (G, M)
du -sh data              # "disk usage" of one folder: -s = total only, -h = readable
du -sh * | sort -h       # size of everything here, smallest first, biggest last
```

- `*` = every file and folder here; `sort -h` sorts sizes written as `12K`, `3.4M`, `1.2G`.
- Usual suspects in a data project: raw data, generated outputs, `.venv` (session 4).

Permission denied: reading ls -l, chmod

```
$ ls -l scripts/report.sh
-rw-r--r--  1 alice  staff  210 Mar 12 10:02 scripts/report.sh
```

`-rw-r--r--` reads in three groups after the first character: **owner** `rw-`, **group** `r--`, **others** `r--`; `r` = read, `w` = write, `x` = execute. No `x`: the file cannot be run as a program.

```
chmod +x scripts/report.sh   # "change mode": add the x (execute) permission
./scripts/report.sh          # ./ = "the file here", run it
```

On Windows the execute permission barely matters; on macOS, Linux and every server it does.

Pack a folder into one file: tar, zip

```
tar czf logs.tar.gz logs/    # create logs.tar.gz from the logs folder
tar tzf logs.tar.gz          # list what is inside, without extracting
tar xzf logs.tar.gz          # extract
```

The letters after `tar`: `c` = create, `t` = list, `x` = extract, `z` = compress (gzip), `f` = the file name follows.

`zip -r logs.zip logs/` and `unzip logs.zip` do the same with `.zip` files on macOS. Git Bash has `tar` but not always `zip`.

Why Git: the problem, the model (9 min)

A familiar story

Alice and Bob work on `analysis.py`, exchanged by e-mail or on a shared drive.

- Monday: Alice adds a monthly total, sends `analysis_v2.py`.
- Tuesday: Bob fixes a bug in his own copy of the *first* version, sends `analysis_v2_bob.py`.
- Wednesday: the monthly totals are wrong, and nobody knows since when.

Questions nobody can answer:

1. Which file is the current version?
2. What exactly changed since last week, who changed it, and why?
3. How do we get back the version that worked on Monday?
4. How do we combine Alice's and Bob's changes without losing one of them?


What Git gives you

need	Git's answer
one current version	one file name, one folder; the history is kept apart
what changed, who, why	every saved version has an author, a date and a message
go back	any saved version can be brought back
combine work	branches and merges (session 2)
share	GitHub (session 3)

Git vs GitHub

Git is a program on your computer; it works offline. **GitHub** is a website that stores Git projects online and adds team features. Today: Git only.

A chain of snapshots



- A **commit** is a saved version of the whole project: a snapshot, with a message, an author and a date. Think of a save point in a video game.
- Each commit has an identifier (`8d44929...`), called its *hash*. The first 4 to 7 characters are enough to name it.
- `main` is the name of the line of work. `HEAD` means "you are here".

The three areas



- You edit files freely. Nothing is saved in Git until you ask.
- `git add` puts a change in the *staging area*: "this goes into my next save".
- `git commit` saves everything that is staged as one commit.
- Two steps on purpose: you choose what belongs together in one save point.

The .git folder

```
git init              # turn the current folder into a Git repository
ls -la                # a hidden folder .git appeared
```

- The whole history lives in `.git`. Never edit it by hand.
- Delete `.git` and your files stay, but the history is gone.
- One repository = one project folder. Never run `git init` in your home folder.

Pitfall — git init in the wrong place

`git status` lists hundreds of files from all over your disk: you ran `git init` in a folder that is too high. Go to that folder, delete its `.git` (`rm -rf .git`), and run `git init` in the project folder.

The core loop (13 min)

Once per computer: tell Git who you are

```
git config --global user.name  "Alice Martin"
git config --global user.email "alice.martin@student.example.edu"
git config --global init.defaultBranch main
git config --global core.editor "code --wait"
```

`--global`	for every repository on this computer
`user.name`, `user.email`	written on every commit you make; use the e-mail of your future GitHub account
`init.defaultBranch main`	name of the first line of work in a new repository. Old Git versions say `master`; we all use `main`
`core.editor "code --wait"`	when Git needs you to write a text (a message), it opens VS Code and waits until you close the tab

The loop you will run a thousand times

```
mkdir my_sales && cd my_sales            # && = then, if the first one worked
git init
code analysis.py                         # write a few lines, save
git status                               # "untracked": Git does not know it yet
git add analysis.py                      # stage it
git commit -m "Add load_sales function" # -m = the message
git log --oneline                        # the history
```

`git log --oneline` shows each commit on one line: its short identifier, then its message. Newest on top.

Pitfall — "LF will be replaced by CRLF"

On Windows Git prints this when you add a file. It is about invisible end-of-line characters and is harmless: ignore it.

Reading git status

```
On branch main
Changes to be committed:            <- staged: will be in the next commit
        new file:   data/sales.csv
Changes not staged for commit:      <- modified, but not staged yet
        modified:   analysis.py
Untracked files:                    <- files Git does not follow at all
        notes.txt
```

- The same file can appear twice: one version staged, newer edits not staged.
- "nothing to commit, working tree clean": everything is saved. The state you want before closing your laptop.

Reading the history: log and show

```
git log                    # every commit: identifier, author, date, message
git log --oneline          # one line per commit: short identifier + message
git log -n 3               # -n 3 = only the last three
git log --stat             # with the list of files changed in each commit
git log -- analysis.py     # only the commits that touched this file
git show 8316eef           # one commit in detail: who, when, message, and the changes
git show HEAD~1            # HEAD~1 = the commit before the current one
```

`HEAD` is the commit you are on, `HEAD~1` the one before, `HEAD~3` three steps back. Options can be combined: `git log --oneline -n 5`.

What changed: git diff

```
git diff                    # my edits that are NOT staged yet
git diff --staged           # what IS staged: exactly what the next commit will contain
git diff HEAD~3 HEAD        # between two commits
```

```
--- a/analysis.py
+++ b/analysis.py
@@ -12,3 +12,5 @@ def total_revenue(rows):
+    if not rows:
+        return 0.0
     return sum(float(r["quantity"]) * float(r["unit_price"]) for r in rows)
```

Lines starting with + were added, with − removed; `@@ -12,3 +12,5 @@` says where in the file.
Habit: read `git diff --staged` before every commit.

A good commit message

Good

- `Add monthly_revenue function`
- `Fix total_revenue crash on empty CSV`
- `Remove unused plotting code`

Short (under 50 characters), starts with a verb, says *what* the commit does.

Useless

- `fix`
- `stuff`
- `final version`
- `asdfgh`

In six months, "fix" tells you nothing.

Rule of thumb: one change, one commit, one clear sentence. Session 3 adds a shared convention for these messages.

.gitignore and undoing (8 min)

.gitignore: what never goes into Git

```
# .gitignore : a text file at the root of the repository, one pattern per line
__pycache__/
.venv/
outputs/
*.png
.env
```

Ignore three kinds of files:

- **generated**: caches, outputs, environments (`__pycache__/`, `outputs/`, `.venv/`)
- **big**: raw data beyond a few MB
- **secret**: passwords and API keys, usually kept in a file called `.env`

Pitfall — too late for files already saved

`.gitignore` only affects files Git does not follow yet. A file already committed stays followed until you run `git rm --cached file` and commit.

Undo, part 1: changes not committed yet

```
git restore --staged analysis.py   # unstage: the edit stays in the file, it just leaves the
      staging area
git restore analysis.py            # throw away my edits: the file goes back to the last
     commit
```

- `--staged`: nothing is lost.
- Without `--staged`: your uncommitted edits to that file are gone for good. Git cannot bring back what was never committed.

Undo, part 2: a bad commit, use git revert

```
git log --oneline          # find the identifier of the bad commit
git revert da319b1         # create a NEW commit that does the opposite of da319b1
```

- VS Code opens with a message `Revert "..."`: keep it, save, close the tab.
- The bad commit stays in the history, followed by the commit that cancels it. Nothing is erased, so nothing can be lost.
- It is always safe, even when teammates already have the bad commit (session 3).

Our rule

To undo a commit, use `git revert`. By default, we never use `git reset`.

git reset: the exception

`git reset` moves the line of work backwards: the commits after that point *disappear* from the history.

```
git reset --soft HEAD~1    # undo my last commit, keep its changes staged, to redo it
    properly
```

- Only acceptable for a commit you *just* made, that exists only on your laptop: you forgot a file, or the message is wrong. `--soft` keeps all your work.
- `git reset --hard` also throws away every uncommitted change. Avoid it: to discard edits, `git restore` is enough and touches nothing else.
- Never on commits that teammates already have: their history and yours would no longer match (session 3).

Tip — the emergency exit

`git reflog` lists every place `HEAD` has been. A commit removed by mistake can be found there and brought back. Only work that was never committed is truly lost.

Safe or not: summary

command	effect	risk
`git status`, `log`, `show`, `diff`	read only	**safe**
`git add`, `git commit`	save a new version	**safe**
`git restore --staged f`	unstage, keep the edit	**safe**
`git revert <id>`	new commit cancelling another	**safe** (the default way to undo)
`git reset --soft HEAD~1`	remove my last commit, keep the work	**rewrites local history** (exception only)
`git restore f`	throw away uncommitted edits to f	**destroys work**
`git reset --hard`	remove commits and edits	**destroys work** (avoid)
`rm -rf .git`	delete the whole history	**destroys work**

Keep this table: it grows a little every session.

Wrap-up (2 min)

Read this repository

```
$ git log --oneline
79ee015 (HEAD -> main) Add monthly_revenue function
da319b1 Add config for the reporting API
f60a1f8 Add shell lab material for TD1
$ git show --stat da319b1 | tail -n 2
 project/config.ini | 3 +++
```

Check yourself — you will do it in the TD

1. Alice notices that `config.ini` contains an API key. Which command removes the file from the current version without erasing history?
2. After that command, what does the first line of `git log --oneline` look like?
3. The key is still visible in the old commit. What should Alice do with the key itself?

Take-aways and TD1

Remember

- one shell for everyone: Git Bash on Windows
- `pwd`, `ls`, `cd`, `Tab`, drag and drop
- `>` `>>` `|`, `grep`, `find`
- edit → `git add` → `git commit`
- `git status` and `git diff` before, `git log` after
- undo a commit: `git revert`

TD1 (1 h 30)

1. install Git, Python, VS Code; configure Git (20 min)
2. shell treasure hunt in `shell-lab` (30 min)
3. your first repository, reading a history, undoing (35 min)
4. checklist (5 min)

Slides, cheat-sheet and TD material:
`https://github.com/msa-datb07-git`

Next session: branches, merges and your first conflict.