Credits - Image f Why Pythor	from I=:					
-	n for DA? ry easy to get sta good fit since it h		ments available f	or Data Analys	s and Data Scier	nce.
 Note - Check god Before clickin Link → https: y&q=%2Fm9 	ng the below link ://trends.google. %2F05z1_,%2Fm%	omaprison. , please sign-in y com/trends/explo 62F0212jm,%2Fn	our google acco ore?cat=1299&d n%2F0j3djl7,%2F	unt on web. ate=today%20 m%2F052tr,%2		
_	n it comes to spo	.com/blog/2020,			Science	e
Da	1. ata ection		3. Data Cleaning			5. lization
	S	2. Data storage	XX	4. Data Analy		6. Decis
Credits - Image f Data Analys As a Data Analyst	st's role	to do the followin	ng things -			
• Finding insig	ng aising	eve the goal				
Questions like -WHYHOWWHENWHAT						
Design DataCreate or use	ist's role tory telling proce Models	ss with the valid				s helping to take decision
Make decisionMore informationhttps://www.	ons from the insign n .northeastern.edu .northeastern.edu	ghts u/graduate/blog/ u/graduate/blog/	/data-analytics-v	s-data-science/		
2. Check if data	estion from online using a cleaning is nece → Clean t	ssary.				
Apply ControlPlot the	Proceed relationship betw orrelation (Bi-var relationship → http://wiki.sta	iate analysis)		Data Dinov 02	0108 HeightsW	eights
1. Collect da 1. Pandas is pyt 2. It is similar to 3. It is one of th	ata from on thon library main o doing analysis on the best open sou	line ly used for data a on Excel. rce libraries avali	analysis.			
	tement	-user	nl page.			
<pre># data stori data = pd.re # check type</pre>	<i>ng</i> ad_html(data_		du/socr/index	php/SOCR_Da	ta_Dinov_0201	08_HeightsWeights'
type(data) list # check len len(data)						
# display ta data[0]	.ble 0 CR Data - 25,000 Re	0 cords of Human				
0 1 1 2	ght(Inches) Weig 65.78 71.52	112.99 136.49				
2 3 3 4 4 5 195 196 196 197	69.40 68.22 67.79 65.80 66.11	153.03 142.34 144.30 120.84 115.78				
197 198 198 199 199 200 200 rows × 3 colu		128.30 127.47 127.88				
data[2] 0 (default) Deut 1 한국어	1 2	ançais Italiano				8 9 Suomi इस भार Danmark Polska Romá
<pre># df df = data[1] # display en print(df) Index H 0 1 1 2</pre>	tire table Meight(Inches) 65.78 71.52	112	.99			
2 3 3 4 4 5 	69.40 68.22 67.79 65.80 66.11 68.24 68.02 71.39	153 142 144 120 115 128 127	.03 .34 .30 .84 .78 .30 .47			
0 1	t(Inches) Weight	112.99				
<pre>1 2 2 3 3 4 4 5 # display th df.tail()</pre>	71.52 69.40 68.22 67.79	136.49 153.03 142.34 144.30				
Index Height 195 196 197 198 199	ght(Inches) Weig 65.80 66.11 68.24 68.02	120.84 115.78 128.30				
# display th df.columns Index(['Index		127.88	ht(Pounds)'],	dtype='obje	ct')	
<pre># isnull df.isnull().</pre>	False s) False	me the columns	s IT any.			
Height (Inches	0 0					
Weight (Pounds dtype: bool # isna df.isna().sur Index Height (Inches Weight (Pounds dtype: int64 • Since the date isna() date • In order to get Above result is cleaned.	taset is sort of big taset. get the actual value	n has non-nan	below function c	an be used.		e actual missing values fr
Weight (Pounds dtype: bool # isna df.isna().sur Index Height (Inches Weight (Pounds dtype: int64 • Since the date isna() date • In order to g	taset is sort of big taset. get the actual valuear, every column datatypes from	n has non-nan	below function c	an be used.		
Weight (Pounds dtype: bool # isna df.isna().sum Index Height (Inches Weight (Pounds dtype: int64) • Since the dam isna() dam isna	int64 float64	DataFrame'> to 199 mns): ull Count Dty- on-null in-	ype t64	an be used.		
Weight (Pounds dtype: bool # isna df.isna().sur Index Height (Inches Weight (Pounds dtype: int64 • Since the dat isna() dat • In order to g Above result is clot b. Check for the # dtypes df.dtypes Index Height (Inches Weight (Pounds dtype: object # info df.info() <class #="" 'panda="" (i="" (pounds="" 1="" 2="" c.="" column="" columns="" data="" description="" dtypes:="" every="" float="" height="" index="" like="" memory="" o="" of="" overall="" rangeindex:="" same="" seems="" td="" the="" the<="" type.="" usage:="" weight=""><td>int64 s) float64 s) float64 s) float64 contains a column on the column on the column has a un</td><td>DataFrame'> to 199 mns): ull Count Dt: on-null infon-null flo</td><td>ype t64 oat64 oat64</td><td>an be used.</td><td>vith further steps</td><td></td></class>	int64 s) float64 s) float64 s) float64 contains a column on the column on the column has a un	DataFrame'> to 199 mns): ull Count Dt: on-null infon-null flo	ype t64 oat64 oat64	an be used.	vith further steps	
Weight (Pounds dtype: bool # isna df.isna().sur Index Height (Inches Weight (Pounds dtype: int64 • Since the dat isna() dat • In order to g Above result is clot b. Check for the # dtypes df.dtypes Index Height (Inches Weight (Pounds dtype: object # info df.info() <class #="" 'panda="" 2="" column<="" columns="" data="" rangeindex:="" td=""><td>int64 s) float64 float</td><td>DataFrame'> to 199 mns): ull Count Dty on-null infon-null flo on-null flo on-null flo on-null flo on-null flo on-null flo on-null flo a frame Weight(Pounds) 200.0000000</td><td>ype t64 oat64 oat64 at all there is the</td><td>an be used.</td><td>vith further steps</td><td>5.</td></class>	int64 s) float64 float	DataFrame'> to 199 mns): ull Count Dty on-null infon-null flo on-null flo on-null flo on-null flo on-null flo on-null flo on-null flo a frame Weight(Pounds) 200.0000000	ype t64 oat64 oat64 at all there is the	an be used.	vith further steps	5.
Weight (Pounds dtype: bool # isna df.isna().sur Index Height (Inches Weight (Pounds dtype: int64 • Since the dat isna() dat • In order to g Above result is classed b. Check for the # dtypes df.dtypes Index Height (Inches Weight (Pounds dtype: object dtype: object dtype: object dtypes: float memory usage: Seems like every same type. c. Overall descripe df.describe (Index # describe df.describe (Index Index # describe df.describe (Index	int64 float64	DataFrame'> to 199 mns): ull Count Dty on-null infon-null flo on-null flo on-n	ype t64 oat64 oat64 at all there is the	an be used.	vith further steps	5.
Weight (Pounds dtype: bool # isna df.isna().sum Index Height (Inches Weight (Pounds dtype: int64) • Since the data isna() data • In order to go Above result is class b. Check for the data isna() data • In order to go Above result is class b. Check for the data isna() data • In order to go Above result is class # dtypes df.dtypes Index Height (Inches Weight (Pounds dtype: object) # info df.info() <class #="" 'panda="" 2="" column<="" columns="" data="" rangeindex:="" td=""><td>taset is sort of big taset. get the actual value ear, every column datatypes from the date of the actual value are revery column datatypes from the date of the actual value ear, every column datatypes from the date of the actual value are revery column of the date of the actual value are revery column of the date of the actual value are revery column of the date of the actual value are revery column of the date of the actual value are revery column of the date of the actual value are revery column of the date of the actual value are revery column of the date of the actual value are revery column of the date of the actual value are revery column of the date of the actual value are revery column of the date of the actual value are revery column of the date of the actual value are revery column of the date of the actual value are revery column of the date of the actual value are revery column of the date of the actual value are revery column of the actual value are revery column of the date of the actual value are revery column of the date of the actual value are revery column of the actual value are reversed at the actual value are rever</td><td>DataFrame'> to 199 mns): ull Count Dty on-null infon-null flo on-null flo on-n</td><td>ype t64 oat64 oat64 at all there is the</td><td>en it is required</td><td>to purify the da</td><td>5.</td></class>	taset is sort of big taset. get the actual value ear, every column datatypes from the date of the actual value are revery column datatypes from the date of the actual value ear, every column datatypes from the date of the actual value are revery column of the date of the actual value are revery column of the date of the actual value are revery column of the date of the actual value are revery column of the date of the actual value are revery column of the date of the actual value are revery column of the date of the actual value are revery column of the date of the actual value are revery column of the date of the actual value are revery column of the date of the actual value are revery column of the date of the actual value are revery column of the date of the actual value are revery column of the date of the actual value are revery column of the date of the actual value are revery column of the date of the actual value are revery column of the actual value are revery column of the date of the actual value are revery column of the date of the actual value are revery column of the actual value are reversed at the actual value are rever	DataFrame'> to 199 mns): ull Count Dty on-null infon-null flo on-null flo on-n	ype t64 oat64 oat64 at all there is the	en it is required	to purify the da	5.
Weight (Pounds dtype: bool # isna df.isna().sur Index Height (Inches Weight (Pounds dtype: int64) • Since the dat isna() dat • In order to get describe (Inches Weight (Pounds dtypes) Index Height (Inches Weight (Pounds dtype: object dtypes) Index Height (Inches Weight (Pounds dtype: object dtypes) # info df.info() <class #="" 'panda="" (i="" (inde<="" (index="" (pounds="" -="" 1="" 2="" c.="" column="" columns="" data="" describe="" descripe="" dtypes:="" every="" float="" height="" index="" like="" memory="" o="" overall="" rangeindex:="" same="" seems="" td="" type.="" usage:="" weight=""><td>taset is sort of big taset. pet the actual value ear, every column datatypes from the data float 64 f</td><td>DataFrame'> to 199 mns): ull Count Dt; con-null infon-null flicon-null flicon-</td><td>ype t64 oat64 oat64 at all there is the</td><td>en it is required</td><td>to purify the da</td><td>5.</td></class>	taset is sort of big taset. pet the actual value ear, every column datatypes from the data float 64 f	DataFrame'> to 199 mns): ull Count Dt; con-null infon-null flicon-null flicon-	ype t64 oat64 oat64 at all there is the	en it is required	to purify the da	5.
Weight (Pounds dtype: bool # isna df.isna().sur Index Height (Inches Weight (Pounds dtype: int64 • Since the dat isna() dat • In order to get a dtype: int64 • Since the dat isna() dat • In order to get a dtypes df.dtypes df.dtypes Index Height (Inches Weight (Pounds dtype: object dtype: object dtype: object dtype: object dtype: object dtype: object dtypes: float memory usage: Seems like every same type. C. Overall descripe df.describe (Index describe df.describe	taset is sort of big taset. get the actual value ear, every column datatypes from the data float64 fl	DataFrame'> to 199 mns): ull Count Dt; con-null infon-null flicon-null flicon-	ype t64 oat64 oat64 at all there is the	en it is required	to purify the da	5.
Weight (Pounds dtype: bool # isna df.isna().su: Index Height (Inches Weight (Pounds dtype: int64 • Since the dat isna() dat • In order to get a dtype: int64 • Since the dat isna() dat • In order to get a dtype: int64 • Since the dat isna() dat • In order to get a dtype: int64 # dtypes df.dtypes Index Height (Inches Weight (Pounds dtype: object a dtype: o	taset is sort of big taset. get the actual value ear, every column datatypes from the da	DataFrame'> to 199 mns): ull Count Dt; con-null infon-null flicon-null flicon-	ype t64 oat64 oat64 at all there is the	en it is required	to purify the da	5.
Weight (Pounds dtype: bool # isna df.isna().sur Index Height (Inches Weight (Pounds dtype: int64 • Since the dat isna() dat • In order to get he dat isna() dat • In order to get he dat isna() dat • In order to get he dat isna() dat • In order to get he dat isna() dat • In order to get he dat isna() dat • Index Height (Inches Weight (Pounds dtype: object dat isna()) * Colass 'panda Range Index: 2 Data columns # Column	taset is sort of big taset. The the actual value ear, every column datatypes from the da	DataFrame'> to 199 mns): ull Count Dt: on-null in: on-null fl: on-	below function of values. Hence we shall be shal	an be used. can proceed very about the data about the data are we should do.	to purify the da	5.
Weight (Pounds dtype: bool # isna df.isna().sur Index Height (Inches Weight (Pounds dtype: int64 • Since the dai isna() dai • In order to graph (Pounds dtype: int64 • Since the dai isna() dai • In order to graph (Pounds dtypes df.dtypes df.dtypes df.dtypes df.dtypes df.dtypes df.dinfo() <pre> </pre> <pre></pre>	taset is sort of big taset. tet the actual value ear, every column datatypes from datatypes from int64 float64 floa	DataFrame '> to 199 mns): ull Count Dt; on-null in: on-null fl: on	below function of values. Hence we have the values. Hence we have the values at all there is the value of the	an be used. can proceed very about the data about the data are we should do.	to purify the da	5.
Weight (Pounds dtype: bool # isna df.isna().sur Index Height (Inches Weight (Pounds dtype: int64 • Since the dat isna() dat isna(taset is sort of big taset. Interest the actual value ear, every column datatypes from int64 i	DataFrame '> In has non-nan on each column In	below function of values. Hence we have below function of values. Hence we have been been below for the decision of the content of the conten	an be used. can proceed very about the data about the data are we should do.	to purify the da	5.
Weight (Pounds dtype: bool # isna df.isna().sur Index Height (Inches Weight (Pounds dtype: inf64 • Since the dat isna() dat isna(taset is sort of big taset. taset. t	DataFrame '> In has non-nan on each column In	below function of values. Hence we have below function of values. Hence we have been been below for the description of the content of the con	an be used. can proceed very about the data about the data are we should do.	to purify the da	5.
Weight (Pounds dtype: bool) # isna	taset is sort of big taset. tet the actual value ear, every column datatypes from the da	DataFrame '> In has non-nan with each column In has non-nan with	below function of values. Hence we have below function of values. Hence we have been below for the second of the s	an be used. e can proceed was about the data are are aff and aff.	vith further steps to purify the da	ta - make sure all the va
# # # # # # # # # # # # # # # # # # #	taset is sort of big taset. tet the actual value ear, every column datatypes from int64 float64 flo	DataFrame'> In has non-nan In each column In each c	below function of values. Hence we shall there is the state of the state of the state of the household excluded Index ghts from the distribution of the household excluded Index ghts from the household excluded Index ghts f	an be used. It is required about the data about the data ata frame df. The second of the second	vith further steps to purify the da visually.	ta - make sure all the va
# # # # # # # # # # # # # # # # # # #	taset is sort of bistaset. The the actual value ear, every column datatypes from the data float 64 and float	DataFrame '> In has non-nan on each column In	below function of values. Hence we shall there is the shall there is the shall there is the shall the shal	an be used. It is required about the data about the data ata frame df. The second of	vith further steps visually. visually. e. e. th this, it can be	aly related. easily noticed the linear
# # # # # # # # # # # # # # # # # # #	taset is sort of bintaset. let the actual value ear, every column datatypes from the data floated flo	DataFrame '> In has non-nan in meach column DataFrame '> In has non-nan in her nan in has non nan in has non nan in has non other variable in has non other variable. In data variables - each of has non other variable in has non other variable in has non other variable. In data variables - each of has non other variable in has non other variable. In data variables - each of has non other variable in has non other variable. In data variables - each of has non other variable. In data variables - each of has non other variable. In data variables - each of has non other variable. In data variables - each of has non other variable. In data variables - each of has non other variable. In data variables - each of has non other variable. In data variables - each of has non other variable. In data variables - each of has non other variable. In data variables - each of has non other variable. In data va	below function of values. Hence we shall be shown that the from the data of the household excluded Index and the household excluded	an be used. It is required It is required It is required It is required It is any two variables. With the data It is a spenses increase and the second of the second	vith further steps visually. visually. e. e. th this, it can be	aly related. easily noticed the linear
# searche de servery # searche de searche d	taset is sort of bintaset. let the actual value ear, every column datatypes from the dat	DataFrame '> In has non-nan In meach column DataFrame '> In has non-nan In meach column DataFrame '> In has non-nan In has n	below function of values. Hence we walked. Hence we walked a water of the second of th	an be used. It is required It is required It is required It is required It is any two variables. With the data It is a spenses increase and the second of the second	vith further steps visually. visually. e. e. th this, it can be	aly related. easily noticed the linear
# plot () **Coverall describe (describe) **Coverall describe (describe) **Coverall describe (describe) **Count 200.00000 **Source describe (describe) **Count 200.000000 **Source describe (describe) **Count 200.00000 **Source	taset is sort of bintaset. pet the actual value ear, every column datatypes from the dat	DataFrame '> In has non-nan In meach column The property of t	below function of values. Hence we will be seem to be the household excluded a pot () to explore to the household excluded index ghts from the diagram of the household excluded a pot () to explore to the household excluded index ghts from the diagram of the household excluded in the household excluded i	an be used. It can proceed we should do. It is required. It is required. It is required. It is any two variables. With the data and the should do. It is any two variables. With the should do. It is a	vith further steps vith further steps vitables are linres e. se. th this, it can be n_examples2.svg	aly related. easily noticed the linear
# sina df. isna () .sur Height (Inches Weight (Pounds dtype: inted disna () .sur Height (Inches Weight (Pounds dtype: inted disna () data isna () da	taset is sort of bintaset. pet the actual value ear, every column datatypes from the dat	DataFrame '> In has non-nan on each column DataFrame '> In has sea on each column DataFrame '> In has variable '> In has var	below function of values. Hence we shall be shown the data of () to explore the household excluded Index ghts from the data of () to explore the household excluded in the hou	an be used. It can proceed we should do. It is required at a frame df . It is required at a frame df . It is controlled to the should do. It is required at a frame df . It is required	vith further steps vith further steps vitables are linres e. se. th this, it can be n_examples2.svg	aly related. easily noticed the linear
# since the date is na () sure weight (Pounds dt is na () sure weight (Pounds dt is na () date is na	taset is sort of bit taset. let the actual value ear, every column datatypes from the da	pataFrame '>	below function of values. Hence we shall there is the same of the content of the	an be used. It can proceed we should do. It is required at a frame df . It is required at a frame df . It is controlled to the should do. It is required at a frame df . It is required	vith further steps vith further steps vitables are linres e. se. th this, it can be n_examples2.svg	aly related. easily noticed the linear
# John Scatter plot in bar he	taset is sort of bistaset. tet the actual value ear, every columns datatypes from the da	DataFrame '> In has non-nan In meach column DataFrame '> In has non-nan In has n	below function of values. Hence we will be a served as	an be used. It can proceed we should do. It is required at a frame df . It is required at a frame df . It is controlled to the should do. It is required at a frame df . It is required	vith further steps vith further steps vitables are linres e. se. th this, it can be n_examples2.svg	aly related. easily noticed the linear
# # # # # # # # # # # # # # # # # # #	taset is sort of bigustaset. the the actual value ear, every columns datatypes from the	DataFrame '> In has non-nan In each column In each	below function of values. Hence we will be a served as	an be used. It can proceed we should do. It is required at a frame of the state o	vith further step: in the purify the date of the purify th	aly related. easily noticed the linear
# states play by both the plotting without the plot	taset is sort of bintaset. test the actual value ear, every column datatypes from the da	DataFrame '> In has non-nan In each column In	below function of values. Hence we value at all there is the value at all there is the value at all there is the value at all the value at all the value at a value	an be used. It can proceed we should do. It is required at a frame of the state o	vith further step: in the purify the date of the purify th	aly related. easily noticed the linear
# # # # # # # # # # # # # # # # # # #	taset is sort of bit taset. tet the actual value ear, every column taset. tet the actual value ear, every column taset. tet the actual value ear, every column tased the float 64 ear, every column tase a universe of the column tase a universe ear, every column tase ear, every	DataFrame '> to 199 to 199 mas): ull Count Dt. to 199 mas): ull Count Dt. don-null fl. on-null fl. on-	below function of values. Hence we will be a state of the following and the following and the following and the household enship between two betained. Pounds) ', kind of the following and th	an be used. It can proceed we should do. It is required at a frame of the state o	vith further step: in the purify the date of the purify th	aly related. easily noticed the linear
## Statter plate	taset is sort of bit taset. tet the actual value are, every column to the date of the dat	are (indices), the in has non-nan in each column by to 199 in each column co	below function of values. Hence we was a state of the control of t	an be used. It can proceed we can proceed we can proceed we can be used. It is required and a can be used to a can be used as a can be used to a can be used	riables are linred e. e. se. th this, it can be n_examples2.svg	ta - make sure all the value of the sure all the value of the sure all the value of the sure of the su