

# Facebook Pixel Web Conversion Tracking

## **PageView Event Setup**

Tag- PageView event in Facebook Pixel Tag Template

Trigger- All Pages Variable- Nothing

## ViewContent Event Setup

## Tag-

ViewContent event in Facebook Pixel Tag Template

Under Object Properties-

content\_type - product\_group/ product
content\_name - {{dlv - item\_name}}
content\_ids - {{dlv - item\_id}}
value - {{dlv - item\_price}}
currency - {{dlv - currency}}

## Trigger-

view\_item dataLayer event in custom event trigger

## Variables -

dlv - item\_name - ecommerce.items.0.item\_namedlv - item\_id - ecommerce.items.0.item\_iddlv - item\_price - ecommerce.items.0.pricedlv - currency - ecommerce.currency

AddToCart Event Setup

## Tag-

### AddToCart event in Facebook Pixel Tag Template

```
Under Object Properties-
```

```
content_type - product_group/ product
content_name - {{dlv - item_name}}
content_ids - {{dlv - item_id}}
value - {{dlv - item_price}}
currency - {{dlv - currency}}
```

### Trigger-

add\_to\_cart dataLayer event under custom event trigger

### Variables -

```
dlv - item_name - ecommerce.items.0.item_namedlv - item_id - ecommerce.items.0.item_iddlv - item_price - ecommerce.items.0.pricedlv - currency - ecommerce.currency
```

## InitiateCheckout Event Setup

## Tag-

InitiateCheckout event in Facebook Pixel Tag Template

```
Under Object Properties-
```

```
content_type - product_group/ product
content_name - {{cJS - product names}}
content_ids - {{cJS - product ids}}
value - {{dlv - value}}
currency - {{dlv - currency}}
```

## Trigger-

begin checkout dataLayer event under custom event trigger

## Variables -

cJS - product names -

#### Method-1 Easy and Updated

```
function() {
  var itemsArray = {{dlv - ecommerce_items}};

  if (itemsArray && itemsArray.length > 0) {
     // Check if there's only one item
     if (itemsArray.length === 1) {

        return itemsArray[0].item_name; // Return the item_id as a string
  for a single product
     } else {

     // If there are multiple items, return an array of item_ids
        return itemsArray.map(function(product) {
        return product.item_name;
      });
     }
  } else {
     return undefined; // Handle the case where itemsArray is undefined
  or empty
  }
}
```

#### Method-2 - (Old Method)

```
function(){
    function getData(input){
        var x = [];
        for (var i = input.length - 1; i >= 0; i--) {
             x.push(input[i].item_name);
        }
        return x;
    }

    var data = getData({{Ecommerce Items}});

    if( data == "undefined" ){
        data = ""; }

    return data;
}
```

#### Method-1 Easy and Updated

```
function() {
  var itemsArray = {{dlv - ecommerce_items}};

  if (itemsArray && itemsArray.length > 0) {
     // Check if there's only one item
     if (itemsArray.length === 1) {

        return itemsArray[0].item_id; // Return the item_id as a string
     for a single product
     } else {

        // If there are multiple items, return an array of item_ids
              return itemsArray.map(function(product) {
                return product.item_id;
           });
        }
     } else {
        return undefined; // Handle the case where itemsArray is undefined
     or empty
     }
}
```

#### Method-2 - Old Method

```
function(){
    function getData(input){
        var x = [];
        for (var i = input.length - 1; i >= 0; i--) {
             x.push(input[i].item_id);
        }
        return x;
    }

    var data = getData({{Ecommerce Items}});

    if( data == "undefined" ){
        data = ""; }

    return data;
}
```

**dlv - value** - ecommerce.value **dlv - currency** - ecommerce.currency

# **Purchase Event Setup**

## Tag-

Purchase event in Facebook Pixel Tag Template

### Under Object Properties-

```
content_type - product_group/ product
content_name - {{cJS - product names}}
content_ids - {{cJS - product ids}}
value - {{dlv - value}}
currency - {{dlv - currency}}
order_id - {{dlv - transaction_id}}
```

## Trigger-

purchase dataLayer event under custom event trigger

### Variables -

cJS - product names - same as Initiate Checkout cJS - product ids - same as Initiate Checkout

dlv - value -ecommerce.valuedlv - currency -ecommerce.currencydlv - transaction\_id -ecommerce.transaction\_id

# **Topics We Will Discuss Today - Part 2**

- 1. InitiateCheckout event setup
- 2. Purchase event setup
- 3. Scrapping data from an array
- 4. Uploading product feed in the commerce manager
- 5. Connecting pixel with commerce manager
- 6. Connecting pixel with ad account and ads
- 7. Custom audience

### **Required Links:**

#### Facebook Custom parameters:

https://developers.facebook.com/docs/marketing-api/conversions-api/paramet ers/custom-data/

#### **Dynamic Remarketing Events:**

https://web.facebook.com/business/help/606577526529702?id=12053766828 32142& rdc=1& rdr

#### Facebook Standard Event:

https://www.facebook.com/business/help/402791146561655?id=12053766828 32142