# **Design Document**

LED SEQUENCE V2.0

By Mohamed Sayed SPRINTS

## **Table of Contents**

TASK DESCRIPTION	2
TASK FLOWCHART	3
HIGH LEVEL DESIGN	4
Layered architecture4	
System modules5	
LOW LEVEL DESIGN	6
APIs	6
MCAL	6
DIO6	
External Interrupt6	
ECUAL	7
LEDs7	
APPLICATION	7


## **Task Description:-**

#### • Hardware Requirements:

- 1) Four LEDs (LED0, LED1, LED2, LED3)
- 2) One button (BUTTON1)

#### Software Requirements:

- 1) Initially, all LEDs are OFF
- 2) Once BUTTON1 is pressed, LED0 will be ON
- 3) Each press further will make another LED is ON
- 4) At the fifth press, LEDO will changed to be OFF
- 5) Each press further will make only one LED is OFF
- 6) This will be repeated forever
- 7) The sequence is described below:-
  - 1) Initially (OFF, OFF, OFF, OFF)
  - 2) Press 1 (ON, OFF, OFF, OFF)
  - 3) Press 2 (ON, ON, OFF, OFF)
  - 4) Press 3 (ON, ON, ON, OFF)
  - 5) Press 4 (ON, ON, ON, ON)
  - 6) Press 5 (OFF, ON, ON, ON)
  - 7) Press 6 (OFF, OFF, ON, ON)
  - 8) Press 7 (OFF, OFF, OFF, ON)
  - 9) Press 8 (OFF, OFF, OFF, OFF)
  - 10) Press 9 (ON, OFF, OFF, OFF)
- 8) Use External Interrupt



# **High Level Design:-**

## **Layered architecture**


## The system may be divided to 4 layers:-


- Microcontroller
- MCAL
- ECUAI
- Application

n	Application
mor	ECUAL
mu	MCAL
CO	Microcontroller

## **System modules**

The system may be divided into drivers:-





## **LOW Level Design:-**

#### **MCAL**

```
void DIO_InitPin (PIn_name pin ,PIN_Status status );

void DIO_init (void);

void DIO_WRitePin (PIn_name pin ,Voltage_type s);

Voltage_type DIO_ReadPin(PIn_name pin);


void DIO_WritePort(PORT_Type Port,u8 data);
```

```
External interrupt

APIs
```

```
void EXI_Enable (ExInterruptSource_type Interrupt);
void EXI_Disable (ExInterruptSource_type Interrupt);
void EXI_Trigger(ExInterruptSource_type Interrupt,TriggerEdge_type trigger);
void EXI_SetCallBack(ExInterruptSource_type Interrupt,void(*pf)(void));
```

## **ECUAL**



## **Application**

```
Application void APP_Init(void);
APIs void APP_Start(void);
```