1. php artisan make:migration create_t_tm_pl_advice_op_table

```
use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

class CreateTTmPlAdviceOpTable extends Migration
{
   /**
    * Run the migrations.
    *
    * @return void
    */
   public function up()
   {
      Schema::create('t_tm_pl_advice_op', function (Blueprint $table) {
         $table->increments('id');
         $table->integer('fin_year_from')->nullable();
         $table->string('int_treasury_code', 5);
         $table->bigInteger('ref_no');
         $table->bigInteger('int_pl_operator_id');
         $table->string('transfer_type', 2);
         $table->string('pay_mode', 1);
         $table->string('memo_number', 30)->nullable();
         $table->date('memo_date')->nullable();
         $table->integer('dml_status_flag')->default(0);
         $table->bigInteger('user_id');
         $table->timestamp('created_timestamp')->useCurrent();
         $table->bigInteger('modified_user_id')->nullable();
         $table->timestamp('modified_timestamp')->nullable();
         $table->date('ref_date');
         $table->decimal('net_amount', 14, 2);
         $table->string('cosa_bill_no', 256)->nullable();
         $table->string('cosa_upload', 1)->nullable();
         $table->decimal('cosa_amount', 14, 2)->nullable();
         $table->bigInteger('approved_objected_by')->nullable();
         $table->date('approve_object_dt')->nullable();
         $table->string('reason', 150)->nullable();
         $table->integer('advice_id')->nullable();
         $table->date('advice_date')->nullable();
         $table->integer('local_advice_id')->nullable();
         $table->date('local_advice_date')->nullable();
         $table->integer('processing_flag')->default(0);
         $table->bigInteger('old_ref_no')->nullable();
         $table->string('resubmit_flag', 1)->nullable();
         $table->string('party_code', 5)->nullable();
```

```
            $table->string('bulk_benf_flag', 1)->nullable();
            $table->string('service_code', 10)->nullable();
            $table->string('pf_flag', 7)->nullable();
            $table->timestamps();
        });
    }

    /**
     * Reverse the migrations.
     *
     * @return void
     */
    public function down()
    {
        Schema::dropIfExists('t_tm_pl_advice_op');
    }
}
```

2. php artisan make:migration create_t_td_pl_advice_op_table

```
use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

class CreateTTdPlAdviceOpTable extends Migration
{
    /**
     * Run the migrations.
     *
     * @return void
     */
    public function up()
    {
        Schema::create('t_td_pl_advice_op', function (Blueprint $table) {
            $table->increments('id');  // Primary key
            $table->integer('fin_year_from');  // Financial year
            $table->string('int_treasury_code', 5);  // Treasury code
            $table->bigInteger('ref_no');  // System-generated reference number
            $table->bigInteger('int_micr_number');  // MICR number for cheque
            $table->string('cheque_number', 10)->nullable();  // Cheque number
            $table->date('cheque_date')->nullable();  // Cheque date
            $table->integer('dml_status_flag')->default(0);  // Deletion status flag
            $table->bigInteger('user_id');  // Created by user ID
            $table->timestamp('created_timestamp')->useCurrent();  // Timestamp
when created
            $table->bigInteger('modified_user_id')->nullable();  // Modified by user ID
            $table->timestamp('modified_timestamp')->nullable();  // Timestamp
when modified
```

```
            $table->string('payee_name', 150);  // Payee name
            $table->integer('school_code')->nullable();  // School code
            $table->integer('scheme_id');  // Scheme ID
            $table->string('description', 100)->nullable();  // Payment description
            $table->decimal('cheque_amount', 14, 2);  // Amount for the cheque
            $table->string('tax_flag', 1)->nullable();  // Tax applicable flag
            $table->string('physical_cheque_number', 6)->nullable();  // Physical
cheque number
            $table->string('salary_type', 5)->nullable();  // Salary type (iOSMS/HRMS)
            $table->string('pf_emp_id', 50)->nullable();  // PF Employee ID
            $table->string('pf_withdrawl_type', 15)->nullable();  // PF withdrawal
type
            $table->timestamps();  // Created_at and updated_at timestamps
        });
    }

    /**
     * Reverse the migrations.
     *
     * @return void
     */
    public function down()
    {
        Schema::dropIfExists('t_td_pl_advice_op');
    }
}
```

3. php artisan make:migration create_t_td_pl_cheque_bt_op_table

```
use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

class CreateTTdPlChequeBtOpTable extends Migration
{
    /**
     * Run the migrations.
     *
     * @return void
     */
    public function up()
    {
        Schema::create('t_td_pl_cheque_bt_op', function (Blueprint $table) {
            $table->increments('id');  // Primary key
            $table->integer('fin_year_from');  // Financial year related to the reference
            $table->string('int_treasury_code', 5);  // Treasury code
            $table->bigInteger('ref_no');  // System-generated reference number
            $table->bigInteger('rec_id');  // Record ID serial number
            $table->integer('scheme_id');  // System-generated PL Scheme ID
```

```
            $table->bigInteger('to_int_pl_operator_id');  // Transfer Operator ID
            $table->integer('to_scheme_id');  // Transfer Scheme ID
            $table->bigInteger('to_bt_serial_number');  // Transfer By transfer
number (System-generated)
            $table->decimal('amount', 14, 2);  // Transfer amount
            $table->integer('dml_status_flag')->default(0);  // Deletion status flag
            $table->bigInteger('user_id');  // User who created the record
            $table->timestamp('created_timestamp')->useCurrent();  // Timestamp
when the record was created
            $table->bigInteger('modified_user_id')->nullable();  // Modified user ID
            $table->timestamp('modified_timestamp')->nullable();  // Timestamp
when the record was modified
            $table->string('cheque_number', 10);  // Cheque number
            $table->string('purpose', 100)->nullable();  // Purpose of the payment
            $table->bigInteger('int_micr_number');  // MICR number for the cheque
            $table->string('operator_treasury_code', 5);  // Operator treasury code
            $table->string('salary_type', 5)->nullable();  // Salary type (iOSMS/HRMS)
            $table->string('pf_emp_id', 50)->nullable();  // PF Employee ID
            $table->string('pf_withdrawl_type', 15)->nullable();  // PF withdrawal
type
            $table->timestamps();  // Created_at and updated_at timestamps
        });
    }

    /**
     * Reverse the migrations.
     *
     * @return void
     */
    public function down()
    {
        Schema::dropIfExists('t_td_pl_cheque_bt_op');
    }
}
```

4. php artisan make:migration create_t_td_pf_transfer_op_table

```
use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

class CreateTTdPfTransferOpTable extends Migration
{
    /**
     * Run the migrations.
     *
     * @return void
     */
    public function up()
```

```
    {
        Schema::create('t_td_pf_transfer_op', function (Blueprint $table) {
            $table->increments('id');  // Primary key
            $table->integer('fin_year_from');  // Financial year related to the reference
            $table->string('int_treasury_code', 5);  // Treasury code of the operator
            $table->bigInteger('ref_no');  // System-generated reference number
            $table->integer('from_school_code');  // Payee school code
            $table->string('to_int_treasury_code', 5);  // Transfer Treasury code
            $table->integer('to_school_code');  // Transfer school code
            $table->integer('dml_status_flag')->default(0);  // Deletion status flag
            $table->bigInteger('user_id');  // User who created the record
            $table->timestamp('created_timestamp')->useCurrent();  // Creation
timestamp
            $table->bigInteger('modified_user_id')->nullable();  // Modified user ID
            $table->timestamp('modified_timestamp')->nullable();  // Modification
timestamp
            $table->string('salary_type', 5)->nullable();  // Salary type (e.g., iOSMS,
HRMS)
            $table->string('pf_emp_id', 50)->nullable();  // PF Employee ID
            $table->string('pf_withdrawl_type', 15)->nullable();  // PF withdrawal
type
            $table->timestamps();  // Laravel's created_at and updated_at
        });
    }

    /**
     * Reverse the migrations.
     *
     * @return void
     */
    public function down()
    {
        Schema::dropIfExists('t_td_pf_transfer_op');
    }
}
```

5. php artisan make:migration create_t_mm_gen_pl_operator_table

```
use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

class CreateTMmGenPlOperatorTable extends Migration
{
    /**
     * Run the migrations.
     *
     * @return void
     */
```

```
    public function up()
    {
        Schema::create('t_mm_gen_pl_operator', function (Blueprint $table) {
            $table->increments('id');  // Primary key
            $table->integer('int_pl_operator_id');  // System-generated operator ID
            $table->string('int_treasury_code', 5);  // Treasury code for the operator
            $table->integer('operator_id');  // Treasury operator code
            $table->string('operator_type', 1);  // Type of operator
(PL/Works/Forest)
            $table->string('govt_nongovt_flag', 1);  // Government or non-government
flag
            $table->string('operator_name', 100);  // Operator name
            $table->string('address', 200);  // Operator address
            $table->string('phone_no1', 20)->nullable();  // Primary phone number
            $table->string('phone_no2', 20)->nullable();  // Secondary phone number
            $table->string('fax', 20)->nullable();  // Fax number
            $table->string('e_mail', 50)->nullable();  // Email address
            $table->string('active_flag', 1)->default('Y');  // Active or inactive status
            $table->integer('int_ddo_id');  // System-generated DDO ID
            $table->string('admin_dept', 2)->nullable();  // Admin department of the
operator
            $table->string('pan', 20)->nullable();  // PAN number of the operator
            $table->string('internal_deposit_code', 9)->nullable();  // Internal deposit
code
            $table->timestamps();  // Laravel's created_at and updated_at
        });
    }

    /**
     * Reverse the migrations.
     *
     * @return void
     */
    public function down()
    {
        Schema::dropIfExists('t_mm_gen_pl_operator');
    }
}
```

6. php artisan make:migration create_mm_gen_treasury_table

```
use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

class CreateMmGenTreasuryTable extends Migration
{
    /**
     * Run the migrations.
```

```
     *
     * @return void
     */
    public function up()
    {
        Schema::create('mm_gen_treasury', function (Blueprint $table) {
            $table->increments('id');  // Primary key
            $table->integer('int_treasury_id');  // System-generated treasury ID
            $table->string('treasury_code', 4);  // Treasury code
            $table->string('treasury_name', 100);  // Name of the treasury
            $table->string('district_code', 2);  // System-generated district code
            $table->string('treasury_srl_number', 4);  // Treasury serial number
            $table->string('address', 200)->nullable();  // Treasury address (line 1)
            $table->string('address1', 200)->nullable();  // Treasury address (line 2)
            $table->string('address2', 200)->nullable();  // Treasury address (line 3)
            $table->string('phone_no1', 20)->nullable();  // Primary phone number
            $table->string('phone_no2', 20)->nullable();  // Secondary phone number
            $table->string('fax', 20)->nullable();  // Fax number
            $table->string('e_mail', 50)->nullable();  // Email address
            $table->string('active_flag', 1)->default('Y');  // Active/inactive status
            $table->string('int_treasury_code', 5);  // System-generated treasury code
            $table->string('treasury_status', 1)->default('A');  // Treasury status
            $table->integer('int_ddo_id');  // Treasury DDO ID
            $table->string('debt_acct_no', 15)->nullable();  // Treasury account
number
            $table->string('nps_registration_no', 10)->nullable();  // NPS registration
number
            $table->string('pension_flag', 1)->default('N');  // Pension payment flag
            $table->timestamps();  // Laravel's created_at and updated_at
        });
    }

    /**
     * Reverse the migrations.
     *
     * @return void
     */
    public function down()
    {
        Schema::dropIfExists('mm_gen_treasury');
    }
}
```