Neovim cheatsheet

leader = `Space` · localleader = `\`

`:Telescope keymaps` fuzzy-searches every mapping · herdr-nvim keys only inside herdr panes

Review an agent's change

1. `<Space>gd` diff the working tree 2. `grr` `gd` to read the code around it 3. `V` select, `<Space>hc` comment 4. `<Space>hs` paste all notes into the agent 5. `<Space>gg` stage and commit in Neogit

Basics

`jk`	leave insert mode
`Esc`	clear search highlight
`<Space>S`	save and source the file
`<Space>y` / `<Space>p` / `<Space>P`	system clipboard: yank, paste after/before
`gx`	open URL under cursor
`gX`	open every URL on the line (or selection)
`<Space>pu`	update plugins (:Lazy update)

Arrow keys are disabled in normal, insert and visual mode.

TERMINAL MODE

`Ctrl+u` / `Ctrl+d`	scroll half page
`Ctrl+b` / `Ctrl+f`	page up / down

Windows

smart-splits

`Ctrl+h/j/k/l`	move between splits, also across Ghostty splits

Comment to the agent

herdr-nvim

`<Space>hc`	comment line, or selection in visual mode
`<Space>hl`	list comments (`Enter` edit, `d` delete)
`<Space>hs`	paste all comments into the agent's input
`<Space>hS`	send all comments and submit
`<Space>hi`	insert a `path:line` reference at the agent

Also `:Herdr comment|list|send|submit|ref`, with ranges like `:5,10Herdr comment`. Loaded only inside herdr panes.

Find

telescope

`<Space>sf`	files
`<Space>s.`	recent files (this project)
`<Space>sg`	live grep (with rg args)
`<Space>sw`	grep word under cursor / selection
`<Space>sr`	resume last search
`<Space>sh`	help tags
`<Space><Space>`	open buffers

IN A PICKER

`Ctrl+n` / `Ctrl+p`	next / previous result
`Ctrl+x` / `Ctrl+v` / `Ctrl+t`	open in split / vsplit / tab
`Ctrl+q`	send results to quickfix
`Esc`	normal mode (`j` `k`, `Esc` again closes)

Jump

flash

`s`	flash: jump to any visible spot
`S`	flash: select a treesitter node
`r`	remote: act elsewhere, e.g. `yr`
`R`	treesitter search (operator/visual)
`Ctrl+s`	in `/` search: toggle flash labels

Undo history

atone

`<Space>a`	toggle the undo tree
`j` / `k`	older / newer state
`Enter`	undo to this state
`q`	close
`?`	help

Code (LSP)

lua go ruby ts zig odin

`gd` / `gD`	definition / declaration
`K`	hover
`grr`	references
`gri`	implementation
`grt`	type definition
`grn`	rename
`gra`	code action
`gO`	document symbols
`Ctrl+s`	signature help (insert mode)
`<Space>uh`	toggle inlay hints
`<Space>f`	format buffer (also on save)

COMPLETION (POPS UP WHILE TYPING)

`Ctrl+n` / `Ctrl+p`	next / previous item
`Ctrl+y`	accept
`Ctrl+e`	dismiss
`Ctrl+x` `Ctrl+o`	ask for completion

DIAGNOSTICS

`]d` / `[d`	next / previous
`Ctrl+w` `d`	show diagnostic at cursor
`<Space>q`	all diagnostics to location list

Project trust

`:Trust [dir]` — allow LSP servers and formatters here

`:Untrust [dir]` — revoke

`:TrustList` — list trusted projects

Untrusted projects get no LSP and no format-on-save, because both can run project code.

Git

`<Space>gg`	Neogit status
`<Space>gd`	Diffview: working tree vs HEAD
`<Space>gh`	Diffview: history of this file

IN NEOGIT

`s` / `u`	stage / unstage
`c` `c`	commit
`P` / `p`	push / pull
`Tab`	expand / collapse
`?`	all keys

IN DIFFVIEW

`Tab` / `Shift+Tab`	next / previous file
`-`	stage / unstage file
`q`	close Diffview
`g?`	all keys

Gitsigns shows blame at line end; hunks via `:Gitsigns preview_hunk`, `stage_hunk`, `reset_hunk`, `next_hunk`.

Files

neo-tree

`\`	neo-tree: reveal current file / close

IN THE TREE

`a`	add (end with / for a folder)
`d` / `r`	delete / rename
`m` / `c`	move / copy
`H`	toggle hidden files
`/`	filter
`?`	all keys