

litis



KNOWLEDGE GRAPH-BASED SYSTEM FOR TECHNICAL DOCUMENT RETRIEVAL

A DEDUCTIVE REASONING-FOCUSED EXPLORATION

PhD student: Matthias SESBOÜÉ
PhD directed by Cecilia ZANNI-MERK
and supervised by Nicolas DELESTRE and Jean-Philippe
KOTOWICZ

September 5, 2024

RESPONDING THESIS

Knowledge Graph-based System for Technical Document Retrieval

A deductive reasoning-focused exploration

- Research objective: Leveraging domain knowledge to enhance Information Retrieval in a technical context.
- CIFRE contract (financed by ANRT) between the Litis lab and the company Traceparts
- Began on March 15th 2021.

From a keyword-based search to a concept-based one.

TRACEPARTS


One of the world's leading CAD-content platforms for Engineering, Industrial Equipment and Machine Design. The CAD-content platform traceparts.com provides access to over 1.8 thousand supplier-certified product catalogues with 2D drawings, 3D CAD models and product datasheets.

- Technical content aimed at an engineering audience from multiple industries
- Content available in 25 languages
- Users can search using :
 - A full text search
 - A list of catalogues
 - Different classifications



Product Content **Everywhere**™

TABLE OF CONTENT

- 1 RELATED WORKS
 - 2 KNOWLEDGE GRAPH-BASED SYSTEM (KGBS)
 - 3 APPLICATION CONTEXT
 - 4 KG-BASED INFORMATION RETRIEVAL
 - 5 EXPERIMENTS
 - 6 CONCLUSION AND FUTURE WORKS
- 

INFORMATION RETRIEVAL




FIGURE: Information Retrieval System overview

Traditional approaches leverage statistics about the text corpus.
Recent methods implement deep learning models and combines multiple approaches.

BM25

BM25 (and its many variants) is:

- based on the Term Frequencies and Inverse Document Frequencies (TF-IDF)
- still widely used in practice
- computes many statistics offline

Traceparts search system is largely based on a BM25 implementation.

KNOWLEDGE GRAPH AND ONTOLOGY

Knowledge Graph (Hogan et. al. 2021): *a knowledge graph is a graph of data intended to accumulate and convey knowledge of the real world, whose nodes represent entities of interest and whose edges represent relations between these entities.*

Ontology (Hogan et. al. 2021): *In the context of computing, an ontology is then a concrete, formal representation of what terms mean within the scope in which they are used (e.g., a given domain).*

In our work, we consider an ontology a particular component of
a Knowledge Graph

KNOWLEDGE ACQUISITION




FIGURE: KGBS: Knowledge acquisition

KNOWLEDGE MODELING




FIGURE: KGBS: Knowledge modeling

KNOWLEDGE GRAPH




FIGURE: KGBS: Knowledge Graph

KNOWLEDGE CONSUMPTION




FIGURE: KGBS: knowledge consumption

KNOWLEDGE GRAPH-BASED SYSTEM ARCHITECTURE




FIGURE: KGBS architecture

ONTOLOGY LEARNING APPLIED FRAMEWORK (OLAF)




FIGURE: KGBS architecture: OLAF

INFORMATION RETRIEVAL ONTOLOGY




FIGURE: KGBS architecture: IR ontology

INDUSTRIAL EXPERIMENTS




FIGURE: KGBS architecture: Industrial experiments

IN THIS PRESENTATION




FIGURE: This presentation KGBS architecture components focus

CORPUS

- Over 1.1 million document families
- Over 127.8 millions individual documents
- 25 languages
- Documents' texts contain average 50 characters and 7 words
- Over 210 thousand tags, amongst which:
 - Over 2.5 thousand suppliers and manufacturers
 - Over 1.9 thousand catalogues
 - Over 208 thousand categories

Some text content examples are:

- *DIN 912*
- *The P01 to P08 pumps are designed to pump lubricating fluids (oil, diesel oil, etc.). Their flow rate is from 1 to 24 L / min; maximum working pressure 10 bar.*

USER SEARCHES

User text searches:

- are composed of domain-specific keywords, notations, identifiers, and acronyms.
- contain on average 13 characters separated into 2 words.
- can come in any languages

Some common search examples are:

motor, din 912, and ball valve.

TRACEPARTS SEARCH SYSTEM CHALLENGES

Traceparts search challenges come from:

- Short multilingual texts
- Technical texts with many synonyms, acronyms, homonyms, and notations
- A large and heterogeneous corpus
- Multiple engineering domains coverage
- High recall but low precision

EXPERIMENTS OBJECTIVE




FIGURE: Text-based vs concept-based search.

EVALUATION METRICS

- Mean Average Precision at k (MAP@k):
 - A sliding (or growing) precision window, averaged over a set of query examples.
 - Ranges from 0 to 1 (1 is the best value).
 - Gives information about the amount and positions of positive results in the k first ones.
- Binary Mean at k (BM@k):
 - Binary average over a set of query examples.
 - Ranges from 0 to 1 (1 is the best value).
 - Provides information about the amount of queries with a positive result in the k first ones.
 - Does not give any detail on the positive result position.

EXPERIMENTS PROTOCOL




FIGURE: Experiments Protocol.

EXPERIMENTS


6 distinct systems built iteratively:

- *Text-based system (baseline)*
- Concept-based system
- **Knowledge Graph-based system with implicit knowledge**

Systems implementations:

- User search concept matching problem as an information retrieval task.
- Leverage user search history as implicit knowledge.
- Query concept enrichment as a graph traversal task.

TEXT-BASED SYSTEM (BASELINE)




TEXT-BASED SYSTEM (BASELINE) RESULTS

@k ↓	Text-based system (baseline)	
	MAP@k	BM@k
@5	0.061	0.114
@25	0.064	0.148
@50	0.064	0.157
@100	0.064	0.161
@350	0.064	0.164

TABLE: Text-based system (baseline) results for different k values.

CONCEPT-BASED SYSTEM




CONCEPT-BASED SYSTEM RESULTS

	Text-based system (baseline)		Concept-based system	
@k ↓	MAP@k	BM@k	MAP@k	BM@k
@5	0.061	0.114	0.152	0.243
@25	0.064	0.148	0.159	0.334
@50	0.064	0.157	0.160	0.371
@100	0.064	0.161	0.161	0.403
@350	0.064	0.164	0.161	0.429

TABLE: Text and concept-based systems results for different k values.

KNOWLEDGE GRAPH-BASED SYSTEM WITH IMPLICIT KNOWLEDGE



KNOWLEDGE GRAPH-BASED SYSTEM WITH IMPLICIT KNOWLEDGE RESULTS

	Text-based system (baseline)		Concept-based system		KG-based system with search history	
@k ↓	MAP@k	BM@k	MAP@k	BM@k	MAP@k	BM@k
@5	0.061	0.114	0.152	0.243	0.115	0.291
@25	0.064	0.148	0.159	0.334	0.122	0.471
@50	0.064	0.157	0.160	0.371	0.123	0.552
@100	0.064	0.161	0.161	0.403	0.123	0.624
@350	0.064	0.164	0.161	0.429	0.124	0.715

TABLE: Text, concept, and KG-based systems results for different k values.

QUANTITATIVE RESULTS

	No results	Less than 400 results (non empty)
Text-based system (baseline)	64.48%	35.44%
Concept-based system	11.43%	88.36%
KG-based system with search history	8.10%	51.59%

TABLE: Comparing all search systems results set corpus.

CONCLUSION

We have:

- Explored a Knowledge Graph-Based System (KGBS) architecture
- Detailed each KGBS containers and activities
- Explored a real-world use case moving from a text-based to a KG-based Information Retrieval (IR) System.
- Introduce and compared 3 IR systems:
 - A text-based IR system
 - A concept-based IR system
 - A KG-based IR system

KG-based systems for IR on a multi corpus of technical documents show promising results overcoming the text-based approaches limitations.

FUTURE WORKS

- KGBS architecture:
 - Implement an end-to-end Knowledge Graph-Based System architecture use case.
 - Further explore the modularity of the architecture
 -
- Knowledge Graph-based Information Retrieval system:
 - Expand the Knowledge Graph
 - Enhance the concept matching task
 - Expand the approach to other domains

PERSPECTIVES: KNOWLEDGE GRAPH




FIGURE: Extended semantic search example.

CONTRIBUTIONS

A top-down approach from a system perspective down to solution implementations.

Contributions:

- A unifying definition of Knowledge Graph
- An architecture for Knowledge Graph-Based Systems
- A framework for Ontology Learning
- An OWL Information Retrieval ontology
- A study of a text-based compared to a Knowledge Graph-based Information Retrieval system

SCIENTIFIC PRODUCTIONS

Peer-reviewed international conference papers:

- An operational architecture for knowledge graph-based systems. Proceedings of the 26th International Conference KES2022.
- (with Marion Schaeffer) Olaf: An ontology learning applied framework. Proceedings of the 27th International Conference KES2023.

Open-source software library (with Marion Schaeffer):

- Ontology Learning Applied Framework Python library implementation:
<https://wikit-ai.github.io/olaf/>

THANK YOU!

Thank you for your time and attention.

I am now ready to answer to any questions.