

1. Create a repo server through http/ftp.

Repo server : A **repo server** (short for **repository server**) is a centralized storage location—essentially a digital warehouse—where software packages, source code, or files are stored, managed, and distributed.

There are two types:

1. Linux package repositories (System admin context)

- Sudo dnf install httpd: Here (dnf) is a package manager from where we are downloading the file.

2. Git/Source code repositories:

- A repo server holds the code for the project and tracks every change made and keeps the history in order to avoid confusions and losing of important data.

Here we are downloading the files in a repo or directory to make it available offline and anyone can download it using the IP address

1. # Install createrepo to generate repo metadata

- sudo dnf install createrepo_c -y

Create a directory to hold your packages

- sudo mkdir -p /var/repo/packages

Here we are creating another folder of downloads folder and installing the package

- sudo dnf download --downloadonly --destdir=. nano

Copy or sync RPMs into it

- sudo cp /path/to/*.rpm (above folder path) /var/repo/packages/

Generate the repo metadata

- sudo createrepo /var/repo/packages/

2. HTTP Repository (Apache)

- sudo dnf install httpd -y
- sudo systemctl enable --now httpd
- sudo firewall-cmd --permanent --add-service=http
- sudo firewall-cmd --reload

Configure the symlink

- `sudo nano /etc/httpd/conf.d/localrepo.conf`

and paste this

Alias /repo /var/repo/packages

<Directory /var/repo/packages>

Options Indexes FollowSymLinks

AllowOverride None

Require all granted

</Directory>

#Then we restart the apache

- `sudo systemctl restart httpd`

Quick Checklist — Run All These on Server

bash# 1. Is Apache running?

- `systemctl status httpd`

2. Does the repo folder exist?

- `ls /var/repo/packages`

3. Does the symlink exist?

- `ls -la /var/www/html/`

4. Restart Apache after any fix

- `sudo systemctl restart httpd`

#Type the ip address of the vm along with the file location in your browser make sure that the system is connected to the same LAN.

`http://192.168.50.166/repo/repo/`

2. Make a DNS server and understand the components & changes.