

# Efficient ML Algorithms: From Theory to Practice

---

Shaocong Ma

October 9, 2025

University of Maryland, College Park

- *Revisiting Zeroth-Order Optimization: Minimum-Variance Two-Point Estimators and Directionally Aligned Perturbations* (ICLR 2025 Spotlight)

**Shaocong Ma**, Heng Huang.

- We developed the DAP, a zeroth-order optimization method specifically designed to overcome key bottlenecks in large language model training and AI4Science tasks.
- Future Research
    - Efficient Inference-Time Training of Large Language Models
    - Fine-Tuning the LLM Agent using Zeroth-Order Optimization
    - Addressing the Theoretical Limit of Multi-Level Optimization

## ■ Zeroth-order optimization

- Training LLMs: Saving GPU memory
- Training Physics Models: Non-differentiable module

## ■ However, existing gradient estimator fails to focus on the “important directions” .

- Existing literature indicates that some neurons in LLMs are more important.
- Our work<sup>1</sup> indicates that the mesh optimization has “important nodes”.

---

<sup>1</sup>Shaocong Ma, James Diffenderfer, Bhavya Kailkhura, and Yi Zhou. “Deep learning of PDE correction and mesh adaption without automatic differentiation.” Machine Learning 114.3 (2025): 1-25.

# DAPs: Directionally Aligned Perturbation

Free Lunch! Identifying the important direction just requires to slightly modify the random perturbation in traditional two-point estimator:

$$\hat{\nabla} f(x) = \frac{f(x + \mu v) - f(x)}{\mu} v$$

Here,  $\mu$  is a small perturbation size.  $v$  is a random vector.


## ■ Traditional Method:

- $\mathbb{E}[vv^T] = I$  (Unbiasedness)
- $\|v\|$  is fixed (Minimum Variance).

## ■ DAP:


- $\mathbb{E}[vv^T] = I$  (Unbiasedness)
- $\nabla f(x)^T v$  is fixed (Minimum Variance).

# Traditional Methods Cannot Identify the Important Directions





**Figure 1:** Illustration of the *directional alignment property* of DAP in  $d = 2$  with estimating the gradient of  $f(x) = x_1^2 + x_2^2$  at  $x = \begin{bmatrix} 0.1 & 1 \end{bmatrix}^\top$ . Traditional zeroth-order estimator is **symmetric**, but we really need a **non-symmetric** estimator.

# Traditional Methods Cannot Identify the Important Directions



**Figure 2:** Comparison of gradient estimation performance with estimating the gradient of  $f(x) = x_1^2 + x_2^2$  at  $x = \begin{bmatrix} 0.1 & 1 \end{bmatrix}^\top$  between uniform random perturbations and DAPs. The **non-symmetric** estimator is more accurate in the direction with larger gradient.

# Practical Experiments



**Figure 3:** Comparison of training loss curves among different random perturbations on **Large Language Model Fine Tuning** and **Mesh Optimization for the Physical Numerical Solver**.

# Future Research



# Efficient Inference-Time Training of Large Language Models

- The generation process of LLMs is a Markov decision process.

Policy:

$$p_{\theta}(\text{Next Token} \mid \text{Previous Token})$$

Transition:

$$\mathbb{P}(s' = \text{Next Token} \mid s = \text{Previous Token}, a = \text{Next Token}) = 1$$

- Maximize the Reward Given by the Process Reward Model:

$$\theta \leftarrow \theta + \eta \times \text{Reward} \times \nabla_{\theta} \log p_{\theta}$$

- Efficient Algorithms (Connections to Previous Research):

- (NIPS 2020) Variance-reduced off-policy TDC learning:  
Non-asymptotic convergence analysis  
**Shaocong Ma**, Yi Zhou, Shaofeng Zou.
- (ICLR 2021) Greedy-GQ with Variance Reduction: Finite-time Analysis and Improved Complexity  
**Shaocong Ma**, Ziyi Chen, Yi Zhou, Shaofeng Zou.

# Fine-Tuning the LLM Agent using Zeroth-Order Optimization

- A LLM agent contains many non-differentiable modules
  - Black-Box LLM parameters (temperature, LoRA weights, ...)
  - Prompts
  - RAG, Search, Tool Use, ...
- Efficient fine-tuning requires advanced techniques:
  - (Submitted) Hybrid Fine-Tuning of LLMs: Theoretical Insights on Generalized Smoothness and Convergence  
**Shaocong Ma**, Peiran Yu, Heng Huang.
  - (ICLR 2025 Spotlight) Revisiting Zeroth-Order Optimization: Minimum-Variance Two-Point Estimators and Directionally Aligned Perturbations  
**Shaocong Ma**, Heng Huang.

# Addressing the Theoretical Limit of Multi-Level Optimization

- Min-Max Optimization:

$$\min_{\theta} \max_{\omega} f(\theta, \omega)$$

The solution  $(\theta^*, \omega^*)$  is a Nash equilibrium of the min-max game.

- Multi-Level Optimization:

$$\min_{\theta} f(\theta, \omega_1, \omega_2, \dots, \omega_N)$$

$$\text{s.t. } \omega_1 \in \arg \min g_1(\theta, \omega_1, \omega_2, \dots, \omega_N)$$

$$\omega_2 \in \arg \min g_2(\theta, \omega_1, \omega_2, \dots, \omega_N)$$

$$\vdots$$

- The solution belongs to Correlated Equilibria:

- (JMLR 2023) Decentralized Robust V-Learning for Solving Markov Games with Model Uncertainty  
**Shaocong Ma**, Ziyi Chen, Shaofeng Zou, Yi Zhou.
- (NIPS 2022) Finding Correlated Equilibrium of Constrained Markov Game: A Primal-Dual Approach  
Ziyi Chen, **Shaocong Ma**, Yi Zhou.