

Tuya device smart_breaker



Model:

Tuya:

Tuya Mod:

Any GET sends all data (like SCHEMA), SET:null works OK, so all dp 'WW'

Power supply: **AC**
Broadcast: **WiFi**
Capabilities: **ALL**

Reference:

Infos:

Sellers: <https://www.aliexpress.com/item/1005001863612580.html>

Known Data Points:

| | | | | | |
|----|----------------------------------------------------------|----|---------|-----------------------|--------------|
| 1 | relay | WW | boolean | true false = ON OFF | BOOLEANONOFF |
| | | | | | |
| 9 | countdown | WW | int | 0..86500 s (24H max.) | |
| | | | | | |
| 38 | restart status | WW | string | off on memory | |
| | | | | | |
| 40 | light mode | WW | string | pos none relay | |
| | no HW: can be used as trigger | | | | |
| 41 | child lock | WW | boolean | true false = ON OFF | BOOLEANONOFF |
| | | | | | |
| 42 | unknow1 | WW | | | |
| | on SCHEMA response, null string | | | | |
| 43 | unknow2 | WW | | | |
| | on SCHEMA response, null string | | | | |
| 44 | inching | WW | string | AQAC AAAC = ON OFF ? | |
| | The inching (temporary) counter is SW, in the tuyu-cloud | | | | |