tuyaDAEMON device Auriol_IAN_114435

Model: H13716b, H13716c

Tuya: `custom` Mod: `433 MHz devices`

Two ensambles:H13726b (temperature, humidity + wind); H13726c (rain)

RTL_433 protocol is #16: AlectoV1-Temperature, AlectoV1-Wind, AlectoV1-Rain.
433 MHz gateway decodes three data packets: random ID every batteries change

Power supply: **BAT**
Broadcast: **other**
Capabilities: **NONE**

Reference:
Infos: *https://www.manua.ls/auriol/ian-114435/manual*
Sellers: *https://fandilidl.it/volantino/2019.01.21.caldo.inverno/17080,Stazione-meteorologica*

User defined Data Points:

_battery_low		PUSH		WIND|RAIN|TEMPERATURE	
	WIND never sent: only TX off.				
_day		PUSH			
	The meteorological day-of-year. The rollover time is user defined (default 09:00:00)				
_dew_point		PUSH		°C	
	calculated by device driver				
_heat_index		PUSH		°C	
	calculated by device driver				
_humidity		PUSH		%	
	from probe H13726B				
_rain_day_mm		PUSH			
	calculated by device driver reset every day at rollower time				
_rain_tot_mm		PUSH			
	from probe H13726C, every 40s cumulate, reset changing batteries				
_temperature		PUSH			
	from probe H13726B, every 3 min.				
_wind_avg_m_s		PUSH			
	from probe H13726B every 50-120 s. last 2 min avg				
_wind_chill		PUSH		°C	
	calculated by device driver				
_wind_day max_m_s		PUSH			
	calculated by device driver reset every day at rollower time				
_wind_dir_		PUSH			

deg	*from probe H13726B, every 40 s. Battery replacement requires calibration: see wiki*				
_wind_max_m_s		PUSH			
	from probe H13726B max in last 10 min				