

Tuya device switch-4CH



Model:

Tuya: switch

Tuya Mod: waq2wj9pjadcglqc

4CH Tuya Switch WiFi Switch Module

Any GET sends all data (like SCHEMA), SET:null works OK, so all dp 'WW'

To SET countdown to 0, toggles relay

Power supply: **USB**

Broadcast: **WiFi**

Capabilities: **ALL**

Reference:

Infos:

Sellers: <https://www.aliexpress.com/item/4001268704361.html>

Known Data Points:

1	relay1	WW	boolean	true false = ON OFF	BOOLEANONOFF
2	relay2	WW	boolean	true false = ON OFF	BOOLEANONOFF
3	relay3	WW	boolean	true false = ON OFF	BOOLEANONOFF
4	relay4	WW	boolean	true false = ON OFF	BOOLEANONOFF
7	countdown1	WW	int	0..86500 s (24H max.)	
	Countdown >= 0: PUSHed every sec. Count to 0, or SET 0: relay toggles.				
8	countdown2	WW	int	0..86500 s (24H max.)	
	Countdown >= 0: PUSHed every sec. Count to 0, or SET 0: relay toggles.				
9	countdown3	WW	int	0..86500 s (24H max.)	
	Countdown >= 0: PUSHed every sec. Count to 0, or SET 0: relay toggles.				
10	countdown4	WW	int	0..86500 s (24H max.)	
	Countdown >= 0: PUSHed every sec. Count to 0, or SET 0: relay toggles.				
13	switch all	WW	boolean	true false = ON OFF	BOOLEANONOFF
101	power-on status	WW	boolean	true false = ON OFF	BOOLEANONOFF
102	mode	WW	string	'selflock' 'inching' 'interlock'	
	'inching' = momentary: time is 'dp' 103				
103	momentary time	WW	int	0...600 = 0...60.0 s	BYTESMALLFLOAT

--	--