StudySearch Website API v2 — Developer Guide

website-api-v2 · Version 2 · Issue 8 · the day it is released, announced in the cover note · Pilot

Issue 8. Issue 8 adds `campus_id`, `campus_name` and `course_count` to provider `campuses[]`, and `nationality_eligibility_status` to scholarships. The API returns them from the release day, which is announced in the cover note; until then build against Issue 7. Everything else in this guide is live today.

For	The developers of the StudySearch website (Wix): Course Finder, University Finder and Scholarship Finder
API	One HTTPS address for Website API v2, nine actions
Environment	Pilot (live). Production uses the same endpoint address with a separate key, issued at go-live
Your key	Sent to you separately by a secure channel. It is never written in this guide or the files that come with it
Files with this guide	`StudySearch-Website-API-v2.openapi.json` (OpenAPI 3.1) and `StudySearch-Website-API-v2.postman_collection.json` (Postman; set the variable `apiKey`); `examples/` (before and after examples); the Issue 8 handover note

1. What the API gives you

The API is the only way the website reads StudySearch data. It returns courses, universities and colleges (providers), scholarships, rankings, logos and the vocabularies for your filters, for Australia, New Zealand and Canada.

Four rules apply to every response:

1. **Null means not held.** A value the platform does not hold is `null` or an empty list. Nothing is filled with a default, an estimate or a value from another record.
2. **Only published data is returned.** A provider the platform has switched off is not returned, with its courses and scholarships. Every record you receive reads `publication_status: "published"`.
3. **Additive only.** Fields, filters and actions are added, never renamed or removed, within v2. Ignore fields you do not use. A breaking change would come as `website-api-v3` at a new address, with its own guide, and v2 would keep running alongside it.
4. **Third-party material carries attribution.** Rankings and logos come with `attribution` and `terms_status`. Both are approved for display (`terms_status: "approved"`). Show the attribution with them. If `terms_status` ever reads `management_decision_pending`, stop displaying that item.

2. Quick start

1. Store the key in Wix Secrets Manager. Call the API from Wix backend code only, never from the browser.
2. Call `reference` and keep the vocabularies (section 7.1).
3. Run a full load with `sync` (section 6) into your Wix collections (section 9). Store `next_cursor` after each page.
4. Schedule a delta: every hour, send the stored cursor to `sync` and apply what comes back.
5. For Course Finder search, call `search` live from your backend with a 15-minute response cache (section 5).
6. Run the acceptance tests in section 12 and send us any failure with its `request_id`.

3. Endpoint and key

```
POST https://fxcwkweaxjtknorudmwp.supabase.co/functions/v1/website-api-v2
Content-Type: application/json
Authorization: Bearer <your key>
```

- Every request body includes an `action`. There is no `contract` field: the address is the version.
- Keep the key in backend-only configuration. Never put it in browser code, page source, CMS records, repositories, screenshots, tickets or ordinary logs.
- Each key has its own limit: **300 requests a minute, all actions together**. Over the limit you get HTTP 429 with a `Retry-After` header.
- Your key works with this address only. If a key is exposed, tell us: we disable it and issue a new one (a key cannot be recovered, only replaced).

Moving from the earlier address. Until now the API was reached at `wix-course-api` with `"contract": "website-search-v2"` in every body. That address and its key keep working, unchanged, until you have moved; we will agree the switch-off date with you. The answers are the same at both addresses. To move: store the new key, change the address, drop the `contract` field, and read `api_version` instead of `contract_version`. Your stored sync cursor works at the new address, so no new full load is needed.

4. Requests and responses

Request

```
{
  "action": "search",
  "filters": { "country_codes": ["AU"] },
  "page": 1,
  "page_size": 20,
  "sort": "relevance"
}
```

- page starts at 1. For the list actions `page_size` is 1–50 (default 20); `sync` pages are covered in section 6.
- Send `Accept-Encoding: gzip` (most HTTP clients do this by default). Replies are then compressed to about a ninth of their size.
- Every response carries `api_version: "website-v2"` and a `request_id`. Quote the `request_id` when you report a problem.
- An error reply is `{ api_version, error: { code, message, detail }, request_id }`; `detail` says what was wrong where it can.
- List actions return `{ total, page, page_size, items, filters_not_applied }`. A filter key the API does not recognise is listed in `filters_not_applied`; it is never silently ignored.
- Detail actions return `{ item }`.

Errors

HTTP	Code	Meaning
400	`INVALID_INPUT`	A malformed filter, page, page size, sort, cursor or missing identifier
400	`INVALID_JSON`	The body is not a JSON object
400	`INVALID_ACTION`	The action is not one of the nine
401	`AUTHENTICATION_REQUIRED`	Missing or invalid key
404	`NOT_FOUND`	The course, provider or scholarship identifier was not found
429	`RATE_LIMITED`	Over 300 a minute for your key; wait for `Retry-After`
503	`SERVICE_UNAVAILABLE`	A bounded service failure; retry later

On 429 or 5xx keep serving your last good copy and retry on the next run.

5. Recommended integration

Tool	How	Why
University Finder, Scholarship Finder	Wix collections filled by `sync`	Fast pages with no API call during a visit
Course Finder	`search` called live from your backend, each response cached 15 minutes; course cards and detail from your `sync` copy	Search uses the platform's relevance and filters; the cache absorbs repeat searches
Filter lists	`reference`, refreshed daily	Vocabularies with counts

Schedule

Job	When
Full load with `sync`	Once at set-up, and again only if your copy is lost
Delta with `sync`	Hourly
`reference`	Daily

When a call or run fails

1. Keep the last good copy in service.
2. Record the error, its `request_id` and the time.
3. Do not save a new cursor.
4. Retry on the next run.

Measured on Pilot (database time): filtered search 0.1–0.6 s; a search sorted by tuition across a whole country about 2 s (add another filter or cache it); course detail under 0.1 s; `reference` under 0.1 s (it is rebuilt every 15 minutes); a `sync` page about 0.5–1 s. Add 0.1–0.3 s for the network.

6. Sync: full load, then only what changed

`sync` keeps your Wix collections current with the fewest calls.

```
{
  "action": "sync",
  "cursor": "<next_cursor from your last reply; leave out for a full load>",
  "page_size": 600
}
```

How it works

1. **Full load.** Call `sync` with no cursor. You get every item the API returns, in pages. Keep calling with `next_cursor` while `has_more` is true. The last page has `full_load_complete: true`.
2. **Changes.** From then on, send the stored cursor. You get only what is new, changed or removed since, and a new `next_cursor`.
3. **Save the cursor only after the page is written to Wix.** If a write fails, send the same cursor again: the same items come back, and upserting by id makes the replay safe.

Request fields

Field	Meaning
`cursor`	The `next_cursor` from your last reply. Leave it out (or `null`) for a full load
`full_load`	`true` starts a full load again

Field	Meaning
`entities`	Optional, on a full load only: any of `reference`, `provider`, `logo`, `rankings`, `scholarship`, `course` (all six by default). A cursor keeps the entities it started with
`page_size`	1–600 (default 600). A page holds at most about 1.7 MB of JSON (about 0.15 MB compressed), so large items (provider details, scholarships) come fewer to a page

Reply fields

Field	Meaning
`items[]`	`{ entity, id, seq, change, item }`. `change` is `upsert` (store `item` by `id`) or `remove` (delete the record with that `id`; no `item`)
`has_more`	More items follow: call again with `next_cursor`
`next_cursor`	Opaque text. Store it as it is
`mode`	`full` or `delta`
`full_load_complete`	`true` on the last page of a full load
`checked_through`	When the platform last finished checking every item for changes (`null` until the first check after a full load has finished)
`as_of`	Time of the reply

Item shapes

Entity	`id`	`item`	Your collection
`course`	course_id	The search item (7.2)	CF_Courses
`provider`	provider_id	The provider detail (7.4)	CF_Providers
`logo`	provider_id	`{ provider_id, logo }` (7.7)	Logo on CF_Providers, file in Wix Media
`rankings`	provider_id	`{ provider_id, rankings[] }` (7.6)	CF_Rankings
`scholarship`	scholarship_id	The scholarship detail (7.5)	CF_Scholarships
`reference`	`reference`	The reference vocabularies (7.1)	CF_Reference

Good to know

- A page may hold fewer than `page_size` items when they are large. Keep going while `has_more` is true.
- The platform checks every item for changes every minute in a rolling pass; a full pass takes about 90 minutes. A change appears in a later delta.
- A removal comes as `change: "remove"`: for example a provider switched off (with its courses, logo and rankings) or a scholarship no longer published.
- **Logos:** each logo link is valid for 365 days (`url_expires_at`). Copy the file into Wix Media and serve your copy; never link to the signed URL from a visitor page. The platform sends a logo again with a new link 30 days before the old one ends, and whenever the file changes (`content_hash`).

6.1 Full load: what to expect

Items and data measured on Pilot on 9 November 2026; calls and times are from 17 October 2026 (the load is about 9% smaller now, so expect a little less).

Measure	Full load
Items	About 38,300 (courses 34,041; providers 1,620; scholarships 1,144; logos 1,465; ranking sets 56; reference 1)
Calls	About 86 at the default page size (600)
Data	About 108 MB of JSON in total, about 14 MB compressed with `Accept-Encoding: gzip` (the compressed figure is estimated from the 17 October ratio); the largest page about 1.7 MB (the first page 150 KB compressed)
Reply time	Under a second a page; the platform builds a page in under 0.3 seconds
Elapsed time	About 1 to 2 minutes (one page at a time)
After the full load	A delta is usually one call; the platform checks every item for changes within about 90 minutes, and a change appears in the next delta after that

6.2 What we expect from your sync job

1. **Run it as a scheduled backend job that can resume.** Save `next_cursor` after each page is written. If the job stops (for example at a Wix time limit), the next run carries on from the saved cursor.
2. **One cursor at a time.** Each call needs the previous reply's cursor; do not start a second full load while one is running.
3. **Stay within 300 calls a minute.** On 429, wait for `Retry-After` and send the same cursor again.
4. **Write each page in one bulk save,** upserting by `id`; delete by `id` on `remove`.
5. **After the full load, run a delta every 5 to 15 minutes.** Run a full load again only to rebuild your collections.
6. **Copy each new or renewed logo into Wix Media** in the run that receives it.

7. Actions and data

Action	Parameters	Returns
`reference`	none	Vocabularies with counts (7.1)
`search`	`filters`, `page`, `page_size`, `sort`	Course list (7.2)
`course`	`course_id` or `course_code`	`{ item }` course detail (7.3)
`providers`	`filters`, `page`, `page_size`, `sort`	Provider list (7.4)
`provider`	`provider_id`	`{ item }` provider detail with rankings and statistics (7.4)
`rankings`	`filters`, `page`, `page_size`	Ranking entries (7.6)
`scholarships`	`filters`, `page`, `page_size`	Scholarship list (7.5)
`scholarship`	`scholarship_id`	`{ item }` scholarship detail with linked courses (7.5)
`sync`	`cursor`, `full_load`, `entities`, `page_size`	Pages of items to store (section 6)

7.1 reference

```
{ "action": "reference" }
```

Per country (AU, NZ, CA): study levels, study areas, subdivisions (states, provinces, regions), cities with metro areas, intake months and English tests, each with course counts. Also: regional categories, institution types with provider counts, university groups, ranking systems with editions, scholarship amount types, study stages and student types, and the sort values for courses and providers. `generated_at` says when the counts were built (every 15 minutes).

7.2 search (Course Finder)

```
{
  "action": "search",
  "filters": {
    "country_codes": ["AU"],
    "keyword": "business",
    "cities": ["Melbourne"],
    "study_level_codes": ["masters_coursework"],
    "intake_months": [2],
    "english_test_codes": ["IELTS"],
    "english_score_max": 6.5,
    "tuition_annual_max": 45000
  },
  "page": 1,
  "page_size": 6
}
```

This returned 35 courses on 29 October 2026. All filters are optional and combine with AND.

Filter	Type	Notes
keyword	text	Title, provider name or course code
country_codes	list	AU, NZ, CA
study_level_codes	list	From reference, e.g. bachelor, masters_coursework
study_area_codes	list	ASCED narrow fields from reference, e.g. asced-0603 (Nursing)
subdivision_codes	list	e.g. AU-VIC, NZ-AUK, CA-ON
cities, postcodes	list	A campus city or metro area, any letter case
regional_categories	list of numbers	Australian Home Affairs category 1, 2 or 3
provider_ids, university_groups	list	Groups: go8, atn, iru, run
institution_types	list	From reference: university, university_college, higher_education_institute, tafe_polytechnic, private_vet, school, wananga, other
delivery_modes	list	on_campus, online, blended, on_campus_and_online
intake_months	list of numbers	1–12
english_test_codes + english_score_max	list + number	Courses whose minimum overall score for that test is at or below the score, on that test's own scale. Give exactly one test code with a score. Test codes: IELTS, PTE, TOEFL_IBT, CAE, DET (Duolingo English Test, 10–160); reference lists the codes held for each country with course counts
tuition_annual_min, tuition_annual_max	number	Annual tuition in the course's own currency; use with country_codes
has_intake, has_english, has_official_url, has_tuition, has_scholarship	true/false	Only courses holding that value

Filter	Type	Notes
`changed_since`	timestamp	Courses changed since then (`sync` is the simpler way to keep a copy)

Sort: `relevance` (default with a keyword), `title_asc` (default otherwise), `tuition_annual_asc`, `tuition_annual_desc`, `duration_asc`, `updated_asc`. Ties are broken by course_id, so paging is stable. Courses with no tuition held sort last under the tuition sorts.

Course fields (search items and `sync` course items)

Field	Notes
`course_id`, `title`	`course_id` is the key to store
`display_code`, `display_code_kind`, `display_code_label`	**The code to show visitors**: the printed code (kind own, for example a CRICOS course code) or a StudySearch code such as `UBC-MA-014` (kind `studysearch`). It never changes
`course_code`	The source system's code. Do not show it; show `display_code`
`provider { provider_id, name, legal_name, institution_type, university_groups[], ranking_summary, logo }`	As in 7.4
`campuses[] { city, postcode, subdivision_code, metro_area, regional_category, regional_category_name, is_primary }`, `campus_city`, `campus_metro_area`	The searched city first. Postcode, metro area and regional category are held for Australia; New Zealand and Canadian campuses mostly have a city and region only
`study_level { code, name }`, `study_area { code, name }`	
`duration_months`, `delivery_modes[]`	From the register or the course page. A duration given in semesters is not converted: `duration_months` is null
`tuition { amount, currency, basis, basis_label, annual_amount, annual_is_derived, year, source }`	See 7.8
`intakes[] { label, month, year, start_date, application_deadline }`	Months for most courses; dates mostly null
`entry_requirements { summary, basis }`, `english_requirements[] { test_code, test_name, min_overall_score, min_band_score, source }`	English only. Academic entry is not held and never implied
`official_url`	The provider's own course page
`scholarship_count`	Linked published scholarships
`subdivision_codes[]`, `publication_status`, `freshness`	`subdivision_codes` are the course's states or provinces from its campuses; a Canadian course with no campus (often online) takes its provider's province. The `subdivision_codes` filter uses the same values

7.3 course (detail)

```
{ "action": "course", "course_code": "082960F" }
```

`course_code` accepts a source code, a StudySearch display code (e.g. `UNBC-BA-019`) or a `course_id`. The detail has every search field plus: `description`, `tuition_history[]` (every year held, latest first), `scholarships[] { scholarship_id, name, official_url, amount_note, amount_is_maximum, application_deadline, saving_per_year, saving_currency }`, `english_note`, `other_matches` (other courses sharing the same source code), and `provider_outcomes_state` with `provider_outcomes[]` (the provider's QILT statistics, as in 7.4). With `edu_country` (7.9) it also carries `entry`, the course's academic entry requirements and the requirement that applies to a student from that country; without it, `entry` holds the course's own published requirements.

7.4 providers and provider (University Finder)

```
{ "action": "providers",
  "filters": { "country_codes": ["AU"], "university_groups": ["go8"] },
  "sort": "qs_rank_asc", "page": 1, "page_size": 6 }
{ "action": "provider", "provider_id": "provider:cricos:00025b" }
```

Filters: `keyword`, `country_codes`, `subdivision_codes`, `cities`, `regional_categories`, `university_groups`, `institution_types`, `study_level_codes` and `study_area_codes` (offered), `has_scholarship`, `ranked_in` (`qs_wur`, `the_wur`), `qs_rank_max`, `the_rank_max`, `has_logo`, `provider_ids`.
Sort: `name_asc` (default), `qs_rank_asc`, `the_rank_asc`, `course_count_desc`.

Field	List / detail	Notes
`provider_id`, `name`, `legal_name`, `website`	list	`name` is the presentable name
`institution_type { code, name, basis }`	list	From the regulators' registers (TEQSA, CRICOS, NZQA). `null` for Canada and a few Australian providers
`campuses[]`	list	One item per campus, see "Provider campuses" below. Each item: `city`, `postcode`, `subdivision_code`, `metro_area`, `regional_category`, `regional_category_name` (as for courses) and `campus_id`, `campus_name`, `course_count`
`course_count`, `study_levels_offered[]`, `study_areas_offered[]`	list	With course counts
`university_groups[]`, `scholarship_count`	list	
`ranking_summary { qs_wur, the_wur }`	list	Latest edition of each: `edition_year`, `rank_display`, `rank_low`; `null` where not ranked
`logo`	list	7.7
`description`, `rankings[]`	detail	`rankings[]` as in 7.6, every edition held
`outcomes_state`, `outcomes[]`	detail	QILT statistics for Australian providers, by study level (UG, PGC, PGR, ALL): `survey`, `survey_name`, `metric_code`, `metric_name`, `study_level`, `study_level_name`, `value`, `unit`, `ci_low`, `ci_high`, `national_benchmark`, `reference_year`, `responses`. Provider level only, never per course. Empty for New Zealand and Canada
`entry_matrix[]`	detail	Academic entry requirements the provider publishes by country of prior education (7.9); narrowed to one country with `edu_country`

An average tuition per provider is not returned: there is no sound basis for one.

Provider campuses. Each item in a provider's `campuses[]` is one campus:

Field	Type	Meaning
`campus_id`	text	The campus's permanent identifier. Store it as the campus key. It never changes for a campus
`campus_name`	text or `null`	The campus name as published (for Australia, the location name on the national register; for New Zealand and Canada, from the provider's pages). Show it as printed. `null` where no name is held
`course_count`	whole number	Courses the API returns at this campus (published, current, offered at this campus). A course taught at three campuses counts at each. `0` means the campus is held but no returned course is linked to it: you may hide such a campus
`city`, `postcode`, `subdivision_code`, `metro_area`, `regional_category`, `regional_category_name`		As before

- **Campuses in the same city are separate items.** Until Issue 7, campuses sharing a city, postcode and region came back as one item with no name. From this issue each campus is its own item (University of Auckland: 9 campuses, all in Auckland). If you grouped by city, group by `campus_id` instead; a city filter still works on `city`.
- **The order of `campuses[]` changes.** Until Issue 7 the items came in the database's own sort order, which was not documented. From this issue they are ordered by `campus_name` (A to Z, names not held last), then `campus_id`. For 489 of 1,620 providers the `campuses[]` array differs from Issue 7 at some position (measured 9 November 2026): 258 return more items and 231 return the same campuses in a different order; for 283 providers the first item is a different campus. Do not rely on position or on `campuses[0]`: key every campus by `campus_id` and sort on your side if your page needs a different order.
- `course_count` counts courses, not enrolments or places. Do not add the counts of a provider's campuses to get its number of courses: use the provider's `course_count`. Some courses have no campus (for example online courses), and some providers register every course at every location, so each campus shows the whole list.
- A campus name may be an address-like label where that is how the register prints the location (for example "RMIT University - 124 Latrobe Street, Melbourne"). Show it as printed; never shorten it to the city.

Example (University of Auckland, `provider:nzqa:7001`, measured 9 November 2026; three of nine items):


```
"campuses": [
  { "city": "Auckland", "postcode": null, "subdivision_code": "NZ-AUK", "metro_area":
null, "regional_category": null, "regional_category_name": null,
    "campus_id": "campus:studysearch:e096aba7-e1eb-4903-9a63-2bfb71e9a8b8:auckland-
city", "campus_name": "Auckland / City", "course_count": 2 },
  { "city": "Auckland", "postcode": null, "subdivision_code": "NZ-AUK", "metro_area":
null, "regional_category": null, "regional_category_name": null,
    "campus_id": "campus:studysearch:e096aba7-e1eb-4903-9a63-2bfb71e9a8b8:city",
"campus_name": "City", "course_count": 53 },
  { "city": "Auckland", "postcode": null, "subdivision_code": "NZ-AUK", "metro_area":
null, "regional_category": null, "regional_category_name": null,
    "campus_id": "campus:studysearch:e096aba7-e1eb-4903-9a63-2bfb71e9a8b8:city-campus",
"campus_name": "City Campus", "course_count": 219 }
]
```


Other providers (measured 9 November 2026, number of items in Issue 7 to Issue 8): RMIT University, `provider:cricos:00122a`, 5 to 6 (two campuses in Melbourne are now separate items); George Brown College, `provider:ca:ircc_dli:o19283850612`, 1 to 4 (all four in Toronto). In Issue 7 the University of Auckland returns one item: `{ "city": "Auckland", "postcode": null, "subdivision_code": "NZ-AUK",`

`"metro_area": null, "regional_category": null, "regional_category_name": null }`. Course `campuses[]` (7.2) are unchanged in this issue.

7.5 scholarships and scholarship (Scholarship Finder)

```
{ "action": "scholarships",
  "filters": { "student_types": ["international"] }, "page": 1, "page_size": 10 }
{ "action": "scholarship", "scholarship_id": "<scholarship_id from the list>" }
```

Filters: `keyword`, `country_codes`, `provider_ids`, `cities`, `subdivision_codes`, `university_groups`, `amount_types` (`fixed_amount`, `percentage_tuition`, `full_tuition`), `open_only`, `study_level_codes`, `study_area_codes`, `student_types` (`international`, `domestic`, `both`), `study_stages` (`commencing`, `current`), `automatic_consideration`, `nationality_codes`, `course_id`. Results are ordered by name. Every scholarship returned is published.

Field	Notes
`scholarship_id`, `name`, `official_url`, `provider { provider_id, name, cities[], country_code, logo }`, `university_id`, `campus_city`	
`amount_value`, `amount_type`, `amount_currency`, `amount_is_maximum`, `amount_note`, `scholarship_percentage`, `value_classification`	`amount_is_maximum` is true for “up to” amounts
`application_deadline`, `application_open_date`, `deadline_is_rolling`, `current_status`	Dates only where the page states one. `current_status`: `open`, `closed`, `opening_soon` or `check_provider`
`study_levels[]`, `study_area_codes[]`	From the linked courses
`study_stages[]`, `student_type`, `study_load`	
`academic_minimum { value, scale, text }`, `min_academic_score`	`min_academic_score` (0–100) only where the provider states a percentage or WAM; ATAR and GPA stay in `academic_minimum` with their scale
`automatic_consideration`, `citizenship_eligibility[]`, `gender`, `age_min`, `age_max`, `renewable`, `eligibility_summary`	`citizenship_eligibility[]` (and its copy `eligible_countries_list[]`): the nationalities the scholarship names, as country codes or region codes (see below). An empty list means none is held, not “open to all”
`nationality_eligibility_status`	`restricted`, `unrestricted`, `unknown` or `under_review`; see “Nationality” below
`course_count`; in detail `linked_courses[] { course_id, course_code, title, saving_per_year, saving_currency, saving_basis }`	Up to 200 linked courses (`linked_courses_truncated` when there are more)
`description`, `award_tiers[]` (detail), `last_verified_date`, `publication_status`	`reference_code` is not held (null)

Nationality. `nationality_eligibility_status` says what the platform knows about nationality for this scholarship:

Value	Meaning	Show
`restricted`	The scholarship’s own wording limits it by nationality or citizenship (it names countries or a region), or it is for domestic students only. `citizenship_eligibility` lists the codes where they are held; it can be empty when the restriction is held but its list is still being read	“Open to citizens of: …” from `citizenship_eligibility`; if the list is empty, “Nationality restrictions apply — see the scholarship page”

Value	Meaning	Show
`unrestricted`	The scholarship states that students of any nationality may apply	"Open to all nationalities"
`unknown`	Nothing about nationality is held. This is **not** "open to all"	"Check nationality eligibility on the scholarship page"
`under_review`	Who the scholarship is for is being checked	Same as `unknown`; it changes in a later sync

- `student_type` (`international`, `domestic`, `both`) is separate: "open to international students" does not mean every nationality is eligible.
- **Region codes** keep their meaning and are never turned into countries: `R-ASEAN` (South-East Asia), `R-SASIA` (South Asia), `R-NASIA` (North and East Asia), `R-CASIA` (Central Asia), `R-PACIFIC` (Pacific), `R-EUROPE` (Europe), `R-MENA` (Middle East and North Africa), `R-AFRICA` (Africa), `R-LATAM` (Latin America), `R-AMERICAS` (the Americas), `R-CARIB` (Caribbean). Show the region name; do not list the region's countries.
- **Filter `nationality_codes`** returns scholarships whose `citizenship_eligibility` names one of the codes you send. It does not return `unknown` or `unrestricted` scholarships, and a country code does not match a region code. For a student from Vietnam send `["VN", "R-ASEAN"]`. For a "scholarships you may be able to apply for" page, show the filter's results together with `unknown` and `unrestricted` scholarships, the latter two with the wording above.
- Measured 9 November 2026 (scholarships returned, 1,144): `restricted` 92 (16 of them with the list still empty; 13 name a region), `unknown` 1,052, `unrestricted` 0, `under_review` 0. Coverage grows as the platform reads more scholarship pages.

Example (Faculty of Engineering Research Scholarship for South Asia, The University of Sydney): Issue 7 `"citizenship_eligibility": ["R-SASIA"], "student_type": "international"`; Issue 8 adds `"nationality_eligibility_status": "restricted"`.

7.6 rankings

```
{ "action": "rankings",
  "filters": { "system_codes": ["qs_wur"], "edition_year": 2027, "country_codes": ["AU"]
},
  "page": 1, "page_size": 20 }
```

Filters: `system_codes` (`qs_wur`, `the_wur`), `edition_year` (default latest), `country_codes`, `provider_ids`, `rank_max`.

Each item: `provider { provider_id, name, country_code, logo }`, `system_code`, `system_name`, `publisher`, `edition_year`, `rank_display` (exactly as published, e.g. `201–250`), `rank_low`, `rank_high`, `is_tied`, `overall_score_display`, `indicators[] { code, label, value_display, rank_display }`, `methodology_url`, `source_url`, `attribution`, `terms_status`.

Held: QS World University Rankings 2021–2027 and Times Higher Education World University Rankings 2016–2026, for the providers matched to StudySearch. Nothing is re-ranked or interpolated. Show `attribution` with every ranking.

Ranking history. The `provider` detail's `rankings[]` holds every edition held for that provider (also in the `rankings` entity of `sync`). Each institution's history starts with the first edition in which it was ranked under its current identity, and some years can be missing (the institution was not ranked that year). On 3 November 2026: QS, 72 providers, 64 from 2021, 6 with a missing year; THE, 77 providers, 57 from 2016, 2 with a missing year.

- **A new institution starts its own history.** Adelaide University has QS 2026 and 2027 and THE 2026 only. Earlier editions ranked the University of Adelaide and the University of South Australia, which are not returned; they are not Adelaide University's history.
- `rank_display` is shown exactly as published (=82, `201–250`). Sort by `edition_year`, never by rank text; use `rank_low` for numeric comparison.

Wix example (backend or page code), one table row per year with gaps shown:

```
// rankings: item.rankings from the provider detail (or the CF_Rankings rows for one
provider)
function rankingHistory(rankings, systemCode, firstYear, lastYear) {
  const byYear = new Map(rankings.filter(r => r.system_code === systemCode).map(r =>
```

```
[r.edition_year, r]));
  const rows = [];
  for (let y = lastYear; y >= firstYear; y--) {           // newest first
    const r = byYear.get(y);
    rows.push(r ? { year: y, rank: r.rank_display, attribution: r.attribution }
                : { year: y, rank: "Not ranked", attribution: null });
  }
  return rows;
}
// Years to show: from the provider's own first edition to the latest edition of the
system (from `reference`):
// const years = rankings.filter(r => r.system_code === "qs_wur").map(r =>
r.edition_year);
// rankingHistory(rankings, "qs_wur", Math.min(...years), latestQsEdition);
```

Show “Not ranked” only between an institution’s first and latest held editions; do not show years before its first edition. Keep the `attribution` text with the rankings.

7.7 Logos

`logo { url, url_expires_at, mime_type, content_hash, updated_at, source_url, attribution, terms_status }`, or `null` where no approved logo is held.

- One primary logo per provider, from the provider’s own website, as published (SVG, PNG or JPEG; not recoloured or resized).
- `url` is a signed link valid for 365 days. Copy the file to Wix Media and serve your copy. Copy it again when `content_hash` changes or when `sync` sends the logo again.
- If signing fails for a call, `url` is `null` for that call only; the rest of the response is unaffected.
- A dark variant and a brand colour are not held.

7.8 Tuition rules

- `basis` is always stated: `annual`, `indicative_annual`, `course_total`, `per_session` or `unspecified`. `basis_label` keeps the provider’s own words.
- `source` is `provider_current` (the provider’s current fee page, preferred) or `regulatory_registered` (the Australian CRICOS registered course total).
- `annual_amount` is the stated annual figure, or is derived from a course total only for courses of 12 months or more (then `annual_is_derived` is true). Per-session and unspecified figures have no annual amount.
- A whole-course total is never presented as per year. An amount under 1,000 is treated as not held (provider pages use $0 or $1 as placeholders).
- Currency is the course’s own (AUD, NZD or CAD). There is no conversion: filter by country before filtering by tuition.
- **University-level costs are not available.** The API returns course tuition only (amount, currency, basis and year). It does not return an average tuition for a provider, cost of living or other compulsory non-tuition costs, and none should be shown as if from StudySearch. Where your page has a “costs” panel, show the course tuition with its basis and year, and link to the provider’s own page for other costs.

7.9 Academic entry requirements

`course` and `provider` take an optional **`edu_country`**: the two-letter ISO country code of the student’s country of prior education, for example `"IN"` for India. Keep the student’s choice in their session and send it with both calls. Any other value is refused with `400 INVALID_INPUT`. `search` does not take it.

```
{ "action": "course", "course_code": "0100714", "edu_country": "IN" }
{ "action": "provider", "provider_id": "provider:cricos:00122a", "edu_country": "IN" }
```

Course detail: `entry` (always present; `null` means not held):

Field	Notes
`min_score`, `min_score_basis`	The course’s minimum entry score and the words the course page prints with it, for example 75 and `"2027 Guaranteed ATAR"`. Show the basis with the number

Field	Notes
`min_scores[]`	Every entry score the course publishes, one item per route, as printed: `{ score, basis, audience, scale, quote, source_url, as_at }`. `audience` is `international`, `all` or `domestic`; `scale` is the grading scale only where the provider states one (otherwise `null`, never worked out). Order: international, all, domestic. Always present; `[]` when none is held. See "Several entry scores" below
`benchmark_band`	The provider's band this course names, only where the course page prints one. Never worked out from a score
`prerequisites[]`, `selection_tasks[]`	`{ text, quote }` as published
`requirements_note`	Other published entry conditions
`resolution`	Only when `edu_country` is sent; see below

Several entry scores (`min_scores[]`). Some courses publish more than one way in, for example ATAR, International Baccalaureate, GCE A Level and pathway programmes. `min_scores[]` lists each one as the provider prints it.

- Show them as a list headed "Entry scores published for this course", one line per item, international first. Use the item's `quote` as the line: it is the provider's own words and always names the route (`basis` is a short label and may not).
- Never convert between routes, never present the list as "or equivalent", and never compare it with the student's results.
- `min_score` and `min_score_basis` are unchanged: keep using them where you show a single score.


```
"min_scores": [
  { "score": 26, "basis": "International Baccalaureate Diploma Programme 26",
"audience": "international", "scale": null,
    "quote": "International Baccalaureate Diploma Programme 26", "source_url":
"https://www.monash.edu/study/course/A2012?international=true", "as_at": "2026-10-05" },
  { "score": 8, "basis": "GCE A Level 8", "audience": "all", "scale": null, "quote":
"GCE A Level 8", "source_url": "https://www.monash.edu/study/course/A2012?
international=true", "as_at": "2026-10-05" },
  { "score": 75, "basis": "ATAR 75", "audience": "domestic", "scale": null, "quote":
"ATAR 75", "source_url": "https://www.monash.edu/study/course/A2012?international=true",
"as_at": "2026-10-05" }
]
```


(Course `0101331`, shortened to three of its six items.)

`resolution`: the requirement that applies to a student from that country. It is worked out in a fixed order, and the first rule that applies is used:

1. a rule the course page states for itself;
2. the provider's row for this course and country;
3. the course's band, looked up in the provider's table for the country;
4. the provider's minimum for the country and the course level;
5. otherwise, contact the provider.

Field	Notes
`country`	The `edu_country` you sent, in capitals
`step`, `rule`	1–5: `course_override`, `course_country_row`, `band_ladder`, `provider_minimum`, `contact_provider`
`outcome`	`minimum_published`, `case_by_case` or `contact_provider`
`rows[]`	`qualification`, `study_level`, `min_grade`, `scale`, `scale_stated`, `band`, `conditions`, `quote`, `as_at`, `edition`, `case_by_case`

Field	Notes
`note`	Why no table row applied, when `step` is 5. One of: “The provider publishes a band table for this country, but the course page prints no band to enter it with.”; “The course band … has no published row for this country and level.”; “The provider publishes rows for this country, none for this course’s level.”; “No published requirement for this country.” You may show it under the “contact the provider” message
`contact`	When `step` is 5: the provider’s website, for the “contact the provider” link. `null` when not held

Show it like this:

- **`minimum_published`:** show each qualification with its minimum, for example “All India Senior School Certificate: minimum average of 75%”.
- **`case_by_case`**, or a row with `case_by_case` true: show **“This qualification is considered case by case”**. Never show “no data”, and never treat it as met. A row is `case_by_case` when it states no minimum on a scale: `min_grade` is null, or `scale` is `"none"`. Where `min_grade` holds the provider’s words (for example “Completion of Senior High School Diploma”), show them as printed with the case-by-case message.
- **A row with `scale_stated` `false`:** the provider prints a grade but does not state the grading scale on its page. Show **“Published requirement: [min_grade]. The provider does not state a grading scale on this page; check the source or contact the provider.”** Show `min_grade` exactly as printed. Do not add a percentage, an ATAR equivalent, a band or any other scale, and do not compare it with the student’s results. This is a published minimum, not case by case: `case_by_case` is `false` and `outcome` stays `minimum_published`.
- **`contact_provider`:** show **“Requirements for your qualification aren’t published — contact the provider”**, with the provider’s website.

The API looks requirements up. It never decides whether a student is eligible.

Provider detail: `entry_matrix[]` (admitted rows; narrowed to `edu_country` when sent): `country`, `study_level` (the provider’s own label), `qualification`, `min_grade`, `scale`, `band`, `course_code` (only on rows for one course), `conditions`, `as_at`, `scale_stated`. `scale` `"none"` means the row states no minimum on a scale: show `min_grade` as printed, when present, with “This qualification is considered case by case” (the same rule as `case_by_case` above). A row with `min_grade` null always has `scale` `"none"`.

`scale_stated` (on each `entry_matrix` item and each `resolution.rows[]` item; always present): whether the provider states the grading scale of `min_grade`.

Value	Meaning	`scale`	Show
`true`	A grade with a stated scale	the scale, for example `"percentage"`	As before: the minimum with its scale
`false`	A grade printed with no stated scale	`null`	“Published requirement: [min_grade]. The provider does not state a grading scale on this page; check the source or contact the provider.”
`null`	No minimum on a scale is stated (case by case)	`"none"`	“This qualification is considered case by case”, as before

A row from the course’s own page (`resolution` `step` 1) always has `scale_stated` `null`. Use `scale_stated === false` as the only test for the “does not state a grading scale” wording; `true` and `null` keep the rendering you have.

Worked example (Pilot, measured 31 October 2026, admitted rows only): RMIT University, Bachelor of Engineering (Honours), CRICOS `0100714`, for a student from India.

```
{ "action": "course", "course_code": "0100714", "edu_country": "IN" }
```

```
"entry": {
  "min_score": 73, "min_score_basis": "2026 ATAR", "min_scores": [ { "score": 73,
"basis": "2026 ATAR", "audience": "domestic", "scale": null, "quote": "2026 ATAR 73.00",
    "source_url": "https://www.rmit.edu.au/study-with-us/levels-of-study/undergraduate-
study/honours-degrees/bachelor-of-engineering-honours-bh126", "as_at": "2026-10-05" } ],
  "benchmark_band": null, "prerequisites": [], "selection_tasks": [],
"requirements_note": null,
  "resolution": {
    "country": "IN", "step": 5, "rule": "contact_provider", "outcome":
"contact_provider", "rows": [],
    "note": "The provider publishes a band table for this country, but the course page
prints no band to enter it with.",
    "contact": "https://www.rmit.edu.au"
  }
}
```


The provider publishes an India table, but this course's page prints no band to enter it with, so the answer is step 5: show "contact the provider". The same provider's table:


```
{ "action": "provider", "provider_id": "provider:cricos:00122a", "edu_country": "IN" }

"entry_matrix": [
  { "country": "IN", "study_level": "Bachelor degrees", "qualification": "All India
Senior School Certificate (AISSC) – 10+2",
    "min_grade": "Minimum average of 65%", "scale": "percentage", "band": "65%",
    "conditions": { "best_n": null, "alternatives": [], "subject_minimums": [] },
"as_at": "2026-10-26", "scale_stated": true },
  { "country": "IN", "study_level": "Bachelor degrees", "qualification": "State Boards
of Education (Higher Secondary Certificate, HSC)",
    "min_grade": "Minimum average of 70%", "scale": "percentage", "band": "65%",
    "conditions": { "best_n": null, "alternatives": [], "subject_minimums": [] },
"as_at": "2026-10-26", "scale_stated": true }
]
```


33 rows for India (345 for all countries). A course that names its band (for example "65%") resolves at step 3 to the rows of that band; this course names none.

A provider row with no minimum on a scale (same provider, measured 31 October 2026):


```
{ "country": "TW", "study_level": "Foundation Studies", "qualification": "Senior High
School Diploma",
  "min_grade": "Completion of Senior High School Diploma", "scale": "none", "band":
null,
  "conditions": { "best_n": null, "alternatives": [], "subject_minimums": [] }, "as_at":
"2026-10-26", "scale_stated": null }
```


Show "Senior High School Diploma: Completion of Senior High School Diploma. This qualification is considered case by case."

A row with a grade but no stated scale (shape only: on 31 October 2026 no admitted row is in this state yet):


```
{ "country": "CN", "study_level": "Bachelor degrees", "qualification": "…",
  "min_grade": "375", "scale": null, "band": null,
  "conditions": { "best_n": null, "alternatives": [], "subject_minimums": [] }, "as_at":
"…", "scale_stated": false }
```


Show "Published requirement: 375. The provider does not state a grading scale on this page; check the source or contact the provider."

The same course without `edu_country` (its own published requirements, and no `resolution`):


```
"entry": { "min_score": 73, "min_score_basis": "2026 ATAR", "min_scores": [ … ],
"benchmark_band": null,
          "prerequisites": [], "selection_tasks": [], "requirements_note": null,
"resolution": null }
```

For a country the provider publishes nothing for (for example `edu_country "ZW"`), `resolution` is step 5 with `note` "No published requirement for this country." Render every step 5 the same way: "contact the provider", with `contact`.

Integrating:

- **What the website shows is built by the website team.** The API returns the data and the outcome words above; it does not provide page components.
- **Website (Wix):** let the student choose their country of prior education once (for example on the course page or in their profile), keep it in their session, and send it as `edu_country` with `course` and `provider` from your backend code, as for every call (the key never reaches the browser). Render `entry.resolution` with the three rules above; show `as_at` with each row. `sync` does not carry entry requirements: fetch them with `course` and `provider` when the page is shown (or cache them by course and country).
- **Zoho:** Zoho's own API (`zoho-api-v2`) is unchanged and carries no entry requirements. A Zoho workflow that needs them for a lead calls Website API v2 `course` with the lead's country of prior education, with a key issued for that use.
- **Other consumers:** treat `entry`, `entry_matrix` and `scale_stated` as optional; a value not held is `null` or empty, never a placeholder.

Showing only what is held. Coverage grows as each provider's published table is admitted by a person (section 8); many courses and providers have none yet.

- Hide the academic entry panel when `entry.min_scores` is `[]`, `entry.min_score`, `entry.benchmark_band` and `entry.requirements_note` are `null`, and `prerequisites` and `selection_tasks` are empty, and the student has not chosen a country. Never show "no requirements" or "none".
- When the student has chosen a country, always show the `resolution` outcome (including "contact the provider" at step 5): it is an answer, not missing data.
- Show only rows that apply: the `entry_matrix` rows for the student's `edu_country` and the course's study level; show `as_at` with each.

8. What is held now

Courses or records the API returns holding a value (31 October 2026; the course totals in the column headings were re-checked on 9 November 2026; coverage grows daily).

Course field	Australia (23,732)	New Zealand (6,495)	Canada (3,814)
Official course page	17,910	3,045	2,665
English requirements	16,043	2,357	2,009
of which Duolingo English Test (DET)	405	0	248
Intake months	9,404	2,142	1,613
Any tuition	23,564	1,421	683
Study area	23,732	6,253	3,774
Study level	23,732	6,275	3,814
Duration (months)	23,732	2,340	1,324
Delivery mode	23,712	2,984	2,520
At least one campus	23,701	2,343	2,102
At least one linked scholarship	8,917	1,456	984
Providers with courses	1,279	289	52

Scholarships returned (9 November 2026): 1,144 (Australia 911, New Zealand 162, Canada 71); all 1,144 are returned for `student_types` international. Providers with an approved logo: 1,465. QS 2027 ranked Australian providers: 38.

Australian universities: 45 (all 9 November 2026). QILT statistics: 116 Australian providers (5 November 2026). Institution type: held for Australian and New Zealand providers (null for Canada).

Provider campuses *(new fields, measured 9 November 2026)*: 3,813 campus items across 1,402 providers (Issue 7 returns them as 3,296 items, merged by city; 258 providers return more items): Australia 3,525 (was 3,074), New Zealand 221 (was 170), Canada 67 (was 52). Every campus has a name. Campuses with `course_count` 0: Australia 2, New Zealand 46, Canada 13.

Scholarship nationality *(new field, 9 November 2026)*: see 7.5.

Rankings (3 November 2026): QS 2021–2027 for 72 providers; THE 2016–2026 for 77 providers.

Academic entry requirements (7.9, 3 November 2026): provider tables admitted for 13 providers (663 rows across their countries); course-level entry rows admitted for 480 courses. More providers' tables and courses have been read and wait for a person's approval before they are returned. A course or provider without admitted rows returns `entry` and `entry_matrix` empty, and resolution step 5.

9. Your Wix collections (suggested)

Collection	Key	Holds
CF_Courses	`course_id`	The course item (7.2). Show `display_code`
CF_Providers	`provider_id`	The provider detail (7.4), with the Wix Media id and `content_hash` of its logo
CF_Rankings	`provider_id` + `system_code` + `edition_year`	Ranking entries (7.6)
CF_Scholarships	`scholarship_id`	The scholarship detail (7.5)
CF_Reference	—	The `reference` reply
CF_SyncState	—	`next_cursor`, last full load, last delta, last `request_id`, counts and errors

Do not mirror the platform's own database; map the fields you need once and ignore the rest.

Wix CMS mapping for the Issue 8 fields.

Collection	Field	From	Type in Wix
CF_Campuses (new, optional)	`_id` / key	`campuses[].campus_id`	Text (key)
CF_Campuses	`provider`	the provider's `provider_id`	Reference to CF_Providers
CF_Campuses	`campusName`, `city`, `postcode`, `subdivisionCode`, `metroArea`, `regionalCategory`	`campus_name`, `city`, `postcode`, `subdivision_code`, `metro_area`, `regional_category`	Text / Number
CF_Campuses	`courseCount`	`course_count`	Number
CF_Scholarships	`nationalityStatus`	`nationality_eligibility_status`	Text (four values)
CF_Scholarships	`nationalities`	`citizenship_eligibility`	Tags

Sync: campuses come inside each `provider` item; on each provider upsert, replace that provider's CF_Campuses rows with the items received (delete rows whose `campus_id` is no longer listed). When the new fields are released, Direct calls (`providers`, `provider`, `scholarships`, `scholarship`) return the new fields from the release day; `sync` deltas pick the changes up over roughly 1.5 hours of rolling passes after the release, so a copy built from `sync`

fills in during that time. The platform sends the changed providers and every scholarship again in the next deltas (about 1,402 providers, the ones that hold a campus, and 1,144 scholarships; about 22 MB of JSON uncompressed in all, about 6 MB of providers and 16 MB of scholarships, so send `Accept-Encoding: gzip`); no new full load is needed and your cursor stays valid.

10. Support

Send: the action and request body (no key), the `request_id`, the HTTP status, the time (with time zone) and whether it affects live search, a scheduled sync or your cached pages. Never include the key.

11. Production

- At go-live you receive a separate Production key by secure channel; the endpoint address does not change.
- Replace the Pilot key in Wix Secrets Manager, run the acceptance tests again, then run a full load with `sync`.
- The Pilot key is disabled after the Production tests pass.

12. Acceptance tests

Counts are as measured on Pilot on 31 October 2026; they change as data is corrected and grows.

#	Test	Expected
1	Key	`reference` with your key at the new address returns 200 with `api_version: "website-v2"`
2	Wrong key	An invalid key returns 401 and no data
3	Reference	Vocabularies for AU, NZ and CA; eight institution types
4	Course search	The example in 7.2 returns 35 courses; each has a February intake, an IELTS minimum at or below 6.5 and annual tuition at or below 45,000
5	Keyword	`keyword` nursing with `cities` Melbourne returns 107 courses, nursing titles first, the same total on every page
6	Canada	`country_codes` CA returns 3,814 courses, each with a `display_code`
7	Display code	`course` with `course_code` UNBC-BA-019 returns that course; `display_code_kind` is `studysearch`
8	Course detail	`course_code` 082960F returns English by test, tuition with basis and linked scholarships; NOPE-XX-999 returns 404
9	University Finder	`providers` with `university_groups` go8 and sort `qs_rank_asc` returns 8 providers
10	Provider detail	`provider` provider:cricos:00025b returns 48 QILT rows and its

#	Test	Expected
		rankings
11	Institution type	`providers` with `country_codes` AU and `institution_types` university returns 45 providers
12	Scholarships	`scholarships` with `student_types` international returns 1,144 records (9 November 2026)
13	Rankings	`rankings` with QS, edition 2027, AU returns 38 entries, each with `attribution` and `terms_status: "approved"`
14	Logos	`providers` with `has_logo` true returns 1,465 providers (9 November 2026); each `logo.url` opens and `url_expires_at` is about a year ahead; your page shows the Wix Media copy
15	Sync full load	`sync` with no cursor: `mode` full and `has_more` true; following `next_cursor` to the end gives `full_load_complete: true`
16	Sync changes	The last `next_cursor` sent again returns only what changed since (often nothing); sending it twice gives the same items
17	Errors	An unknown action returns 400 `INVALID_ACTION`; a 429 is handled by waiting for `Retry-After`
25	Provider campuses	`provider` with `provider_id` provider:nzqa:7001 returns 9 `campuses` items, each with a `campus_id`, a `campus_name` and a `course_count`; all have `city` Auckland. (9 November 2026)
26	Nationality status	Every `scholarships` item has `nationality_eligibility_status`; no item with an empty `citizenship_eligibility` is `unrestricted` unless stated by the scholarship; `nationality_codes` [“VN”,“R-ASEAN”] returns both country and region scholarships
27	Ranking history	`provider` provider:cricos:04249j (Adelaide University) returns `rankings` for QS 2026, QS 2027 and THE 2026 only; your page shows no earlier years for it
18	Nulls and new fields	A value not held is null or empty, never a placeholder; an unknown field in a response is ignored safely
19	Key safety	The key is absent from browser bundles, page source, CMS records and browser network requests

#	Test	Expected
20	Entry, contact provider	`course` with `course_code` 0100714 and `edu_country` IN returns `entry.resolution` with `step` 5 and `outcome` `contact_provider`; your page shows “contact the provider”
21	Entry, provider table	`provider` with `provider_id` provider:cricos:00122a returns 345 `entry_matrix` rows; with `edu_country` IN, 33 rows, all `country` IN
22	Entry, invalid country	`edu_country` ZZ or IND returns 400 `INVALID_INPUT`
24	Entry, several scores	`course` with `course_code` 0101331 returns `entry.min_scores` with 6 items, the first `audience` `international` (IB 26), and `min_score` unchanged; a course without scores returns `min_scores: []`. On 31 October 2026, 41 courses hold scores (116 items; 24 courses with more than one)
23	Entry, scale stated	`provider` with `provider_id` provider:cricos:00122a returns `scale_stated` on every `entry_matrix` item (`true` on 312, `null` on 33 on 31 October 2026); a row with `scale_stated` `false` is shown with the “does not state a grading scale” wording, never as a percentage, band or case by case

13. Changes to this guide

Changes within Website API v2 are additive. A change to the API (a new field, filter, action or behaviour) reissues this guide with a new date and a line here. Data grows between issues; the counts in this guide are measures on the date shown.

Date	Change
15 October 2026	First issue, with the OpenAPI file and Postman collection. Changes from the Version 2 handover of 14 October 2026: a developer key; `reference` rebuilt every 15 minutes; `sync` pages may hold fewer items than `page_size`
15 October 2026 (issue 2)	`sync` pages hold up to 200 items (was 50; default 200), and a page also stops at about 550 KB. A full load is about 250 calls, about 5 minutes (was about 1,400 calls, about 25 minutes). Sections 6.1 and 6.2 added: what to expect from a full load, and what we expect from your sync job
16 October 2026 (issue 3)	Website API v2 at its own address, `website-api-v2`, with its own key: no `contract` field; responses carry

Date	Change
	`api_version: "website-v2"` instead of `contract_version`; errors add `message` and `detail` (and `INVALID_JSON`); 300 calls a minute per key, all actions together. Same actions, fields and answers. The earlier address keeps working until you have moved
17 October 2026 (issue 4)	`sync` pages hold up to 600 size units (was 200; default 600): a full load is about 86 calls, about 1 to 2 minutes (was about 260 calls, about 5 minutes); a caller that sends a smaller `page_size` keeps getting smaller pages. Replies are compressed when you send `Accept-Encoding: gzip` (about 15 MB for a full load instead of about 113 MB). New English test code DET (Duolingo English Test, overall score 10–160) in `english_requirements`, the `english_test_codes` filter and `reference`
29 October 2026 (issue 5)	`course` and `provider` take an optional `edu_country` (the student's country of prior education). The course detail gains `entry` (the course's academic entry requirements and, with `edu_country`, the requirement that applies, worked out in a fixed order with "case by case" and "contact the provider" outcomes); the provider detail gains `entry_matrix[]` (the provider's published requirements by country). Section 7.9 added; acceptance tests 20 to 22 added
31 October 2026 (issue 6)	`entry_matrix[]` items and `entry.resolution.rows[]` items gain `scale_stated`: `false` when the provider prints a grade but does not state its grading scale (`scale` is `null`; show the "does not state a grading scale" wording), `true` when the scale is stated, `null` for case by case. Section 7.9 and acceptance test 23 updated
31 October 2026 (issue 7)	The course detail's `entry` gains `min_scores[]`: every entry score the course publishes, as printed (`score`, `basis`, `audience`, `scale`, `quote`, `source_url`, `as_at`). `min_score` and `min_score_basis` are unchanged. Section 7.9 and acceptance test 24 added
The day it is released, announced in the cover note (issue 8)	Provider `campuses[]`: one item per campus (campuses sharing a city are no longer merged, so a provider can return more items: University of Auckland 1 to 9, RMIT 5 to 6, George Brown College 1 to 4), and the order of `campuses[]` changes to `campus_name`, then `campus_id` (it was the database's own order). Each item gains `campus_id`, `campus_name` and `course_count`; existing campus fields unchanged. Key campuses by `campus_id`; do not rely on position or on `campuses[0]`. Scholarships gain `nationality_eligibility_status` (`restricted`, `unrestricted`, `unknown`, `under_review`); `citizenship_eligibility` and `eligible_countries_list` unchanged. Sections 7.4, 7.5 and 9 updated; acceptance tests 25 and 26 added