

Sample 12-3

画像復元

合成モデル

画像処理特論

村松 正吾

動作確認: MATLAB R2020a

Image restoration

Synthesis model

Advanced Topics in Image Processing

Shogo MURAMATSU

Verified: MATLAB R2020a

準備

(Preparation)

```
clear
close all
import msip.download_img
msip.download_img
```

```
kodim01.png already exists in ./data/
kodim02.png already exists in ./data/
kodim03.png already exists in ./data/
kodim04.png already exists in ./data/
kodim05.png already exists in ./data/
kodim06.png already exists in ./data/
kodim07.png already exists in ./data/
kodim08.png already exists in ./data/
kodim09.png already exists in ./data/
kodim10.png already exists in ./data/
kodim11.png already exists in ./data/
kodim12.png already exists in ./data/
kodim13.png already exists in ./data/
kodim14.png already exists in ./data/
kodim15.png already exists in ./data/
kodim16.png already exists in ./data/
kodim17.png already exists in ./data/
kodim18.png already exists in ./data/
kodim19.png already exists in ./data/
kodim20.png already exists in ./data/
kodim21.png already exists in ./data/
kodim22.png already exists in ./data/
kodim23.png already exists in ./data/
kodim24.png already exists in ./data/
See Kodak Lossless True Color Image Suite
```

パラメータ設定

(Parameter settings)

- sgm: ノイズ標準偏差 σ_w (Standard deviation of noise)
- nlevels: ウェーブレット段数 (Wavelet levels)

```
% Parameter settings
```

```
isaprxleft = true;
```

```
lambda = 10^-0.1
```

```
lambda = 0.7943
```

```
gamma = 10^0.3
```

```
gamma = 1.9953
```

```
sgmuint8 = 10;
```

```
sgm = sgmuint8/255;
```

```
nlevels = 3;
```

```
niters = 80;
```

画像の読込

(Read image)

```
u = rgb2gray(im2double(imread('./data/kodim01.png')));
```

観測画像

(Observation image)

- $\mathbf{v} = \mathbf{P}\mathbf{u} + \mathbf{w}$
- $\mathbf{u} = \mathbf{D}\mathbf{s}$
- $\mathbf{w} \sim \text{Norm}(\mathbf{w} | \boldsymbol{\mu}_w = \mathbf{0}, \sigma_w^2 \mathbf{I})$

```
% Definition of measurment process
```

```
psf = fspecial('motion',21,11);
```

```
measureproc = @(x) imfilter(x,psf,'conv','circular');
```

```
% Adjoint process of the measurment process
```

```
measureadjp = @(x) imfilter(x,psf,'corr','circular');
```

```
% Simulation of AWGN
```

```
v = imnoise(measureproc(u),'gaussian',0,sgm^2);
```

非間引きハール DWT

(Undecimated Haar DWT)

```
import msip.udhaarwtdec2
```

```
import msip.udhaarwtrec2
```

完全再構成の確認 (Check the perfect reconstruction)

非間引きハール DWT はパーセバルタイト性 (The undecimated DWT satisfies the Parseval tight property,)

$$\mathbf{D}\mathbf{D}^T = \mathbf{I}$$

を満たすため、 \mathbf{D} の転置システムは完全再構成分析システムとなり得る。 (and thus its transposition system can be a PR analysis system.)

```
[coefs,scales] = udhaarwtdec2(v,nlevels);  
r = udhaarwtrec2(coefs,scales);  
assert(norm(v-r,"fro")^2/numel(v)<1e-18,'Perfect reconstruction is violated.')
```

合成辞書と転置辞書の定義 (Definition of synthesis dictionary and its adjoint)

```
% Definon of dictonay and its adjoint  
adjdic = @(x) udhaarwtdec2(x,nlevels); % D  
syndic = @(x) udhaarwtrec2(x,scales); % D.'
```

近接勾配法

(Proximal gradient method)

問題設定 (Problem setting)

$$\hat{\mathbf{s}} = \arg \min_{\mathbf{s}} \frac{1}{2} \|\mathbf{v} - \mathbf{P}\mathbf{D}\mathbf{s}\|_2^2 + \lambda \|\mathbf{s}\|_1$$

アルゴリズム (Algorithm)

1. Initialization: $\mathbf{s}^{(0)}, t \leftarrow 0$
2. Proximal gradient descent: $\mathbf{s}^{(t+1)} \leftarrow \text{prox}_{\gamma\lambda}(\mathbf{s}^{(t)} - \gamma \nabla_{\mathbf{s}} f(\mathbf{s}^{(t)}))$
3. If a stopping criteria is satisfied then finish, otherwise $t \rightarrow t + 1$ and go to Step 2.

ただし, (where)

- $\nabla_{\mathbf{s}} f(\mathbf{s}) = \mathbf{D}^T \mathbf{P}^T (\mathbf{P}\mathbf{D}\mathbf{s} - \mathbf{v})$
- $\text{prox}_{\gamma\lambda \|\cdot\|_1}(\mathbf{s}) = \mathcal{T}_{\gamma\lambda}(\mathbf{s}) = \text{sign}(\mathbf{s}) \odot \max(\text{abs}(\mathbf{s}) - \gamma\lambda \mathbf{1}, \mathbf{0})$

ソフト閾値処理 (Soft-thresholding)

```
softthresh = @(x,t) sign(x).*max(abs(x)-t,0);
```

初期化 (Initialization)

```
[coefs,scales] = udhaarwtdec2(v,nlevels);  
sp = coefs;
```

近接勾配降下 (Proximal gradient descent)

- $\gamma < 2/\beta$: Step size
- β : Lipschitz constant of ∇f , where $\beta = (\sigma_{\max}(\mathbf{PD}))^2$

```
beta = max(abs(fftn(psf,2.^nextpow2(size(v)))),[],'all');
assert(gamma < 2/beta,'Step size condition is violated.')
if isaprxleft
    mask = ones(size(coefs));
    mask(1:prod(scales(1,:))) = 0;
    lambda = lambda * mask;
end
for idx=0:niters-1
    % Proximal gradient descent
    sg = adjdic(measureadjp(measureproc(syndic(sp))-v));
    sc = softthresh(sp-gamma*sg,gamma*lambda);
    % Update
    sp = sc;
end
```

復元画像

(Restored image)

```
r = syndic(sc);
```

画像表示

(Image show)

```
figure(1)
imshow(u);
title('Original image u')
```

Original image u



```
figure(2)
imshow(v)
title(sprintf('Blurred image v : PSNR = %5.2f [dB]',psnr(u,v)))
```

Blurred image v: PSNR = 20.07 [dB]



```
figure(3)
imshow(r)
title(sprintf('Restored image r w/ ISTA : PSNR = %5.2f [dB]',psnr(u,r)))
```

Restored image r w/ ISTA:PSNR = 21.74 [dB]



© Copyright, Shogo MURAMATSU, All rights reserved.