

## Sample 10-3

### 冗長変換

ムーア・ペンローズの一般逆行列

画像処理特論

村松 正吾

動作確認: MATLAB R2020a

### Redundant transforms

Moore-Penrose inverse

Advanced Topics in Image Processing

Shogo MURAMATSU

Verified: MATLAB R2020a

準備

(Preparation)

```
close all
```

合成フィルタバンクの大域行列表現

(Global matrix representation of synthesis filter bank)

```
% # of inputs
nSamples = 4;

% Synthesis filters
f0 = [ 1 1 ]/2;
f1 = [ -1 1 ]/2;

% (Circular) convolution matrix
nF = max(length(f0),length(f1));
X = [zeros(nF-1,nSamples-nF+1) eye(nF-1); eye(nSamples)]; % Circular extension matrix
C = [zeros(nSamples,nF-1) eye(nSamples) zeros(nSamples,nF-1)]; % Clipping matrix

% Atoms in (circular) convolution matrix
d0 = C*convmtx(f0.',nSamples+nF-1)*X;
d1 = C*convmtx(f1.',nSamples+1)*X;
```

辞書 (Dictionary) **D**

```
% Dictionary D (Global matrix representation of synthesis filter bank)
D = zeros(nSamples,2*nSamples);
D(:,1:2:end) = d0;
D(:,2:2:end) = d1;
```

```
disp(D)
```

```
0.5000 -0.5000 0 0 0 0 0.5000 0.5000
0.5000 0.5000 0.5000 -0.5000 0 0 0 0
0 0 0.5000 0.5000 0.5000 -0.5000 0 0
0 0 0 0 0.5000 0.5000 0.5000 -0.5000
```

ムーア・ペンローズ一般逆行列

(Moore-Penrose's inverse)

$$\mathbf{T} = \mathbf{D}^T(\mathbf{D}\mathbf{D}^T)^{-1} = \mathbf{D}^+$$

```
T = pinv(D);
disp(T)
```

```
0.5000 0.5000 0 0
-0.5000 0.5000 0 0
0 0.5000 0.5000 0
0 -0.5000 0.5000 0
0 0 0.5000 0.5000
0 0 -0.5000 0.5000
0.5000 -0.0000 0 0.5000
0.5000 -0.0000 0 -0.5000
```

分析合成処理

(Analysis-synthesis process)

```
% Signal generation
u = rand(nSamples,1);
disp(u)
```

```
0.1361
0.8693
0.5797
0.5499
```

```
% Analysis process
s = T*u;
disp(s)
```

```
0.5027
0.3666
0.7245
-0.1448
0.5648
-0.0149
0.3430
-0.2069
```

```
% Energy of subband Coef. vector s
disp(['||s||_2^2 = ' num2str(norm(s,2).^2)])
```

```
||s||_2^2 = 1.4126
```

```
% Synthesis process
v = D*s;
```

```
disp(v)
```

```
0.1361  
0.8693  
0.5797  
0.5499
```

```
% MSE evaluation
```

```
mymse = @(x,y) mean((x(:)-y(:)).^2);  
disp(['MSE = ', num2str(mymse(u, v))]);
```

```
MSE = 1.5407e-32
```

他の一般逆行列

(Another generalized inverse)

```
% Coefficients of analysis filters
```

```
gamma = -0.5;  
delta = 1 - gamma;
```

```
% Analysis filters
```

```
h0 = [ gamma delta ];  
h1 = [ gamma -delta ];
```

```
% (Circular) convolution matrix
```

```
nH = max(length(h0),length(h1));  
X = [eye(nSamples) ; eye(nH-1) zeros(nH-1,nSamples-nH+1) ]; % Circular extension matrix  
C = [zeros(nSamples,nH-1) eye(nSamples) zeros(nSamples,nH-1)]; % Clipping matrix
```

```
% Global matrix representation of analysis filter bank
```

```
t0 = C*convmtx(h0.',nSamples+1)*X;  
t1 = C*convmtx(h1.',nSamples+1)*X;  
T = zeros(2*nSamples,nSamples);  
T(1:2:end,:) = t0;  
T(2:2:end,:) = t1;  
disp(T)
```

```
1.5000    -0.5000         0         0  
-1.5000    -0.5000         0         0  
0         1.5000    -0.5000         0  
0        -1.5000    -0.5000         0  
0         0         1.5000    -0.5000  
0         0        -1.5000    -0.5000  
-0.5000         0         0         1.5000  
-0.5000         0         0        -1.5000
```

```
% Analysis process
```

```
s = T*u;  
disp(s)
```

```
-0.2305  
-0.6387  
1.0141  
-1.5938  
0.5946  
-1.1445  
0.7568
```

-0.8928

```
% Energy of subband Coef. vector s
disp(['||s||_2^2 = ' num2str(norm(s,2).^2)])
```

||s||\_2^2 = 7.0629

```
% Synthesis process
```

```
v = D*s;
disp(v)
```

0.1361  
0.8693  
0.5797  
0.5499

```
% MSE evaluation
```

```
disp(['MSE = ', num2str(mymse(u, v))]);
```

MSE = 6.163e-33

$\gamma$  に対するサブバンド係数のエネルギー変化  
(Energy change of sub-band coefficient vector w.r.t.  $\gamma$ )

```
% Sweep gamma and evaluate energy of subband coefficient vectors
```

```
gammas = linspace(-1.0,2.0,32);
```

```
engs = zeros(length(gammas),1);
```

```
mses = zeros(length(gammas),1);
```

```
for idx = 1:length(gammas)
```

```
    % Analysis filters
```

```
    gamma = gammas(idx);
```

```
    delta = 1 - gamma;
```

```
    h0 = [ gamma delta ];
```

```
    h1 = [ gamma -delta ];
```

```
    % (Circular) convolution matrix
```

```
    nH = max(length(h0),length(h1));
```

```
    X = [eye(nSamples) ; eye(nH-1) zeros(nH-1,nSamples-nH+1) ]; % Circular extension matrix
```

```
    C = [zeros(nSamples,nH-1) eye(nSamples) zeros(nSamples,nH-1)]; % Clipping matrix
```

```
    % Global matrix representation of analysis filter bank
```

```
    t0 = C*convmtx(h0.',nSamples+1)*X;
```

```
    t1 = C*convmtx(h1.',nSamples+1)*X;
```

```
    T = zeros(2*nSamples,nSamples);
```

```
    T(1:2:end,:) = t0;
```

```
    T(2:2:end,:) = t1;
```

```
    % Analysis process
```

```
    s = T*u;
```

```
    % Energy of subband Coef. vector s
```

```
    engs(idx) = norm(s,2).^2;
```

```
    % MSE evaluation
```

```

v = D*s;
mses(idx) = mymse(u, v);
end


```

グラフ描画 (Plot)

```

figure(1)
yyaxis left
plot(gammas,engs)
xlabel('\gamma')
ylabel('||\bf s||_2^2')
grid on
hold on
yyaxis right
plot(gammas,mses,':')
ylabel('MSE')
hold off

```



© Copyright, Shogo MURAMATSU, All rights reserved.