

Sample 13-1

辞書学習

カルーネン-レーベ変換（主成分分析）

画像処理特論

村松 正吾

動作確認: MATLAB R2020a

Dictionary learning

Karhunen-Loève transform (principle component analysis)

Advanced Topics in Image Processing

Shogo MURAMATSU

Verified: MATLAB R2020a

準備

(Preparation)

```
clear
close all
import msip.download_img
msip.download_img
```

lena.png already exists in ./data/
baboon.png already exists in ./data/
goldhill.png already exists in ./data/
barbara.png already exists in ./data/

パラメータ設定

(Parameter settings)

- ブロックサイズ (Block size)

```
szBlk = [ 8 8 ];
```

画像の読込

(Read image)

- $\mathbf{u} \in \mathbb{R}^N$

```
u = rgb2gray(im2double(imread('./data/lena.png')));
meanu = mean(u(:));
```

カルーネン-レーベ変換（主成分分析）

(Karhunen-Loève transform (principle component analysis))

問題設定 (Problem setting):

$$\widehat{\Phi} = \arg \max_{\Phi \in \mathbb{R}^{M \times M}} \text{tr}(\Phi_{:,1:p}^T \widehat{\Sigma}_y \Phi_{:,1:p}), \text{ s.t. } \Phi^T \Phi = \mathbf{I}_M, \forall p \in \{1, 2, \dots, M\}$$

ただし, $\widehat{\Sigma}_y$ は観測ベクトル $\{\mathbf{y}_n\}_n$ (零平均を仮定) の標本分散共分散行列 (where, $\widehat{\Sigma}_y$ is the sample covariance matrix of the observation vectors $\{\mathbf{y}_n\}_n$ (assumed to have zero mean:))

$$\widehat{\Sigma}_y = \frac{1}{S-1} \sum_{n=1}^S \mathbf{y}_n \mathbf{y}_n^T$$

解 (Solution):

固有値分解 (Eigendecomposition)

$$\widehat{\Phi}^T \widehat{\Sigma}_y \widehat{\Phi} = \Lambda$$

ただし, $\Lambda = \text{diag}(\lambda_1, \lambda_2, \dots, \lambda_M)$, $\lambda_1 \geq \lambda_2 \geq \dots \geq \lambda_M$ は $\widehat{\Sigma}_y$ の固有値. (where, $\Lambda = \text{diag}(\lambda_1, \lambda_2, \dots, \lambda_M)$, $\lambda_1 \geq \lambda_2 \geq \dots \geq \lambda_M$ are the eigenvalues of $\widehat{\Sigma}_y$.)

画像 \mathbf{u} からのデータ行列 \mathbf{Y} の生成 (Generation of data matrix \mathbf{Y} of image \mathbf{u})

```
Y = im2col(u,szBlk,'distinct');  
Y = Y - mean(Y,2);
```

標本分散共分散行列 $\widehat{\Sigma}_y$ の計算 (Calculation of sample covariance matrix $\widehat{\Sigma}_y$)

```
SigmaY = cov(Y.');
```

標本分散共分散行列 $\widehat{\Sigma}_y$ の固有値分解 (Eigendecomposition of sample covariance matrix $\widehat{\Sigma}_y$)

```
[Phi,Lambda] = eig(SigmaY);
```

固有値 λ の大きさの降順に列ベクトルをソート (Sorting column vectors in the descending order of the eigenvalues λ)

```
[~,idx] = sort(diag(Lambda),'descend');  
Phi = Phi(:,idx);
```

固有ベクトルを基底画像に変換 (Reshape the eigenvectors into basis images)

```
nBases = prod(szBlk);  
basisImages = zeros(szBlk(1),szBlk(2),nBases);  
for iBasis = 1:nBases
```


```
basisImages(:, :, iBasis) = reshape(Phi(:, iBasis), szBlk(1), szBlk(2));  
end
```

画像表示
(Image show)

```
figure(1)  
imshow(u);  
title('Original image u')
```



```
figure(2)  
montage(imresize(basisImages, 8, 'nearest') + .5, 'BorderSize', [2 2])  
title('Basis images of KLT (PCA)')
```



© Copyright, Shogo MURAMATSU, All rights reserved.