Sample 12-3

画像復元

合成モデル

画像処理特論

村松 正吾

動作確認: MATLAB R2023a

Image restoration

Synthesis model

Advanced Topics in Image Processing

Shogo MURAMATSU

Verified: MATLAB R2023a

準備

(Preparation)

```
clear
close all
import msip.download_img
msip.download_img
```

```
kodim01.png already exists in ./data/
kodim02.png already exists in ./data/
kodim03.png already exists in ./data/
kodim04.png already exists in ./data/
kodim05.png already exists in ./data/
kodim06.png already exists in ./data/
kodim07.png already exists in ./data/
kodim08.png already exists in ./data/
kodim09.png already exists in ./data/
kodim10.png already exists in ./data/
kodim11.png already exists in ./data/
kodim12.png already exists in ./data/
kodim13.png already exists in ./data/
kodim14.png already exists in ./data/
kodim15.png already exists in ./data/
kodim16.png already exists in ./data/
kodim17.png already exists in ./data/
kodim18.png already exists in ./data/
kodim19.png already exists in ./data/
kodim20.png already exists in ./data/
kodim21.png already exists in ./data/
kodim22.png already exists in ./data/
kodim23.png already exists in ./data/
kodim24.png already exists in ./data/
See Kodak Lossless True Color Image Suite
```

パラメータ設定

(Parameter settings)

- sgm: ノイズ標準偏差 (Standard deviation of noise)
- nlevels: ウェーブレット段数 (Wavelet levels)

```
% Parameter settings
isaprxleft = true;
lambda = 10^-0.1

lambda = 0.7943

gamma = 10^0.3

gamma = 1.9953

sgmuint8 = 10;
sgm = sgmuint8/255;
nlevels = 3;
niters = 80;
```

画像の読込

(Read image)

```
u = rgb2gray(im2double(imread('./data/kodim23.png')));
```

観測画像

(Observation image)

- •
- •
- •

```
% Definition of measurment process
psf = fspecial('motion',21,11);
measureproc = @(x) imfilter(x,psf,'conv','circular');
% Adjoint process of the measurment process
measureadjp = @(x) imfilter(x,psf,'corr','circular');
% Simulation of AWGN
v = imnoise(measureproc(u),'gaussian',0,sgm^2);
```

非間引きハール DWT

(Undecimated Haar DWT)

```
import msip.udhaarwtdec2
import msip.udhaarwtrec2
```

完全再構成の確認 (Checki the perfect reconstruction)

非間引きハール DWT はパーセバルタイト性 (The undecimated DWT satisfies the Parseval tight property,)

を満たすため、 の転置システムは完全再構成分析システムとなり得る. (and thus Its transposition system can be a PR analysis system.)

```
[coefs,scales] = udhaarwtdec2(v,nlevels);
r = udhaarwtrec2(coefs,scales);
assert(norm(v-r,"fro")^2/numel(v)<1e-18,'Perfect reconstruction is violated.')</pre>
```

合成辞書と転置辞書の定義 (Definition of synthesis dictionary and its adjoint)

```
% Definition of dictionay and its adjoint
adjdic = @(x) udhaarwtdec2(x,nlevels); % D
syndic = @(x) udhaarwtrec2(x,scales); % D.'
```

近接勾配法

(Proximal gradient method)

問題設定 (Problem setting)

アルゴリズム (Algorithm)

- 1. Initialization: ,
- 2. Proximal gradient descent:
- 3. If a stopping critera is satisfied then finish, otherwise and go to Step 2.

ただし、(where)

•

ソフト閾値処理 (Soft-thresholding)

```
softthresh = @(x,t) sign(x).*max(abs(x)-t,0);
```

初期化 (Initialization)

```
[coefs,scales] = udhaarwtdec2(v,nlevels);
sp = coefs;
```

近接勾配降下 (Proximal gradient descent)

- : Step size
- : Lipschitz constant of , where

```
beta = max(abs(fftn(psf,2.^nextpow2(size(v)))),[],'all');
assert(gamma < 2/beta,'Step size condition is violated.')
if isaprxleft
    mask = ones(size(coefs));
    mask(1:prod(scales(1,:))) = 0;
    lambda = lambda * mask;
end
for idx=0:niters-1
    % Proximal gradient descent
    sg = adjdic(measureadjp(measureproc(syndic(sp))-v));
    sc = softthresh(sp-gamma*sg,gamma*lambda);
    % Update
    sp = sc;
end</pre>
```

復元画像

(Restored image)

```
r = syndic(sc);
```

画像表示

(Image show)

```
figure(1)
imshow(u);
title('Original image u')
```



```
figure(2)
imshow(v)
```


title(sprintf('Blurred image v: PSNR = %5.2f [dB]',psnr(u,v)))

Blurred image v:PSNR = 23.69 [dB]



```
figure(3)
imshow(r)
title(sprintf('Restored image r w/ ISTA: PSNR = %5.2f [dB]',psnr(u,r)))
```

Restored image r w/ ISTA:PSNR = 26.67 [dB]



© Copyright, Shogo MURAMATSU, All rights reserved.