# Sample 7-5

幾何学処理

畳み込みの随伴作用素

画像処理特論

村松 正吾

動作確認: MATLAB R2020a

# **Geometric image processing**

Adjoint of convolution

Advanced Topics in Image Processing

Shogo MURAMATSU

Verified: MATLAB R2020a

準備

(Preparation)


```
close all
```

# インパルス応答の生成

(Generation of impulse response)

```
ftype = "prewitt";
h = rot90(fspecial(ftype),2)
```

```
figure(1)
stem3(h,'filled')
axis ij
title('Impulse response of h[n]')
```



### 二変量循環畳み込みの行列表現

(Matrix representation of bivariate circular convolution)

周期 Q の循環畳み込み演算 (Circular convolution with period Q)

$$\{\nu[\mathbf{n}]\}_{\mathbf{n}} = \{h[\mathbf{n}]\}_{\mathbf{n}} \bigcirc \{u[\mathbf{n}]\}_{\mathbf{n}} = \sum_{\mathbf{k} \in \Omega \subset \mathbb{Z}^2} h[\mathbf{k}] \{u[((\mathbf{n} - \mathbf{k}))_{\mathbf{Q}}]\}_{\mathbf{n}}$$

```
% Input array size
N1 =6;
N2 =4;

% Find the matrix representation of the bivariate downsampling
N = N1*N2;
T = [];
for idx = 1:N
    % Generating a standard basis vector
    e = zeros(N1,N2);
    e(idx) = 1;
    % Response to the standard basis vector
    t = imfilter(e,h,'conv','circ');
    T(:,idx) = t(:);
end
```

行列表現 (Matrix represntation)

```
\% Matrix representation of the bivariate downsampling \ensuremath{\mathsf{T}}
```

```
T = 24 \times 24
  0
     -1
                                             0 . . .
             0
         -1
                                             0
        0 -1
                                  -1
      0
        1 0 -1 0 0
                                 0 -1
     0 0 1 0 -1 0 0 0 1 0 0 0 1 0 0 0 1
  0
                                         -1
                                             0
  -1
                                             0
        0 0 0 1 0 -1 0 0
  0
     -1
                                         1
                                             0
         -1 0
                0 0 1 0
     0
                              -1
  1
                                             1
         0 -1 0 0 0 1 0
1 0 -1 0 0 0 1
                                  -1
  0
     1
                                      0
                                             0
                                     -1
```

#### 二変量循環畳み込みの随伴作用素

(Adjoint operator of bivariate circular convolution)

エルミート転置 (Herimitian transposition)

 $\bullet$   $\mathbf{T}^H$ 

% Adjoint matrix of the bivariate circular convolution  $\ensuremath{\mathsf{T'}}$ 

随伴作用素(Adjoint operator)

$$T^*(\{\boldsymbol{v}[\mathbf{m}]\}_{\mathbf{m}}) = \mathrm{vec}_{\Omega_{\mathbf{u}}}^{-1} \circ \mathbf{T}^H \mathrm{vec}_{\Omega_{\mathbf{v}}}(\{\boldsymbol{v}[\mathbf{m}]\}_{\mathbf{m}})$$

```
% Adjoint operator T*
adjOp = @(x) reshape(T'*x(:),[N1 N2]);
```

#### 内積の保存の確認

(Confirmation of the preservation of the inner product)

入力配列の生成 (Generation of an input array)

```
• \{u[\mathbf{n}]\}_{\mathbf{n}}
```

```
% Generation of an input array u
arrayU = randn(N1,N2);
```

循環畳み込みの出力 (Output of the circular convolution)

```
• \{v[\mathbf{m}]\}_{\mathbf{m}} = T(\{u[\mathbf{n}]\}_{\mathbf{n}})
```

```
% Circular convolution (v=Tu)
arrayV = imfilter(arrayU,h,'conv','circ');
```

任意の出力領域配列生成(Generation of an arbitrary array in output range)

```
% Array generation in the same domain with arrayV
arrayY = randn(size(arrayV),'like',arrayV);
```

内積 (Inner product)

```
\alpha = \langle \mathbf{y}, \mathbf{v} \rangle = \langle \mathbf{y}, \mathbf{T} \mathbf{u} \rangle
```

```
% Inner product <y,v>=<y,Tu>
innprodA = dot(arrayY(:),arrayV(:))
```

innprodA = -0.5761

循環畳み込みの随伴作用素 (The adjoint operator of circular convolution)

```
\mathbf{r} = \mathbf{T}^H \mathbf{v}
```

```
% Adjoint operation of circular convolution (r=T'v)
arrayR = adjOp(arrayY)
```

```
arrayR = 6 \times 4
  -2.3182 -1.8764
                   -2.4241
                            -1.7791
          -0.3046 -1.7407
                             -1.5339
  -3.6957
   2.8798
            5.1064
                     3.1533
                              3.1104
           2.0279
                    1.6786
  -0.3144
                              3.1066
                   -0.7292
  -0.5616
          -3.2301
                             -1.3313
          -1.7233
   4.0100
                     0.0621
                             -1.5727
```

$$\beta = \langle \mathbf{r}, \mathbf{u} \rangle = \langle \mathbf{T}^H \mathbf{y}, \mathbf{u} \rangle$$

```
% Inner product <r,u>=<T'v,u>
innprodB = dot(arrayR(:),arrayU(:));

% Verify the preservation of the inner product
err = abs(innprodA - innprodB);
disp(['|<y,Tu> - <T''y,u>| = ' num2str(err)])
```

```
|\langle y, Tu \rangle - \langle T'y, u \rangle| = 3.1086e-15
```


## 反転インパルス応答による循環畳み込み

(Circular convolution with the reversal impulse response)

$$\{r[\mathbf{n}]\}_{\mathbf{n}} = \{\overline{h}[-\mathbf{n}]\}_{\mathbf{n}} \bigcirc \{y[\mathbf{n}]\}_{\mathbf{n}} = \sum_{\mathbf{k} \in \Omega \subset \mathbb{Z}^2} \overline{h}[-\mathbf{k}]\{y[((\mathbf{n} - \mathbf{k}))_{\mathbf{Q}}]\}_{\mathbf{n}}$$

```
% Revaersal impulse response
f = conj(rot90(h,2))
```

```
figure(2)
stem3(f,'filled')
axis ij
title('Impulse response of f[n]')
```



```
% Circular convolution with impulse response f
arrayS = imfilter(arrayY,f,'conv','circ')
```

```
arrayS = 6 \times 4
             -1.8764
                       -2.4241
                                 -1.7791
  -2.3182
   -3.6957
            -0.3046
                     -1.7407
                                 -1.5339
   2.8798
            5.1064
                      3.1533
                                3.1104
   -0.3144
             2.0279
                       1.6786
                                  3.1066
```

```
-0.5616 -3.2301 -0.7292 -1.3313
4.0100 -1.7233 0.0621 -1.5727
```

### 行列演算とIMFILTERの比較

```
% Definition of MSE
mymse = @(x,y) sum((x-y).^2,'all')/numel(x);

% Evaluation
disp(['MSE between matrix operation and IMFILTER: ' num2str(mymse(arrayR,arrayS))])
```

MSE between matrix operation and IMFILTER: 1.3382e-31

© Copyright, Shogo MURAMATSU, All rights reserved.