

Sample 10-1

冗長変換

非間引きハール DWT

画像処理特論

村松 正吾

動作確認: MATLAB R2023a

Redundant transforms

Undecimated Haar DWT

Advanced Topics in Image Processing

Shogo MURAMATSU

Verified: MATLAB R2023a

準備

(Preparation)

```
close all
```

入力信号の生成

(Generation of input)

```
% Input signal  
u = rand(16,1); % Set to even length
```

並列フィルタバンク実装

(Parallel filter bank implementation)

分析フィルタバンクをデシメータで、合成フィルタバンクをインタポレータで実装 (Analysis filter banks are implemented with decimators and synthesis filter banks are implemented with interpolators.)

```
% # of channels  
nChs = 2;  
  
% Analysis filters  
h0 = [ 1 1 ]/2;  
h1 = [ 1 -1 ]/2;  
  
% Synthesis filters  
f0 = [ 1 1 ]/2;  
f1 = [ -1 1 ]/2;
```

```

% Analysis process
s0 = conv(h0,u);
s1 = conv(h1,u);

% Synthesis process
v0 = conv(f0,s0);
v1 = conv(f1,s1);
v = v0 + v1;

```

信号表示

(Signal display)

```


figure(1)
% Input
subplot(3,2,1)
stem(0:length(u)-1,u,'filled')
title('Input u[n]')
xlabel('n')
ax = gca;
ax.XLim = [ 0 length(v)];

% Subband 0
subplot(3,2,3)
stem(0:length(s0)-1,s0,'filled')
title('Subbnad s_0[n]')
xlabel('m')
ax = gca;
ax.XLim = [ 0 length(v)];
ax.YLim = [ min([s0(:);s1(:)]) max([s0(:);s1(:)]) ]);

% Subband 1
subplot(3,2,4)
stem(0:length(s1)-1,s1,'filled')
title('Subbnad s_1[n]')
xlabel('m')
ax = gca;
ax.XLim = [ 0 length(v)];
ax.YLim = [ min([s0(:);s1(:)]) max([s0(:);s1(:)]) ]);

% Output
subplot(3,2,5)
stem(0:length(v)-1,v,'filled')
title('Outut v[n]')
xlabel('n')
ax = gca;
ax.XLim = [ 0 length(v)];

```



```
% MSE 評価
mymse = @(x,y) mean((x(:)-y(:)).^2);
disp(['MSE = ', num2str(mymse(u, v(2:end-1))))];
```


```
MSE = 1.0111e-33
```

インパルス応答（基底ベクトル）

(Impluse responses of synthesis filters; basis vectors)

```
figure(2)
% Low-pass filter
subplot(1,2,1)
impz(f0)
ax = gca;
ax.YLim = [ min([f0(:);f1(:)]) max([f0(:);f1(:)]) ];


% High-pass filter
subplot(1,2,2)
impz(f1)
ax = gca;
ax.YLim = [ min([f0(:);f1(:)]) max([f0(:);f1(:)]) ];
```



周波数応答

(Frequency responses)

```
figure(3)
fftPoints = 512;
F = zeros(fftPoints,nChs);
% Low-pass filter
[F(:,1),W] = freqz(f0,1,fftPoints);
% High-pass filter
F(:,2) = freqz(f1,1,fftPoints);
plot(W/pi,abs(F)) %20*log10(abs(F))
axis([0 1 0 1]) % -70 10]
xlabel('Normalized Frequency (x\pi rad/sample)')
ylabel('Magnitude' % (dB)')
grid on
```



恒等変換

(Noble identity)

以下の性質が成り立つ。(The following properties hold.)

- $\rightarrow [H(z^M)] \rightarrow [\downarrow M] \rightarrow \iff \rightarrow [\downarrow M] \rightarrow [H(z)] \rightarrow$
- $\rightarrow [\uparrow M] \rightarrow [F(z^M)] \rightarrow \iff \rightarrow [F(z)] \rightarrow [\uparrow M] \rightarrow$

なお, $H(z^M)$ および $F(z^M)$ は, $H(z)$ および $F(z)$ のインパルス応答 $\{h[n]\}_n$ と $\{f[n]\}_n$ をそれぞれ補間率 M で零値挿入したインパルス応答をもつ。(where $H(z^M)$ and $F(z^M)$ have the impulse responses of upsampled ones of $H(z)$ and $F(z)$ with factor M , respectively.)

- $$H(z^M) = \sum_{m=-\infty}^{\infty} h[m]z^{-Mm} = \sum_{n=-\infty}^{\infty} h_{\uparrow M}[n]z^{-n}$$
- $$F(z^M) = \sum_{m=-\infty}^{\infty} f[m]z^{-Mm} = \sum_{n=-\infty}^{\infty} f_{\uparrow M}[n]z^{-n}$$

非間引き Haar DWT の実装

(Implementation of undecimated Haar DWT)

```

% Period for circular convolution
period = 32;

% 3-level hierachical analysis filters
h1_0 = h1; % H0
h0_L = h0; % L0
h1_1 = conv(h0_L,upsample(h1,2)); % H1
h0_L = conv(h0_L,upsample(h0,2)); % L1
h1_2 = conv(h0_L,upsample(h1,4)); % H2
h0_L = conv(h0_L,upsample(h0,4)); % L2
h0_2 = h0_L;

% 3-level hierachical synthesis filters
f1_0 = f1; % H0
f0_L = f0; % L0
f1_1 = conv(f0_L,upsample(f1,2)); % H1
f0_L = conv(f0_L,upsample(f0,2)); % L1
f1_2 = conv(f0_L,upsample(f1,4)); % H2
f0_L = conv(f0_L,upsample(f0,4)); % L2
f0_2 = f0_L;

% 3-level hierachical analysis process
s30 = cconv(h0_2,u,period); % L3
s31 = cconv(h1_2,u,period); % H3
s21 = cconv(h1_1,u,period); % H2
s11 = cconv(h1_0,u,period); % H1

% 3-level hierachical synthesis process
v30 = cconv(f0_2,s30,period); % L3
v31 = cconv(f1_2,s31,period); % H3
v21 = cconv(f1_1,s21,period); % H2
v11 = cconv(f1_0,s11,period); % H1
v = v30 + v31 + circshift(v21,4) + circshift(v11,6); % Delay in each channel is
taken into account

```

信号表示

(Signal display)

```

figure(4)
% Input
subplot(3,4,1)
stem(0:length(u)-1,u,'filled')
title('Input u[n]')
xlabel('n')
ax = gca;
ax.XLim = [ 0 period];

% Subband 30
subplot(3,4,5)

```

```

stem(0:length(s30)-1,s30,'filled')
title('s_0[n]')
ax = gca;
ax.YLim = [ -1 1 ];


% Subband 31
subplot(3,4,6)
stem(0:length(s31)-1,s31,'filled')
title('s_1[n]')
ax = gca;
ax.YLim = [ -1 1 ];

% Subband 21
subplot(3,4,7)
stem(0:length(s21)-1,s21,'filled')
title('s_2[n]')
ax = gca;
ax.YLim = [ -1 1 ];

% Subband 11
subplot(3,4,8)
stem(0:length(s11)-1,s11,'filled')
title('s_3[n]')
ax = gca;
ax.YLim = [ -1 1 ];

% Output
subplot(3,4,9)
stem(0:length(v)-1,v,'filled')
title('Output v[n]')
xlabel('n')
ax = gca;
ax.XLim =[ 0 period ];

```



% MSE 評価


```
disp(['MSE = ', num2str(mymse([u(:); zeros(length(v)-length(u),1)],circshift(v,-7)))]])
```

MSE = 7.3784e-33

インパルス応答（局所基底ベクトル）

(Impulse responses of synthesis filters; local basis vectors)


```
% 3-level hierachical synthesis process
figure(5)
f = cell(4,1);
f{1} = f0_2;
f{2} = f1_2;
f{3} = f1_1;
f{4} = f1_0;
for idx = 1:length(f)
    subplot(length(f),1,idx)
    stem(0:length(f{idx})-1,f{idx}, 'filled')
    title(['f_' num2str(idx) '[n]'])
    xlabel('n')
    ax = gca;
    ax.XLim =[0 7];
end
```

周波数応答

(Frequency responses)

```
figure(6)
fftPoints = 512;
F = zeros(fftPoints,4);
for idx = 1:length(f)
    if idx == 1
        [F(:,idx),W] = freqz(f{idx},1,fftPoints);
    else
        F(:,idx) = freqz(f{idx},1,fftPoints);
    end
end
plot(W/pi, abs(F)) %20*log10(abs(F))
axis([0 1 0 1]) % -70 10]
xlabel('Normalized Frequency (x\pi rad/sample)')
ylabel('Magnitude') % (dB)')
title('Frequency responses of synthesis filters')
legend({'F_0','F_1','F_2','F_3'})
grid on
```



© Copyright, Shogo MURAMATSU, All rights reserved.